

---

---

**Test conditions for numerically controlled  
turning machines and turning centres —**

**Part 6:  
Accuracy of a finished test piece**

*Conditions d'essai des tours à commande numérique et des centres de  
tournage —*

**iTeh STANDARD PREVIEW**  
*Partie 6: Exactitude d'une pièce d'essai usinée*  
**(standards.iteh.ai)**

ISO 13041-6:2009

<https://standards.iteh.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009>



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 13041-6:2009](https://standards.iteh.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009)

<https://standards.iteh.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

**Contents**

Page

Foreword.....	iv
Introduction .....	v
<b>1</b> <b>Scope</b> .....	<b>1</b>
<b>2</b> <b>Normative references</b> .....	<b>1</b>
<b>3</b> <b>Preliminary remarks</b> .....	<b>1</b>
<b>3.1</b> <b>Measuring units</b> .....	<b>1</b>
<b>3.2</b> <b>Reference to ISO 230</b> .....	<b>2</b>
<b>3.3</b> <b>Test sequence</b> .....	<b>2</b>
<b>3.4</b> <b>Tests to be performed</b> .....	<b>2</b>
<b>3.5</b> <b>Measuring instruments</b> .....	<b>2</b>
<b>3.6</b> <b>Fixing of test pieces</b> .....	<b>2</b>
<b>3.7</b> <b>Materials of test pieces, tooling and cutting parameters</b> .....	<b>2</b>
<b>3.8</b> <b>Sizes of test pieces</b> .....	<b>2</b>
<b>3.9</b> <b>Information to be recorded</b> .....	<b>3</b>
<b>3.10</b> <b>Machine size categories</b> .....	<b>3</b>
<b>4</b> <b>Machining tests</b> .....	<b>5</b>
<b>Bibliography</b> .....	<b>12</b>

ITeCh STANDARD PREVIEW  
(standards.iteh.ai)

[ISO 13041-6:2009](https://standards.iteh.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009)

<https://standards.iteh.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13041-6 was prepared by Technical Committee ISO/TC 39, *Machine tools*, Subcommittee SC 2, *Test conditions for metal cutting machine tools*.

This second edition cancels and replaces the first edition (ISO 13041-6:2005), which has been technically revised.

ISO 13041 consists of the following parts, under the general title *Test conditions for numerically controlled turning machines and turning centres*:

- *Part 1: Geometric tests for machines with a horizontal workholding spindle*
- *Part 2: Geometric tests for machines with a vertical workholding spindle*
- *Part 3: Geometric tests for machines with inverted vertical workholding spindles*
- *Part 4: Accuracy and repeatability of positioning of linear and rotary axes*
- *Part 5: Accuracy of feeds, speeds and interpolations*
- *Part 6: Accuracy of a finished test piece*
- *Part 7: Evaluation of contouring performance in the coordinate planes*
- *Part 8: Evaluation of thermal distortions*

## Introduction

A numerically controlled turning machine is a machine tool in which the principal motion is the rotation of the workpiece against the stationary cutting tool(s) and where cutting energy is brought by the workpiece and not by the tool. This machine is controlled by a numerical control (NC) providing automatic functioning in accordance with ISO 13041-1:2004, 3.3, and can be of single spindle or multi-spindle type.

A turning centre is an NC turning machine equipped with power-driven tool(s) and the capacity to orientate the workholding spindle around its axis. This machine can include additional features, such as automatic tool changing from a magazine.

The objective of the ISO 13041 series is to supply as wide and comprehensive information as possible on geometric, positional, contouring, thermal and machining tests, which can be carried out for comparison, acceptance, maintenance or any other purpose.

The ISO 13041 series specifies, with reference to the relevant parts of ISO 230, tests for turning centres and numerically controlled turning machines with/without tailstocks, standing alone or integrated in flexible manufacturing systems. It also establishes the tolerances or maximum acceptable values for the test results corresponding to general purpose and normal accuracy turning centres and numerically controlled turning machines.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 13041-6:2009](https://standards.iteh.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009)

<https://standards.iteh.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 13041-6:2009

<https://standards.iteh.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009>

# Test conditions for numerically controlled turning machines and turning centres —

## Part 6: Accuracy of a finished test piece

### 1 Scope

This part of ISO 13041 specifies, with reference to ISO 230-1, a series of cutting tests, under finishing conditions, of standard test pieces. It also specifies the characteristics and dimensions of the test pieces themselves.

This part of ISO 13041 is intended to supply minimum requirements for assessing the cutting accuracy of the machine.

iTeh STANDARD PREVIEW

### 2 Normative references (standards.iteh.ai)

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 230-1:1996, *Test code for machine tools — Part 1: Geometric accuracy of machines operating under no-load or finishing conditions*

ISO 1101, *Geometrical Product Specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out*

ISO 13041-1:2004, *Test conditions for numerically controlled turning machines and turning centres — Part 1: Geometric tests for machines with a horizontal workholding spindle*

ISO 13041-2, *Test conditions for numerically controlled turning machines and turning centres — Part 2: Geometric tests for machines with a vertical workholding spindle*

ISO 13041-3, *Test conditions for numerically controlled turning machines and turning centres — Part 3: Geometric tests for machines with inverted vertical workholding spindles*

### 3 Preliminary remarks

#### 3.1 Measuring units

In this part of ISO 13041, all linear dimensions, deviations and corresponding tolerances are expressed in millimetres; angular dimensions are expressed in degrees, and angular deviations and the corresponding tolerances are expressed in ratios, but in some cases microradians or arcseconds may be used for clarification purposes. The equivalence of the following expressions should always be kept in mind.

$$0,010/1\ 000 = 10\ \mu\text{rad} \approx 2''$$

### 3.2 Reference to ISO 230-1

To apply this part of ISO 13041, reference shall be made to ISO 230-1, especially for the installation of the machine before testing, warming up of the machine, description of measuring methods, and evaluation and presentation of the results.

### 3.3 Test sequence

The sequence in which the tests are presented in this part of ISO 13041 in no way defines the practical order of testing.

### 3.4 Tests to be performed

When testing a machine, it is not always necessary or possible to carry out all the tests described in this part of ISO 13041. When the tests are required for acceptance purposes, it is up to the user to choose, in agreement with the supplier/manufacturer, those tests relating to the components and/or the properties of the machine which are of interest. These tests are to be clearly stated when ordering a machine. Mere reference to this part of ISO 13041 for the acceptance tests, without specifying the tests to be carried out, and without agreement on the relevant expenses, cannot be considered as binding for any contracting party.

When testing machines with moving cross rail, the tolerances given in this part of ISO 13041 apply when the position of the cross rail is fixed at a certain location (preferably in mid-travel of the cross rail or some other predetermined position subject to agreement between the supplier/manufacturer and the user).

### 3.5 Measuring instruments

The measuring instruments indicated in the tests described in Clause 4 are examples only. Other instruments measuring the same qualities and having at least the same accuracy may be used. Linear displacement sensors shall have a resolution of 0,001 mm or better. See ISO 14253-1, ISO/TS 14253-2 and ISO/TR 16015.

<https://standards.itech.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009>

### 3.6 Fixing of test pieces

The test piece shall be conveniently mounted on a proper fixture or chuck, such that maximum stability of tools and fixture is achieved. The mounting surfaces of the fixture and the test piece shall be flat and/or cylindrical. It is recommended that suitable means of fixturing be used to allow for tool breakthrough (if applicable).

**NOTE** Fixing of the test piece can have a significant impact on the results of the tests. Therefore, parameters associated with fixing the test piece, such as type and number of jaws, and amount of clamping force, are considered carefully.

### 3.7 Materials of test pieces, tooling and cutting parameters

The test piece material, tooling and the subsequent cutting parameters are subject to agreement between supplier/manufacturer and user, and shall be recorded. The test piece material shall be specified with proper material designations.

### 3.8 Sizes of test pieces

If the test pieces are machined several times, with a consequent reduction of external dimensions, it is recommended that the final test piece, when used for acceptance purposes, comply with the dimensions specified in this part of ISO 13041.

If the test pieces come from previous cutting tests and are re-useable, their characteristic dimensions shall remain within 10 % of those indicated in this part of ISO 13041. When the test pieces are re-used, a shallow cut shall be made to clean up all surfaces before new finishing test cuts are taken.



It is also recommended that type and serial number of the machine, date of test and names and orientation of the axes be marked on the test pieces and that they be delivered with the machine for reference purposes.

In principle, no more than one piece of each type shall be machined for acceptance purposes. In case of special requirements, such as statistical assessment of the machine performance, the machining of more test pieces is to be subject to agreement between the supplier/manufacturer and user.

Preliminary cuts shall be taken in order to make the depth of cut as constant as possible.

### 3.9 Information to be recorded

For tests made according to the requirements of this part of ISO 13041, the following information shall be compiled as completely as possible and shall be included in the test report:

- a) material and dimensions of the test piece;
- b) material and dimensions of the tool;
- c) cutting speed(s);
- d) feedrate(s) (feed velocity);
- e) depth(s) of cut;
- f) axes used for machining;
- g) test piece fixing conditions;
- h) other cutting parameters, e.g. cutting fluid.

### 3.10 Machine size categories

ISO 13041-6:2009

<https://standards.iteh.ai/catalog/standards/sist/32754076-e4d-449e-883a->

For the purposes of the ISO 13041 series, machines are classified into size categories depending on their work spindle orientation (see ISO 13041-1 for horizontal workholding spindle, ISO 13041-2 for vertical workholding spindle, and ISO 13041-3 for inverted vertical workholding spindle).

The categories and size ranges are referenced in the cutting tests of this part of ISO 13041 and are therefore repeated here for the convenience of the user.

ISO 13041-1 NC turning machines and turning centres with horizontal workholding spindle are classified into three size categories, on the basis of the criteria specified in Table 1.

**Table 1 — Size range for machines with horizontal workholding spindle**

Criteria	Category 1	Category 2	Category 3
Swing diameter over bed	$D \leq 250$	$250 < D \leq 500$	$500 < D \leq 1\ 000$
Nominal bar diameter	$d' \leq 25$	$25 < d' \leq 63$	$63 < d'$
Nominal diameter of chuck	$d \leq 125$	$125 < d \leq 250$	$250 < d$

NOTE 1 The nominal chuck diameter is defined in ISO 3442-1 and ISO 3442-2.

NOTE 2 The choice of criteria is at the manufacturer's discretion.

ISO 13041-2 NC turning machines and turning centres with vertical workholding spindles are classified into four categories, on the basis of the criteria specified in Table 2.

**Table 2 — Size ranges for machines with vertical workholding spindle**

Criteria	Category 1	Category 2	Category 3	Category 4
Nominal diameter of chuck	$d \leq 500$	$500 < d \leq 1\,000$	$1\,000 < d \leq 5\,000$	$d > 5\,000$
Diameter of workholding spindle/table	$D \leq 500$	$500 < D \leq 1\,000$	$1\,000 < D \leq 5\,000$	$D > 5\,000$

NOTE 3 The nominal chuck diameter is defined in ISO 3442-1 and ISO 3442-2.

ISO 13041-3 NC turning machines and turning centres with inverted vertical workholding spindle are classified into three size categories, on the basis of the criteria specified in Table 3.

**Table 3 — Size ranges for machines with inverted vertical workholding spindle**

Criteria	Category 1	Category 2	Category 3
Nominal diameter of chuck	$d \leq 250$	$250 < d \leq 400$	$d > 400$
Maximum turning diameter	$D \leq 315$	$315 < D \leq 500$	$D > 500$

NOTE 4 The nominal chuck diameter is defined in ISO 3442-1 and ISO 3442-2.

iTech STANDARD PREVIEW  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/32754076-ef4d-449e-883a-210c29f69e9a/iso-13041-6-2009>

4 Machining tests

<p><b>Object</b> Turning a cylindrical test piece: a) circularity; b) consistency of machined diameters.</p>	M1																																																															
<p><b>Diagram</b></p>																																																																
<p><b>Key</b> 1 chuck l shall be chosen to suit the measuring instrument. The distance between the chuck face and the first step, <math>\phi D_p</math>, shall be less than L</p>																																																																
<p>For machines with horizontal workholding spindle (ISO 13041-1): For bar machines: <math>L = 2,5 \times d'</math> (nominal bar diameter) <math>D_{p, \min} = 0,3 \times L</math>; For chucking machines: <math>L = 0,8 \times d</math> (nominal chuck diameter), or <math>L = 0,66 \times</math> maximum turning length (Z stroke), whichever is smaller. <math>D_{p, \min} = 0,3 \times L</math></p>	<p>For machines with vertical workholding spindle (ISO 13041-2) or inverted vertical workholding spindle (ISO 13041-3): <math>L = 0,8 \times d</math> (nominal chuck diameter), or <math>L = 0,66 \times</math> maximum turning length (Z stroke), whichever is smaller. <math>L_{\max} = 1\ 500</math> <math>D_{p, \min} = 0,3 \times L</math> <math>D_{p, \max} = 1\ 000</math></p>																																																															
<table border="1" style="width:100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="3" style="width:15%;">Tolerance</th> <th colspan="3" style="width:25%;">Machines with horizontal spindle (ISO 13041-1)</th> <th colspan="4" style="width:25%;">Machines with vertical spindle (ISO 13041-2)<sup>a</sup></th> <th colspan="3" style="width:25%;">Machines with inverted vertical spindle (ISO 13041-3)</th> <th rowspan="3" style="width:10%;">Measured deviation</th> </tr> <tr> <th colspan="3">Category</th> <th colspan="4">Category</th> <th colspan="3">Category</th> </tr> <tr> <th>1</th><th>2</th><th>3</th> <th>1</th><th>2</th><th>3</th><th>4</th> <th>1</th><th>2</th><th>3</th> </tr> </thead> <tbody> <tr> <td>a) Circularity</td> <td>0,005</td><td>0,005</td><td>0,005</td> <td>0,005</td><td>0,005</td><td>0,01</td><td>0,015</td> <td>0,005</td><td>0,005</td><td>0,005</td> <td rowspan="2" style="vertical-align: middle;">Machine class and category: a) b)</td> </tr> <tr> <td>b) Consistency of diameters</td> <td>0,01</td><td>0,015</td><td>0,02</td> <td>0,015</td><td>0,02</td><td>0,03</td><td>0,04</td> <td>0,01</td><td>0,015</td><td>0,02</td> </tr> </tbody> </table>										Tolerance	Machines with horizontal spindle (ISO 13041-1)			Machines with vertical spindle (ISO 13041-2) <sup>a</sup>				Machines with inverted vertical spindle (ISO 13041-3)			Measured deviation	Category			Category				Category			1	2	3	1	2	3	4	1	2	3	a) Circularity	0,005	0,005	0,005	0,005	0,005	0,01	0,015	0,005	0,005	0,005	Machine class and category: a) b)	b) Consistency of diameters	0,01	0,015	0,02	0,015	0,02	0,03	0,04	0,01	0,015	0,02
Tolerance	Machines with horizontal spindle (ISO 13041-1)			Machines with vertical spindle (ISO 13041-2) <sup>a</sup>				Machines with inverted vertical spindle (ISO 13041-3)			Measured deviation																																																					
	Category			Category				Category																																																								
	1	2	3	1	2	3	4	1	2	3																																																						
a) Circularity	0,005	0,005	0,005	0,005	0,005	0,01	0,015	0,005	0,005	0,005	Machine class and category: a) b)																																																					
b) Consistency of diameters	0,01	0,015	0,02	0,015	0,02	0,03	0,04	0,01	0,015	0,02																																																						
<p><sup>a</sup> Tolerances apply only to machines with fixed cross rail. Tolerances for machines with adjustable height cross rails will depend on the method of locating and/or adjusting the cross rail after raising or lowering and should be agreed between the supplier and the user.</p>																																																																
<p><b>Measuring instruments</b> For a), roundness measuring machine. For b), micrometer.</p>																																																																
<p><b>Observations and references to ISO 230-1:1996, 4.1, 6.6 and 6.8</b> For b), readings are taken at each band in one plane only, the variation of the readings between adjacent bands shall not exceed 75 % of the tolerance. The machine axes used shall be recorded.</p>																																																																
<p>NOTE A thick walled tube instead of a solid rod can be used as the cylindrical test blank.</p>																																																																