



Designation: F318 – 06

Standard Practice for Sampling Airborne Particulate Contamination in Cleanrooms for Handling Aerospace Fluids¹

This standard is issued under the fixed designation F318; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers a procedure for sampling airborne particulate matter larger than 5 μm in size. The method is designed to be used in specific areas, commonly called cleanrooms in the aerospace industry, where aerospace fluids are handled.

NOTE 1—Practice F50 is an alternative procedure.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D1193 Specification for Reagent Water

D1836 Specification for Commercial Hexanes

D2021 Specification for Neutral Detergent, 40 Percent Alkylbenzene Sulfonate Type (Withdrawn 2000)³

E2042 Practice for Cleaning and Maintaining Controlled Areas and Clean Rooms

F25 Test Method for Sizing and Counting Airborne Particulate Contamination in Cleanrooms and Other Dust-Controlled Areas

F50 Practice for Continuous Sizing and Counting of Airborne Particles in Dust-Controlled Areas and Clean Rooms Using Instruments Capable of Detecting Single Sub-Micrometre and Larger Particles

F312 Test Methods for Microscopical Sizing and Counting Particles from Aerospace Fluids on Membrane Filters

¹ This practice is under the jurisdiction of ASTM Committee E21 on Space Simulation and Applications of Space Technology and is the direct responsibility of Subcommittee E21.05 on Contamination.

Current edition approved April 1, 2006. Published April 2006. Originally approved in 1965. Last previous edition approved in 2004 as F318 – 04. DOI: 10.1520/F0318-06.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

3. Terminology

3.1 *Definitions:*

3.1.1 *cleanroom*—an area in which the temperature, humidity, and the airborne particulate contamination are controlled as required.

3.1.2 *uninterrupted airflow pattern*—the pattern of airflow that exists in a given area, when no personnel or equipment are present to interrupt the airflow.

4. Summary of Practice

4.1 This practice is based on the impingement of particles on a filter membrane using a vacuum technique. The number of air samples required in a given area will be based upon the geometric floor area, the disturbance to the uninterrupted airflow pattern, and the room volume. See also Practice E2042 and Test Method F25.

5. Apparatus

5.1 *Filter Holder*—Aerosol open-type for a filter membrane.

5.2 *Vacuum Pump or Aspirator*—Minimum capacity 25 in. (635 mm) Hg at 10 standard L/min.

5.3 *Flowmeter*—Orifice-type, rotameter-type or equivalent positive flow-indicating device, capable of being calibrated to a $\pm 5\%$ flow accuracy under sample area ambient conditions. Calibration must be at a given vacuum using a given diameter and length of line from the vacuum source to the filter holder containing a filter membrane of the same pore size as used in the test sample.

5.4 *Membrane Filter*—A nominal overall diameter with grid lines, in dimensional accord with the filter holder, may be used. The pore size should be selected with regard to pertinent particle ranges and a specified flow rate across an effective sampling area of $1000\text{ mm}^2 \pm 5\%$. Color contrast is recommended to aid in identification of particulate matter.

5.5 *Forceps*—Stainless steel, nonmagnetic, unserrated tips.

5.6 *Microscope and Associated Apparatus*—For a description of a suitable apparatus, refer to Test Methods F312.

5.7 *Wash Bottle*, fitted with an in-line filtration capability.