

ETSI EN 300 674-2-1 V2.1.1 (2016-09)



**Transport and Traffic Telematics (TTT);
Dedicated Short Range Communication (DSRC)
transmission equipment (500 kbit/s / 250 kbit/s)
operating in the 5 795 MHz to 5 815 MHz frequency band;
Part 2: Harmonised Standard covering the essential
requirements of article 3.2 of the Directive 2014/53/EU;
Sub-part 1: Road Side Units (RSU)**

PREVIEW
https://standards.etsi.org/standards-search/EN-300-674-2-1-V2-1-1-2016-09/4e03-8e00-8a00-09538951/

Reference

REN/ERM-TG37-26

Keywords

data, DSRC, harmonised standard, radio,
regulation, RTTT, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	10
3.3 Abbreviations	12
4 Technical requirements specifications	13
4.1 Mechanical and electrical design.....	13
4.1.1 Units.....	13
4.1.2 Controls	13
4.2 General characteristics	13
4.2.1 RSU classes	13
4.2.2 Carrier frequencies.....	14
4.2.3 Modulation.....	14
4.2.4 Antenna characteristic.....	14
4.3 Environmental conditions.....	14
4.3.1 Environmental profile.....	14
4.3.2 Power supply	14
4.4 Conformance requirements	15
4.4.1 Transmitter parameters	15
4.4.1.1 General	15
4.4.1.2 Maximum equivalent isotropically radiated power	15
4.4.1.3 Transmitter frequency error	15
4.4.1.4 Transmitter spectrum mask.....	15
4.4.1.5 Transmitter unwanted emissions.....	16
4.4.2 Receiver parameters.....	16
4.4.2.1 Receiver spurious emissions	16
4.4.2.2 Blocking.....	16
4.4.2.3 Sensitivity	17
5 Testing for compliance with technical requirements.....	17
5.1 Environmental conditions for testing	17
5.2 Interpretation of the measurement results	17
5.3 Essential radio test suites.....	18
5.3.1 Transmitter parameters	18
5.3.1.1 Maximum equivalent isotropically radiated power.....	18
5.3.1.1.1 General	18
5.3.1.1.2 Radiated measurements	18
5.3.1.1.3 Conducted measurements	19
5.3.1.2 Transmitter Frequency error.....	19
5.3.1.2.1 General	19
5.3.1.2.2 Radiated measurements	19
5.3.1.2.3 Conducted measurements	20
5.3.1.3 Transmitter spectrum mask.....	20
5.3.1.3.1 General	20
5.3.1.3.2 Radiated measurements	21
5.3.1.3.3 Conducted measurements	22
5.3.1.4 Transmitter unwanted emissions.....	23
5.3.1.4.1 General	23
5.3.1.4.2 Radiated measurements	24

5.3.2	Receiver parameters.....	25
5.3.2.1	Receiver unwanted emissions in the spurious domain	25
5.3.2.1.1	General	25
5.3.2.1.2	Radiated measurements	25
5.3.2.2	Blocking	26
5.3.2.2.1	General	26
5.3.2.2.2	Radiated measurements	26
5.3.2.3	Sensitivity	27
5.3.2.3.1	General	27
5.3.2.3.2	Radiated measurements	27
Annex A (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU		29
Annex B (normative): Basics on testing		30
B.1	General conditions.....	30
B.1.1	Power source	30
B.1.2	Thermal balance	30
B.1.3	Test signals	30
B.1.4	Test sites	31
B.1.4.1	Shielded anechoic chamber.....	31
B.1.4.2	Open area test site	32
B.1.4.3	Test fixture	33
B.1.5	General requirements for RF cables	34
B.1.6	Conducted measurements	35
B.1.6.1	One antenna connector arrangement.....	35
B.1.6.2	Two antenna connectors arrangement.....	36
B.1.6.3	Test site requirements	36
B.1.6.4	Site preparation for conducted measurements	36
B.1.6.4.1	Monochromatic signals	36
B.1.6.4.2	Modulated signals	37
B.1.7	Radiated measurements	37
B.1.7.1	One antenna arrangement	37
B.1.7.2	Two antennas arrangement	39
B.1.7.3	Test site requirements	40
B.1.7.3.1	Measurement distances	40
B.1.7.3.2	Free-space wave propagation	40
B.1.7.4	Test and substitution antennas	41
B.1.7.5	Site preparation for RSU measurements	41
B.1.7.5.1	Arrangement for transmit parameters.....	41
B.1.7.5.2	Arrangement for receive parameters	42
B.2	Instruments	44
B.2.1	Receiving device	44
B.2.2	RF power sensor	45
B.2.3	Combiner	45
B.3	Power of modulated RSU carrier	45
B.4	Bit error ratio measurements	46
B.4.1	Basics	46
B.4.2	BER measurement	47
B.4.3	FER measurement	47
B.4.3.1	Mathematical expressions.....	47
B.4.3.2	Equipment.....	47
B.4.3.3	Procedure	48
Annex C (informative): Guidance on declaring the environmental profile		49
C.1	Recommended environmental profile	49
C.2	Normal environmental conditions	49
C.3	Extreme environmental conditions.....	49

Annex D (informative):	Bibliography	50
Annex E (informative):	Change History	51
History		52

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/9d18fc55-4d4c-4e03-8e00-8a6ba1938685/etsi-en-300-674-2-1-v2.1.1-2016-09>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.6] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.5].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 2, sub-part 1 of a multi-part deliverable covering Transport and Traffic Telematics (TTT); Dedicated Short Range Communication (DSRC) transmission equipment (500 kbit/s / 250 kbit/s) operating in the 5 795 MHz to 5 815 MHz frequency band, as identified below:

Part 1: "General characteristics and test methods for Road Side Units (RSU) and On-Board Units (OBU)";

Part 2: "**Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU**";

Sub-part 1: "**Road Side Units (RSU)**";

Sub-part 2: "On-Board Units (OBU)".

National transposition dates

Date of adoption of this EN:	12 September 2016
Date of latest announcement of this EN (doa):	31 December 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2017
Date of withdrawal of any conflicting National Standard (dow):	30 June 2018

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document applies to Transport and Traffic Telematics (TTT) systems:

- with a Radio Frequency (RF) output connection and specified antenna or with an integral antenna;
- for data transmission only;
- operating on radio frequencies in the 5,725 GHz to 5,875 GHz Short Range Devices frequency band.

The applicability of the present document covers only the Road Side Units (RSU).

The present document does not necessarily include all the characteristics which may be required by a user, nor does it necessarily represent the optimum performance achievable.

The present document complies with the Commission Implementing Decision 2013/752/EU [1] and CEPT/ERC Recommendation 70-03 [2]. It is a specific standard covering various TTT applications.

The present document applies to the following radio equipment types operating in all or in part of the following service frequency bands given in table 1.

Table 1: Frequency bands and centre frequencies f_{TX} allocated for DSRC

	Pan European Service Frequencies	National Service Frequencies
Channel 1	5,795 GHz to 5,800 GHz, $f_{TX} = 5,7975$ GHz	
Channel 2	5,800 GHz to 5,805 GHz, $f_{TX} = 5,8025$ GHz	
Channel 3		5,805 GHz to 5,810 GHz, $f_{TX} = 5,8075$ GHz
Channel 4		5,810 GHz to 5,815 GHz, $f_{TX} = 5,8125$ GHz

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Commission Implementing Decision 2013/752/EU of 11 December 2013 amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices and repealing Decision 2005/928/EC.
- [2] CEPT/ERC Recommendation 70-03 (2016): "Relating to the use of Short Range Devices (SRD)".
- [3] CEN EN 12253:2004: "Road transport and traffic telematics - Dedicated short-range communication - Physical layer using microwave at 5,8 GHz".

- [4] ETSI TR 100 028 (V1.4.1) (12-2001) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [5] IEC 60721-3-4:1995 including Amendment 1:1996: "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 4: Stationary use at non-weatherprotected locations".
- [6] IEC 60721-3-5:1997: "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 5: Ground vehicle installations".
- [7] CEN EN 12795:2003: "Road transport and traffic telematics - Dedicated Short Range Communication (DSRC) - DSRC data link layer: medium access and logical link control".
- [8] CEN EN 12834:2003: "Road transport and traffic telematics - Dedicated Short Range Communication (DSRC) - DSRC application layer".
- [9] ISO 14906 (2011): "Electronic fee collection -- Application interface definition for dedicated short-range communication".
- [10] CEPT/ERC Recommendation 74-01E (2011): "Unwanted emissions in the spurious domain".
- [11] ETSI TR 102 273-2 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [12] ETSI TR 102 273-6 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 6: Test fixtures".
- [13] CISPR 16-1 (2015): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1: Radio disturbance and immunity measuring apparatus".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] Void.
- [i.3] ETSI TR 102 273-4 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".
- [i.4] Commission Directive 95/54/EC of 31 October 1995 adapting to technical progress Council Directive 72/245/EEC on the approximation of the laws of the Member States relating to the suppression of radio interference produced by spark-ignition engines fitted to motor vehicles and amending Directive 70/156/EEC on the approximation of the laws of the Member States relating to the type-approval of motor vehicles and their trailers.
- [i.5] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

- [i.6] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [i.5] and the following apply:

adjacent channel: channel at a distance of 5 MHz relative to the centre frequency, i.e. in the channel at the next upper or lower centre frequency

bit: acronym for "binary digit" which can have one out of two possible values

EXAMPLE: 0/1, or +1/-1, or low/high.

bit rate: in a bit stream, the number of bits occurring per unit time, usually expressed in bits per second

boresight: direction of maximum radiation of a directional antenna

NOTE: If boresight cannot be determined unambiguously, then boresight may be declared by the manufacturer.

carrier frequency: frequency f_{Tx} to which the RSU transmitter is tuned

NOTE: In DSRC, the carrier frequency is in the centre of a channel, see table 2 of the present document.

carrier signal or carrier: harmonic signal whose nominal single frequency f_{Tx} can vary within a range specified by the carrier frequency tolerance and which is capable of being modulated by a second, symbol-carrying signal

channel: continuous part of the radio-frequency spectrum to be used for a specified emission or transmission

NOTE: A radio-frequency channel may be defined by two specified limits, or by its centre frequency and its bandwidth, or any equivalent indication. It is often designated by a sequential number. A radio-frequency channel may be time-shared in order to allow radio communication in both directions by simplex operation. The term "channel" is sometimes used to denote two associated radio-frequency channels, each of which is used for one of two directions of transmission, i.e. in fact a telecommunication circuit.

co-channel: transmission using the same channel (frequency band of 5 MHz width)

cross-polar discrimination (XPD): ratio P_{LHCP} / P_{RHCP} of power P_{LHCP} of the left hand circular polarized wave to the power P_{RHCP} of the right hand circular wave when the total power of the transmitted wave is $P_{LHCP} + P_{RHCP}$

downlink: transmission in direction from RSU to OBU

ellipticity of polarization: ratio of the polarization main axes of an elliptic polarized radio wave

EXAMPLE: The ellipticity of circular polarized radio waves is one.
The ellipticity of linear polarized waves is infinity.

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

equivalent isotropically radiated power: signal power fed into an ideal loss-less antenna radiating equally in all directions that generates the same power flux at a reference distance as the one generated by a signal fed into the antenna under consideration in a predefined direction within its far field region

integral antenna: antenna, with or without a connector, designed as an indispensable part of the equipment

OBU sleep mode: optional mode for battery powered OBUs that allows to save battery power

NOTE: In this mode, the OBU can only detect the presence of a DSRC downlink signal to initiate under certain defined conditions a transition to the stand-by mode.

OBU stand-by mode: mode, in which the OBU is capable of receiving DSRC downlink signals, but is never transmitting

operating frequency: nominal frequency at which equipment is operated; also referred to as the operating centre frequency

NOTE: Equipment may be able to operate at more than one operating frequency.

out-of-band emissions: emissions on a frequency or frequencies immediately outside the necessary bandwidth which results from the modulation process and which cannot be reduced without affecting the corresponding transmission of information, but excluding spurious emissions (see also CEPT/ERC Recommendation 74-01E [10])

polarization: locus of the tip of the electrical field vector in a plane perpendicular to the direction of transmission

EXAMPLE: Horizontal and vertical linear polarization.
Left and right hand circular polarization.

Portable Equipment (PE): generally intended to be self-contained, free standing and portable

NOTE: A PE would normally consist of a single module, but may consist of several interconnected modules. It is powered by one or more internal batteries.

radiated measurements: measurements which involve the measurement of a radiated electromagnetic field

spurious emissions: emission on a frequency, or frequencies, which are outside an exclusion band of $\pm 2,5$ times the channel spacing around the selected centre frequency f_{Tx} , and the level of which may be reduced without affecting the corresponding transmission of information

NOTE: Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products but exclude out-of-band emissions (see also CEPT/ERC Recommendation 74-01E [10]).

uplink: transmission in direction from OBU to RSU

3.2 Symbols

For the purposes of the present document, the following symbols apply:

A_{CW}	Amplitude of CW signal
A_{mod}	Amplitude of modulated signal
ATN_{AT2}	Attenuation of attenuator AT2
ATN_{BLN}	Attenuation of balun BLN
ATN_{CA1}	Attenuation of calibrated coaxial cable 1
BER	Bit Error Ratio
C_F	Number of frames transmitted
C_E	Number of erroneous frames received
d	Distance between phase centres of transmitting and receiving antenna
$d_{displace}$	Horizontal displacement of TTA and RTA antenna phase centres
d_{F1}	Distance from transmitting antenna to first Fresnel ellipse
d_{F2}	Distance from first Fresnel ellipse to receiving antenna
D_{fb}	Distance between neighbouring ferrite beads
D_i	Directivity relative to an isotropic radiator
$D_{0,TA}$	Largest linear dimension of test antenna
$D_{0,EUT}$	Largest linear dimension of EUT antenna
$EIRP_{max}$	Maximum e.i.r.p. of RSU

$EIRP_{MaxObuTx}$	Maximum e.i.r.p. generated by the OBU in a single side band
$EIRP_{ObuTx}$	e.i.r.p. generated by the OBU within a single side band
$EIRP_{OBU}$	e.i.r.p. generated by the OBU antenna
$EIRP_{TSM}$	e.i.r.p. referred to transmitter spectrum mask
Δf_{RSU}	Frequency error of RSU
Δf_s	Sub-carrier frequency error
f	Frequency
f_c	Centre frequency of receiving device or of MSS2 used for calibration
FER	Frame error ratio
f_{ObuTx}	Actual centre frequency of the lower and upper side band of the OBU uplink channel
f_{MSS1}	Frequency of MSS1
f_{offset}	Offset frequency
f_s	Nominal OBU sub-carrier frequency
f_{Tx}	Nominal RSU carrier frequency
$f_{Tx,actual}$	Actual centre frequency of the downlink carrier
f_u	Nominal centre frequency of unwanted signal
f_{u1}, f_{u2}	Centre frequencies of unwanted signal
G_c	Conversion gain
G_{corr}	Correction gain
$G_{OBU,Rx}$	Gain of OBU receiving antenna
$G_{OBU,Tx}$	Gain of OBU transmitting antenna
G_{RSA}	Gain of receiving substitution antenna
G_{TA}	Gain of test antenna
G_{TSA}	Gain of transmitting substitution antenna
$G_{RSU,Tx}$	Gain of RSU transmitting antenna
k	Expansion factor (coverage factor)
$\lg(.)$	Logarithm to the base ten
m	Modulation index
N	Total number of transmitted bits within a single frame
P_{CW}	Power of CW signal
P_{D11a}	Power limit for communication (upper)
P_{D11b}	Power limit for communication (lower)
P_{inc}	Incident signal power as received by an ideal isotropical receiving antenna
$P_{inc,scan}$	Incident signal power obtained from a scanning process
$P_{inc,dBm}$	P_{inc} in dBm
P_{LHCP}	Signal power of left hand circular polarized wave
P_{max}	Maximum signal power
P_{mod}	Power of modulated signal
P_{MMS1}	Output signal power of MSS1
P_{MMS2}	Output signal power of MSS2
P_{ObuRx}	Incident signal power to OBU, referred to an ideal isotropical receiving antenna
P_{pol}	Signal power of wave with corresponding polarization
P_v	Signal power of wave featuring vertical polarization
P_h	Signal power of wave featuring horizontal polarization
P_{PM1}	Signal power measured by the power meter 1
P_{ref}	Reference signal power limit in Watt
$P_{ref,dBm}$	Reference signal power limit in dBm
P_{reTx}	Retransmitted signal power
P_{RSA}	Signal power obtained from receiving substitution antenna
P_{RHCP}	Signal power of right hand circular polarized wave
P_{ssb}	Signal power within single side band

P_{sens}	Declared sensitivity of receiver
P_{spurious}	Signal power of spurious signal
P_{tot}	Sum of signal power $P_1 + P_2$, or $P_1 + P_2 + \dots + P_5$, whichever applies
$P_{\text{tot,dBm}}$	P_{tot} in dBm
P_{TSM}	Transmitter spectrum mask
P_{u}	Power of unwanted signal at RSU antenna
$P_{\text{u max}}$	Unwanted signal power limit at RSU antenna
P_{w}	Signal power of wanted signal
P_0	Reference signal power of 1 mW corresponding to 0 dBm
RBW	Resolution bandwidth
T_{CW}	Duration of CW signal
T_{mod}	Duration of modulated signal
$V_{\text{max}}, V_{\text{min}}$	Maximal amplitude of modulated output signal of RSU caused by data bit 1, or 0
α	Tilt angle of test antenna
α_{displace}	Displacement angle between TTA and RTA
θ	Angle relative to OBU boresight indicating worst case direction
θ°	Value of θ measured in degree
λ	Wavelength
ρ_{RSA}	Reflection coefficient at antenna connector of the receiving substitution antenna
ρ_{TSA}	Reflection coefficient at antenna connector of the transmitting substitution antenna

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in CEN EN 12253 [3] and the following apply:

AT1	Attenuator 1
AT2	Attenuator 2
BER	Bit Error Ratio
BLN	Balun
BST	Beacon Service Table
CC	Coaxial Circulator
CISPR	Comité International Spécial des Perturbations Radioélectriques
CRC	Cyclic Redundancy Checking
CW	Continuous Wave
DC	Direct Current
doa	date of announcement
dop	date of publication
dow	date of withdrawal
DSRC	Dedicated Short Range Communication
e.i.r.p.	Equivalent Isotropically Radiated Power also called EIRP, eirp, E.I.R.P.
EC	European Community
EFC	Electronic Fee Collection
EFTA	European Free Trade Association
EUT	Equipment Under Test
FCCA	Ferrited Coaxial CABLE
FCCA1	Ferrited Coaxial CABLE 1
FER	Frame Error Ratio
IEC	International Electrotechnical Commission
LHCP	Left Hand Circular Polarized
LOS	Line-Of-Sight
LP	Linear Polarized
M_{centre}	Centre point between phase centres of TTA and RTA
MSS1	Monochromatic Signal Source 1
MSS2	Monochromatic Signal Source 2
OBU	On Board Unit
PE	Portable Equipment
PM1	Power Meter 1

ppm	parts per million (10^{-6})
RBW	Resolution BandWidth
RD	Receiving Device
REC	RECommendation
RF	Radio Frequency
RRxA	RSU Receiving Antenna
RSA	Receiving Substitution Antenna
RSU	Road Side Unit
RTA	Receiving Test Antenna
RTTT	Road Transport and Traffic Telematics
RTxA	RSU Transmitting Antenna
Rx	Receiver
SMS1	Signal or Message Source 1
SR	Special Report
TA	Test Antenna
TM1	Test Message 1
TS1	Test Signal 1
TS2	Test Signal 2
TSA	Transmitting Substitution Antenna
TSM	Transmitter Spectrum Mask
TTA	Transmitting Test Antenna
TTT	Transport and Traffic Telematics
Tx	Transmitter
VBW	Video BandWidth
VST	Vehicle Service Table
VSWR	Voltage Standing Wave Ratio
XP	Cross Polarized
XPD	Cross-Polar Discrimination

4 Technical requirements specifications

4.1 Mechanical and electrical design

4.1.1 Units

The present document specifies the characteristics of Road Side Units.

Transmitters and receivers may be individual or combination units; some units may be transmitter only, some units may be receiver only and some units may combine transmitter and receiver functionalities.

4.1.2 Controls

Those controls which if maladjusted might increase the interference possibilities to and from the equipment shall only be accessible by partial or complete disassembly of the device and requiring the use of tools.

4.2 General characteristics

4.2.1 RSU classes

There exist three classes of RSUs which are distinguished by the parameter D2 (4) "in band spurious emissions with modulated carrier wave" of CEN EN 12253 [3].

Those classes are called class A, class B and class C, see table 3. The manufacturer shall declare to which class the equipment complies with.

NOTE: The use of class A for new equipment is not recommended.