



SLOVENSKI STANDARD

SIST EN 301 025 V2.1.1:2016

01-marec-2016

Radiotelefonska oprema za območje VHF za splošne komunikacije in pripadajoča oprema za digitalni selektivni klic (DSC) razreda D - Harmonizirani standard, ki zajema bistvene zahteve členov 3.2 in 3.3(g) direktive 2014/53/EU

VHF radiotelephone equipment for general communications and associated equipment for Class D Digital Selective Calling (DSC) - Harmonised Standard covering the essential requirements of articles 3.2 and 3.3(g) of the Directive 2014/53/EU

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 025 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016)

[https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-](https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016)

[c7712b375274/sist-en-301-025-v2-1-1-2016](https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016)

Ta slovenski standard je istoveten z: EN 301 025 V2.1.1

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
-----------	---------------------------------------	---

SIST EN 301 025 V2.1.1:2016

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 025 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016>

ETSI EN 301 025 V2.1.1 (2015-12)



**VHF radiotelephone equipment for general communications
and associated equipment for Class "D"
Digital Selective Calling (DSC);
Harmonised Standard covering the essential requirements
of articles 3.2 and 3.3(g) of the Directive 2014/53/EU**

SIST EN 301 025 V2.1.1:2016
SIST EN 301 025 V2.1.1:2016
c7712b375274/sist-en-301-025-v2-1-1-2016

Reference

REN/ERM-TG26-137

Keywords

DSC, maritime, radio, traffic, VHF**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 025 V2.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/etsi-en-301-025-v2-1-1-2016>
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	9
Foreword.....	9
Modal verbs terminology.....	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	11
3.1 Definitions.....	11
3.2 Symbols.....	12
3.3 Abbreviations	12
4 General and operational requirements.....	12
4.1 General	12
4.2 Composition	12
4.3 Construction	13
4.4 Controls and indicators.....	13
4.5 DSC interface for non-integrated controllers	14
4.6 Display	14
4.7 Handset and loudspeaker.....	14
4.8 Safety precautions	14
4.9 Labelling.....	14
4.10 Warm up.....	14
5 Technical requirements	14
5.1 Switching time.....	14
5.2 Class of emission and modulation characteristics	15
5.3 DSC operation	15
5.3.1 General.....	15
5.4 Multiple watch facilities	15
5.4.1 General.....	15
5.4.2 Scanning provisions.....	15
5.4.3 Scanning characteristics.....	16
6 General conditions of measurement	16
6.1 Arrangements for test signals applied to the receiver input.....	16
6.2 Squelch.....	16
6.3 Transmission time limitation.....	16
6.4 Normal test modulation	16
6.5 Artificial antenna.....	16
6.6 Arrangements for test signals applied to the transmitter input	17
6.7 Test channels	17
6.8 Generation and examination of the digital selective call signal	17
6.9 Standard test signals for DSC.....	17
6.10 Determination of the symbol error ratio in the output of the receiving part.....	17
6.11 Void.....	17
6.12 Test conditions, power sources, and ambient temperatures.....	17
6.12.1 Normal and extreme test conditions.....	17
6.12.2 Test power source	18
6.13 Normal test conditions.....	18
6.13.1 Normal temperature and humidity	18
6.13.2 Normal power sources	18
6.13.2.1 Battery power source.....	18
6.13.2.2 Other power sources.....	18
6.14 Extreme test conditions	18
6.14.1 Extreme temperatures	18
6.14.2 Extreme values of test power sources	18

6.14.2.1	Battery power source.....	18
6.14.2.2	Other power sources.....	18
6.15	Procedure for tests at extreme temperatures.....	18
7	Environmental tests.....	19
7.1	Introduction.....	19
7.2	Procedure.....	19
7.3	Performance check.....	19
7.4	Vibration test.....	19
7.4.1	Definition.....	19
7.4.2	Method of measurement.....	20
7.4.3	Requirement.....	20
7.5	Temperature tests.....	20
7.5.1	Definition.....	20
7.5.2	Dry heat.....	20
7.5.2.1	Definition.....	20
7.5.2.2	Method of measurement.....	20
7.5.2.3	Requirement.....	20
7.5.3	Damp heat.....	21
7.5.3.1	Definition.....	21
7.5.3.2	Method of measurement.....	21
7.5.3.3	Requirement.....	21
7.5.4	Low temperature.....	21
7.5.4.1	Definition.....	21
7.5.4.2	Method of measurement.....	21
7.5.4.3	Requirement.....	21
8	Transmitter.....	21
8.1	Frequency error.....	21
8.1.1	Definition.....	21
8.1.2	Method of measurement.....	21
8.1.3	Limits.....	22
8.2	Carrier power.....	22
8.2.1	Definition.....	22
8.2.2	Method of measurement.....	22
8.2.3	Limits.....	22
8.2.3.1	Normal test conditions.....	22
8.2.3.2	Extreme test conditions.....	22
8.3	Frequency deviation.....	22
8.3.1	Definition.....	22
8.3.2	Maximum permissible frequency deviation.....	22
8.3.2.1	Method of measurement.....	22
8.3.2.2	Limits.....	23
8.3.3	Reduction of frequency deviation at modulation frequencies above 3 kHz.....	23
8.3.3.1	Method of measurement.....	23
8.3.3.2	Limits.....	23
8.4	Sensitivity of the modulator, including microphone.....	24
8.4.1	Definition.....	24
8.4.2	Method of measurement.....	24
8.4.3	Limits.....	24
8.5	Audio frequency response.....	24
8.5.1	Definition.....	24
8.5.2	Method of measurement.....	25
8.5.3	Limit.....	25
8.6	Audio frequency harmonic distortion of the emission.....	25
8.6.1	Definition.....	25
8.6.2	Method of measurement.....	26
8.6.2.1	General.....	26
8.6.2.2	Normal test conditions.....	26
8.6.2.3	Extreme test conditions.....	26
8.6.3	Limits.....	26
8.7	Adjacent channel power.....	26

iTech STANDARD PREVIEW

(standards.itech.ai)

SIST EN 301 025 V2.1.1:2016

<https://standards.itech.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523->[c7712b375274/sist-en-301-025-v2-1-1-2016](https://standards.itech.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016)

8.7.1	Definition.....	26
8.7.2	Method of measurement	26
8.7.3	Limits.....	27
8.8	Conducted spurious emissions conveyed to the antenna	27
8.8.1	Definition.....	27
8.8.2	Method of measurement	27
8.8.3	Limit	27
8.9	Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna	27
8.9.1	Definitions	27
8.9.2	Method of measurement	27
8.9.3	Limits.....	28
8.10	Transient frequency behaviour of the transmitter.....	28
8.10.1	Definitions	28
8.10.2	Method of measurement	29
8.10.3	Limits.....	31
8.11	Residual modulation of the transmitter	31
8.11.1	Definition.....	31
8.11.2	Method of measurement	31
8.11.3	Limit	31
8.12	Frequency error (demodulated DSC signal).....	31
8.12.1	Definition.....	31
8.12.2	Method of measurement	31
8.12.3	Limits.....	32
8.13	Modulation index for DSC	32
8.13.1	Definition.....	32
8.13.2	Method of measurement	32
8.13.3	Limits.....	32
8.14	Modulation rate for DSC.....	32
8.14.1	Definition.....	32
8.14.2	Method of measurement	32
8.14.3	Limits.....	32
8.15	Testing of free channel transmission on DSC channel.....	32
8.15.1	Definition.....	32
8.15.2	Method of measurement.....	32
8.15.3	Requirement.....	33
9	Radiotelephone receiver	33
9.1	Harmonic distortion and rated audio-frequency output power	33
9.1.1	Definition.....	33
9.1.2	Methods of measurement	33
9.1.3	Limits.....	33
9.2	Audio frequency response	33
9.2.1	Definition.....	33
9.2.2	Method of measurement	33
9.2.3	Limits.....	34
9.3	Maximum usable sensitivity.....	34
9.3.1	Definition.....	34
9.3.2	Method of measurement	35
9.3.3	Limits.....	35
9.4	Co-channel rejection.....	35
9.4.1	Definition.....	35
9.4.2	Method of measurement	35
9.4.3	Limit	35
9.5	Adjacent channel selectivity.....	35
9.5.1	Definition.....	35
9.5.2	Method of measurement	36
9.5.3	Limits.....	36
9.6	Spurious response rejection.....	36
9.6.1	Definition.....	36
9.6.2	Method of measurement	36
9.6.3	Limit	36
9.7	Intermodulation response	37

9.7.1	Definition.....	37
9.7.2	Method of measurement	37
9.7.3	Limit	37
9.8	Blocking or desensitization	37
9.8.1	Definition.....	37
9.8.2	Method of measurement	37
9.8.3	Limit	38
9.9	Spurious emissions	38
9.9.1	Definition.....	38
9.9.2	Method of measuring the power level	38
9.9.3	Limit	38
9.10	Receiver radiated spurious emissions.....	38
9.10.1	Definition.....	38
9.10.2	Method of measurements.....	38
9.10.3	Limit	39
9.11	Receiver residual noise level	39
9.11.1	Definition.....	39
9.11.2	Method of measurement	39
9.11.3	Limit	39
9.12	Squelch operation.....	39
9.12.1	Definition.....	39
9.12.2	Method of measurement	40
9.12.3	Limits.....	40
9.13	Squelch hysteresis	40
9.13.1	Definition.....	40
9.13.2	Method of measurement	40
9.13.3	Limit	40
9.14	Multiple watch characteristic	41
9.14.1	Definition.....	41
9.14.2	Method of measurement	41
9.14.3	Limits.....	41
10	Receiver for DSC decoder.....	41
10.1	Maximum usable sensitivity.....	41
10.1.1	Definition.....	41
10.1.2	Method of measurement	41
10.1.3	Limits.....	42
10.2	Co-channel rejection.....	42
10.2.1	Definition.....	42
10.2.2	Method of measurement	42
10.2.3	Limits.....	42
10.3	Adjacent channel selectivity.....	42
10.3.1	Definition.....	42
10.3.2	Method of measurement	42
10.3.3	Limits.....	42
10.4	Spurious response and blocking immunity.....	43
10.4.1	Definition.....	43
10.4.2	Method of measurement	43
10.4.3	Limits.....	43
10.5	Intermodulation response	43
10.5.1	Definition.....	43
10.5.2	Method of measurement	43
10.5.3	Limits.....	43
10.6	Dynamic range	44
10.6.1	Definition.....	44
10.6.2	Method of measurement	44
10.6.3	Limit	44
10.7	Spurious emissions	44
10.7.1	Definition.....	44
10.7.2	Method of measuring the power level	44
10.7.3	Limit	44
10.8	Simultaneous reception	44

iTech STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 025 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016>

10.8.1	Definition.....	44
10.8.2	Method of measurement	44
10.8.3	Limits.....	45
10.9	DSC Signalling.....	45
10.9.1	Display.....	45
10.9.2	Watchkeeping receiver	45
10.9.3	Individual DSC calls.....	45
10.9.4	All ships calls.....	45
10.9.5	DSC call functionality	45
10.9.6	DSC message composition	45
10.9.7	Prioritized wait.....	45
10.9.8	Alarms	45
10.9.9	Standby	45
10.9.10	Sending distress automated requirements	45
10.9.11	Display- sending distress	45
10.9.12	Distress button sub procedure.....	46
10.9.13	Transmission of the alert attempt.....	46
10.9.14	Updating position.....	46
10.9.15	Handling received DSC messages - sending distress.....	46
10.9.16	Alarms - sending distress	46
10.9.17	Determining subsequent communications - sending distress.....	46
10.9.18	Automated tuning - sending distress	46
10.9.19	Cancelling the distress alert	46
10.9.20	Acknowledgements - sending distress	46
10.9.21	Termination - sending distress	46
10.9.22	Warnings - sending distress	46
10.9.23	Tasks - receiving distress	46
10.9.24	Display - receiving distress.....	46
10.9.25	Handling received DSC messages - receiving distress	46
10.9.26	Alarms - receiving distress	47
10.9.27	Determining subsequent communications - receiving distress	47
10.9.28	Automated tuning - receiving distress	47
10.9.29	Acknowledgements - receiving distress	47
10.9.30	Termination - receiving distress.....	47
10.9.31	Warnings - receiving distress.....	47
10.9.32	Tasks - sending non distress	47
10.9.33	Display - sending non distress	47
10.9.34	Handling received DSC messages - sending non distress.....	47
10.9.35	Alarms - sending non distress.....	47
10.9.36	Automated tuning - sending non distress	47
10.9.37	Delayed acknowledgements - sending non distress	47
10.9.38	Termination - sending non distress	47
10.9.39	Warnings - sending non distress	47
10.9.40	Tasks - receiving non distress	48
10.9.41	Display - receiving non distress	48
10.9.42	Handling received DSC messages - receiving non distress	48
10.9.43	Alarms - receiving non distress.....	48
10.9.44	Automated tuning - receiving non distress	48
10.9.45	Acknowledgements - receiving non distress.....	48
10.9.46	Termination - receiving non distress.....	48
10.9.47	Warnings - receiving non distress.....	48
10.9.48	Communication automated procedure	48
10.9.49	Tasks - communication	48
10.9.50	Display - communication.....	48
10.9.51	Handling received DSC messages - communication	48
10.9.52	Tuning of the receiver and transmitter - communication.....	48
10.9.53	Termination - communication.....	48
10.9.54	Tasks of handling incoming calls while engaged	49
10.9.55	Termination of automated procedures	49
10.9.56	Actions after termination of an automated procedure.....	49
10.9.57	Putting automated procedures on hold.....	49
10.9.58	Controlling non-terminated automated procedures on hold.....	49

11	Testing for compliance with technical requirements.....	49
11.1	Test conditions, power supply and ambient temperatures.....	49
11.2	Interpretation of the measurement results	49
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	51
Annex B (normative):	Measuring receiver for adjacent channel power measurement.....	54
B.1	Power measuring receiver specification.....	54
B.1.1	General	54
B.1.2	IF filter	54
B.1.3	Attenuation indicator.....	55
B.1.4	r.m.s. value indicator	55
B.1.5	Oscillator and amplifier.....	55
Annex C (informative):	Bibliography.....	56
History		57

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 025 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/d37e73ae-b3db-4376-8523-c7712b375274/sist-en-301-025-v2-1-1-2016>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared in reply to the Commission's standardisation request Commission Implementing Decision C(2015) 5376 final of 04.08.2015 to provide a means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment.

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in tables A.1 and A.2 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

National transposition dates

Date of adoption of this EN:	SIST EN 301 025 V2.1.1:2016	18 December 2015
Date of latest announcement of this EN (doa):	75274/sist-en-301-025-v2-1-1-2016	31 March 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):		30 September 2016
Date of withdrawal of any conflicting National Standard (dow):		30 September 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document covers the minimum requirements for general communication for shipborne fixed installations using a VHF radiotelephone operating in certain frequency bands allocated to the maritime mobile service using either 25 kHz or 25 kHz and 12,5 kHz channels and associated equipment for DSC - class D.

These requirements include the relevant provisions of the ITU Radio Regulations, appendix 18 [1], Recommendations ITU-R M.493-13 [3] (where class D is defined), M.825-3 [i.4] and incorporate the relevant guidelines of the IMO as detailed in IMO Circular MSC/Circ-803 [i.1].

The present document also specifies technical characteristics, methods of measurement and required test results.

The present document contains requirements to demonstrate that "... *Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*" [i.3] and that "...*radio equipment supports certain features ensuring access to emergency services*" [i.3].

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Directive 2014/53/EU [i.3] may apply to equipment within the scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ITU Radio Regulations, appendix 18 (2012): "Table of transmitting frequencies in the VHF maritime mobile band".
- [2] ETSI EN 300 338-3 (V1.1.1) (02-2010): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service Part 3: Class D DSC".
- [3] Recommendation ITU-R M.493-13 (2009): "Digital selective-calling system for use in the maritime mobile service".
- [4] Recommendation ITU-R M.1084-5 (2012): "Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service".
- [5] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] IMO Circular MSC/Circ-803: "Participation of non-SOLAS ships in the Global Maritime Distress and Safety System (GMDSS)".
- [i.2] Recommendation ITU-R SM.332-4: "Selectivity of receivers".
- [i.3] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.4] Recommendation ITU-R M.825-3 (1998): "Characteristics of a transponder system using digital selective calling techniques for use with vessel traffic services and ship-to-ship identification".
- [i.5] Recommendation ITU-T O.41 (1994): "Psophometer for use on telephone-type circuits".
- [i.6] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] ETSI TR 100 028-2 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.8] ETSI TS 101 570-3 (V1.1.1) (06-2012): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Interoperability Testing for Maritime Digital Selective Calling (DSC) Radios; Part 3: Class D Test Descriptions".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

block: inhibit a function by making it inaccessible from the user interface

carrier frequency: frequency to which the transmitter or receiver is tuned

class D: intended to provide minimum facilities for VHF DSC distress, urgency and safety as well as routine calling and reception, not necessarily in full accordance with IMO GMDSS carriage requirements for VHF installations

NOTE: See Recommendation ITU-R M.493-13 [3].

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

frequency deviation: difference between the instantaneous frequency of the modulated RF signal and the carrier frequency

G2B: phase-modulation with digital information, with a sub-carrier for DSC operation

G3E: phase-modulation (frequency modulation with a pre-emphasis of 6 dB/octave) for speech

modulation index: ratio between the frequency deviation and the frequency of the modulation signal

3.2 Symbols

For the purposes of the present document, the following symbols apply:

λ lambda (wavelength)

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ad	amplitude difference
AIS	universal shipborne Automatic Identification System
d.c.	direct current
DSC	Digital Selective Calling
e.m.f.	electromotive force
EFTA	European Free Trade Association
EUT	Equipment Under Test
fd	frequency difference
FM	Frequency Modulation
FSK	Frequency Shift Keying
IF	Intermediate Frequency
IMO	International Maritime Organization
ITU-R	International Telecommunication Union, Radiocommunications sector
ITU-T	International Telecommunication Union, Telecommunications sector
MPFD	Maximum Permissible Frequency Deviation
ppm	parts per million
r.m.s.	root mean square
RF	Radio Frequency
SINAD	Signal + Noise + Distortion to Noise + Distortion
SOLAS	Safety Of Life And Sea
VHF	Very High Frequency

STANDARD PREVIEW
(standards.itc.ch.ai)

SIST EN 301 025 V2.1.1:2016

<https://standards.iteh.ai/catalog/standards/sis/0/d57e75ae-b5db-4376-8523-877090000000/etsi-en-301-025-v2-1-1-2016>

4 General and operational requirements

4.1 General

The manufacturer shall declare that compliance to the requirements of clause 4 is achieved and shall provide relevant documentation.

4.2 Composition

The equipment shall, as a minimum, include:

- a VHF radiotelephone transmitter;
 - a VHF radiotelephone receiver; and
- either:
- a dedicated channel 70 watchkeeping receiver for DSC decoder;
 - a DSC encoder; and
 - a DSC decoder;
- or:
- a dedicated DSC controller interface.

4.3 Construction

All controls shall be of sufficient size to enable the usual control functions to be easily performed and the number of controls should be the minimum necessary for simple and satisfactory operation.

Adequately detailed operating instructions shall be provided with the equipment.

The equipment shall be capable of operating on single frequency and two-frequency channels with manual control (simplex).

The equipment shall be able to operate on all channels defined in appendix 18 to the Radio Regulations [1], noting in particular footnotes m) and e).

Additional VHF channels for maritime use outside those defined by appendix 18 to the Radio Regulations may also be provided where permitted by relevant administrations. These channels shall be clearly identified for use as relating to the relevant administration(s) and accessed through (a) positive action(s) for enabling use of this/these channel(s) but means shall be provided to block any or all of these additional channels if required by the relevant administration(s).

If 12,5 kHz channels are implemented in the equipment it shall be in accordance with Recommendation ITU-R M.1084-5 [4].

The equipment shall be so designed that use of channel 70 for purposes other than DSC is prevented, and that use of channels AIS1 and AIS2 for purposes other than AIS is prevented.

It shall not be possible to transmit while any frequency synthesizer used within the transmitter is out of lock.

It shall not be possible to transmit during channel switching operations.

4.4 Controls and Indicators

The user shall not have access to any control which, if wrongly set, might impair the technical characteristics of the equipment.

If the equipment can be operated from more than one position, the control unit provided at the position from where the vessel is normally navigated shall have priority and the individual control units shall be provided with an indicator showing whether the equipment is in operation.

The following controls or functions shall be provided:

- on/off switch for the entire installation with a visual indication that the installation is in operation;
- a manual non-locking push-to-talk switch to operate the transmitter with a visual indication that the transmitter is activated and facilities to limit the transmission time to a maximum of 5 min. A short audible alarm and a visual indication may be provided to show when the transmission will be automatically terminated within the next 10 s. It shall be possible to reoperate the push to talk switch and reactivate the transmitter after a 10 s period;
- a switch for reducing transmitter output power to no more than 1 W with a visual indication that low power is selected;
- an audio-frequency power volume control;
- a squelch control;
- a control for dimming to extinction the equipment illumination with the exception of a visual indicator (see clause 4.6);
- controls for multiple watch facilities, if provided (see clause 5.4).

The equipment shall have means to select manually a channel and shall indicate the designator (where applicable), as shown in appendix 18 to the Radio Regulations [1], of the channel at which the installation is set. The channel designator shall be legible irrespective of the external lighting conditions.