



SLOVENSKI STANDARD
SIST EN 301 783 V2.1.1:2016
01-april-2016

Komercialno dostopna amaterska radijska oprema - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU

Commercially available amateur radio equipment - Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 301 783 V2.1.1**
<https://standards.iteh.ai/catalog/standards/sist/5216d366-4666-4adf-bc81-3f0f584eb3f3/sist-en-301-783-v2-1-1-2016>

ICS:

33.060.01	Radijske komunikacije na splošno	Radiocommunications in general
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 301 783 V2.1.1:2016 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 783 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/5216d56b-46b6-4adf-bc81-3f0f584eb3f3/sist-en-301-783-v2-1-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/5216d56b-46b6-4adf-bc81-3f0f584eb3f3/sist-en-301-783-v2-1-1-2016>

ETSI EN 301 783 V2.1.1 (2016-01)



**Commercially available amateur radio equipment;
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU**

[SIST EN 301 783 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/5216d56b-46b6-4adf-bc81-3f0f584eb3f3/sist-en-301-783-v2-1-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/5216d56b-46b6-4adf-bc81-3f0f584eb3f3/sist-en-301-783-v2-1-1-2016>

Reference

REN/ERM-TG26-139

Keywords

amateur, EMC, mobile, radio, service**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 783 V2.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/5216d56b-46b6-4adf-bc81-3f0f584eb710/etsi-en-301-783-v2-1-1-2016>
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definitions, symbols and abbreviations	7
3.1 Definitions.....	7
3.2 Symbols.....	7
3.3 Abbreviations	7
4 General and operational requirements.....	7
4.1 Environmental profile.....	7
4.2 EUT test frequencies	7
4.3 Test power source.....	8
4.3.0 General requirements.....	8
4.3.1 Mains voltage.....	8
4.3.2 Regulated lead-acid battery power sources used on vehicles.....	8
4.3.3 Other power sources	8
4.4 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)	8
4.5 Test load (artificial antenna).....	8
4.6 PEP.....	8
4.7 Transmitter automatic shut-off facility.....	9
4.8 Arrangement for analogue test signals at the input of the transmitter	9
4.9 Arrangement for test signals at the input of the receiver.....	9
4.10 Characteristics of test signals at the input of the receiver.....	9
4.11 Characteristics of test signals at the input of the transmitter.....	9
4.11.0 General requirements.....	9
4.11.1 Analogue signals.....	10
4.11.2 Digital signals	10
4.12 Reference bandwidths for spurious measurements.....	10
4.13 Transmit exclusion bandwidths for spurious measurements	10
4.14 Interpretation of the measurement results	11
5 Technical requirements - Transmitters.....	11
5.1 Maximum power (PX) (conducted).....	11
5.1.0 General requirement	11
5.1.1 Definition.....	11
5.1.2 Method of measurement	11
5.2 Unwanted emissions in the spurious domain.....	12
5.2.1 Definition.....	12
5.2.2 Method of measurement	12
5.2.2.1 Method of measuring conducted spurious emissions with an artificial antenna	12
5.2.2.2 Method of measuring the effective radiated power with an external antenna connector	12
5.2.2.3 Method of measuring the effective radiated power with an integral antenna.....	13
5.2.3 Limits.....	13
5.3 Spurious radiations	14
5.3.1 Definition.....	14
5.3.2 Methods of measurement.....	15
5.3.2.1 Method of measuring the power level in a specified load.....	15
5.3.2.2 Method of measuring the effective radiated power	15
5.3.2.3 Method of measuring the effective radiated power	16
5.3.3 Limits.....	16
6 Technical requirements - Receivers	16
6.1 Maximum usable sensitivity.....	16

6.1.1	Definition.....	16
6.1.2	Method of measurement	17
6.1.2.1	Amplitude modulation AM.....	17
6.1.2.2	Single sideband modulation SSB	17
6.1.2.3	Frequency modulation FM.....	17
6.1.2.4	Other types of modulation.....	17
6.1.3	Limits.....	17
6.2	Adjacent channel selectivity.....	17
6.2.1	Definition.....	17
6.2.2	Method of measurement	17
6.2.2.1	Amplitude modulation AM.....	17
6.2.2.2	Single sideband modulation SSB	18
6.2.2.3	Frequency modulation FM.....	18
6.2.2.4	Other types of modulation.....	18
6.2.3	Limits.....	18
6.3	Conducted RF immunity	18
6.3.1	Definition.....	18
6.3.2	Method of measurement	19
6.3.2.1	Method of measurement (analogue).....	19
6.3.2.2	Method of measurement (digital).....	19
6.3.2.3	Unwanted signal parameters (analogue and digital)	20
6.3.3	Limit	20
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	21
History		22

ITEH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 783 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/5216d56b-46b6-4adf-bc81-3f0f584eb3f3/sist-en-301-783-v2-1-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/5216d56b-46b6-4adf-bc81-3f0f584eb3f3/sist-en-301-783-v2-1-1-2016>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared in reply to the Commission's standardisation request Commission Implementing Decision C(2015) 5376 final of 04.08.2015 to provide a means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment.

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

National transposition dates

Date of adoption of this EN:	SIST EN 301 783 V2.1.1:2016	18 December 2015
Date of latest announcement of this EN (doa):	https://standards.iteh.ai/catalog/standards/sist/5216d56b-46b6-4adf-bc81-558eb3f3/sist-en-301-783-v2-1-1-2016	31 March 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):		30 September 2016
Date of withdrawal of any conflicting National Standard (dow):		30 September 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document applies to the following radio equipment types:

- Radio equipment intended to be used by radio amateurs within the meaning of article 1, definition 53, of the International Telecommunications Union (ITU) Radio Regulations [1] and which is available commercially.

NOTE: This sort of equipment is traditionally supplied with an antenna connector.

The present document also specifies technical characteristics, methods of measurement and required test results.

The present document contains requirements to demonstrate that "... *Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*" [i.5].

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Radio Equipment Directive [i.5] may apply to equipment within the scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ITU Radio Regulations (2012).
- [2] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Recommendation ITU-R SM.329-10 (2003): "Unwanted emissions in the spurious domain".
- [i.2] CEPT/ERC/Recommendation 74-01 (2011): "Unwanted emissions in the spurious domain".
- [i.3] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.4] Standardisation request M/536: "Commission implementing decision of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council".

- [i.5] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Single SideBand (SSB): any emission using Single SideBand (SSB) suppressed carrier format

3.2 Symbols

For the purposes of the present document, the following symbols apply:

Bn	Necessary bandwidth of an emission
PX	Maximum PEP

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AM	Amplitude Modulation (A3E)
CBW	Channel BandWidth
CSP	Channel Spacing
DC	Direct Current
EUT	Equipment Under Test
FM	Frequency Modulation (F3E)
HF	High Frequency
ITU-R	International Telecommunication Union, Radiocommunications sector
PEP	Peak Envelope Power
RBW	Resolution BandWidth
RF	Radio Frequency
SINAD	(Signal + Noise + Distortion) / (Noise + Distortion)
SSB	Single SideBand (J3E)
Tx	Transmit
UHF	Ultra High Frequency
VHF	Very High Frequency

4 General and operational requirements

4.1 Environmental profile

The environmental profile for operation of the equipment shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the required operational environmental profile.

4.2 EUT test frequencies

Testing shall be performed with the EUT set to frequencies as follows:

- single-band equipment: test at the centre of the band;
- double-band equipment: test at the centre of both bands;
- HF multi-band equipment or VHF/UHF multi-band equipment: test at the centre of the lowest, the centre of the middle, and the centre of the highest band;

- HF/VHF, HF/UHF or HF/VHF/UHF combined equipment: test at the centre of the lowest HF band, the centre of the middle HF band, the centre of the highest HF band, the centre of the lowest VHF/UHF band, the centre of the middle VHF/UHF band, and the centre of the highest VHF/UHF band.

4.3 Test power source

4.3.0 General requirements

During testing the power source of the equipment shall be replaced by a test power source capable of producing the nominal supply voltage for the equipment as declared by the manufacturer. The internal impedance of the test power source shall be low enough for its effect on the test results to be negligible. For the purpose of tests, the voltage of the power source shall be measured at the input terminals of the equipment.

For battery operated equipment the battery shall be removed and the test power source shall be applied as close to the battery terminals as practicable.

During tests of DC powered equipment the power source voltages shall be maintained within a tolerance of $< \pm 1\%$ relative to the voltage at the beginning of each test. The value of this tolerance is critical for power measurements, using a smaller tolerance will provide better measurement uncertainty values.

4.3.1 Mains voltage

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage or any of the declared voltages for which the equipment was designed.

The frequency of the test power source corresponding to the ac mains shall be between 49 Hz and 51 Hz.

4.3.2 Regulated lead-acid battery power sources used on vehicles

When the radio equipment is intended for operation from the usual types of regulated lead-acid battery power source used on vehicles the normal test voltage shall be 1,1 times the nominal voltage of the battery (for nominal voltages of 6 V and 12 V, these are 6,6 V and 13,2 V respectively).

4.3.3 Other power sources

For operation from other power sources or types of battery (primary or secondary), the normal test voltage shall be that declared by the equipment manufacturer.

4.4 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)

Where equipment has an internal 50 Ω connector it shall be permitted to perform the tests at this connector.

Equipment may also have a temporary internal 50 Ω connector installed for the purposes of testing.

No connection shall be made to any internal permanent or temporary antenna connector during the performance of radiated emissions measurements, unless such action forms an essential part of the normal intended operation of the equipment, as declared by the manufacturer.

4.5 Test load (artificial antenna)

For conducted measurements of the transmitter, a power attenuator ("artificial antenna") shall be used, exhibiting a substantially non-reactive, non-radiating load of 50 Ω to the antenna connector and capable of dissipating the transmitter output power.

4.6 PEP

The PEP is the average power in watts supplied to the artificial antenna by a transmitter during one RF cycle at the highest crest of the modulation envelope. For practical purposes the methods of measurements in clause 5.1 should be used.

4.7 Transmitter automatic shut-off facility

If the equipment is fitted with an automatic transmitter shut-off facility it shall be made inoperative for the duration of the type test, unless it has to be left operative to protect the equipment.

4.8 Arrangement for analogue test signals at the input of the transmitter

For the purpose of the present document, in the case of analogue equipment, the transmitter audio frequency modulation signal shall be applied to the terminals of the audio input connector with any microphone disconnected, unless otherwise stated.

4.9 Arrangement for test signals at the input of the receiver

RF test signal sources which are applied to the receiver shall present an impedance of 50 Ω to the receiver input. This requirement shall be met irrespective of whether one or more signals using a combining network are applied to the receiver simultaneously.

The levels of the test signals shall be expressed in terms of the emf at the receiver input connector.

The effects of any intermodulation products and noise produced in the test signal sources shall be negligible.

4.10 Characteristics of test signals at the input of the receiver

Wanted RF test signals applied to the receiver shall have the modulation characteristics as specified in table 1.

Table 1: Wanted test signal

Mode	Units	Modulation
AM	60	% AM (1 kHz)
FM	60	% of the maximum permissible frequency deviation (1 kHz)
SSB	1 kHz offset	None
Other modes	as declared by the manufacturer	as declared by the manufacturer

Table 2: Unwanted test signal

Mode	Units	Modulation
AM	60	% AM (400 Hz)
FM	60	% of the maximum permissible frequency deviation (400 Hz)
SSB	Offset specified by test	None
Other modes	as declared by the manufacturer	as declared by the manufacturer

4.11 Characteristics of test signals at the input of the transmitter

4.11.0 General requirements

The manufacturer shall declare details of the modulation scheme used and identify how the percentage modulation can be measured or specified.

Equipment capable of transmission of digital information shall be tested with modulation as specified in clause 4.11.2. Equipment using analogue transmission shall be tested with modulation as specified in clause 4.11.1. Equipment capable of both analogue and digital transmission shall be tested separately in each mode.