

## SLOVENSKI STANDARD SIST ISO 22514-2:2014

01-januar-2014

Nadomešča: SIST ISO 21747:2006

Statistične metode za obvladovanje procesov - Sposobnost in delovanje - 2. del: Procesne sposobnosti in delovanje časovno odvisnih modelnih procesov

Statistical methods in process management - Capability and performance - Part 2: Process capability and performance of time-dependent process models

# iTeh STANDARD PREVIEW (standards.iteh.ai)

Méthodes statistiques dans la gestion de processus - Aptitude et performance - Partie 2: Aptitude de processus et performance des modèles de processus dépendants du temps https://standards.iteh.ai/catalog/standards/sist/889979f1-5c59-4d70-b9ff-

aeba998ef2a8/sist-iso-22514-2-2014

Ta slovenski standard je istoveten z: ISO 22514-2:2013

## <u>ICS:</u>

03.120.30 Uporaba statističnih metod

Application of statistical methods

SIST ISO 22514-2:2014

en



# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 22514-2:2014 https://standards.iteh.ai/catalog/standards/sist/889979f1-5c59-4d70-b9ffaeba998ef2a8/sist-iso-22514-2-2014

#### SIST ISO 22514-2:2014

# INTERNATIONAL STANDARD

# ISO 22514-2

First edition 2013-09-01

## Statistical methods in process management — Capability and performance —

Part 2:

# Process capability and performance of time-dependent process models

S Méthodes statistiques dans la gestion de processus — Aptitude et performance —

Pa<u>stie</u> 2: <u>Aptitude de pr</u>ocessus et performance des modèles de https://standards.iteh.processus.dépendants.du/temps</u>)-4d70-b9ffaeba998et2a8/sist-iso-22514-2-2014



Reference number ISO 22514-2:2013(E)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 22514-2:2014 https://standards.iteh.ai/catalog/standards/sist/889979f1-5c59-4d70-b9ffaeba998ef2a8/sist-iso-22514-2-2014



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Page

## Contents

Fore	word		iv
Intro	oductio	n	v
1	Scop	е	
2	Norn	native references	
3	<b>Term</b> 3.1 3.2	<b>is, definitions, symbols and abbreviated terms</b> Symbols Abbreviations	<b>1</b> 1 2
4	Proc	ess analysis	
5	Time	e-dependent distribution models	
6	<b>Proc</b> 6.1 6.2 6.3	ess capability and performance indices Methods for determination of performance and capability indices — Overview One-sided specification limits Use of different calculation methods	<b>15</b> 15 18 20
7	Repo	orting process performance/capability indices	
Bibli	iograph	y	

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 22514-2:2014

https://standards.iteh.ai/catalog/standards/sist/889979f1-5c59-4d70-b9ffaeba998ef2a8/sist-iso-22514-2-2014

#### ISO 22514-2:2013(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 96, *Applications of statistical methods*, Subcommittee SC 4, *Applications of statistical methods in process management*.

This first edition of ISO 22514-2 cancels and replaces ISO 21747:2006, of which it constitutes a technical revision.

ISO 22514 consists of the following parts, Stander the general title Statistical methods in process management — Capability and performance i/catalog/standards/sist/889979f1-5c59-4d70-b9ffacba998ef2a8/sist-iso-22514-2-2014

- Part 1: General principles and concepts
- Part 2: Process capability and performance of time-dependent process models
- Part 3: Machine performance studies for measured data on discrete parts
- Part 4: Process capability estimates and performance measures
- Part 5: Process capability statistics for attribute characteristics
- Part 6: Process capability statistics for characteristics following a multivariate normal distribution
- Part 7: Capability of measurement processes
- Part 8: Machine performance of a multi-state production process

## Introduction

Many standards have been created concerning the quality capability/performance of processes by international, regional and national standardization bodies and also by industry. All of them assume that the process is in a state of statistical control, with stationary, normally distributed processes. However, a comprehensive analysis of production processes shows that, over time, it is very rare for processes to remain in such a state.

In recognition of this fact, this part of ISO 22514 provides a framework for estimating the quality capability/performance of industrial processes for an array of standard circumstances. These circumstances are categorized based on the stability of the mean and variance, as to whether they are constant, changing systematically, or changing randomly. As such, the quality capability/performance can be assessed for very differently shaped distributions with respect to time.

In other parts of ISO 22514 more detailed information about calculations of indices can be found. It should be noted that where the capability indices given in this part of ISO 22514 are computed they only form point estimates of their true values. It is therefore recommended that wherever possible the indices' confidence intervals are computed and reported.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 22514-2:2014</u> https://standards.iteh.ai/catalog/standards/sist/889979f1-5c59-4d70-b9ffaeba998ef2a8/sist-iso-22514-2-2014



# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 22514-2:2014 https://standards.iteh.ai/catalog/standards/sist/889979f1-5c59-4d70-b9ffaeba998ef2a8/sist-iso-22514-2-2014

# Statistical methods in process management — Capability and performance —

## Part 2: **Process capability and performance of time-dependent process models**

## 1 Scope

2

This part of ISO 22514 describes a procedure for the determination of statistics for estimating the quality capability or performance of product and process characteristics. The process results of these quality characteristics are categorized into eight possible distribution types. Calculation formulae for the statistical measures are placed with every distribution.

The statistical methods described in this part of ISO 22514 only relate to continuous quality characteristics. They are applicable to processes in any industrial or economical sector.

NOTE This method is usually applied in case of a great number of serial process results, but it can also be used for small series (a small number of process results). **PREVIEW** 

# Normative references (standards.iteh.ai)

The following documents, in whole of in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3534-2, Statistics — Vocabulary and symbols — Part 2: Applied statistics

ISO 5479, Statistical interpretation of data — Tests for departure from the normal distribution

ISO 22514-1, Statistical methods in process management — Capability and performance — Part 1: General principles and concepts

## 3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms and definitions given in ISO 3534-2 and ISO 22514-1, and the following symbols and abbreviated terms, apply.

### 3.1 Symbols

Cp	process capability index
C <sub>pk</sub>	minimum process capability index
$C_{\mathrm{pk}L}$	lower process capability index
$C_{\mathrm{pk}U}$	upper process capability index
<i>C</i> 4	constant based on subgroup size <i>n</i>
Δ	dispersion of the process

#### SIST ISO 22514-2:2014

## ISO 22514-2:2013(E)

$\Delta_{\rm L}$	difference between $X_{\rm mid}$ and $X_{0,135\%}$ of the distribution of the product characteristic
$\Delta_{\rm U}$	difference between $X_{99,865\%}$ and $X_{mid}$ of the distribution of the product characteristic
<i>d</i> <sub>2</sub>	constant based on subgroup size <i>n</i>
k	number of subgroups of the same size <i>n</i>
μ	average location of the process
L	lower specification limit
M <sub>l,d</sub>	Calculation methods with location method label $l$ and dispersion method label $d$
Ν	sample size
$p_L$	lower fraction nonconforming
$p_{\mathrm{t}}$	total fraction nonconforming
р <sub>U</sub>	upper fraction nonconforming
Pp	process performance index
P <sub>pk</sub>	minimum process performance index
P <sub>pkL</sub>	lower process performance index DARD PREVIEW
$P_{\mathrm{pk}U}$	upper process performance transdards.iteh.ai)
$R_i$	range of the <i>i</i> th subgroup <u>SIST ISO 22514-2:2014</u>
S	https://standards.iteh.ai/catalog/standards/sist/889979f1-5c59-4d70-b9ff- standard deviation, realized value action/standards/sist-iso-22514-2-2014
σ	standard deviation, population
S	standard deviation, sample statistic
$S_i$	observed sample standard deviation of the <i>i</i> th subgroup
St	standard deviation, with the subscript "t" indicating total standard deviation
U	upper specification limit
<i>X</i> 0,135 %	0,135 % distribution quantile
<i>X</i> 99,865 %	99,865 % distribution quantile
<i>X</i> <sub>50 %</sub>	50 % distribution quantile
X <sub>mid</sub>	distribution midpoint
3.2 Abbre	viations

- ANOVA analysis of variance
- SPC statistical process control

### 4 Process analysis

The purpose of process analysis is to obtain knowledge of a process. This knowledge is necessary for controlling the process efficiently and effectively so that the products realized by the process fulfil the quality requirement. It is a general assumption of this part of ISO 22514 that a process analysis has been carried out and subsequent process improvements have been implemented.

The behaviour of a characteristic under consideration can be described by the distribution, the location, the dispersion and the shape, parameters of which are time-dependent functions, in general. Different models of such resulting distributions the parameters of which are time-dependent functions are discussed in <u>Clauses 6</u> and <u>7</u>. To indicate whether a time-dependent distribution model fits, statistical methods [e.g. estimating parameters, analysis of variance (ANOVA)] including graphical tools (e.g. probability plots, control charts) are used.

The values of the characteristics under consideration are typically determined on the basis of samples taken from the process flow. The sample size and frequency should be chosen depending on the type of process and the type of product so that all important changes are detected in time. The samples should be representative for the characteristic under consideration. To asses the stability of the process a control chart should be used. Information on the use of control charts can be found in ISO 7870-2.

### 5 Time-dependent distribution models

The instantaneous distribution characterizes the behaviour of the characteristic under investigation during a short interval. Usually, it is the time interval during which the sample (e.g. the subgroup) can be taken from the process. Observing the process continuously in time for a longer time interval the output from the process is called the resulting process distribution and it is described by a corresponding time-dependent distribution model that reflects **arcs.tten.al**)

- the instantaneous distribution of the characteristic under consideration, and
- the changes of its location, dispersion and shape parameters during the time interval of process observation.

In practice, the resulting distribution can be represented by the whole data set, e.g. when SPC is applied, by all subgroups gained during the interval of the process observation.

Time-dependent distribution models can be classified into four groups according to whether the location and dispersion moments are constant or changing (see <u>Table 1</u>).

- a) A process whose location and dispersion are constant is in time-dependent distribution model A. In this case only, all the means and variances of the instantaneous distributions are equal to each other and they are equal to the resulting distribution.
- b) If the dispersion of a process is changing with time, but the location stays constant, the process is said to be in time-dependent distribution model B.
- c) If the dispersion is constant, but the location is changing, we have time-dependent distribution model C.
- d) Otherwise, we have time-dependent distribution model D.

Process average μ(t)	iation s(t) Constant	It Short Normal distributed distributed							Resulting	t Resulting Any shap									
		Α	A2		T OIN	nor normal distributed	ed distributed – unimodal			oe – unimodal	oe - unimodal								
	Not constant			Location		Short time distribu- tion	tand	Resulting distribution	<u>S</u> .ai/ca ba99	Resulting distribution	SO 22514-2:2014 g/standards/sist/889979f1-5c59-4d70-b9ff a8/sist-iso-22514-2-2014								
			C1	Random		Normal distributed	el	discributed	A TA	N	DARD PREVIEW ards.iteh.ai)								
		C	C2	Random		Normal distributed	Not	normal distrib- uted – unimodal		Anvs									
														C3	Systematic	(e.g. trend)	Normal distributed		Any shape
			C4	Systematic and random	(e.g. lot to lot)	Normal distributed		Any shape (e.g. multimodal)											

Table 1 — Classification of time-dependent distribution models

ISO 22514-2:2013(E)