

ETSI EN 300 175-3 V2.7.1 (2017-11)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard available at
https://standards.iteh.ai/catalog/standards/sis/23c0bbae-ac38-4fb9-9cb4-b2302c2c45f1/etsi-en-300-175-3-v2-7-1-2017-11

Reference

REN/DECT-00307-3

KeywordsDECT, IMT-2000, MAC, mobility, radio, TDD,
TDMA**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	16
Foreword.....	16
Modal verbs terminology.....	16
1 Scope	17
2 References	17
2.1 Normative references	17
2.2 Informative references.....	18
3 Definitions, symbols and abbreviations	19
3.1 Definitions.....	19
3.2 Symbols and abbreviations.....	19
4 Description of the MAC layer	22
4.1 MAC layer reference model	22
4.1.1 General.....	22
4.1.2 Cluster Control Function (CCF)	23
4.1.3 Cell Site Functions (CSF).....	23
4.1.4 Relationship to physical layer elements.....	23
4.2 Frame and multiframe structures.....	24
4.2.1 General.....	24
4.2.2 Frame structure	24
4.2.3 Multiframe structure	25
4.3 State definitions.....	26
4.3.1 PP states.....	26
4.3.2 RFP states	27
5 Overview of MAC layer services.....	28
5.1 General	28
5.1.0 Service groupings	28
5.1.1 Broadcast Message Control (BMC).....	28
5.1.2 Connectionless Message Control (CMC).....	28
5.1.3 Multi-Bearer Control	28
5.2 Service descriptions.....	28
5.2.1 Common functions.....	28
5.2.2 BMC service	29
5.2.3 CMC service	29
5.2.4 MBC services.....	29
5.3 Logical channels.....	30
5.3.0 Overview	30
5.3.1 MBC connection endpoints (MC-SAP logical channels)	30
5.3.1.1 The higher layer C-plane channels, C	30
5.3.1.2 The higher layer U-Plane channels, I	31
5.3.1.3 The higher layer U-Plane control channels, G_F and G_{FA}	31
5.3.1.4 The higher layer U-Plane channel in E+U type slots, I_{PF}	31
5.3.2 CMC endpoints (MB-SAP logical channels).....	32
5.3.2.1 The connectionless C-Plane channels, CL	32
5.3.2.2 The connectionless U-Plane channels, SI_N and SI_P	32
5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI_{PF}	32
5.3.3 BMC endpoint (MA-SAP logical channel).....	33
5.3.3.1 The slow broadcast channel, B_S	33
5.3.3.2 The ULE broadcast channel, B_U	33
5.3.4 Internal MAC control channels.....	33
5.3.4.1 The system information channel, Q	33
5.3.4.2 Identities channel, N.....	33
5.3.4.3 The MAC control channel, M	33
5.3.4.4 MAC paging channel, P	34

5.3.4.5	The Compound System Information Channel, Q_C	34
5.3.4.6	The Split Identities Channel, N_S	34
5.3.4.7	The ULE MAC Control Channel, M_U	34
5.3.4.8	The ULE Paging Channel, P_U	34
5.4	SAP definitions	35
5.4.0	General.....	35
5.4.1	MA SAP	35
5.4.2	MB SAP.....	35
5.4.3	MC SAP.....	35
5.4.4	ME SAP.....	36
5.4.5	Order of transmission.....	36
5.5	Bearer.....	36
5.5.0	General.....	36
5.5.1	Bearer types	37
5.5.2	Bearer operation.....	37
5.6	Connection oriented services.....	37
5.6.0	General.....	37
5.6.1	Connection types	38
5.6.1.0	General	38
5.6.1.1	Basic connections.....	38
5.6.1.2	Advanced connections	38
5.6.1.2.0	General	38
5.6.1.2.1	Rules for ECN selection in advanced connections	39
5.6.1.2.2	Expedited operations in advanced connections	39
5.6.1.3	Connection identifiers	39
5.6.1.4	Complementary connections	39
5.6.2	Symmetric and asymmetric connections.....	40
5.6.2.0	General	40
5.6.2.1	Symmetric connections	40
5.6.2.2	Asymmetric connections	46
5.7	Broadcast and connectionless services.....	56
5.7.0	General.....	56
5.7.1	The broadcast services	56
5.7.1.0	General	56
5.7.1.1	The continuous broadcast service	56
5.7.1.2	The non-continuous broadcast service	57
5.7.2	The connectionless services	57
5.7.2.0	General	57
5.7.2.1	Connectionless downlink services	57
5.7.2.1.0	General	57
5.7.2.1.1	Coding of TA and BA bits in connectionless downlink services	58
5.7.2.2	Connectionless uplink services	58
5.8	ULE Broadcast services	59
5.8.0	General.....	59
5.8.1	The continuous ULE broadcast service	59
6	Multiplexing.....	59
6.0	General	59
6.1	CCF multiplexing functions	59
6.2	CSF multiplexing functions.....	60
6.2.0	General.....	60
6.2.1	Bit Mappings (MAP)	65
6.2.1.0	General	65
6.2.1.1	D-field mapping (D-MAP).....	65
6.2.1.1.0	General	65
6.2.1.1.1	D-field mapping for the double slot structure (physical packet P80)	66
6.2.1.1.2	D-field mapping for the full slot structure (physical packet P32).....	66
6.2.1.1.3	D-field mapping for the short slot structure (physical packet P00)	67
6.2.1.1.4	D-field mapping for the variable slot structure (physical packet P00j)	68
6.2.1.2	A-field Mapping (A-MAP)	69
6.2.1.3	B-field Mapping (B-MAP).....	70
6.2.1.3.0	General	70

6.2.1.3.1	Unprotected format.....	70
6.2.1.3.2	Encoded protected format.....	72
6.2.1.3.3	Multisubfield protected format.....	72
6.2.1.3.4	Singlesubfield protected format switches.....	75
6.2.1.3.5	Constant-size subfield protected format.....	76
6.2.2	Time multiplexers.....	79
6.2.2.0	General.....	79
6.2.2.1	Tail MULTipleXer (T-MUX).....	79
6.2.2.1.0	General.....	79
6.2.2.1.1	T-MUX algorithm for RFP transmissions.....	80
6.2.2.1.2	T-MUX algorithm for PT transmissions.....	81
6.2.2.2	B-field control multiplexer (E/U-MUX).....	82
6.2.2.3	B-field mode multiplexer E-type and E+U-type modes.....	84
6.2.2.3.1	E-type and E+U-type modes for slots with more than one subfield.....	84
6.2.2.3.2	Half slot (j=80) modes for 2-level modulation.....	98
6.2.2.4	Priority scheme in E or E+U mode.....	99
6.2.3	MAC Encryption.....	100
6.2.4	Scrambling.....	100
6.2.5	Error control.....	102
6.2.5.0	General.....	102
6.2.5.1	R-CRC overview.....	102
6.2.5.2	R-CRC generation and checking.....	103
6.2.5.3	X-CRC overview.....	103
6.2.5.4	X-CRC generation and checking.....	104
6.2.5.5	B-CRC generation and checking.....	106
6.2.6	Broadcast controller.....	106
7	Medium access layer messages.....	106
7.0	General.....	106
7.1	Header field.....	107
7.1.1	Overview/formatting.....	107
7.1.2	Tail identification, TA, bits a_0 to a_2	107
7.1.3	The "Q1/BCK" bit, bit a_3	107
7.1.4	B-field identification, BA, bits a_4 to a_6	108
7.1.5	The "Q2" bit, bit a_7	109
7.2	Messages in the tail field.....	109
7.2.1	Overview.....	109
7.2.2	Identities information (N_T).....	110
7.2.3	System information and multiframe marker (Q_T).....	110
7.2.3.1	General.....	110
7.2.3.2	Static system information.....	111
7.2.3.2.1	General, $Q_H = 0, 1$ (hex).....	111
7.2.3.2.2	Q_H and Normal-Reverse (NR).....	111
7.2.3.2.3	Slot Number (SN).....	111
7.2.3.2.4	Start Position (SP).....	112
7.2.3.2.5	ESCAPE bit (ESC).....	112
7.2.3.2.6	Number of transceivers.....	112
7.2.3.2.7	Extended RF carrier information available (M_c).....	113
7.2.3.2.8	RF carriers available (RF-cars).....	113
7.2.3.2.9	Spare bits (SPR).....	113
7.2.3.2.10	Carrier number.....	113
7.2.3.2.11	Extended static system information available (Ext-System-Info) and spare bit.....	114
7.2.3.2.12	Primary receiver Scan Carrier Number (PSCN).....	114
7.2.3.3	Extended RF carrier information part 1.....	114
7.2.3.3.1	General, $Q_H = 2$ (hex).....	114
7.2.3.3.2	Further RF carrier extensions.....	115
7.2.3.3.3	Number of RF carriers.....	115
7.2.3.4	Fixed part capabilities.....	115
7.2.3.4.1	General, $Q_H = 3$ (hex).....	115
7.2.3.4.2	Standard capabilities.....	115
7.2.3.5	Extended fixed part capabilities.....	117
7.2.3.5.1	General, $Q_H = 4$ (hex).....	117

7.2.3.5.2	Extended Physical and MAC layer capabilities.....	117
7.2.3.5.3	Extended higher layer capabilities.....	118
7.2.3.6	Secondary access rights identities.....	118
7.2.3.6.1	General, $Q_H = 5$ (hex).....	118
7.2.3.6.2	SARI message.....	119
7.2.3.7	Multiframe number.....	119
7.2.3.7.1	General, $Q_H = 6$ (hex).....	119
7.2.3.7.2	Multiframe number.....	119
7.2.3.8	Escape.....	119
7.2.3.8.1	General, $Q_H = 7$ (hex).....	119
7.2.3.8.2	Escape information.....	119
7.2.3.9	Extended RF carrier information part 2.....	119
7.2.3.9.1	General, $Q_H = 9$ (hex).....	119
7.2.3.10	Transmit information.....	120
7.2.3.10.1	General, $Q_H = B$ (hex).....	120
7.2.3.11	Extended fixed part capabilities (part 2).....	121
7.2.3.11.1	General, $Q_H = C$ (hex).....	121
7.2.3.11.2	Extended Physical and MAC layer capabilities (part 2).....	121
7.2.3.11.3	Extended higher layer capabilities (part 2).....	122
7.2.3.12	Extended static system information.....	122
7.2.3.12.1	General, $Q_H = D$ (hex).....	122
7.2.3.12.2	Spare bits (Spare).....	122
7.2.3.12.3	RFP slot scheme info.....	122
7.2.4	Paging Tail (P_T).....	123
7.2.4.1	General format.....	123
7.2.4.1.1	P_T format for full and long page messages.....	123
7.2.4.1.2	P_T format for short page messages.....	123
7.2.4.1.3	P_T format for zero length page messages.....	123
7.2.4.1.4	P_T format for MAC_Resume and Control page message.....	123
7.2.4.2	P_T header format.....	124
7.2.4.2.1	General format.....	124
7.2.4.2.2	Bit a_8 is the extend flag.....	124
7.2.4.2.3	B_5 SDU length indication.....	125
7.2.4.3	MAC layer information for P_T	125
7.2.4.3.1	Information type.....	125
7.2.4.3.2	Fill bits / Blind long slot ($j=640 \wedge j=672$) information.....	125
7.2.4.3.3	Blind full slot information.....	126
7.2.4.3.4	Bearer description.....	126
7.2.4.3.5	Escape.....	127
7.2.4.3.6	Dummy or connectionless downlink bearer marker.....	127
7.2.4.3.7	Bearer handover/replacement and no-emission mode information.....	127
7.2.4.3.8	RFP status and modulation types.....	128
7.2.4.3.9	Active carriers.....	130
7.2.4.3.10	RFP power level.....	130
7.2.4.3.11	Blind double slot/RFP-FP interface resource information.....	131
7.2.4.3.12	Extended modulation types.....	131
7.2.5	MAC control (M_T).....	132
7.2.5.1	General format and contents.....	132
7.2.5.2	Basic connection control.....	132
7.2.5.2.1	General.....	132
7.2.5.2.2	Format for most messages.....	132
7.2.5.2.3	WAIT.....	133
7.2.5.2.4	ATTRIBUTES_T_{Req;Cfm}.....	133
7.2.5.3	Advanced connection control.....	133
7.2.5.3.1	General.....	133
7.2.5.3.2	ACCESS_REQUEST.....	134
7.2.5.3.3	BEARER_HANDOVER_REQUEST.....	134
7.2.5.3.4	CONNECTION_HANDOVER_REQUEST.....	134
7.2.5.3.5	UNCONFIRMED_ACCESS_REQUEST.....	134
7.2.5.3.6	BEARER_CONFIRM.....	135
7.2.5.3.7	WAIT.....	135
7.2.5.3.8	ATTRIBUTES_T_{Req;Cfm}.....	135

7.2.5.3.9	BANDWIDTH_T_{Req;Cfm}.....	138
7.2.5.3.10	Channel_list.....	138
7.2.5.3.11	Unconfirmed_dummy.....	139
7.2.5.3.12	Unconfirmed_handover.....	139
7.2.5.3.13	RELEASE.....	139
7.2.5.4	MAC layer test messages.....	140
7.2.5.4.0	General.....	140
7.2.5.4.1	Basic format.....	140
7.2.5.4.2	FORCE_TRANSMIT.....	141
7.2.5.4.3	LOOPBACK_DATA.....	141
7.2.5.4.4	DEFEAT_ANTENNA_DIVERSITY.....	142
7.2.5.4.5	ESCAPE.....	143
7.2.5.4.6	NETWORK_TEST.....	143
7.2.5.4.7	CLEAR_TEST_MODES.....	143
7.2.5.4.8	CHANGE_MODULATION_SCHEME.....	143
7.2.5.5	Quality control.....	144
7.2.5.5.0	General.....	144
7.2.5.5.1	Prolonged preamble diversity.....	145
7.2.5.6	Broadcast and connectionless services.....	146
7.2.5.7	Encryption control.....	146
7.2.5.8	B-field setup, first PT transmission.....	147
7.2.5.9	Escape.....	148
7.2.5.10	TARI message.....	148
7.2.5.11	REP connection control.....	148
7.2.5.11.1	General.....	148
7.2.5.11.2	Format for most messages.....	148
7.2.5.11.3	REP CHANNEL MAP REQUEST.....	149
7.2.5.11.4	REP CHANNEL MAP CONFIRM.....	149
7.2.5.12	Advanced connection control part 2.....	149
7.2.5.12.1	General.....	149
7.2.5.12.2	Short description of the advanced connection control part 2 messages.....	149
7.2.5.12.3	Format for most advanced connection control part 2 messages.....	150
7.2.5.12.4	Format for "ready for release with G _{FA} " and "expedited release with G _{FA} " messages.....	150
7.2.5.12.5	Reason codes in "ready for release with G _{FA} " and "expedited release with G _{FA} " messages.....	152
7.2.5.12.6	Format for "Null or GFACHannel transmission" message.....	153
7.3	Messages in the B-field.....	154
7.3.1	Overview.....	154
7.3.2	Advanced connection control.....	155
7.3.2.1	General format.....	155
7.3.2.2	BEARER_REQUEST.....	156
7.3.2.3	BEARER_CONFIRM.....	156
7.3.2.4	WAIT.....	157
7.3.2.5	ATTRIBUTES_B_{Req;Cfm}.....	157
7.3.2.6	BANDWIDTH_B_{Req;Cfm}.....	158
7.3.2.7	CHANNEL_LIST.....	158
7.3.2.8	UNCONFIRMED_DUMMY.....	158
7.3.2.9	UNCONFIRMED_HANDOVER.....	159
7.3.2.10	RELEASE.....	159
7.3.3	Null or I _{PF} segmentation info.....	160
7.3.3.0	General.....	160
7.3.3.1	Spare or I _{PF} segmentation info.....	161
7.3.3.2	Extended NCF bits.....	162
7.3.4	Quality control.....	162
7.3.4.1	General format.....	162
7.3.4.2	Bearer and connection control.....	162
7.3.4.3	RESET.....	164
7.3.4.4	Bearer quality in an asymmetric connection.....	164
7.3.5	Extended system information.....	165
7.3.5.1	General format.....	165
7.3.5.2	TARI messages.....	165
7.3.5.3	"no-emission" mode sync information or ULE Dummy Bearer subfield 2.....	165
7.3.5.3.0	General.....	165

7.3.5.3.1	"no-emission" mode sync information for dummy bearer.....	165
7.3.5.3.2	ULE Dummy Bearer subfield 2.....	166
7.3.5.4	ULE Dummy Bearer subfield 3.....	166
7.3.5.5	ULE Dummy Bearer subfield 0.....	166
7.3.5.6	ULE Dummy Bearer subfield 1.....	167
7.3.6	G _F channel data packet.....	167
7.3.7	Escape.....	167
8	Medium access layer primitives.....	168
8.0	General.....	168
8.1	Connection oriented service primitives.....	168
8.1.0	General.....	168
8.1.1	Connection setup: MAC_CON {req;ind;cfm}.....	168
8.1.2	Connection modification: MAC_MOD {req;ind;cfm}.....	170
8.1.3	CO data transmit ready: MAC_CO_DTR {ind}.....	171
8.1.4	CO data transfer: MAC_CO_DATA {req;ind}.....	171
8.1.5	Restart DLC: MAC_RES_DLC {ind}.....	171
8.1.6	Connection release: MAC_DIS {req;ind}.....	172
8.1.7	MAC bandwidth: MAC_BW {ind;res}.....	172
8.1.8	Encryption.....	172
8.1.8.1	Load encryption key: MAC_ENC_KEY {req}.....	172
8.1.8.2	Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm}.....	173
8.1.9	C-plane switching procedure.....	173
8.1.9.1	C-plane switching procedure: MAC_Cs_Cf {req, cfm, ind, res}.....	173
8.1.9.2	C-plane switching procedure: MAC_CsCf_END {ind}.....	173
8.2	Connectionless and broadcast service primitives.....	174
8.2.1	Paging: MAC_PAGE {req;ind}.....	174
8.2.2	Downlink connectionless: MAC_DOWN_CON {req;ind}.....	174
8.2.3	Uplink connectionless: MAC_UP_CON {req;ind;cfm}.....	175
8.2.4	"no-emission" mode.....	175
8.3	Management primitives.....	175
8.3.0	General.....	175
8.3.1	Connection control.....	175
8.3.1.1	Connection setup: MAC_ME_CON {ind}.....	175
8.3.1.2	Connection setup allowed: MAC_ME_CON_ALL {req}.....	175
8.3.1.3	Bearer release: MAC_ME_REL {req}.....	176
8.3.1.4	MBC release report: MAC_ME_REL_REP {ind}.....	176
8.3.2	System information and identities.....	176
8.3.2.1	FP information preloading: MAC_ME_RFP_PRELOAD {req}.....	176
8.3.2.2	PT information preloading: MAC_ME_PT_PRELOAD {req}.....	176
8.3.2.3	System information output: MAC_ME_INFO {ind;res}.....	176
8.3.2.4	Extended system info: MAC_ME_EXT. {req;ind;res;cfm}.....	176
8.3.3	Channel map: MAC_ME_CHANMAP {ind;res}.....	177
8.3.4	Status reports: MAC_ME_STATUS {req;ind;res;cfm}.....	177
8.3.5	Error reports: MAC_ME_ERROR {ind;res}.....	177
8.4	Flow control.....	177
8.4.1	MA SAP flow control.....	177
8.4.2	MB SAP flow control.....	177
8.4.3	MC SAP flow control.....	177
9	Broadcast and connectionless procedures.....	180
9.1	Downlink broadcast and connectionless procedures.....	180
9.1.0	General.....	180
9.1.1	Downlink broadcast procedure.....	180
9.1.1.1	Broadcast information.....	180
9.1.1.2	Channel selection for downlink broadcast services.....	180
9.1.1.3	Downlink broadcast procedure description.....	182
9.1.2	Downlink connectionless procedure.....	182
9.1.2.1	Channel selection at the RFP.....	182
9.1.2.2	Downlink connectionless procedure description.....	182
9.1.3	Paging broadcast procedure.....	182
9.1.3.0	General.....	182

9.1.3.1	RFP paging broadcasts.....	183
9.1.3.2	PP paging procedures.....	185
9.1.3.2.1	PP paging detection.....	185
9.1.3.2.2	PP paging processing.....	185
9.1.4	Downlink connectionless procedures for ULE.....	185
9.1.4.0	General.....	185
9.1.4.1	Transmission over the ULE dummy bearer.....	186
9.1.4.2	Transmission over the additional C/L bearers.....	186
9.1.4.2.0	General.....	186
9.1.4.2.1	MAC signalling.....	186
9.1.4.3	Announcement via the B _U paging channel.....	187
9.1.4.4	Routing and instance separation.....	187
9.1.4.5	Additional attributes.....	187
9.1.4.6	Encryption.....	187
9.1.4.7	Destination and addressing: unicast and multicast.....	187
9.1.4.7.0	General.....	187
9.1.4.7.1	C/L downlink unicast service.....	187
9.1.4.7.2	C/L downlink multicast service.....	188
9.1.4.7.3	Identities in C/L downlink multicast service.....	188
9.1.4.8	Scrambling.....	188
9.1.4.9	Time references for the multicast transmission.....	188
9.1.4.9.1	Time reference for transmission over the dummy bearer.....	188
9.1.4.9.2	Time reference for transmission over additional C/L bearers.....	189
9.2	Uplink connectionless procedures.....	189
9.2.1	General.....	189
9.2.2	Bearer selection for the connectionless uplink.....	189
9.2.3	Procedure for the connectionless uplink.....	190
9.2.3.1	Predicates.....	190
9.2.3.2	PT D-field construction.....	190
9.2.3.3	PT transmission sequence.....	190
9.2.3.4	FT procedure.....	191
9.3	Non-continuous broadcast procedure.....	191
9.3.0	General.....	191
9.3.1	Request for specific Q channel information.....	191
9.3.1.0	General.....	191
9.3.1.1	A-field procedure.....	191
9.3.1.2	B-field procedure.....	192
9.3.2	Request for a new dummy bearer.....	192
9.4	"No-emission" mode procedures.....	192
9.4.0	General.....	192
9.4.1	Initiation of the "no-emission" mode.....	193
9.4.1.1	Successful activation (countdown to zero).....	193
9.4.1.2	Multiframe countdown stopped by FT.....	193
9.4.1.3	Multiframe countdown stopped by PT.....	194
9.4.1.4	PT does not receive multiframe countdown "zero".....	195
9.4.2	Behaviour during power-down-mode.....	195
9.4.3	Waking up, FT initiated.....	195
9.4.4	Waking up, PT initiated.....	199
9.5	Ultra Low Energy (ULE) Mode Procedures.....	200
9.5.0	General.....	200
9.5.1	Initiation of the ULE Mode.....	200
9.5.1.0	General.....	200
9.5.1.1	ULE Dummy Bearer Subfield 0.....	201
9.5.1.2	ULE Dummy Bearer Subfield 1.....	201
9.5.1.3	ULE Dummy Bearer Subfield 2.....	204
9.5.1.3.0	General.....	204
9.5.1.3.1	M _U Channel Info 1 coding.....	205
9.5.1.3.2	M _U Channel Info 2 coding.....	206
9.5.1.4	ULE Dummy Bearer Subfield 3.....	207
9.5.1.5	Elements of the ULE paging system.....	208
9.6	U-NEMo mode procedures.....	209
9.6.1	General.....	209

9.6.2	Initiation of the U-NEMo mode.....	209
9.6.3	Behaviour during U-NEMo mode	209
9.6.4	Waking up, PT initiated	209
9.6.5	Raising a dummy bearer	211
9.6.5.1	General	211
9.6.5.2	Scanning, blind slot map, blind slot count	211
9.6.5.3	Identity Free ULE dummy	211
9.6.5.4	NEMo++ dummy	211
9.6.6	Waking up, FT initiated	212
9.6.6.1	Waking up for ULE without waking from no-emissions mode	212
9.6.6.2	Waking up for ULE and waking from no-emissions mode	212
10	Connection oriented service procedures.....	213
10.1	Overview	213
10.2	C/O connection setup	213
10.2.0	Introduction.....	213
10.2.1	General.....	213
10.2.2	Initiation of a basic and a normal connection setup	214
10.2.3	Initiation of a fast connection setup	214
10.2.4	Connection setup procedure description	214
10.2.4.1	Creation of MBCs	214
10.2.4.2	Establishment of a single bearer duplex connection of a known service type	216
10.2.4.3	Establishment of multi-bearer connections and connections needing service negotiation	217
10.2.4.3.0	General	217
10.2.4.3.1	Symmetric connection	219
10.2.4.3.2	Asymmetric uplink connection.....	219
10.2.4.3.3	Asymmetric downlink connection.....	220
10.2.4.3.4	Connection established	220
10.2.5	Expedited connections	220
10.3	C/O connection modification	220
10.3.1	Advanced connection: bandwidth modification.....	220
10.3.1.0	General	220
10.3.1.1	Suspend and resume	222
10.3.1.1.0	General	222
10.3.1.1.1	Expedited suspend and resume	222
10.3.1.2	MAC resume paging	223
10.3.1.3	ULE resume paging.....	223
10.3.2	Advanced connection: service type or slot type modification	223
10.3.2.0	General	223
10.3.2.1	Procedure for service type modification	223
10.3.2.2	Procedures for slot type modification	224
10.3.2.2.1	Procedure for slot type modification full to double	224
10.3.2.2.2	Procedure for slot type modification double to full	225
10.3.2.2.3	Procedures for slot type modification to/from long	225
10.3.2.2.4	Procedure for slot type modification in multibearer connections	226
10.3.2.3	Procedure for ECN number modification in an advanced connection	226
10.3.3	Connection type modification.....	226
10.3.3.0	General	226
10.3.3.1	Procedure for connection type modification basic to advanced	227
10.3.3.1.1	General procedure	227
10.3.3.1.2	Procedure for connection type modification basic to advanced plus slot type modification full to double	227
10.3.3.1.3	Procedure for connection type modification basic to advanced plus slot type modification full to long.....	228
10.3.3.2	Procedure for connection type modification advanced to basic	228
10.3.4	Modulation type modification.....	229
10.3.4.0	General	229
10.3.4.1	Adaptive code rate.....	230
10.4	C/O connection release.....	230
10.4.1	General.....	230
10.4.1.0	Release causes.....	230
10.4.1.1	C/O connection release in packet mode connections	231

10.4.2	Procedure description	231
10.5	C/O bearer setup	232
10.5.1	Single bearer setup procedures	232
10.5.1.0	General	232
10.5.1.1	Basic bearer setup procedure.....	232
10.5.1.2	A-field advanced single bearer setup procedure	234
10.5.1.2.0	General	234
10.5.1.2.1	PT initiated	234
10.5.1.2.2	FT initiated	237
10.5.1.3	B-field single bearer setup procedure.....	238
10.5.1.3.0	General	238
10.5.1.3.1	PT initiated	238
10.5.1.3.2	FT initiated	240
10.5.1.4	Double simplex setup procedure	241
10.5.1.4.1	Terminology and Predicates	241
10.5.1.4.2	General description.....	241
10.5.1.4.3	Channel selection procedure for circuit mode connections	242
10.5.1.4.4	Channel selection procedure for packet mode connections	242
10.5.1.4.5	Indirect setup procedure	243
10.5.1.4.6	Direct setup procedure.....	244
10.5.1.4.7	Handling of encrypted connections	247
10.5.1.5	Complementary connection bearer setup	248
10.5.1.6	Double duplex bearer setup procedure: Mapping procedure.....	249
10.5.1.7	Usage of TA special code "111" and M _T message "B-field setup, first PT transmission"	250
10.5.1.7.0	General	250
10.5.1.7.1	Default rules for TA code "111".....	250
10.5.1.7.2	Default rules for M _T message "B-field setup, first transmission"	251
10.5.1.8	Expedited bearer setup procedures.....	251
10.5.1.8.1	General	251
10.5.1.8.2	Procedure for Single-burst setup and release.....	252
10.5.1.8.3	Procedure for Multi burst setup.....	253
10.5.1.8.4	Announcement "Ready for Release".....	255
10.5.1.8.5	Indirect FT initiated expedited bearer setup procedure	256
10.5.1.8.6	Insertion of U-plane in "Expedited access request" messages.....	256
10.5.1.8.7	Connected state (TBC) in expedited bearer setup.....	256
10.5.1.8.8	Encryption synchronization in expedited bearer setup	257
10.5.1.8.9	Use of short slots in expedited connections.....	257
10.5.2	Channel list procedures.....	258
10.5.2.1	General	258
10.5.2.2	Description of the channel list messages.....	258
10.5.2.3	Usage of the channel list messages	259
10.6	C/O bearer handover	260
10.6.1	General.....	260
10.6.2	Duplex bearer handover procedure	261
10.6.3	Double simplex bearer handover	261
10.6.4	Bearer replacement	262
10.6.4.1	General bearer replacement.....	262
10.6.4.2	Frequency replacement	262
10.7	C/O bearer release	263
10.7.1	General.....	263
10.7.2	Bearer release procedure description	264
10.7.2.1	Unacknowledged release procedure.....	264
10.7.2.1.0	General	264
10.7.2.1.1	Crossed bearer release procedure	264
10.7.2.2	Acknowledged release procedure.....	265
10.7.2.3	Fast release procedure	265
10.7.2.4	REP relayed bearer release.....	266
10.7.3	Expedited bearer release procedures.....	266
10.7.3.0	General	266
10.7.3.1	General Expedited Release procedure.....	266
10.7.3.1.0	Usage	266
10.7.3.1.1	Procedure description	266

10.7.3.1.2	Exceptional cases and error handling	267
10.7.3.2	Special cases of expedited release procedures	267
10.7.3.2.1	Single-message expedited release procedure.....	267
10.7.3.2.2	Abnormal expedited release procedure.....	268
10.8	C/O data transfer	268
10.8.1	Higher layer associated signalling (C)	268
10.8.1.0	General	268
10.8.1.1	C _S channel data	268
10.8.1.1.0	General	268
10.8.1.1.1	Transmission principle	269
10.8.1.1.2	Numbering principle.....	269
10.8.1.2	C _F channel data	269
10.8.1.2.0	General	269
10.8.1.2.1	Transmission principle	270
10.8.1.2.2	Numbering principle.....	270
10.8.1.3	Q1 and Q2 bit settings for all services except I _{P_error_correct}	270
10.8.1.3.0	Coding of the bits	270
10.8.1.3.1	Q1 and Q2 bit settings for MAC service I _N	270
10.8.1.3.2	Q1 and Q2 bit settings for MAC service I _{P_error_detect}	271
10.8.1.3.3	Q2 bit settings.....	271
10.8.1.3.4	Q1 bit settings.....	272
10.8.1.3.5	Q1 and Q2 settings when B-field is in E-mux modes.....	273
10.8.1.3.6	Q1 and Q2 settings when B-field is in "no-B-field" mode	274
10.8.1.3.7	Q1, Q2 and BCK settings when there are transitions in the coding rules or when the rules applicable to both directions are not the same	275
10.8.1.3.8	Q1 and Q2 settings when B-field mode is unknown	275
10.8.2	MOD-2 protected I channel operation (I _P).....	275
10.8.2.1	General	275
10.8.2.1.0	Introduction to MOD-2 protected I channel operation (I _P).....	275
10.8.2.1.1	Use of selective reception.....	276
10.8.2.2	Limiting the lifetime of packets	276
10.8.2.2.0	General	276
10.8.2.2.1	Lifetime setting and management.....	276
10.8.2.3	A-field shall always be correct.....	278
10.8.2.4	Use of the acknowledge bits.....	278
10.8.2.4.0	General	278
10.8.2.4.1	Q2 and BCK bit setting for I _{P_error_correction} services	278
10.8.2.4.2	BCK bit setting.....	279
10.8.2.5	Data jump procedures	279
10.8.2.5.0	General	279
10.8.2.5.1	New MOD-2 numbering in case of Bearer replacement	279
10.8.2.5.2	Unilateral jump.....	279
10.8.2.5.3	MAC I _P bearer reset.....	281
10.8.2.6	Bearer handover and bearer replacement procedures.....	281
10.8.2.6.1	General	281
10.8.2.6.2	Bearer handover in a MOD-2 protected I channel.....	281
10.8.2.6.3	Bearer replacement in a MOD-2 protected I channel	282
10.8.2.7	Exchange of data from/to higher layers	282
10.8.2.7.0	General	282
10.8.2.7.1	Operation if I _{PF} channel is supported.....	283
10.8.3	Higher layer unprotected information (I _N) and MAC_error_detection services (I _P).....	283
10.8.3.1	I _{N_minimum_delay} service (I _{NA})	283
10.8.3.2	I _{N_normal_delay} service (I _{NB}).....	283
10.8.3.3	I _{P_error_detection} service	284
10.8.3.3.0	General	284
10.8.3.3.1	Operation if I _{PF} channel is supported.....	284
10.8.3.4	I _{P_encoded_protected} service (I _{PX})	284
10.8.4	Higher layer U-plane channel (I _{PF}) in E+U type mux	285
10.8.4.1	Purpose of the I _{PF} channel	285
10.8.4.2	Activation of the E+U type mux mode	285
10.8.4.3	I _{PF} procedures.....	285
10.8.4.3.0	General	285

10.8.4.3.1	I _{PF} basic procedures	286
10.8.4.3.2	I _{PF} advanced procedures	286
10.8.4.3.3	Special case: slots not multiple of 64 bits.....	287
10.8.4.4	I _{PF} Mod-2 protected operation.....	287
10.8.4.5	I _{PF} _error_detect operation	288
10.8.4.6	I _{PF} _operation with I _N service	288
10.8.4.7	Backcompatibility rule	288
10.9	C/O procedures for FT connections with CRFP.....	288
10.9.0	General.....	288
10.9.1	Dual C/O bearer setup.....	288
10.9.2	C/O connection release of connection with CRFP.....	288
10.9.3	C/O connection suspend and resume	289
11	Medium access layer management procedures	289
11.1	Broadcasting.....	289
11.1.1	RFP transmission	289
11.1.2	PP reception.....	289
11.2	Extended system information	289
11.2.1	PP requests.....	289
11.2.2	RFP response	290
11.3	PP states and state transitions	290
11.3.0	General.....	290
11.3.1	Actions in Idle_Unlocked and Active_Unlocked states.....	290
11.3.2	Entry into the Idle_Locked state	290
11.3.3	Actions in the Idle_Locked state.....	290
11.3.3.0	General	290
11.3.3.1	Page detection in Idle_Locked state.....	291
11.3.3.2	Setup detection in Idle_Locked state	291
11.3.4	Idle_Locked and Active_Locked state transitions	292
11.4	Physical channel selection.....	292
11.4.0	General.....	292
11.4.1	The channel selection lists	292
11.4.2	Physical channel and RFP selection at the PP.....	294
11.4.3	Physical channel selection at the RFP.....	296
11.4.4	Hand over criteria due to in-connection base identification	297
11.4.5	Handover criteria due to interference.....	297
11.4.6	Exception in channel selection rules for Ultra Low Energy devices	298
11.5	In-connection quality control	298
11.5.1	RFPI handshake	298
11.5.2	Frequency control	298
11.5.2.1	RFP measurement of frequency error	298
11.5.2.2	PT frequency correction	298
11.6	Maximum allowed system load at RFPs	299
11.7	PMID and FMID definitions	299
11.7.1	FMID definition.....	299
11.7.2	PMID definition.....	299
11.7.2.0	General	299
11.7.2.1	'X'PMID definition.....	299
11.8	RFP idle receiver scan sequence	299
11.9	PT receiver scan sequence.....	300
11.10	Management of connections associated with Broadband data links.....	300
11.11	Management procedures for "no-emission" mode.....	301
11.11.0	General.....	301
11.11.1	Behaviour during "no-emission" mode.....	301
11.12	Physical channel selection procedures for DECT Ultra Low Energy (ULE)	301
11.12.1	General.....	301
11.12.2	Overall architecture of ULE channel selection processes	302
11.12.3	Process M0 (RFP side pre-selection process)	302
11.12.4	Broadcast mechanism	303
11.12.5	Process M1 (PP side channel selection process).....	303
11.12.6	Setup attempt and evaluation of responses	304
11.12.7	Process M2 (collision handling/collision avoidance process).....	306