



**Digital Enhanced Cordless Telecommunications (DECT);  
Common Interface (CI);  
Part 4: Data Link Control (DLC) layer**

*iTeh STANDARD PREVIEW  
(standards.iteh.ai)  
Full standard available at  
<https://standards.iteh.ai/catalog/standards/sis/42549c7-85c7-49af-b5eb-090718ed60e1/etsi-en-300-175-4-v2-6-6-2017-06>*

---

Reference

REN/DECT-00307-4

---

Keywords

DECT, DLC, IMT-2000, mobility, radio, TDD,  
TDMA

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.  
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members  
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	13
Foreword.....	13
Modal verbs terminology.....	13
1 Scope .....	14
2 References .....	14
2.1 Normative references .....	14
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations .....	16
3.1 Definitions.....	16
3.2 Symbols and abbreviations.....	16
4 Data Link Control (DLC) layer overview .....	19
4.1 General .....	19
4.2 C-plane services .....	20
4.3 U-plane services .....	20
4.4 Lower Layer Management Entity (LLME) .....	24
5 C-plane service characteristics .....	24
5.1 Data link service (LAPC+Lc).....	24
5.1.1 General.....	24
5.1.2 LAPC types of operation .....	25
5.1.3 Establishment of information transfer modes .....	25
5.1.3.1 Data Link Identifier (DLI) .....	25
5.1.3.2 LAPC states.....	25
5.2 Broadcast service (Lb).....	26
6 Frame structures for C-plane services .....	27
6.1 Data link service frame structure.....	27
6.1.0 Frame format type FA.....	27
6.1.1 General frame structure .....	27
6.1.2 Lc frame delimiting and transparency .....	28
6.1.3 Transmission order .....	28
6.1.4 Routing to logical channels.....	28
6.1.4.0 General .....	28
6.1.4.1 C <sub>F</sub> /CL <sub>F</sub> logical channel.....	29
6.1.4.2 C <sub>S</sub> /CL <sub>S</sub> logical channel.....	29
6.1.5 Invalid frames .....	29
6.2 Broadcast service frame structure.....	30
6.2.1 Standard frame structure .....	30
6.2.2 Extended frame structure .....	30
7 Elements of procedures and formats of fields for C-plane peer-to-peer communication.....	31
7.1 General .....	31
7.2 Address field formats .....	31
7.3 Address field parameters .....	31
7.3.1 RESErved bit (RES).....	31
7.3.2 Command Response (C/R) bit .....	31
7.3.3 SAPI field .....	31
7.3.4 New Link Flag (NLF) bit.....	32
7.3.5 LLN-field.....	32
7.3.6 Data Link Identifiers (DLI).....	32
7.4 Control field formats .....	33
7.5 Control field parameters .....	33
7.5.1 Poll/Final (P/F) bit .....	33
7.5.2 Multiple frame operation variables and sequence numbers .....	33
7.5.2.1 Modulus .....	33

7.5.2.2	Send state Variable V(S) .....	33
7.5.2.3	Acknowledge state Variable V(A) .....	34
7.5.2.4	Send sequence Number N(S) .....	34
7.5.2.5	Receive state Variable V(R) .....	34
7.5.2.6	Receive sequence Number N(R) .....	34
7.5.3	Unacknowledged operation variables and sequence numbers .....	34
7.5.4	Supervisory and Unnumbered function bits S and U .....	34
7.6	Length indicator field format .....	34
7.7	Length indicator field parameters .....	35
7.7.1	Length indicator field extension bit (N) .....	35
7.7.2	More data bit (M) .....	35
7.7.3	Length parameter (L <sub>i</sub> ) .....	35
7.7.4	Extended length parameter (L <sub>JJ</sub> ) .....	36
7.7.5	Reserved bit (RES) .....	36
7.8	Fill field format .....	36
7.9	Checksum field format .....	36
7.10	Checksum field parameters .....	36
7.11	Commands and responses .....	37
7.11.0	General .....	37
7.11.1	Information (I) command .....	38
7.11.2	Receive Ready (RR) command/response .....	38
7.11.3	Receive Not Ready (RNR) command/response .....	39
7.11.4	REJect (REJ) command/response .....	39
7.11.5	Set Asynchronous Balanced Mode (SABM) command .....	39
7.11.6	Disconnect Mode (DM) response .....	39
7.11.7	Unnumbered Information (UI) command .....	40
7.11.8	DISConnect (DISC) command .....	40
7.11.9	Unnumbered ACK (UA) response .....	40
8	Primitives .....	40
8.1	Primitive types .....	40
8.2	Primitives to the MAC layer (lower layer) .....	40
8.3	Primitives to the NWK layer (higher layer) .....	41
8.3.0	General .....	41
8.3.1	Parameter definitions .....	41
8.3.2	S-SAP primitives .....	42
8.3.2.0	List of primitives .....	42
8.3.2.1	DL_ESTABLISH primitive .....	42
8.3.2.2	DL_RELEASE primitive .....	43
8.3.2.3	DL_DATA primitive .....	43
8.3.2.4	DL_UNIT_DATA primitive .....	43
8.3.2.5	DL_SUSPEND primitive .....	43
8.3.2.6	DL_RESUME primitive .....	44
8.3.2.7	DL_ENC_KEY primitive .....	44
8.3.2.8	DL_ENCRYPT primitive .....	44
8.3.2.9	DL_SERVICE_MOD primitive .....	45
8.3.3	B-SAP primitives .....	45
8.3.3.0	List of primitives .....	45
8.3.3.1	DL_BROADCAST primitive .....	45
8.3.3.2	DL_EXPEDITED primitive .....	45
8.4	Primitives to the interworking unit .....	46
8.4.0	General .....	46
8.4.1	Parameter definitions .....	46
8.4.2	LU <sub>X</sub> -SAP primitives .....	46
8.4.2.0	List of primitives .....	46
8.4.2.1	DL_U_DATA primitive .....	46
8.4.2.2	DL_U_UNIT_DATA primitive .....	47
8.4.2.3	DL_U_ERROR primitive .....	47
9	C-plane peer-to-peer procedures .....	47
9.1	General .....	47
9.2	Point to point acknowledged operation .....	48

9.2.1	Procedure for the use of the P/F bit .....	48
9.2.1.1	Class A acknowledged information transfer .....	48
9.2.1.2	Class B acknowledged information transfer .....	48
9.2.2	Use of LLN .....	48
9.2.2.1	Class A operation .....	48
9.2.2.2	Class B operation .....	48
9.2.3	Link establishment and information transfer in class A operation.....	49
9.2.3.1	Establishing class A operation .....	49
9.2.3.2	Class A acknowledged information transfer .....	49
9.2.3.3	Transmission of class A I-frames .....	50
9.2.3.4	Reception of class A I-frames .....	50
9.2.3.5	Receiving acknowledgements .....	50
9.2.3.6	Waiting for acknowledgement .....	51
9.2.3.7	Release of class A operation .....	51
9.2.3.8	Re-establishment of class A operation .....	52
9.2.4	Establishing class B multiple frame operation.....	52
9.2.4.1	Overview .....	52
9.2.4.2	Class B multiple frame establishment procedures.....	52
9.2.4.3	Class B LLN assignment procedures .....	54
9.2.4.3.0	General .....	54
9.2.4.3.1	PT establishment .....	54
9.2.4.3.2	FT establishment .....	54
9.2.5	Link maintenance and information transfer in class B multiple frame operation .....	54
9.2.5.0	General .....	54
9.2.5.1	Transmitting I-frames.....	55
9.2.5.2	Receiving I-frames .....	55
9.2.5.2.0	General .....	55
9.2.5.2.1	P bit set to 1 .....	55
9.2.5.2.2	P bit set to 0.....	56
9.2.5.3	Sending and receiving acknowledgements.....	56
9.2.5.3.1	Sending acknowledgements .....	56
9.2.5.3.2	Receiving acknowledgements .....	56
9.2.5.4	Receiving REJ-frames.....	56
9.2.5.5	Receiving RNR-frames .....	57
9.2.5.6	LAPC own receiver busy condition.....	58
9.2.5.7	Waiting acknowledgement.....	59
9.2.5.8	Appropriate supervisory frame.....	59
9.2.6	Release of class B multiple frame operation.....	59
9.2.7	Link suspension and resumption.....	60
9.2.7.1	Link suspension.....	60
9.2.7.1.0	General .....	60
9.2.7.1.1	Class B acknowledged suspend.....	61
9.2.7.1.2	Unacknowledged suspend .....	61
9.2.7.2	Class B link resumption .....	62
9.2.7.3	Connection handover .....	63
9.2.7.3.0	General .....	63
9.2.7.3.1	Class A connection handover .....	65
9.2.7.3.2	Class B connection handover .....	65
9.2.7.3.3	Expiry of connection handover timer .....	66
9.2.8	Re-establishment of class B multi-frame operation.....	66
9.2.8.1	Criteria for re-establishment.....	66
9.2.8.2	Procedure .....	66
9.2.9	Exception handling .....	67
9.2.9.1	General .....	67
9.2.9.2	Class B exception condition reporting and recovery.....	67
9.2.9.2.0	General .....	67
9.2.9.2.1	N(S) sequence error .....	67
9.2.9.2.2	N(R) sequence error .....	68
9.2.9.2.3	Timer recovery condition .....	68
9.2.9.2.4	Collision of identical transmitted and received commands .....	68
9.3	Unacknowledged operation.....	68
9.3.1	Use of LLN for unacknowledged information transfer.....	68

9.3.2	Class U link establishment.....	68
9.3.3	Unacknowledged information transfer.....	68
9.3.3.1	Transmission of unacknowledged information .....	68
9.3.3.2	Reception of unacknowledged information .....	69
9.3.4	Unacknowledged release .....	69
9.4	Broadcast operation .....	69
9.4.1	Normal operation .....	69
9.4.1.1	Procedure in the Fixed radio Termination (FT) .....	69
9.4.1.2	Procedure in the Portable radio Termination (PT) .....	69
9.4.2	Expedited operation .....	70
9.4.2.1	Procedure in the Fixed radio Termination (FT) .....	70
9.4.2.2	Procedure in the Portable radio Termination (PT) .....	70
9.5	MAC layer interfaces .....	70
9.5.1	MC-SAP .....	70
9.5.1.1	C-plane overview .....	70
9.5.1.2	C-plane service data procedures.....	71
9.5.1.3	U-plane service data .....	71
9.5.2	MB-SAP .....	71
9.5.2.0	General.....	71
9.5.2.1	C-plane service data procedures.....	72
9.5.2.2	U-plane service data .....	72
9.5.3	MA-SAP .....	72
9.5.3.1	Overview.....	72
9.5.3.2	Service data procedures.....	72
10	Management procedures.....	73
10.1	Lower Layer Management Entity (LLME) .....	73
10.2	MAC connection management.....	73
10.2.0	General.....	73
10.2.1	MAC connection set-up .....	73
10.2.2	MAC connection release.....	74
10.2.3	MAC connection modification .....	74
10.2.4	MAC connection identifiers.....	75
10.2.4.1	Overview.....	75
10.2.4.2	Advanced MAC Connection Identifiers (AMCI).....	75
10.2.4.3	Basic MAC Connection Identifiers (BMCI) .....	75
10.2.4.4	MAC Connection Endpoint Identifier (MCEI) .....	76
10.2.5	Selection of logical channel (C <sub>s</sub> or C <sub>F</sub> ).....	76
10.3	DLC C-plane (LAPC) management.....	76
10.3.0	General.....	76
10.3.1	Provision of link signature .....	77
10.3.2	Routing of connection oriented links .....	77
10.3.3	Routing of connectionless links .....	77
10.4	DLC U-plane (LUX) management.....	77
10.4.0	General.....	77
10.4.1	U-plane establishment.....	77
10.4.2	U-plane release .....	78
10.4.3	U-plane suspend and resume .....	78
10.5	Connection handover management .....	78
10.6	Cipherring management.....	79
10.6.1	Cipherring management in cases where the NWK layer executes the cipherring related MM procedure .....	79
10.6.1.0	General .....	79
10.6.1.1	Providing a key to the MAC layer .....	79
10.6.1.2	Starting and stopping the cipherring.....	79
10.6.1.3	Connection handover .....	80
10.6.2	Cipherring management in cases where the NWK layer does not execute the cipherring related MM procedure .....	80
10.7	Broadband data link management .....	80
11	U-plane service characteristics.....	81
11.1	General .....	81
11.2	LU1 TRansparent UnProtected service (TRUP) .....	81



11.3	LU2 Frame RELay service (FREL).....	82
11.3.1	General.....	82
11.3.2	Checksum operation .....	83
11.3.3	Segmentation and transmission class .....	83
11.3.4	Data transmission.....	84
11.3.4.1	Send side procedure .....	84
11.3.4.2	Receive side procedure .....	84
11.4	LU3 Frame SWItching service (FSWI).....	84
11.5	LU4 Forward Error Correction (FEC) service.....	85
11.6	LU5 Basic RATE adaption service (BRAT).....	85
11.6.1	Overview .....	85
11.6.2	Protected service operation .....	86
11.6.2.1	General .....	86
11.6.2.2	Data buffering and initial rate adaptation.....	87
11.6.2.3	Multi-channel set multiplexing .....	88
11.6.2.4	Segmentation of Multiplexed Data Units (MDU).....	89
11.6.2.5	Frame sequencing and addition of control and fill octets.....	90
11.6.2.6	Frame transmission .....	91
11.6.3	Unprotected service operation .....	91
11.6.3.1	General .....	91
11.6.3.2	Data buffering and initial rate adaption.....	92
11.6.3.3	Multi-channel set multiplexing .....	92
11.6.3.4	Segmentation of MDUs.....	93
11.6.3.5	Frame transmission .....	93
11.7	LU6 Secondary RATE adaption (SRAT) service .....	94
11.7.1	General.....	94
11.8	LU16 ESCape Service (ESC).....	95
11.8.1	General.....	95
11.9	LU7 64 kbit/s data bearer service .....	95
11.9.1	General.....	95
11.9.2	Physical layer service.....	95
11.9.3	MAC layer service.....	96
11.9.4	DLC layer service .....	96
11.9.4.1	Architectural model.....	96
11.9.4.1.0	General .....	96
11.9.4.1.1	Transmit (Tx) frame buffering .....	96
11.9.4.1.2	Receive (Rx) frame buffering .....	96
11.9.4.2	Automatic-Repeat-Request (ARQ) and Forward Error Control (FEC).....	97
11.9.4.2.0	General .....	97
11.9.4.2.1	Control field .....	98
11.9.4.2.2	Information field.....	100
11.9.4.2.3	ARQ checksum.....	101
11.9.4.3	Procedures for normal operation .....	101
11.9.4.3.0	General .....	101
11.9.4.3.1	Establishment and synchronization procedures .....	101
11.9.4.3.2	Active phase .....	103
11.9.4.3.3	Release.....	105
11.9.4.4	Exceptional procedures .....	105
11.9.4.4.0	General .....	105
11.9.4.4.1	Invalid frame condition .....	105
11.9.4.4.2	Establishment .....	105
11.9.4.4.3	Transmitting frames.....	105
11.9.4.4.4	Receiving frames .....	105
11.9.4.4.5	Sending acknowledgements .....	105
11.9.4.4.6	Forwarding of received data .....	105
11.9.4.4.7	N(R) sequence error .....	106
11.9.4.4.8	N(O) sequence error .....	106
11.9.4.4.9	N(S) sequence error.....	106
11.9.4.4.10	Format error.....	106
11.9.4.4.11	Abnormal release.....	107
11.9.4.4.12	Implicit reset.....	107
11.9.5	Network layer service .....	107

11.9.5.1	LCE service .....	107
11.9.5.2	CC service .....	107
11.10	LU8 service .....	107
11.10.0	General.....	107
11.10.1	Physical layer service.....	107
11.10.2	MAC layer service.....	107
11.10.3	DLC layer service .....	108
11.11	LU9 - Unprotected Rate Adaption for V series Equipment (RAVE) Service .....	108
11.11.1	Overview .....	108
11.11.1.0	General .....	108
11.11.1.1	FU9 frame structure .....	109
11.11.1.1.1	General frame structure .....	109
11.11.1.1.2	FU9 buffering procedures.....	109
11.11.1.1.3	Connection handover.....	109
11.11.1.1.4	Transmission order .....	109
11.11.2	Alignment signal management .....	110
11.11.2.1	General .....	110
11.11.2.2	Procedures .....	110
11.11.3	V.24 Signalling .....	111
11.11.3.1	General .....	111
11.11.3.2	Transmitter procedures.....	112
11.11.3.3	Receiver procedures .....	112
11.11.4	Rate Coding .....	112
11.11.4.1	General .....	112
11.11.4.2	Transmitter procedures.....	113
11.11.4.3	Receiver procedures .....	113
11.11.5	DECT Independent Clocking (DIC) .....	114
11.11.5.1	General .....	114
11.11.5.2	Measurement of phase differences .....	114
11.11.5.3	Compensation control rules .....	115
11.11.5.3.1	General .....	115
11.11.5.3.2	Optimizing error resilience.....	115
11.11.6	Information field.....	116
11.11.6.1	General .....	116
11.11.6.2	User data rates.....	116
11.11.6.3	Information field filling rule .....	116
11.11.7	Primitives.....	117
11.12	LU10 Enhanced Frame RELay (EFREL) service .....	118
11.12.1	General.....	118
11.12.2	Segmentation and transmission class.....	119
11.12.3	Data transmission.....	119
11.12.3.1	Send side procedures.....	119
11.12.3.1.0	General .....	119
11.12.3.1.1	"Early transmission" option.....	120
11.12.3.2	Receive side procedure .....	120
11.12.3.2.0	General .....	120
11.12.3.2.1	Standard SDU delivery mode .....	120
11.12.3.2.2	In-sequence SDU delivery mode .....	120
11.12.3.2.3	PDU-in-sequence delivery mode.....	121
11.12.3.2.4	PDU-as-received delivery mode.....	121
11.12.4	SDU boundaries definition .....	121
11.12.4.0	General .....	121
11.12.4.1	Infinite SDU mode .....	121
11.12.5	Use over C/L downlink channels.....	122
11.12.5.0	General .....	122
11.12.5.1	Use over C/L downlink channels: unicast mode .....	122
11.12.5.2	Use over C/L downlink channels: multicast mode .....	122
11.12.5.2.0	General .....	122
11.12.5.2.1	DLC acknowledgement in multicast mode.....	122
11.13	LU11 service .....	122
11.13.0	General.....	122
11.13.1	Physical layer service.....	122



11.13.2	MAC layer service .....	122
11.13.3	DLC layer service .....	123
11.14	LU12 UNprotected Framed service (UNF) .....	123
11.14.1	General.....	123
11.14.2	DLC layer service .....	123
11.14.2.0	General .....	123
11.14.2.1	Segmentation.....	124
11.14.2.2	Data transmission.....	125
11.14.2.2.1	Send side procedure.....	125
11.14.2.2.2	Receive side procedure.....	125
11.15	LU13 Enhanced Frame RELay service with CRC (EFREL-CRC) .....	126
11.15.1	General.....	126
11.15.2	SDU CRC generation.....	126
11.15.3	Use over C/L downlink channels .....	126
11.15.3.0	General .....	126
11.15.3.1	Use over C/L downlink channels: unicast mode .....	127
11.15.3.2	Use over C/L downlink channels: multicast mode .....	127
11.15.3.2.0	General .....	127
11.15.3.2.1	DLC acknowledgement in multicast mode.....	127
11.16	LU14 Enhanced Frame RELay service with CCM (EFREL-CCM) .....	127
11.16.1	General.....	127
11.16.2	LU14 SDU structure .....	127
11.16.2.0	General .....	127
11.16.2.1	SDU sizes .....	128
11.16.2.2	Security model .....	128
11.16.2.3	SDU processing.....	129
11.16.2.4	Limitations .....	129
11.16.2.5	CCM sequence numbers .....	129
11.16.2.6	CCM control procedures .....	129
11.16.3	Use over C/L downlink channels .....	130
11.16.3.0	General .....	130
11.16.3.1	Use over C/L downlink channels: unicast mode .....	130
11.16.3.2	Use over C/L downlink channels: multicast mode .....	130
11.16.3.2.0	General .....	130
11.16.3.2.1	DLC acknowledgement in multicast mode.....	130
12	Frame structures for U-plane services.....	130
12.1	General .....	130
12.2	FU1 frame structure.....	131
12.2.1	General frame structure .....	131
12.2.2	FU1 buffering procedures .....	132
12.2.3	Minimum delay (speech) operation .....	133
12.2.4	Connection handover .....	133
12.2.5	Transmission order .....	133
12.3	FU2 frame structure.....	133
12.3.1	General frame structure .....	133
12.3.2	FU2 buffering procedures .....	134
12.3.3	Connection handover .....	134
12.3.4	Transmission order .....	134
12.4	FU3 frame structure.....	134
12.4.1	General frame structure .....	134
12.4.2	FU3 buffering procedures .....	135
12.4.3	Connection handover .....	136
12.4.4	Transmission order .....	136
12.5	FU4 frame structure.....	136
12.5.1	General frame structure .....	136
12.5.2	FU4 buffering procedures .....	137
12.5.3	Connection handover .....	137
12.5.4	Transmission order .....	137
12.6	FU5 frame structure.....	137
12.6.1	General frame structure .....	137
12.6.2	FU5 buffering procedures .....	138

12.6.3	Connection handover .....	139
12.6.4	Transmission order .....	139
12.7	FU6 frame structure.....	139
12.7.1	General frame structure .....	139
12.7.2	FU6 buffering procedures.....	140
12.7.3	Connection handover .....	140
12.7.4	Transmission order .....	140
12.8	FU7 frame structure.....	140
12.9	FU8 frame structure.....	140
12.10	FU9 frame structure.....	140
12.11	FU10 frame structure.....	141
12.11.1	General frame structure .....	141
12.11.1.0	General .....	141
12.11.1.1	Specific for MAC service $I_{PK}$ .....	143
12.11.2	Transmission of FU10c and FU10d frames .....	144
12.11.2.0	General .....	144
12.11.2.1	Insertion of the FU10c frame in an FU10a frame of the opposite link.....	144
12.11.2.2	Transmission of the F10c frame using the $G_F$ channel.....	144
12.11.2.3	Insertion of the FU10d frame in an FU10a frame of the opposite link .....	145
12.11.2.4	Transmission of the FU10d frame using the $G_{FA}$ channel.....	145
12.11.3	FU10 buffering procedures .....	145
12.11.4	Connection handover .....	145
12.11.5	Transmission order .....	145
12.12	FU12 frame structure.....	146
12.12.1	General frame structure .....	146
12.12.2	FU12 buffering procedures .....	146
12.12.3	Connection handover .....	147
12.12.4	Transmission order .....	147
13	Elements of procedures and formats of fields for U-plane peer-to-peer communication .....	147
13.1	General .....	147
13.2	Address elements.....	147
13.2.1	Address field format .....	147
13.2.2	Address field parameters .....	148
13.3	Length indicator elements .....	148
13.3.1	Length indicator field format .....	148
13.3.1.1	Length indicator field format for all services except LU10 .....	148
13.3.1.2	Length indicator field format for service LU10 .....	148
13.3.2	Length indicator field parameters .....	149
13.3.2.1	Length indicator field parameters for all services except LU10.....	149
13.3.2.2	Length indicator field parameters for LU10 service .....	150
13.3.2.2.0	General .....	150
13.3.2.2.1	Meaning of the more (M) bit .....	152
13.4	Sequence number elements .....	153
13.4.1	Send sequence number format .....	153
13.4.2	Send sequence number parameters .....	153
13.4.3	Receive sequence number format .....	153
13.4.4	Receive sequence number parameters .....	154
13.5	Fill elements - Fill field format .....	154
14	U-plane peer-to-peer procedures .....	154
14.1	General .....	154
14.2	Frame transmission principles .....	154
14.2.1	Sequence numbering.....	154
14.2.2	Acknowledgements.....	155
14.2.2.1	Sending acknowledgements .....	155
14.2.2.2	Receiving acknowledgements .....	155
14.2.3	Transmission classes.....	155
14.2.3.0	General .....	155
14.2.3.1	Class 0: No $LU_X$ retransmission or sequencing.....	155
14.2.3.2	Class 1: no $LU_X$ retransmission.....	156
14.2.3.2.0	General .....	156

14.2.3.2.1	Class 1: use over C/L downlink channels.....	156
14.2.3.3	Class 2: variable throughput, limited delay LU <sub>X</sub> retransmission.....	156
14.2.3.4	Class 3: fixed throughput LU <sub>X</sub> retransmission.....	157
14.2.4	Operation parameter negotiation.....	157
14.3	Frame transmission procedures.....	157
14.3.1	General.....	157
14.3.2	Class 0 procedures.....	157
14.3.2.0	General.....	157
14.3.2.1	Sending side procedure.....	158
14.3.2.2	Receiving side procedure.....	158
14.3.3	Class 1 procedures.....	158
14.3.3.0	General.....	158
14.3.3.1	Sending side procedure.....	158
14.3.3.2	Receiving side procedure.....	159
14.3.4	Class 2 procedures.....	159
14.3.4.0	General.....	159
14.3.4.1	Sending side procedure.....	159
14.3.4.1.0	General.....	159
14.3.4.1.1	Synchronization message sending side procedure (LU10).....	161
14.3.4.1.2	Tx side end-of-activity rule.....	161
14.3.4.1.3	Abnormal SDU termination/abort signal (LU10 only).....	162
14.3.4.1.4	Retransmission procedure.....	163
14.3.4.2	Receiving side procedure.....	163
14.3.4.2.0	General.....	163
14.3.4.2.1	Acknowledgement procedure.....	163
14.3.4.2.2	Rx side end-of-activity rule.....	165
14.3.4.2.3	Retransmission request procedure.....	165
14.3.4.2.4	SDU delivery procedure.....	166
14.3.4.2.5	Synchronization message receiver side procedure (LU10).....	166
14.3.4.2.6	Reception of an abnormal SDU termination/abort signal (LU10).....	167
14.3.5	Class 3 procedures.....	167
14.3.5.0	General.....	167
14.3.5.1	Sending side procedure.....	167
14.3.5.2	Receiving side procedure.....	168
<b>Annex A (normative): System parameters.....</b>		<b>170</b>
A.1	LAPC timer values.....	170
A.2	U-plane timer values.....	171
A.3	Constants.....	171
A.3.1	Retransmission counter (N250).....	171
A.3.2	Maximum number of CHO attempts (N251).....	171
<b>Annex B (normative): Checksum algorithms.....</b>		<b>172</b>
B.1	Arithmetic conventions.....	172
B.2	Coding algorithm.....	172
B.3	Decoding algorithm.....	172
B.4	Some examples.....	173
<b>Annex C (informative): MAC connection states.....</b>		<b>174</b>
<b>Annex D (normative): Mapping of agreed channel rates to MCS sizes.....</b>		<b>175</b>
D.0	General.....	175
D.1	Protected class operation.....	175
D.2	Unprotected class operation.....	176
<b>Annex E (normative): LU12 applications.....</b>		<b>177</b>

E.1	G.729.1 over 32 kbit/s channel.....	177
E.1.0	General .....	177
E.1.1	G.729.1 payload format.....	177
E.1.1.0	General.....	177
E.1.1.1	G.729.1 payload header coding .....	178
E.1.2	Operations .....	180
E.1.2.1	Encoder bit rate.....	180
E.1.2.2	Protection against random errors .....	180
<b>Annex F (informative):</b>	<b>Bibliography.....</b>	<b>181</b>
<b>Annex G (informative):</b>	<b>Change history .....</b>	<b>182</b>
History .....		183

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/425a69c7-85c7-49af-b5eb-090718ed60e1/etsi-en-300-175-4-v2.7.1-2017-11>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document is part 4 of a multi-part deliverable ([1] to [8]). Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in ETSI TR 101 178 [i.1] and ETSI ETR 043 [i.2].

<b>Proposed national transposition dates</b>	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.