

ETSI EN 300 175-8 V2.7.1 (2017-11)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard: https://standards.iteh.ai/catalog/standards/sist/300-175-8-10b-5722-4a85-849a-9a8b77f6572c/etsi-en-300-175-8-10b-5722-4a85-849a-9a8b77f6572c

 Reference

REN/DECT-00307-8

 Keywords

7 kHz, audio, broadband, codec, DECT,
handsfree, IMT-2000, loudspeaking, mobility,
narrowband, quality, radio, speech, TDD, TDMA,
telephony, terminal

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	12
Foreword.....	12
Modal verbs terminology.....	12
1 Scope	13
2 References	13
2.1 Normative references	13
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations	16
3.1 Definitions.....	16
3.2 Symbols and abbreviations.....	17
4 Configurations.....	19
4.1 Reference configuration	19
4.1.1 Basic configuration	19
4.1.2 Portable Part (PP)	21
4.1.2.1 Functional organization.....	21
4.1.2.2 Volume control	21
4.1.3 Fixed Part (FP).....	21
4.1.3.1 Digital interface.....	21
4.1.3.2 Analog interface	23
4.1.3.3 FP adaptive volume control	23
4.2 Test configurations	23
5 Encoding.....	23
5.0 General	23
5.1 32 kbit/s full term (ADPCM) G.726.....	24
5.1.1 Algorithm.....	24
5.1.2 Bit sequence.....	24
5.1.3 Characteristics of G.726 ADPCM codec.....	24
5.2 64 kbit/s PCM G.711.....	24
5.2.1 Algorithm.....	24
5.2.2 Bit sequence.....	24
5.2.3 Characteristics of G.711 PCM codec.....	25
5.2.4 Automatic detection of FAX/modem tone and switch to G.711	25
5.3 Wideband speech codec G.722 at 64 kbit/s.....	25
5.3.0 General.....	25
5.3.1 Algorithm.....	25
5.3.2 Bit sequence.....	25
5.3.3 Characteristics of G.722 wideband codec.....	25
5.3.4 Optional Packet Loss Concealment algorithm (PLC).....	26
5.4 Wideband speech codec G.729.1 up to 32 kbit/s.....	26
5.4.1 Algorithm.....	26
5.4.2 Bit sequence.....	26
5.4.3 Characteristics of G.729.1 codec	26
5.4.4 Packet Loss Concealment algorithm (PLC).....	27
5.4.5 Supported bit rate in DECT	27
5.5 Super-wideband MPEG-4 speech and audio coding	27
5.5.1 Algorithm.....	27
5.5.2 64 kbit/s, MPEG-4 ER AAC-LD codec.....	28
5.5.3 32 kbit/s, MPEG-4 ER AAC-LD codec.....	28
5.6 Other codings	28
6 Transmission aspects.....	29
6.1 Relative level.....	29
6.2 Acoustic reference level	29
6.3 Volume control.....	29

7	Audio specifications	29
7.1	Overall description	29
7.1.1	Introduction to DECT audio specifications	29
7.1.2	Introduction to the audio types	29
7.1.3	List of Audio types	30
7.1.4	Audio types for Portable Parts	31
7.1.5	Audio types for Fixed Parts	32
7.1.6	Complete DECT system	32
7.1.7	Structure of the specification of the audio types	32
7.1.8	Audio Types and codecs	38
7.1.9	Audio Types and physical interfaces	38
7.2	Audio types applicable to Portable Parts	38
7.2.0	General	38
7.2.1	Performance levels of DECT Portable Parts (handsets)	38
7.2.2	Type 0: Reference PP (RePP)	39
7.2.3	PP Type 1a: "Classic" GAP narrowband handset	40
7.2.3.1	Introduction	40
7.2.3.2	Compatible services and codecs	40
7.2.3.3	Specification	40
7.2.4	PP Type 1b: "Improved" GAP narrowband handset	40
7.2.4.1	Introduction	40
7.2.4.2	Compatible services and codecs	40
7.2.4.3	Specification	40
7.2.5	PP Type 1c: HATS-tested "standard" narrowband handset	41
7.2.5.1	Introduction	41
7.2.5.2	Compatible services and codecs	41
7.2.5.3	Specification	41
7.2.6	PP Type 1d: HATS-tested "improved" narrowband handset	41
7.2.6.1	Introduction	41
7.2.6.2	Compatible services and codecs	41
7.2.6.3	Specification	41
7.2.7	PP Type 3a: HATS tested narrowband "standard" loudspeaking handsfree	42
7.2.7.1	Introduction	42
7.2.7.2	Compatible services and codecs	42
7.2.7.3	Specification	42
7.2.8	PP Type 3b: HATS tested narrowband "improved" loudspeaking handsfree	42
7.2.8.1	Introduction	42
7.2.8.2	Compatible services and codecs	42
7.2.8.3	Specification	42
7.2.9	PP Type 2a: P.311-tested wideband handset	43
7.2.9.1	Introduction	43
7.2.9.2	Compatible services and codecs	43
7.2.9.3	Specification	43
7.2.10	PP Type 2b: HATS-tested "standard" wideband handset or headset	43
7.2.10.1	Introduction	43
7.2.10.2	Compatible services and codecs	43
7.2.10.3	Specification	43
7.2.11	PP Type 2c: HATS tested "improved" wideband handset or headset	44
7.2.11.1	Introduction	44
7.2.11.2	Compatible services and codecs	44
7.2.11.3	Specification	44
7.2.12	PP Type 4a: HATS tested wideband "standard" loudspeaking handsfree	44
7.2.12.1	Introduction	44
7.2.12.2	Compatible services and codecs	44
7.2.12.3	Specification	44
7.2.13	PP Type 4b: HATS tested wideband "improved" loudspeaking and handsfree	45
7.2.13.1	Introduction	45
7.2.13.2	Compatible services and codecs	45
7.2.13.3	Specification	45
7.2.14	PP Type 5a: super-wideband 14 kHz handset	45
7.2.14.1	Introduction	45
7.2.14.2	Compatible services and codecs	45

7.2.14.3	Specification.....	45
7.2.15	PP Type 5b: super-wideband 14 kHz loudspeaking handsfree	45
7.2.15.1	Introduction.....	45
7.2.15.2	Compatible services and codecs.....	45
7.2.15.3	Specification.....	45
7.2.16	PP Type 6: PPs with external 2 wire, 3,1 kHz telephony interface.....	46
7.2.16.1	Introduction.....	46
7.2.16.2	Compatible services and codecs.....	46
7.2.16.3	Specification.....	46
7.3	Audio transmission types applicable to Fixed Parts	46
7.3.0	General.....	46
7.3.1	FP Type 0: Reference FP (ReFP).....	46
7.3.2	FP Type 1a: "classical" Fixed Part for ISDN Network	47
7.3.2.1	Introduction.....	47
7.3.2.2	Compatible services and codecs.....	47
7.3.2.3	Specifications	47
7.3.2.3.1	Transcoding and equalization	47
7.3.2.3.2	PP type detection	48
7.3.2.3.3	Activation of audio processing functions	48
7.3.2.3.4	Transmission specification	48
7.3.3	FP Type 1b: "new" Fixed Part for ISDN Network	48
7.3.3.1	Introduction.....	48
7.3.3.2	Compatible services and codecs.....	49
7.3.3.3	Specification.....	49
7.3.3.3.1	Transcoding and equalization	49
7.3.3.3.2	PP type detection	49
7.3.3.3.3	Activation of audio processing functions	49
7.3.3.3.4	Transmission specification	50
7.3.4	FP Type 2: FP with analog 2-wire interface, 3,1 kHz service	50
7.3.4.1	Introduction.....	50
7.3.4.2	Compatible services, physical interfaces and codecs	50
7.3.4.3	Specification.....	50
7.3.4.3.1	Transcoding, equalization and conversion	50
7.3.4.3.2	PP type detection and activation of audio processing functions.....	51
7.3.4.3.3	Transmission specification	51
7.3.5	FP Type 3: VoIP narrowband Fixed Part.....	51
7.3.5.1	Introduction.....	51
7.3.5.2	Compatible services, physical interfaces and codecs	51
7.3.5.3	Specification.....	52
7.3.5.3.1	Transcoding and equalization	52
7.3.5.3.2	PP type detection	52
7.3.5.3.3	Activation of audio processing functions	52
7.3.5.3.4	Transmission specification	53
7.3.6	FP Type 4: ISDN wideband Fixed Part	53
7.3.6.1	Introduction.....	53
7.3.6.2	Compatible services and codecs.....	53
7.3.6.3	Specification.....	54
7.3.6.3.1	Transcoding and equalization	54
7.3.6.3.2	PP type detection	54
7.3.6.3.3	Activation of audio processing functions	54
7.3.6.3.4	Transmission specification	54
7.3.7	FP Type 5: VoIP wideband Fixed Part	55
7.3.7.1	Introduction.....	55
7.3.7.2	Compatible services, physical interfaces and codecs	55
7.3.7.3	Specification.....	55
7.3.7.3.1	Transcoding and equalization	55
7.3.7.3.2	PP type detection	55
7.3.7.3.3	Activation of audio processing functions	56
7.3.7.3.4	Transmission specification	56
7.3.8	FP Type 6a: FP handling an Internal call inside a DECT FP (any service)	56
7.3.8.1	Introduction.....	56
7.3.8.2	Compatible services, physical interfaces and codecs	56

7.3.8.3	Specification.....	57
7.3.9	FP Type 6b: FP handling an n-party conference inside a DECT FP (any service).....	57
7.3.9.1	Introduction.....	57
7.3.9.2	Compatible services, physical interfaces and codecs.....	57
7.3.9.3	Specification for the conference bridge.....	57
7.3.10	FP Type 7: DECT Repeater part (REP).....	57
7.3.10.1	Introduction.....	57
7.3.10.2	Compatible services, physical interfaces and codecs.....	57
7.3.10.3	Specification.....	57
7.4	Additional features.....	58
7.4.1	Introduction.....	58
7.4.2	Echo canceller in Fixed Part.....	58
7.4.3	Echo suppressor in Fixed Part.....	59
7.5	Transmission characteristics for Portable Parts.....	59
7.5.1	Transmission characteristics for Portable Part type 1a ("Classic GAP" handset).....	59
7.5.1.1	PP frequency responses.....	59
7.5.1.1.1	Sending.....	59
7.5.1.1.2	Receiving.....	60
7.5.1.2	PP sending and receiving loudness ratings.....	60
7.5.1.2.1	Nominal values.....	60
7.5.1.2.2	User-controlled volume control in PP.....	60
7.5.1.2.3	PP adaptive volume control.....	61
7.5.1.3	Sidetone.....	61
7.5.1.3.1	Talker sidetone.....	61
7.5.1.3.2	Listener sidetone.....	61
7.5.1.4	Terminal coupling loss.....	62
7.5.1.4.1	Weighted Terminal Coupling Loss (TCLw).....	62
7.5.1.4.2	Stability loss.....	62
7.5.1.5	Distortion.....	62
7.5.1.5.1	Sending.....	62
7.5.1.5.2	Receiving.....	63
7.5.1.5.3	Sidetone.....	63
7.5.1.6	Out of band signals.....	63
7.5.1.6.1	Sending (discrimination against out of band input signals).....	63
7.5.1.6.2	Receiving (spurious out of band signals).....	63
7.5.1.7	Noise.....	63
7.5.1.7.1	Sending.....	63
7.5.1.7.2	Band-limited noise.....	63
7.5.1.7.3	Receiving.....	63
7.5.1.7.4	Level of sampling frequency (receiving).....	64
7.5.1.8	Acoustic shock.....	64
7.5.1.8.0	General.....	64
7.5.1.8.1	Continuous signal.....	64
7.5.1.8.2	Peak signal.....	64
7.5.1.9	PP Delay.....	64
7.5.1.10	PP ambient noise rejection.....	64
7.5.2	Additional requirements for PP type 1b ("improved GAP" handset).....	64
7.5.2.0	General.....	64
7.5.2.1	Terminal coupling loss.....	64
7.5.2.1.1	Weighted Terminal Coupling Loss (TCLw).....	64
7.5.2.2	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	65
7.5.2.3	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	65
7.5.2.4	Activation in Sending Direction.....	65
7.5.2.5	Activation in Receiving Direction.....	66
7.5.3	Transmission characteristics for PP types 1c and 1d (HATS tested, narrowband telephony handsets).....	66
7.5.3.1	PP frequency responses.....	66
7.5.3.1.1	Sending.....	66
7.5.3.1.2	Receiving.....	67
7.5.3.2	PP sending and receiving loudness ratings.....	69
7.5.3.2.1	Nominal values.....	69
7.5.3.2.2	User-controlled volume control in PP.....	70
7.5.3.2.3	PP adaptive volume control.....	70

7.5.3.3	Sidetone.....	71
7.5.3.3.1	Talker sidetone	71
7.5.3.3.2	D Factor.....	71
7.5.3.3.3	Sidetone delay	71
7.5.3.4	Terminal coupling loss.....	71
7.5.3.4.1	TCLw of Portable Part.....	71
7.5.3.4.2	Stability loss	72
7.5.3.5	Distortion	72
7.5.3.5.1	Sending Distortion.....	72
7.5.3.5.2	Receiving Distortion.....	72
7.5.3.6	Out of band signals.....	72
7.5.3.6.1	Out-of-band Signals in Send direction	72
7.5.3.6.2	Out-of-band signals in receiving direction	73
7.5.3.7	Noise	73
7.5.3.7.1	Sending.....	73
7.5.3.7.2	Receiving.....	73
7.5.3.8	Acoustic shock.....	74
7.5.3.8.0	General	74
7.5.3.8.1	Continuous signal	74
7.5.3.8.2	Peak signal.....	74
7.5.3.9	Delay.....	74
7.5.3.10	Variation of gain with input level-sending.....	74
7.5.3.11	Double Talk Performance	75
7.5.3.11.0	General	75
7.5.3.11.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	75
7.5.3.11.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,S,dt}$	75
7.5.3.11.3	Detection of Echo Components during Double Talk.....	76
7.5.3.11.4	Minimum activation level and sensitivity of double talk detection.....	76
7.5.3.12	Switching characteristics.....	76
7.5.3.12.0	General	76
7.5.3.12.1	Activation in Sending Direction.....	76
7.5.3.12.2	Activation in Receiving Direction.....	77
7.5.3.12.3	Silence Suppression and Comfort Noise Generation.....	77
7.5.3.12.4	Performance in sending direction in the presence of background noise.....	77
7.5.3.12.5	Speech Quality in the Presence of Background Noise.....	77
7.5.3.12.6	Quality of Background Noise Transmission (with Far End Speech).....	78
7.5.3.12.7	Quality of background noise transmission (with Near End Speech)	78
7.5.3.13	Quality of echo cancellation.....	78
7.5.3.13.0	General	78
7.5.3.13.1	Temporal echo effects	78
7.5.3.13.2	Spectral Echo Attenuation	78
7.5.4	Transmission characteristics for PP types 3a and 3b (narrowband loudspeaking and handsfree devices).....	79
7.5.4.1	Sending sensitivity/frequency response	79
7.5.4.2	Receive sensitivity/frequency response.....	79
7.5.4.3	Sending loudness rating	82
7.5.4.4	Receive loudness rating.....	82
7.5.4.5	Sending distortion	83
7.5.4.6	Receiving distortion	83
7.5.4.7	Out-of-band signals in sending direction	83
7.5.4.8	Out-of-band signals in receiving direction.....	84
7.5.4.9	Sending noise	84
7.5.4.10	Receiving noise	84
7.5.4.11	Terminal Coupling Loss of PP.....	85
7.5.4.12	Stability Loss of PP.....	85
7.5.4.13	Double Talk Performance	85
7.5.4.13.0	General	85
7.5.4.13.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	85
7.5.4.13.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	86
7.5.4.13.3	Detection of Echo Components during Double Talk.....	86
7.5.4.13.4	Minimum activation level and sensitivity of double talk detection.....	87
7.5.4.14	Switching characteristics.....	87

7.5.4.14.0	General	87
7.5.4.14.1	Activation in Sending Direction	87
7.5.4.14.2	Activation in Receiving Direction	87
7.5.4.14.3	Silence Suppression and Comfort Noise Generation	88
7.5.4.14.4	Performance in sending direction in the presence of background noise	88
7.5.4.14.5	Speech Quality in the Presence of Background Noise	88
7.5.4.14.6	Quality of Background Noise Transmission (with Far End Speech)	88
7.5.4.14.7	Quality of background noise transmission (with Near End Speech)	88
7.5.4.15	Quality of echo cancellation	89
7.5.4.15.0	General	89
7.5.4.15.1	Temporal echo effects	89
7.5.4.15.2	Spectral Echo Attenuation	89
7.5.5	Transmission characteristics for PP type 2a (P.311 tested, wideband handset)	89
7.5.5.0	General	89
7.5.5.1	Sending characteristics	89
7.5.5.1.1	Loudness rating	89
7.5.5.1.2	Sensitivity/frequency characteristics	90
7.5.5.1.3	Noise	90
7.5.5.1.4	Distortion	90
7.5.5.1.5	Discrimination against out-of-band input signals	90
7.5.5.2	Receiving characteristics	90
7.5.5.2.1	Loudness rating	90
7.5.5.2.2	Sensitivity/frequency characteristics	90
7.5.5.2.3	Noise	90
7.5.5.2.4	Distortion	91
7.5.5.2.5	Spurious out-of-band receiving signals	91
7.5.5.3	Sidetone characteristics	91
7.5.5.3.1	Talker sidetone	91
7.5.5.3.2	Sidetone distortion	91
7.5.5.4	Echo path loss characteristics	91
7.5.5.4.1	Weighted terminal coupling loss	91
7.5.5.4.2	Stability loss	92
7.5.6	Transmission characteristics for PP type 2b and 2c (HATS tested wideband handsets)	92
7.5.6.1	PP frequency responses	92
7.5.6.1.1	Sending	92
7.5.6.1.2	Receiving	93
7.5.6.2	PP send and receive loudness ratings	95
7.5.6.2.1	Nominal values	95
7.5.6.2.2	User-controlled volume control in PP	96
7.5.6.2.3	PP adaptive volume control	96
7.5.6.3	Sidetone	96
7.5.6.3.1	Talker sidetone	96
7.5.6.3.2	D Factor	97
7.5.6.3.3	Sidetone delay	97
7.5.6.4	Terminal coupling loss	97
7.5.6.4.1	Weighted Terminal Coupling Loss (TCL _w)	97
7.5.6.4.2	Stability loss	97
7.5.6.5	Distortion	98
7.5.6.5.1	Sending Distortion	98
7.5.6.5.2	Receiving Distortion	98
7.5.6.6	Noise	98
7.5.6.6.1	Sending	98
7.5.6.6.2	Receiving	99
7.5.6.7	Acoustic shock	99
7.5.6.7.0	General	99
7.5.6.7.1	Continuous signal	99
7.5.6.7.2	Peak signal	99
7.5.6.8	Delay	99
7.5.6.9	Variation of gain with input level-sending	99
7.5.6.10	Double talk Performance	100
7.5.6.10.0	General	100
7.5.6.10.1	Attenuation Range in Sending Direction during Double Talk A _{H,S,dt}	100

7.5.6.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	101
7.5.6.10.3	Detection of Echo Components during Double Talk.....	101
7.5.6.10.4	Minimum activation level and sensitivity of double talk detection.....	101
7.5.6.11	Switching characteristics.....	102
7.5.6.11.0	General.....	102
7.5.6.11.1	Activation in Sending Direction.....	102
7.5.6.11.2	Activation in Receiving Direction.....	102
7.5.6.11.3	Silence Suppression and Comfort Noise Generation.....	102
7.5.6.11.4	Performance in Sending in the Presence of Background Noise.....	102
7.5.6.11.5	Speech Quality in the Presence of Background Noise.....	103
7.5.6.11.6	Quality of Background Noise Transmission (with Far End Speech).....	103
7.5.6.11.7	Quality of background noise transmission (with Near End Speech).....	103
7.5.6.12	Quality of echo cancellation.....	103
7.5.6.12.0	General.....	103
7.5.6.12.1	Temporal echo effects.....	103
7.5.6.12.2	Spectral Echo Attenuation.....	104
7.5.7	Transmission characteristics for PP types 4a and 4b (HATS Tested wideband loudspeaking and handsfree devices).....	104
7.5.7.1	Sending sensitivity/frequency response.....	104
7.5.7.2	Receive sensitivity/frequency response.....	105
7.5.7.3	Sending loudness rating.....	108
7.5.7.4	Receive loudness rating.....	108
7.5.7.5	Sending distortion.....	109
7.5.7.6	Receiving distortion.....	109
7.5.7.7	Out-of-band signals in sending direction.....	110
7.5.7.8	Out-of-band signals in receiving direction.....	110
7.5.7.9	Sending noise.....	110
7.5.7.10	Receiving noise.....	110
7.5.7.11	Terminal Coupling Loss.....	111
7.5.7.12	Stability Loss.....	111
7.5.7.13	Double Talk Performance.....	111
7.5.7.13.0	General.....	111
7.5.7.13.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	112
7.5.7.13.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	112
7.5.7.13.3	Detection of Echo Components during Double Talk.....	112
7.5.7.13.4	Minimum activation level and sensitivity of double talk detection.....	113
7.5.7.14	Switching characteristics.....	113
7.5.7.14.0	General.....	113
7.5.7.14.1	Activation in Sending Direction.....	113
7.5.7.14.2	Activation in Receiving Direction.....	113
7.5.7.14.3	Silence Suppression and Comfort Noise Generation.....	114
7.5.7.14.4	Performance in sending direction in the presence of background noise.....	114
7.5.7.14.5	Speech Quality in the Presence of Background Noise.....	114
7.5.7.14.6	Quality of Background Noise Transmission (with Far End Speech).....	114
7.5.7.14.7	Quality of background noise transmission (with Near End Speech).....	114
7.5.7.15	Quality of echo cancellation.....	115
7.5.7.15.1	Temporal echo effects.....	115
7.5.7.15.2	Spectral Echo Attenuation.....	115
7.6	Transmission characteristics for Fixed Parts.....	115
7.6.1	Transmission characteristics for FP type 1a ("Classic" Fixed Part with ISDN Network interface, 3,1 kHz service).....	115
7.6.1.1	Reduction of echo from PP.....	115
7.6.1.2	FP Network echo control.....	116
7.6.1.3	FP adaptive volume control.....	117
7.6.1.4	FP Delay.....	117
7.6.2	Transmission characteristics for FP type 1b ("new" Fixed Part with ISDN Network interface, 3,1 kHz service).....	117
7.6.2.0	General.....	117
7.6.2.1	FP Network echo control.....	117
7.6.2.2	FP adaptive volume control.....	117
7.6.2.3	FP Delay.....	118
7.6.3	Transmission characteristics for FP type 2 (Fixed Part with analog 2-wire interface, 3,1 kHz service).....	118

7.6.3.1	FP adaptive volume control	118
7.6.3.2	Network echo control	118
7.6.3.3	Additional requirements for DECT FP provided with a 2-wire PSTN interface	119
7.6.3.3.0	Test methods	119
7.6.3.3.1	General requirements	119
7.6.3.3.2	Speech performance characteristics	119
7.6.3.4	FP Delay	120
7.6.4	Transmission characteristics for FP type 3 (Fixed Part with VoIP interface, 3,1 kHz service)	120
7.6.4.1	Send delay	120
7.6.4.2	Receive delay	120
7.6.4.3	Adaptive volume control	121
7.6.5	Transmission characteristics for FP type 4 (Fixed Part with ISDN network interface, wideband service)	121
7.6.5.1	FP adaptive volume control	121
7.6.5.2	FP Delay	121
7.6.6	Transmission characteristics for FP type 5 (Fixed Part with VoIP interface, wideband service)	121
7.6.6.1	Send Delay	121
7.6.6.2	Receive delay	122
7.6.6.3	FP adaptive volume control	122
8	Additional features	122
8.1	Loudspeaking hands-free and headset facilities	122
8.1.1	Loudspeaking hands-free facility	122
8.1.2	Headset facility	122
8.2	Tandem with mobile radio network	122
8.2.0	General	122
8.2.1	Tandem with GSM	123
8.2.1.0	Configuration	123
8.2.1.1	Network echo control	123
8.2.1.2	Terminal coupling loss	123
8.2.1.3	The GSM mobile transmitter operates in continuous mode	123
8.2.1.4	The GSM mobile transmitter operates in discontinuous mode, DTX	123
8.3	DECT connected to the GSM fixed network	123
8.3.0	General	123
8.3.1	Network echo control	124
8.3.2	Terminal coupling loss	124
8.4	Wireless Relay Stations (WRS)	124
8.4.0	General	124
8.4.1	Modified FP network echo control requirements for implementation of 2 and 3 CRFP links in cascade	125
Annex A (informative): Description of "reference" echo control devices		126
A.0	General	126
A.1	Handset echo	126
A.1.0	Applicability	126
A.1.1	Overview	126
A.1.1.1	Connection to the PSTN/ISDN	126
A.1.1.1.0	General	126
A.1.1.1.1	Local and national calls	126
A.1.1.1.2	Long distance connections with echo control devices in the PSTN/ISDN, e.g. calls via satellites	126
A.1.1.2	Connection to the GSM network	127
A.1.2	Implementation of the FP echo control function	127
A.1.2.0	General	127
A.1.2.1	Suppression threshold	128
A.1.2.2	Static characteristics of activation control	128
A.1.2.3	Dynamic characteristics of activation control	128
A.2	Network echo	128
A.2.0	Applicability	128
A.2.1	Soft suppressor implementation of requirement 2	129
A.2.1.0	General	129

A.2.1.1	Static characteristics	130
A.2.1.2	Dynamic characteristics	130
A.2.2	Additional echo control for a 2-wire interface of requirement 1	130
A.2.3	Echo canceller used for both requirements 1 and 2	131
Annex B (informative):	Local loop application	132
B.0	General	132
B.1	DECT tethered local loop replacement with 2-wire PP end system.....	132
B.1.0	Configuration	132
B.1.1	TCLw requirements.....	132
B.1.2	Network echo	133
Annex C (informative):	GSM Discontinuous Transmission (DTX), and Voice Activity Detection (VAD).....	134
Annex D (informative):	Speech levels in relation to ambient room noise and examples of adaptive volume control settings	135
Annex E (informative):	Echo related topics.....	136
E.1	Summary table on echo parameters for PPs and FPs	136
E.2	General information about Delay-Echo interaction for DECT terminals.....	142
Annex F (informative):	Guidelines on specific requirements.....	145
F.1	Delay requirements for FPs with VoIP interface	145
F.1.1	Delay requirements for FP type 3 (Fixed Part with VoIP interface, 3,1 kHz service).....	145
F.1.1.0	General.....	145
F.1.1.1	Send delay.....	145
F.1.1.2	Receive delay.....	146
F.1.2	Delay requirements for FP type 5 (Fixed Part with VoIP interface, wideband service).....	147
F.1.2.0	General.....	147
F.1.2.1	Send Delay.....	147
F.1.2.2	Receive delay.....	148
Annex G (informative):	Bibliography.....	150
Annex H (informative):	Change history	151
History		152

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 8 of a multi-part deliverable ([1] to [7]). Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in ETSI TR 101 178 [i.6] and ETSI ETR 043 [i.7].

National transposition dates	
Date of adoption of this EN:	25 September 2017
Date of latest announcement of this EN (doa):	31 December 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2018
Date of withdrawal of any conflicting National Standard (dow):	30 June 2019

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document is one of the parts of the specification of the Digital Enhanced Cordless Telecommunications (DECT) Common Interface (CI).

This part of the DECT CI specifies the speech and audio coding and transmission requirements.

In order to ensure satisfactory interworking of different portable and fixed units, it is necessary to specify the transmission performance of the analog information over the digital link. This requires not only use of a common speech algorithm, but also standardization of frequency responses, reference speech levels (or loudness) at the air interface and various other parameters.

The present document applies to DECT equipment which includes all the necessary functions to provide real-time two-way speech conversation. Several speech services are defined in the present document, including conventional 3,1 kHz telephony, wideband 7 kHz voice transmission and super-wideband 14 kHz service. DECT Fixed part providing such services may be connected to the public circuit switched (PSTN/ISDN) network, to private networks or to the Internet.

Tethered fixed point local loop applications are not required to comply with the requirements of the present document.

For the DECT systems which connect to the Public Switched Telephone Network (PSTN) via an analog interface, the additional requirements, which are implemented in the FP, have as much as possible been aligned with ETSI TBR 038 [29].

A summary of the control and the use of the DECT echo control functions, to guide on need for options to manufacturers and installers, is found in annex A.

Information concerning test methods can be found in ETSI EN 300 176-1 [9] and ETSI EN 300 176-2 [10] (previously covered by ETSI TBR 010 [i.5]). The test methods take into account that DECT is a digital system.

The present document includes New Generation DECT, a further development of the DECT standard introducing wideband speech, improved data services, new slot types and other technical enhancements.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".