ETSITS 103 383 V12.7.0 (2015-02)



Smart Cards; Specification Embedded UICC; Requirements Specification (Release 12)

Reference RTS/SCP-ReUICCvc70 Keywords embedded, Smart Card

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intell	ectual Property Rights		5	
Forev	vord		5	
Moda	al verbs terminology		5	
	22			
1	•			
2				
2.1 2.2		eses.		
3 3.1		viations		
3.1a		er study		
3.2	Abbreviations		9	
4	Abstract (informative		10	
	Abstract (informative	tive)	10	
5	Background (informa	tive)	11	
5.1	Overview of the use	cases	11	
5.2	Use Case: 1 - Provis	ioning of multiple eUICCs for M2M	11	
5.2.1	Use case I - exam	mple a) - Utility Meters	11	
5.2.2	Use case 1 - exam	mple b) - Security Camera	11	
5.2.3 5.3	Use case 1 - exal	npie c) - Telemanes	12	
5.3.1	Use case 2 - Provisioning of an eUICC for a first subscription with a new connected device			
5.3.2				
5.4	Use case 3 - Change of subscription for a device			
5.4.1		nple a) - Change of subscription by consumer		
5.4.2		mple b) - Change of subscriptions for devices for enterprise workforce		
5.5	Use Case 4 - Change	e of SM-SR	13	
5.6	Use Case 5 - Termin	al state and capabilities reporting	13	
6	Requirements		14	
6.1	General		14	
6.2	Profile, Application	and File Structure	14	
6.3				
6.4	Security		16	
6.5	Profile Interoperabil	ity and Interactions	17	
6.6	•			
6.7	•			
6.8	Policy Rules		18	
Anne	ex A (informative):	Void	19	
Anne	ex B (informative):	States (see also annex D)	20	
B.1	States of eUICC		20	
B.2				
B.3	States of Applications	s in Profiles	20	
Anne	ex C (informative):	Logical aspects of eUICC Architecture and associated Security		
		Credentials	21	
Anne	ex D (informative):	Profiles and NAA (Network Access Application) States	22	
Annex E (informative):		Profile Aspects	23	

Histo	nrv		27
Annex F (informative):		Change history	25
E.2	Profile Related Principal	ples	23
E.1	Profile Content		23

INTERNITATION OF BRANCH OF THE STANDARD OF THE

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for ETSI members and non-members, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- the first digit:

 - or greater indicates TC SCP approved document under change control.
- presented to TC SCP for information, are the dead of the result of the r or greater indicates TC SCP and cond digit is incremas, etc. the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- the third digit is incremented when editorial only changes have been incorporated in the document.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "may not", "need", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

Work on Machine-to-Machine (M2M) applications has given rise to the possibility of having a UICC that is embedded in a communication device in such a way that the UICC is not easily accessible or replaceable. The ability to change network subscriptions on such devices becomes problematic, thus necessitating new methods for securely and remotely provisioning access credentials on these Embedded UICCs (eUICC) and managing subscription changes from one MNO to another.

In its current state, the present document is to be considered as a "work in progress". It contains a restricted set of requirements related to the provisioning of profiles in an eUICC as well as general requirements on the architecture of the eUICC. As a consequence, some of the elements required to specify a complete technical solution are missing, among which are requirements for:

- management of profiles;
- management of credentials;
- the policy control function;

which will be defined in further versions of the present document.

I ah SI A DARI Raids to the standards of the standards of

1 Scope

The present document defines the use cases and requirements for an embedded UICC.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

• In the case of a reference to a TC SCP document, a non specific reference implicitly refers to the latest version of that document in the same Release as the present document.

Referenced documents which are not found to be publicly available in the expected location might be found at http://docbox.etsi.org/Reference.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 221: "Smart Cards; UCC-Terminal interface; Physical and logical characteristics".
- [2] ETSI TS 102 671: "Smart Cards; Machine to Machine UICC; Physical and logical characteristics".
- [3] ETSI TS 102 223; "Smart Cards; Card Application Toolkit (CAT)".
- [4] ETSI TS 102 241: "Smart Cards: UICC Application Programming Interface (UICC API) for Java Card (TM)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

• In the case of a reference to a TC SCP document, a non specific reference implicitly refers to the latest version of that document in the same Release as the present document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Recommendation ITU-T E.212: "The international identification plan for public networks and subscriptions".
- [i.2] ETSI TR 102 216: "Smart cards; Vocabulary for Smart Card Platform specifications".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 102 216 [i.2] and the following apply:

Embedded UICC: UICC which is not easily accessible or replaceable, is not intended to be removed or replaced in the terminal, and enables the secure changing of subscriptions

Enabled Profile: profile, the files and/or applications (e.g. NAA) of which are selectable over the UICC-Terminal interface

eUICC Management Credentials: credentials used to verify the authorization for the establishment of Profile Management Credentials and Profile Provisioning Credentials

eUICC Supplier: supplier of the eUICC modules and resident software (such as firmware and operating system)

Mobile Network Operator (MNO): entity providing communication services to its customers through mobile networks

Network Access Application (NAA): application residing on an eUICC that provides authorization to access a network

EXAMPLE: A USIM application.

NOTE: Copied from TR 102 216 [i.2], to be deleted when the current document is finalised.

Network Access Credentials (NAC): data required to authenticate to an ITU E.212 [i.1] Network

NOTE: Network Access Credentials may include data such as Ki/K, and IMSI stored within a NAA.

Operational Profile: Profile containing one or more network access applications and associated network access credentials

Operational Subscription: subscription that enables a device to access an ITU E.212 [i.1] network for the purpose of accessing telecommunication and related services

Policy: principles reflected in a set of rules that govern the behaviour of an eUICC and/or entities involved in the remote management of the eUICC

Policy Control Function: function that defines, updates or removes Policy Rules to implement a Policy

Policy Enforcement Function: function that executes Policy Rules to implement a Policy

Policy Rule: defines the actions required to implement a Policy and the conditions under which they are executed

eUICC Policy Control Credentials: credentials used for authorisation and authentication for the establishment and update of the Policy Rules defined on the eUICC outside Profiles

NOTE: This definition might be refined according to the decision about the need to have Policy Rules defined inside and/or outside Profiles.

Profile: combination of a file structure, data and applications to be provisioned onto, or present on, an eUICC

Profile Access Credentials: data required to exist within a Profile so that secured communication can be set up between an external entity and the eUICC in order to manage that Profile's structure and its data (e.g. operator OTA keys)

Profile Container: logical container for a Profile on an eUICC providing security services, enabling separation of Profiles and providing secure communication

Profile Container Initialisation: process of preparing a Profile Container so that it is ready for Profile Installation

Profile Loading: transfer of a profile from a Profile Provisioning Credentials holder into the eUICC so that it is ready for installation

Profile Transport: transfer of a cryptographically protected Profile from a Profile Management Credential holder to the eUICC

Profile Installation: process of allocating resources and registering parameters for a Profile to bring it to a state where it can be enabled

Profile Provisioning Credentials: data required to exist within an eUICC so that a Profile downloaded from an external entity can be decrypted and installed on the eUICC

Profile Management Credentials: data required to exist within an eUICC so that a secured communication can be set up between an external entity and the eUICC in order to manage the Profiles on the eUICC

Profile Management Operations: consists of Profile Transport, Profile deletion, Profile enabling, and Profile disabling

Provisioning: container creation and initialisation, loading, and installation of a Profile into an eUICC

Provisioning Profile: Profile containing one or more network access applications, and associated network access credentials which, when installed on an eUICC, enables access to communication network(s), to provide transport capability for eUICC management and profile management between the eUICC and an SM-SR

Provisioning Subscription: subscription, with its associated provisioning Profile, that enables a device to access a mobile network for the purpose of management of operational Profiles on the eUICC

Subscriber: entity that has a subscription with a telecommunications service provider

Subscription: commercial relationship for the supply of services between the Subscriber and Telecommunications Service Provider

Subscription Manager: combination of the functions of the SM-SR and the SM-DP

Subscription Manager - Data Preparation (SM-DP): role that prepares operational and provisioning Profiles to be securely provisioned on the eUICC e.g. encryption of Profile

NOTE 1: Also known as Profile Provisioning Credentials holder

NOTE 2: "securely" is felt to relate to requirements captured in an appropriate section of the present document. The term "securely" may be removed from this definition once those requirements are specified.

Subscription Manager - Secure Routing (SM-SR): role that securely performs functions which directly manage the operational and provisioning Profiles on the CUICC

NOTE: "securely" is felt to relate to requirements captured in an appropriate section of the present document. The term "securely" may be removed from this definition once those requirements are specified.

Telecommunications Service Provider: MNO, or party trusted by the MNO acting on behalf of the MNO, which provides services to the subscriber

3.1a Definitions for further study

Definitions are required for the following terms:

• Initialised State:

NOTE: This definition is required. Best proposal so far: "refers to the state the eUICC is in when an operational profile is either not active or not present, and the eUICC is only accessible for the purpose of management of operational Profiles".

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATR Answer To Reset

CAT Card Application Toolkit

CSIM CDMA Subscriber Identity Module

eUICC embedded UICC FFS For Further Study

IMSI International Mobile Subscriber Identity

ISIM IM Services Identity Module

M2M Machine to Machine (communication)

MNO Mobile Network Operator
NAA Network Access Application
NAC Network Access Credentials.
OEM Original Equipment Manufacturer

OTA Over-The-Air

PCF Policy Control Function
PIN Personal Identification Number
PMC Profile Management Credentials

PUK PIN Unblocking Key

RAM Remote Application Management

RFM Remote File Management

SD Security Domain

SIM Subscriber Identity Module SM Subscription Manager

SM-DP Subscription Manager - Data Preparation SM-SR Subscription Manager - Secure Routing

SP Service Provider TBD To Be Defined

USIM Universal Subscriber Identity Module

4 Abstract (informative)

The present document enables remote management of an embedded UICC (eUICC) for purposes of changing an MNO subscription without requiring a physical removal and replacement of the UICC in the end Device.

The present document develops use cases and requirements for the "enhanced, remote management" of a UICC, which is embedded in a communication device, i.e. where the UICC is not intended to be removed. This type of embedded UICC (eUICC) is compatible with Machine-to-Machine (M2M) applications. The eUICC may be embedded at the manufacturing site in advance, depending on the country and network operator, and is compatible for use in a variety of end-user equipment. In these scenarios there may be a requirement to remotely change a subscription easily, similar to what is currently achieved by physically changing the UICC.

The purpose for defining these requirements is to provide ease of use and deployment benefits for end users/consumers and thereby stimulate the M2M sector. A further intent is to enable the creation of common standards and processes for remote management of profiles on an eUICC, such that interoperability is ensured.

It is noted that new business models and usage scenarios, primarily driven by M2M, struggle when supported by the traditional UICC/SIM card. For example:

- By installing a physical UICC, the user is connected to a specific network, as the card only provides access to one network. Should the user wish to (or need to) use another network, then they or the M2M Service Provider has to fit another card in the user's device.
- Changing a UICC may be problematic since that M2M equipment may be remotely located and/or hermetically sealed. It should be noted that where the UICC is not intended to be sealed and inaccessible, the portability of traditional form factor UICC cards is perceived to be a user benefit.
- Non-standard provisioning and re-provisioning methods are being defined and used. These present security implications and a risk of fragmentation within the industry.

New remote provisioning/re-provisioning mechanisms are required to support the new business models and usage scenarios.