

SLOVENSKI STANDARD
SIST EN 300 392-2 V2.1.1:2003
01-december-2003

Prizemni snopovni radio (TETRA) – Govor in podatki (V+D) – 2. del: Radijski vmesnik (AI)

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: [EN 300 392-2 Version 2.1.1](#)

<https://standards.iteh.ai/catalog/standards/sist/1bc05d1e-09e7-4016-8f7a-5cde19845006/sist-en-300-392-2-v2-1-1-2003>

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	------------------------------------	--------------------------------------

SIST EN 300 392-2 V2.1.1:2003 **en**

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 392-2 V2.1.1:2003

<https://standards.iteh.ai/catalog/standards/sist/1bc05d1e-09e7-4016-8f7a-5cde19845006/sist-en-300-392-2-v2-1-1-2003>

ETSI EN 300 392-2 V2.1.1 (2000-12)

European Standard (Telecommunications series)

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 392-2 V2.1.1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/1bc05d1e-09e7-4016-8f7a-5cde19845006/sist-en-300-392-2-v2-1-1-2003>



Reference

REN/TETRA-03023-02

Keywords

radio, TETRA, V+D

ETSI

650 Route des Lucioles
 F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
 Association à but non lucratif enregistrée à la
 Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 392-2 V2.1.1:2003](#)
<https://standards.iteh.ai/catalog/standards/sist/1bc05d1e-09e7-4016-8f7a-5cde19845006/sist-en-300-392-2-v2-1-1-2003>

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
 Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
 The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
 All rights reserved.

Contents

Intellectual Property Rights	29
Foreword	29
1 Scope.....	30
2 References	31
3 Definitions and abbreviations.....	33
3.1 Definitions	33
3.2 Abbreviations.....	37
4 Radio aspects.....	39
4.1 Introduction.....	39
4.2 Set of logical channels.....	39
4.3 Reference configuration.....	39
4.4 Error control schemes.....	40
4.5 Multiple access and time slot structure.....	40
4.5.1 Hyperframes, multiframe and frames	41
4.5.2 Time slots and bursts.....	41
4.5.3 Mapping of logical channels onto physical channels	41
4.6 Coding, interleaving and scrambling.....	42
4.7 Modulation.....	42
4.8 Transmission and reception	42
4.9 Other radio-related functions	42
4.10 Performance.....	43
4.11 TETRA modes of operation.....	43
4.11.1 Transmission modes.....	43
4.11.1.1 D-CT mode	43
4.11.1.2 D-CTT mode	43
4.11.1.3 D-MCCTT mode	43
4.11.1.4 U-MST mode	43
4.11.2 Control modes.....	44
4.11.2.1 NCM.....	44
4.11.2.2 MC mode	44
5 Modulation	44
5.1 Introduction.....	44
5.2 Modulation type	44
5.3 Modulation rate	44
5.4 Modulation symbol definition	44
5.5 Modulated signal definition	45
5.6 Modulation filter definition	45
5.7 Modulation block diagram.....	46
6 Radio transmission and reception.....	46
6.1 Introduction.....	46
6.2 Frequency bands and channel arrangement	46
6.3 Reference test planes	46
6.4 Transmitter characteristics	47
6.4.1 Output power	47
6.4.1.1 BS	47
6.4.1.2 MS	48
6.4.2 Unwanted conducted emissions.....	48
6.4.2.1 Definitions.....	48
6.4.2.2 Unwanted emissions close to the carrier	49
6.4.2.2.1 Emission during the useful part of the burst	49
6.4.2.2.2 Emission during the switching transients.....	49
6.4.2.3 Unwanted emissions far from the carrier	50
6.4.2.4 Unwanted emissions during the CLCH and BLCH	50

6.4.2.5	Unwanted emissions in the non-transmit state	50
6.4.3	Unwanted radiated emissions	50
6.4.4	RF tolerance	50
6.4.5	RF Output power time mask.....	51
6.4.5.1	BS	52
6.4.5.2	MS	52
6.4.6	Transmitter intermodulation attenuation	52
6.4.6.1	Definition.....	52
6.4.6.2	BS	52
6.4.6.3	MS	52
6.4.7	Intra-BS intermodulation requirements.....	53
6.5	Receiver characteristics	53
6.5.1	Blocking characteristics	53
6.5.1.1	Definition.....	53
6.5.1.2	Specification.....	53
6.5.2	Spurious response rejection	54
6.5.2.1	Definition	54
6.5.2.2	Specification.....	54
6.5.3	Intermodulation response rejection	54
6.5.3.1	Definition.....	54
6.5.3.2	Specification.....	54
6.5.4	Unwanted conducted emissions.....	54
6.5.4.1	Definition	54
6.5.4.2	Specification.....	55
6.5.5	Unwanted radiated emissions	55
6.6	Transmitter/receiver performance	55
6.6.1	Modulation accuracy.....	55
6.6.1.1	Ideal case.....	55
6.6.1.2	Vector error magnitude requirement at symbol time.....	55
6.6.2	Receiver performance	56
6.6.2.1	Nominal error rates.....	57
6.6.2.2	Dynamic reference sensitivity performance.....	57
6.6.2.2.1	BS receiver performance /catalog/standards/sist/1hc05d1e-09e7-4016-8f7a- 5006/sist-en-300-392-2-v2.1.1-2003	57
6.6.2.2.2	MS receiver performance /catalog/standards/sist/1hc05d1e-09e7-4016-8f7a- 5006/sist-en-300-392-2-v2.1.1-2003	58
6.6.2.3	Receiver performance at reference interference ratios.....	58
6.6.2.3.1	BS receiver performance	59
6.6.2.3.2	MS receiver performance	59
6.6.2.4	Static reference sensitivity performance	59
6.6.2.4.1	BS receiver performance	60
6.6.2.4.2	MS receiver performance	60
6.6.2.5	MS receiver performance for synchronization burst acquisition	60
6.6.3	Propagation conditions.....	60
6.6.3.1	Propagation conditions - introduction.....	61
6.6.3.2	Tap-gain process types.....	61
6.6.3.3	Propagation models	62
7	Radio sub-system synchronization	62
7.1	Introduction.....	62
7.2	General description of synchronization system.....	62
7.3	Timebase counters.....	63
7.3.1	Timing counters	63
7.3.2	Values of the counters.....	63
7.4	Timing of transmitted signals.....	63
7.5	BS requirements for synchronization	64
7.6	MS requirements for synchronization.....	64
8	Channel coding and scrambling	64
8.1	Introduction.....	64
8.2	General	65
8.2.1	Interfaces in the error control structure	65
8.2.2	Notation.....	66
8.2.3	Definition of error control codes.....	66

8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes	66
8.2.3.1.1	Encoding by the 16-state mother code of rate $\frac{1}{4}$	66
8.2.3.1.2	Puncturing of the mother code	67
8.2.3.1.3	Puncturing scheme of the RCPC code of rate $\frac{2}{3}$	67
8.2.3.1.4	Puncturing scheme of the RCPC code of rate $\frac{1}{3}$	67
8.2.3.1.5	Puncturing scheme of the RCPC code of rate $\frac{292}{432}$	67
8.2.3.1.6	Puncturing scheme of the RCPC code of rate $\frac{148}{432}$	67
8.2.3.2	Shortened (30,14) Reed-Muller (RM) code	68
8.2.3.3	(K_1+16 , K_1) block code	68
8.2.4	Definition of interleaving schemes	69
8.2.4.1	Block interleaving	69
8.2.4.2	Interleaving over N blocks	69
8.2.5	Definition of scrambling	69
8.2.5.1	Scrambling method	69
8.2.5.2	Scrambling sequence	69
8.3	Error control schemes	70
8.3.1	Access Assignment Channel (AACH)	71
8.3.2	Broadcast Synchronization Channel (BSCH)	71
8.3.3	Traffic channels in circuit switched mode	72
8.3.3.1	Traffic CHannel, net rate = 4,8 kbit/s (TCH/4,8)	72
8.3.3.2	Traffic CHannel, net rate = 2,4 kbit/s (TCH/2,4)	73
8.3.3.3	Traffic CHannel, net rate = 7,2 kbit/s (TCH/7,2)	73
8.3.3.4	Speech Traffic Channel, full slot (TCH/S)	74
8.3.3.5	Speech Traffic Channel, half slot (TCH/S)	74
8.3.4	Signalling channels for signalling and packet mode data	74
8.3.4.1	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH/HD), Broadcast Network CHannel (BNCH), and STealing CHannel (STCH)	74
8.3.4.2	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH/HU)	75
8.3.4.3	Signalling CHannel for (mapping onto Full bursts (SCH/F))	75
9	Channel multiplexing for V+D	76
9.1	Introduction	76
9.2	Logical channels	76
9.2.1	Logical channels hierarchy	76
9.2.2	Traffic channels	76
9.2.3	Control CHannels (CCH)	76
9.2.3.1	General	76
9.2.3.2	BCCH	77
9.2.3.3	LCH	77
9.2.3.4	SCH	77
9.2.3.5	AACH	77
9.2.3.6	STCH	77
9.3	The physical resource	78
9.3.1	General	78
9.3.2	RF channels	78
9.3.3	Timeslots	79
9.3.4	TDMA frame	79
9.3.5	Timeslot numbering	79
9.3.6	Subslot	79
9.3.7	Multiframe	79
9.3.8	Hyperframe	79
9.3.9	Frame alignment	79
9.4	Physical channels	79
9.4.1	General	79
9.4.2	Types of physical channels	79
9.4.2.1	CP channel	80
9.4.2.2	TP channel	80
9.4.2.3	UP channel	80
9.4.3	Bursts	80
9.4.3.1	General	80
9.4.3.2	Modulation symbol numbering	80
9.4.3.3	Modulation bit numbering	80

9.4.3.4	Burst timing.....	81
9.4.4	Type of bursts	81
9.4.4.1	General.....	81
9.4.4.2	Modulation bits allocation.....	83
9.4.4.2.1	Control uplink Burst (CB)	83
9.4.4.2.2	Linearization uplink Burst (LB).....	83
9.4.4.2.3	Linearization downlink burst	84
9.4.4.2.4	Normal Uplink Burst (NUB).....	84
9.4.4.2.5	Normal continuous downlink burst	84
9.4.4.2.6	Synchronization continuous downlink burst	84
9.4.4.2.7	Normal discontinuous downlink burst.....	85
9.4.4.2.8	Synchronization discontinuous downlink burst.....	86
9.4.4.3	Burst fields.....	86
9.4.4.3.1	Frequency correction field.....	86
9.4.4.3.2	Normal training sequence	86
9.4.4.3.3	Extended training sequence	87
9.4.4.3.4	Synchronization training sequence.....	87
9.4.4.3.5	Tail bits.....	87
9.4.4.3.6	Phase adjustment bits	87
9.4.5	Transmission modes.....	88
9.4.5.1	BS continuous transmission	88
9.4.5.2	BS timesharing transmission	88
9.4.5.3	MS multiple slot transmission	89
9.5	Mapping of logical channels into physical channels	90
9.5.1	General mapping of logical channels	90
9.5.2	Mapping of BCCH and CLCH	91
9.5.3	Mapping of SCH	92
9.5.4	Mapping of TCH and STCH.....	92
9.5.5	Mapping of AACH	92
9.6	Monitoring pattern for transmitting MSs.....	92
9.7	BS timesharing transmission.....	93
9.7.1	Carrier sharing.....	93
9.7.2	MCCH sharing.....	93
9.8	Modes of control	93
9.8.1	NCM	93
9.8.2	MCM.....	94
10	Radio subsystem link control	94
10.1	Introduction.....	94
10.2	RF power control.....	95
10.3	Radio link measurements.....	95
10.3.1	Received signal strength.....	95
10.3.1.1	Sample duration for signal strength measurement.....	95
10.3.2	Signal quality.....	95
10.3.3	Round-trip MS-BS path delay	95
11	Call Control (CC) service description.....	95
11.1	Introduction.....	95
11.2	Services offered.....	95
11.3	CC service.....	96
11.3.1	CC primitives exchanged through the TNCC-SAP.....	96
11.3.2	Service primitives at the TNCC-SAP.....	96
11.3.3	Primitive description.....	97
11.3.3.1	TNCC-ALERT primitive	97
11.3.3.2	TNCC-COMPLETE primitive	98
11.3.3.3	TNCC-DTMF primitive	98
11.3.3.4	TNCC-MODIFY primitive	99
11.3.3.5	TNCC-NOTIFY primitive	99
11.3.3.6	TNCC-PROCEED primitive	100
11.3.3.7	TNCC-RELEASE primitive	100
11.3.3.8	TNCC-SETUP primitive	100
11.3.3.9	TNCC-TX primitive	101

11.3.4	Parameter description.....	102
11.4	States for CC SAP.....	109
12	Supplementary Services (SS) service description	109
12.1	Introduction.....	109
12.2	Services offered.....	110
12.3	SS service	110
12.3.1	Primitives exchanged through TNSS-SAP	110
12.3.2	Parameter description.....	110
13	Short Data Service (SDS) service description.....	111
13.1	Introduction.....	111
13.2	Services offered.....	111
13.3	SDS	111
13.3.1	SDS primitives exchanged through the TNSDS-SAP	111
13.3.2	Service primitives at the TNSDS-SAP.....	112
13.3.2.1	TNSDS-STATUS primitive	112
13.3.2.2	TNSDS-REPORT primitive	113
13.3.2.3	TNSDS-UNITDATA primitive.....	113
13.3.2.4	TNSDS-CANCEL primitive	114
13.3.3	Parameter description.....	114
13.3.4	State description.....	116
13.3.4.1	NULL state.....	116
13.3.4.2	SHORT DATA INITIATED state.....	116
13.3.5	Service state diagram for the TNSDS-SAP	117
14	CMCE protocol	117
14.1	Introduction.....	117
14.2	Overview of CMCE.....	117
14.2.1	Communication routes of the CMCE model.....	118
14.2.2	Protocol structure and protocol stack	118
14.2.3	Addressing rules	120
14.2.4	CC, SS and SDS sub-entities	121
14.2.4.1	CC sub-entity.....	121
14.2.4.2	SS sub-entity	121
14.2.4.3	SDS sub-entity.....	122
14.2.5	PC sub-entity	122
14.2.6	Internal routes.....	122
14.2.7	Intra-CMCE primitive summary.....	125
14.2.7.1	Down link CC PDU parameters	125
14.2.7.2	Uplink CC PDU parameters.....	125
14.2.7.3	Downlink SS PDU parameters	125
14.2.7.4	Uplink SS PDU parameters.....	126
14.2.7.5	Down link SDS PDU parameters	126
14.2.7.6	Uplink SDS PDU parameters	126
14.2.7.7	CMCE management primitives	126
14.2.7.7.0	ACTIVITY request	126
14.2.7.7.1	BREAK indication	126
14.2.7.7.1a	BUSY indication	126
14.2.7.7.2	CANCEL request	126
14.2.7.7.3	CLOSE indication	126
14.2.7.7.4	CONFIGURE indication	127
14.2.7.7.5	CONFIGURE request.....	127
14.2.7.7.6	IDENTITIES request.....	127
14.2.7.7.6a	IDLE indication	127
14.2.7.7.6b	INFO indication	127
14.2.7.7.7	OPEN indication	127
14.2.7.7.8	REOPEN indication	127
14.2.7.7.9	REPORT indication.....	128
14.2.7.7.10	RESUME indication.....	128
14.3	Overview of services required by the CMCE	128
14.4	CMCE protocol states.....	128
14.4.1	States for PC.....	128

14.4.1.1	CLOSED.....	128
14.4.1.2	OPEN.....	129
14.4.2	States for CC.....	129
14.4.2.1	IDLE	131
14.4.2.2	MO-CALL-SETUP.....	131
14.4.2.3	MT-CALL-SETUP.....	131
14.4.2.4	CALL ACTIVE.....	132
14.4.2.5	CALL DISCONNECT.....	132
14.4.2.6	WAIT.....	132
14.4.3	States for SS	132
14.4.4	States for SDS.....	132
14.5	Procedures	133
14.5.1	Individual CC procedures.....	133
14.5.1.1	Call set-up procedures	134
14.5.1.1.1	Incoming call	135
14.5.1.1.2	Outgoing call	136
14.5.1.1.3	Colliding calls.....	137
14.5.1.1.4	Unsuccessful call set-up	138
14.5.1.1.5	Call rejection.....	138
14.5.1.2	Call maintenance procedures.....	138
14.5.1.2.1	Transmission control procedures.....	139
14.5.1.2.2	Call status information procedures.....	143
14.5.1.2.3	Call modification procedures	143
14.5.1.2.4	Call restoration procedures	145
14.5.1.2.5	DTMF procedures	147
14.5.1.2.6	Calls to and from external subscribers.....	148
14.5.1.3	Call disconnection procedures.....	149
14.5.1.3.1	User initiated disconnection.....	149
14.5.1.3.2	Network initiated disconnection.....	150
14.5.1.3.3	Reception of disconnection request.....	150
14.5.1.3.4	Expiry of timers	150
14.5.1.3.5	Colliding disconnection.....	151
14.5.1.4	U-Plane switching	151
14.5.1.4.1	End of call set-up phase.....	151
14.5.1.4.2	During call maintenance phase	152
14.5.1.4.3	Call disconnection phase	152
14.5.2	Group CC procedures.....	152
14.5.2.1	Call set-up procedures	153
14.5.2.1.1	Incoming call	154
14.5.2.1.2	Outgoing call	155
14.5.2.1.3	Colliding calls.....	156
14.5.2.1.4	Unsuccessful call set-up	156
14.5.2.1.5	Call rejection.....	156
14.5.2.2	Call maintenance procedures.....	156
14.5.2.2.1	Transmission control procedures.....	157
14.5.2.2.2	Call status information procedures.....	161
14.5.2.2.3	Call modification procedures	161
14.5.2.2.4	Call restoration procedures	163
14.5.2.2.5	DTMF procedures	165
14.5.2.2.6	Temporary address handling procedures	165
14.5.2.2.7	Calls to and from external subscribers.....	166
14.5.2.3	Call disconnection procedures.....	166
14.5.2.3.1	User initiated disconnection.....	167
14.5.2.3.2	Network initiated disconnection.....	167
14.5.2.3.3	Reception of disconnection request.....	167
14.5.2.3.4	Colliding disconnection	168
14.5.2.3.5	Expiry of timers	168
14.5.2.4	U-Plane switching	169
14.5.2.4.1	End of call set-up phase.....	169
14.5.2.4.2	During call maintenance phase	169
14.5.2.4.3	Call disconnection phase	170
14.5.2.5	Void	170

14.5.2.6	Acknowledged group call procedures.....	170
14.5.2.7	Call ownership.....	171
14.5.3	Traffic channel assignment procedures.....	172
14.5.3.1	SwMI related procedures	172
14.5.3.2	MS related procedures	173
14.5.3.2.1	General procedures.....	173
14.5.3.2.2	Procedures for acceptance of individually-addressed channel allocation	174
14.5.3.2.3	Procedures for acceptance of group-addressed channel allocation.....	174
14.5.4	SS procedures	176
14.5.5	SDS procedures	176
14.5.5.1	Incoming short data message	176
14.5.5.2	Outgoing short data messages	176
14.5.6	PC procedures.....	177
14.5.6.1	Access to the communication resources.....	177
14.5.6.2	Access priority handling	177
14.5.6.2.1	Cancel.....	178
14.5.6.3	CMCE PDU exchange.....	178
14.5.6.3.1	Choice of layer 2 service	178
14.5.6.4	Control information exchange.....	178
14.5.6.5	PC protocol error conditions	179
14.5.6.5.1	PDU Type error.....	179
14.5.6.5.2	Invalid call identifier	179
14.5.6.5.3	MS busy.....	179
14.5.6a	Subscriber class	179
14.6	Protocol timers.....	180
14.7	PDU descriptions	181
14.7.1	PDU description tables - downlink	182
14.7.1.1	D-ALERT	182
14.7.1.2	D-CALL PROCEEDING	182
14.7.1.3	D-CALL RESTORE	183
14.7.1.4	D-CONNECT	183
14.7.1.5	D-CONNECT ACKNOWLEDGE.....	184
14.7.1.6	D-DISCONNECT.....	184
14.7.1.7	D-FACILITY	184
14.7.1.8	D-INFO.....	185
14.7.1.9	D-RELEASE	185
14.7.1.10	D-SDS-DATA	186
14.7.1.11	D-STATUS	186
14.7.1.12	D-SETUP	187
14.7.1.13	D-TX CEASED.....	187
14.7.1.14	D-TX CONTINUE	188
14.7.1.15	D-TX GRANTED	188
14.7.1.16	D-TX INTERRUPT	189
14.7.1.17	D-TX WAIT	189
14.7.2	PDU description tables - uplink.....	190
14.7.2.1	U-ALERT	190
14.7.2.2	U-CALL RESTORE	190
14.7.2.3	U-CONNECT	191
14.7.2.4	U-DISCONNECT	191
14.7.2.5	U-FACILITY	191
14.7.2.6	U-INFO.....	192
14.7.2.7	U-STATUS	192
14.7.2.8	U-SDS-DATA	193
14.7.2.9	U-RELEASE	194
14.7.2.10	U-SETUP	194
14.7.2.11	U-TX CEASED.....	195
14.7.2.12	U-TX DEMAND	195
14.7.3	PDU description tables - downlink and uplink	195
14.7.3.1	General rules for function not supported.....	195
14.7.3.2	CMCE FUNCTION NOT SUPPORTED	195
14.8	Information elements coding.....	196
14.8.1	Area Selection.....	196

The STANDARD PREVIEW
(standards.iteh.ai)

14.8.2	Basic service information	197
14.8.3	Call identifier.....	197
14.8.3a	Call identifier present.....	197
14.8.4	Call ownership.....	197
14.8.5	Called party type identifier.....	197
14.8.6	Called party SNA.....	198
14.8.7	Called party extension.....	198
14.8.8	Called party SSI.....	198
14.8.9	Calling party type identifier.....	198
14.8.10	Calling party extension.....	199
14.8.11	Calling party SSI.....	199
14.8.12	Call priority	199
14.8.13	Call status.....	199
14.8.14	Call queued.....	200
14.8.15	Continue	200
14.8.16	Call time-out	200
14.8.17	Call time-out, set-up phase	200
14.8.17a	Circuit mode type.....	201
14.8.17b	CLIR control.....	201
14.8.17c	Communication type	201
14.8.18	Disconnect cause.....	202
14.8.18a	DM-MS address.....	202
14.8.19	DTMF	202
14.8.19a	DTMF digit	203
14.8.19b	DTMF type	203
14.8.20	External subscriber number	204
14.8.21	Encryption control.....	204
14.8.21a	Encryption flag.....	204
14.8.22	Facility	205
14.8.23	Hook method selection.....	205
14.8.24	Length indicator.....	205
14.8.25	New call identifier.....	205
14.8.26	Modify.....	205
14.8.27	https://standards.iteh.ai/catalog/standards/sist/1hc05d1e-09e7-4016-8f7a-5cde19845006/sist-en-300-392-2-v2-1-1-2003	206
14.8.27a	Other party type identifier	206
14.8.27b	Other party SNA	206
14.8.27c	Other party extension	206
14.8.27d	Other party SSI	206
14.8.28	PDU type.....	207
14.8.29	Poll request.....	207
14.8.30	Poll response	207
14.8.31	Poll response addresses	207
14.8.32	Poll response number	208
14.8.33	Poll response percentage	208
14.8.34	Pre-coded status.....	208
14.8.35	Proprietary.....	209
14.8.36	Request to transmit/send data	209
14.8.37	Reset call time-out timer (T310).....	209
14.8.38	Short data type identifier	209
14.8.39	Simplex/duplex selection.....	209
14.8.39a	Slots per frame.....	210
14.8.40	Speech service	210
14.8.41	Temporary address.....	210
14.8.42	Transmission grant.....	210
14.8.43	Transmission request permission	210
14.8.44	Transmitting party type identifier	211
14.8.45	Transmitting party extension	211
14.8.46	Transmitting party SSI	211
14.8.47	TX demand priority.....	211
14.8.48	Type 3 element identifier.....	212
14.8.49	User defined data-1	212
14.8.50	User defined data-2	212

ITEH STANDARD PREVIEW
(standards.iteh.ai)

14.8.51	User defined data-3	212
14.8.52	User defined data-4	213
15	Mobility Management (MM) service description.....	213
15.1	Introduction.....	213
15.2	Services offered.....	213
15.3	Primitive description	214
15.3.1	Service state model for the MS	214
15.3.2	Service primitives at the TNMM-SAP, MS/LS side	214
15.3.3	Primitive description	215
15.3.3.1	TNMM-ATTACH DETACH GROUP IDENTITY primitive.....	215
15.3.3.2	TNMM-DEREGISTRATION primitive	215
15.3.3.3	TNMM-DISABLING primitive	216
15.3.3.4	TNMM-ENABLING primitive	216
15.3.3.5	TNMM-ENERGY SAVING primitive	216
15.3.3.6	TNMM-REPORT primitive	216
15.3.3.7	TNMM-REGISTRATION primitive	216
15.3.3.8	TNMM-SERVICE primitive	217
15.3.3.9	TNMM-STATUS primitive	217
15.3.4	Parameters description	218
15.3.5	State description for the MS	221
15.3.5.1	Not updated.....	221
15.3.5.2	Wait updating	221
15.3.5.3	Updated.....	222
15.3.5.4	Temporary disabled	222
15.3.5.5	Permanently disabled	222
15.3.6	Service state diagram for the TNMM-SAP	223
16	MM protocol	226
16.1	Introduction.....	226
16.2	MM procedures	227
16.2.1	General	227
16.2.2	Services provided by the protocol.....	227
16.2.3	Underlying services assumed by the protocol.....	228
16.2.4	Services assumed from the local environment.....	228
16.3	Protocol functions	228
16.3.1	Activation and control of underlying MLE Service	229
16.3.1.1	Activation procedure	229
16.3.1.2	Deactivation procedure	230
16.3.1.3	Maintenance procedures	230
16.3.1.3.1	Report and cancel handling	230
16.3.1.3.2	Stealing permission and stealing repeats flag handling	231
16.3.1.3.3	Busy handling	231
16.3.1.3.4	Activity handling	231
16.4	Registration procedure	231
16.4.1	MLE initiated registration procedure	231
16.4.1.1	Normal registration	232
16.4.1.2	Forward registration	236
16.4.2	User application initiated registration procedure	238
16.4.3	Infrastructure initiated registration procedure	243
16.4.4	Colliding registrations	245
16.4.5	Expiry of timer T351	245
16.4.6	Expiry of LA timers	245
16.4.7	Lifetime of ASSI/(V)ASSI	245
16.4.7.1	ASSI/(V)ASSI validity at migration	245
16.4.7.2	ASSI/(V)ASSI validity by MS initiative	246
16.4.7.3	ASSI/(V)ASSI validity at registration rejection	246
16.4.8	Temporary registration	246
16.4.9	Subscriber class procedures	246
16.4.10	Frequency band capability procedures	247
16.5	Enable and disable procedures	248
16.6	De-registration procedure	248

iTeh STANDARD PREVIEW
(standards.iteh.ai)

16.6.1	Trunking mode de-registration	248
16.6.2	Direct mode related de-registration.....	248
16.7	Energy economy.....	249
16.7.1	Energy economy mode procedure.....	249
16.7.2	Procedures for requesting Direct Mode dual watch operation	250
16.7.2.1	Introduction.....	250
16.7.2.2	MS requesting to start, modify or resume dual watch mode	251
16.7.2.3	MS terminating dual watch mode.....	253
16.7.2.4	SwMI modifying or terminating dual watch mode	253
16.7.2.5	Changing between modes	254
16.7.2.6	General dual watch procedures.....	254
16.7.2.7	Reduced dual watch without informing SwMI.....	255
16.7.3	Expiry of timer T352.....	255
16.8	Attachment/detachment of group identities and group reporting procedures.....	255
16.8.1	Infrastructure initiated attachment/detachment of group identities procedure.....	256
16.8.2	MS initiated attachment/detachment of group identities procedure	257
16.8.3	SwMI initiated group report procedure	258
16.8.4	MS initiated group report procedure	259
16.8.5	Expiry of timer T353.....	260
16.8.6	Colliding requests for group attachment/detachment and group reporting	260
16.8.7	Group Identity Address Type usage in Group Identity downlink/uplink.....	261
16.8.8	PDU or function not supported	262
16.9	MM PDU structures and contents	262
16.9.1	MM PDU general description.....	262
16.9.2	MM PDU description tables - downlink.....	262
16.9.2.1	D-ATTACH/DETACH GROUP IDENTITY	262
16.9.2.2	D-ATTACH/DETACH GROUP IDENTITY ACKNOWLEDGEMENT.....	263
16.9.2.3	D-DISABLE (Void).....	263
16.9.2.4	D-ENABLE (Void).....	263
16.9.2.5	D-MM STATUS.....	263
16.9.2.5.1	D-MM STATUS generic structure.....	263
16.9.2.5.2	D-CHANGE OF ENERGY SAVING MODE REQUEST.....	264
16.9.2.5.3	D-CHANGE OF ENERGY SAVING MODE RESPONSE ^{e7-4016-8f7a-}	264
16.9.2.5.4	D-DUAL WATCH MODE RESPONSE ^{0-392-2-v2.1-1-2003}	264
16.9.2.5.5	D-TERMINATING DUAL WATCH MODE RESPONSE.....	265
16.9.2.5.6	D-CHANGE OF DUAL WATCH MODE REQUEST	266
16.9.2.5.7	Direct mode gateway related D-MM STATUS.....	266
16.9.2.5.8	D-MS FREQUENCY BANDS REQUEST	266
16.9.2.6	D-STATUS (Void)	266
16.9.2.7	D-LOCATION UPDATE ACCEPT	267
16.9.2.8	D-LOCATION UPDATE COMMAND	267
16.9.2.9	D-LOCATION UPDATE REJECT	268
16.9.2.10	D-LOCATION UPDATE PROCEEDING	268
16.9.3	MM PDU descriptions - uplink.....	269
16.9.3.1	U-ATTACH/DETACH GROUP IDENTITY	269
16.9.3.2	U-ATTACH/DETACH GROUP IDENTITY ACKNOWLEDGEMENT	269
16.9.3.3	U-ITSI DETACH	269
16.9.3.4	U-LOCATION UPDATE DEMAND	270
16.9.3.5	U-MM STATUS.....	270
16.9.3.5.1	U-MM STATUS generic construction	270
16.9.3.5.2	U-CHANGE OF ENERGY SAVING MODE REQUEST.....	271
16.9.3.5.3	U-CHANGE OF ENERGY SAVING MODE RESPONSE.....	271
16.9.3.5.4	U-DUAL WATCH MODE REQUEST	272
16.9.3.5.5	U-TERMINATING DUAL WATCH MODE REQUEST	272
16.9.3.5.6	U-CHANGE OF DUAL WATCH MODE RESPONSE	273
16.9.3.5.7	U-START OF DIRECT MODE OPERATION	273
16.9.3.5.8	Direct mode gateway related U-MM STATUS.....	274
16.9.3.5.9	U-MS FREQUENCY BANDS INFORMATION	274
16.9.4	PDU description tables - downlink and uplink	274
16.9.4.1	MM FUNCTION NOT SUPPORTED	274
16.10	MM information elements coding	275
16.10.1	Address extension	275

16.10.2	Cipher control	275
16.10.3	Cipher parameters	276
16.10.4	Cipher key type (Void)	276
16.10.5	Class of MS	276
16.10.6	Class of usage	277
16.10.7	Disabling type	277
16.10.7A	Default group attachment lifetime	277
16.10.8	Distribution on 18th frame	278
16.10.8A	DMO carrier	278
16.10.9	Energy saving mode	279
16.10.10	Energy saving information	279
16.10.11	Frame Number	279
16.10.11A	Frequency band definition	280
16.10.12	Group identity accept/reject	280
16.10.13	Group identity acknowledgement request	280
16.10.14	Group identity acknowledgement type	280
16.10.15	Group identity address type	281
16.10.16	Group identity attachment lifetime	281
16.10.17	Group identity attach/detach mode	281
16.10.18	Group identity attach/detach type identifier	281
16.10.19	Group identity attachment	281
16.10.20	Group identity detachment downlink	282
16.10.21	Group identity detachment uplink	282
16.10.22	Group identity downlink	282
16.10.23	Group identity location accept	283
16.10.24	Group identity location demand	283
16.10.25	Group identity location demand ack (void)	283
16.10.26	Group identity report	283
16.10.27	Group identity uplink	284
16.10.27A	Group report response	284
16.10.28	Group Short Subscriber Identity (GSSI)	284
16.10.29	KSG number	284
16.10.30	LA	285
16.10.31	LA	285
16.10.32	LANC	285
16.10.33	LA timer	285
16.10.34	LA information	286
16.10.34A	Length of the copied PDU	286
16.10.35	Location update type	286
16.10.35A	Location update accept type	287
16.10.36	MCC	287
16.10.37	MNC	287
16.10.37A	Mode change information	287
16.10.37B	MS operating with type 2 repeater	288
16.10.38	Multiframe Number (MN)	288
16.10.38A	Not-supported PDU type	288
16.10.38B	Number of frequency band definitions	288
16.10.39	PDU type	289
16.10.40	New registered area	289
16.10.41	Proprietary	289
16.10.41A	Reason for dual watch change by SwMI	290
16.10.41B	Reduced mode	290
16.10.42	Reject cause	290
16.10.43	Request to append LA	291
16.10.43A	Re-send interval	291
16.10.43B	Result of dual watch request	291
16.10.44	SSI	291
16.10.45	SCCH information	292
16.10.46	SCCH information and distribution on 18th frame	292
16.10.47	SCK number	292
16.10.47A	Start of direct mode operation cause	292
16.10.48	Status downlink	293