



SLOVENSKI STANDARD
SIST EN 300 386 V2.1.1:2016
01-september-2016

Oprema za telekomunikacijska omrežja - Zahteve za elektromagnetno združljivost (EMC) - Harmonizirani standard, ki zajema bistvene zahteve direktive 2014/30/EU

Telecommunication network equipment - ElectroMagnetic Compatibility (EMC) requirements - Harmonised Standard covering the essential requirements of the Directive 2014/30/EU

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 386 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/594a5ede-24c9-4b2a-8441-202722ab07c4/sist-en-300-386-v2-1-1-2016)

Ta slovenski standard je istoveten z: **ETSI EN 300 386 V2.1.1 (2016-07)**

ICS:

33.050.01	Telekomunikacijska terminalska oprema na splošno	Telecommunication terminal equipment in general
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 300 386 V2.1.1:2016 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 386 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/594a5ede-24c9-4b2a-8441-262722a8c9e4/sist-en-300-386-v2-1-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/594a5ede-24c9-4b2a-8441-262722a8c9e4/sist-en-300-386-v2-1-1-2016>

ETSI EN 300 386 V2.1.1 (2016-07)



**Telecommunication network equipment;
ElectroMagnetic Compatibility (EMC) requirements;
Harmonised Standard covering the essential requirements
of the Directive 2014/30/EU**

<https://standards.iteh.ai/catalog/standards/sist/594a5ede-24c9-4b2a-8441-262722a8c9e4/sist-en-300-386-v2-1-1-2016>

ReferenceREN/ERM-EMC-330

KeywordsEMC, harmonised standard, network, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 386 V2.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/594a5ede-24c9-4b2a-8441-262722a8c94c/sist-en-300-386-v2-1-1-2016>

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
1 Scope	7
2 References	8
2.1 Normative references	8
2.2 Informative references.....	10
3 Definitions and abbreviations.....	12
3.1 Definitions	12
3.2 Abbreviations	15
4 Installation environment.....	16
5 Immunity: test methods	16
5.0 General requirements	16
5.1 Electrostatic discharge.....	17
5.2 Electrical fast transients/burst.....	17
5.3 Surges	17
5.3.1 Signal line ports	17
5.3.2 AC power ports.....	17
5.4 Immunity to continuous conducted signals.....	17
5.4.1 Low frequency (≤ 150 kHz).....	17
5.4.2 Radio frequency (> 150 kHz).....	17
5.4.2.1 AC power port.....	17
5.4.2.2 DC power port.....	18
5.4.2.3 Signal line port.....	18
5.5 Immunity to radiated electromagnetic fields.....	18
5.6 Immunity to power supply disturbances: AC and DC power ports.....	18
5.6.1 Test of immunity to low frequency disturbances: AC power ports	18
5.6.2 Test of immunity to low frequency disturbances: DC power ports	18
6 Emission: test methods.....	18
6.0 General	18
6.1 AC power port.....	18
6.2 DC power port.....	19
6.3 Wired network and telecommunication Ports.....	19
6.4 Radiated emission.....	19
7 Test levels and limits	19
7.0 General requirements	19
7.1 Emission.....	20
7.1.1 Enclosure port, Radiated electromagnetic field emissions.....	20
7.1.2 AC ports.....	20
7.1.2.1 Conducted emissions.....	20
7.1.2.2 Current harmonics.....	20
7.1.2.3 Voltage fluctuations	20
7.1.3 DC ports, Conducted emissions	20
7.1.4 Wired network or Telecommunication ports, Conducted emissions	20
7.2 Immunity	21
7.2.1 Equipment operating in telecommunication centres	21
7.2.1.1 Telecommunication centres, enclosure port.....	21
7.2.1.2 Telecommunication centres, ports for outdoor signal lines.....	22
7.2.1.3 Telecommunication centres, ports for indoor signal lines.....	23
7.2.1.4 Telecommunication centres, AC power ports	24
7.2.1.5 Telecommunication centres, DC power ports	24
7.2.2 Equipment operating in locations other than telecommunication centres.....	25

7.2.2.1	Other than telecommunication centres, enclosure port	25
7.2.2.2	Other than telecommunication centres, ports for outdoor signal lines	26
7.2.2.3	Other than telecommunication centres, ports for indoor signal lines	27
7.2.2.4	Other than telecommunication centres, AC power ports.....	28
7.2.2.5	Other than telecommunication centres, DC power ports.....	29
8	General test configuration	30
9	General operational conditions during testing.....	30
9.0	General requirements	30
9.1	Equipment configuration.....	30
9.2	Operation of multimedia network equipment.....	31
10	General immunity conditions	31
10.0	General	31
10.1	General performance criteria.....	31
11	Switching equipment specific requirements.....	32
11.1	Test configuration.....	32
11.2	Operational conditions	33
11.2.0	General.....	33
11.2.1	Emission	34
11.2.2	Immunity	34
11.3	Specific immunity performance criteria	34
11.3.0	General.....	34
11.3.1	Digital port performance criteria	34
11.3.1.1	Performance criterion A (continuous phenomena).....	34
11.3.1.2	Performance criterion B (transient phenomena).....	34
11.3.1.3	Performance criterion C (interruptions).....	34
11.3.2	Analogue port performance criteria	34
11.3.2.1	Performance criterion A (continuous phenomena).....	34
11.3.2.2	Performance criterion B (transient phenomena).....	35
11.3.2.3	Performance criterion C (interruptions).....	35
12	Transmission equipment specific requirements.....	35
12.1	Test configuration.....	35
12.2	Operational conditions	36
12.2.0	General.....	36
12.2.1	Emission	36
12.2.2	Immunity	36
12.3	Specific immunity performance criteria	36
12.3.1	Digital signal ports.....	36
12.3.1.0	General	36
12.3.1.1	Performance criterion A (continuous phenomena).....	36
12.3.1.2	Performance criterion B (transient phenomena).....	37
12.3.1.3	Performance criterion C (interruptions)	37
12.3.2	Analogue voice frequency signal ports.....	37
12.3.2.0	General	37
12.3.2.1	Performance criterion A (continuous phenomena).....	37
12.3.2.2	Performance criterion B (transient phenomena).....	37
12.3.3	SDH and PDH interfaces	37
12.3.3.1	Tributary and aggregate interfaces.....	37
12.3.4	ISDN interfaces	37
12.3.4.1	Primary rate access ISDN interfaces	37
12.3.4.2	Network termination NT1 for ISDN "U" interfaces.....	37
12.3.4.3	Basic access ISDN interfaces	38
12.3.5	Analogue interfaces	38
12.3.5.1	Trunk interfaces and leased line interfaces	38
12.3.5.2	Subscriber interfaces	38
12.3.6	V.10, V.11, V.24, V.28, V.36, X.24 and similar V.- and X.- series interfaces	38
12.3.7	Ethernet and packet-data interfaces	38
12.3.7.0	General	38
12.3.7.1	Performance criterion A (continuous phenomena).....	38
12.3.7.2	Performance criterion B (transient phenomena).....	38

12.3.8	Service and maintenance interfaces	38
12.3.9	Synchronization interfaces	38
12.3.9.0	General	38
12.3.9.1	Performance criterion A (continuous phenomena)	39
12.3.9.2	Performance criterion B (transient phenomena)	39
12.3.10	Remote alarm interfaces	39
12.3.10.0	General	39
12.3.10.1	Performance criterion A (continuous phenomena)	39
12.3.10.2	Performance criterion B (transient phenomena)	39
12.4	Digital Subscriber Line (DSL) Access Systems	39
12.4.1	Test configuration	39
12.4.2	Operational conditions	40
12.4.3	Immunity	40
12.4.4	Specific Immunity performance criteria	40
12.4.4.0	General	40
12.4.4.1	Performance Criteria A (continuous phenomena)	40
12.4.4.2	Performance Criteria B (transient phenomena)	41
12.4.4.3	Performance Criteria C (interruptions)	41
13	Power supply equipment specific conditions	41
13.0	General	41
13.1	Test configuration	41
13.2	Operational conditions	42
13.2.1	Emission	42
13.2.2	Immunity	42
13.3	Specific immunity performance criteria	43
13.3.0	General	43
13.3.1	Alternating current secondary interface	43
13.3.1.1	Performance criterion A (continuous phenomena)	43
13.3.1.2	Performance criterion B (transient phenomena)	43
13.3.2	Direct current secondary interface	44
13.3.2.1	Performance criterion A (continuous phenomena)	44
13.3.2.2	Performance criterion B (transient phenomena)	44
13.3.3	Control/signal interface	44
13.3.4	Tertiary supply interface	44
14	Supervisory equipment specific conditions	44
14.1	Test configuration	44
14.2	Operational conditions	45
14.3	Specific immunity performance criteria	45
14.3.1	Performance criterion A (continuous phenomena)	45
14.3.2	Performance criterion B (transient phenomena)	46
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/30/EU	47
Annex B (normative):	Surges: test method for ports of signal lines remaining within the building	48
B.0	General	48
B.1	Test set-up for signal ports	48
Annex C (informative):	Evaluation of test results	50
Annex D (informative):	Guidance on EMC performance requirements and methods of measurement for RF ports (also covered by CENELEC EN 50083-2) of multimedia network equipment	52
Annex E (informative):	Bibliography	53
History	54

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared to provide one voluntary means of conforming to the essential requirements of Directive 2014/30/EU [i.31] of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to electromagnetic compatibility (recast).

NOTE: The corresponding Commission's standardisation request to provide one voluntary means of conforming to the essential requirements Directive 2014/30/EU on the harmonisation of the laws of the Member States relating to electromagnetic compatibility (recast) [i.31] is expected shortly.

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

SIST EN 300 386 V2.1.1:2016

[https://standards.iteh.ai/catalog/standards/sist/594a5ede-24c9-4b2a-8441-](https://standards.iteh.ai/catalog/standards/sist/594a5ede-24c9-4b2a-8441-262761a9a161/en-300-386-v2-1-1-2016)

262761a9a161/en-300-386-v2-1-1-2016

National transposition dates

Date of adoption of this EN:	6 June 2016
Date of latest announcement of this EN (doa):	30 September 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2017
Date of withdrawal of any conflicting National Standard (dow):	30 September 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document covers the EMC requirements for non-radio equipment intended to be used within a public telecommunications network, which provides telecommunications between Network Termination Points (NTPs) (i.e. excluding terminal equipment beyond the NTPs). Examples of such equipment are:

- Switching equipment. Such equipment includes:
 - local telephone exchanges;
 - remote switching concentrators;
 - international switches;
 - telex switches;
 - network packet switches;
 - base station controllers, radio network controllers;
 - network servers and gateways.
- Non-radio transmission equipment and ancillary equipment. Such equipment includes:
 - multiplexers;
 - line equipment and repeaters, e.g. equipment for:
 - Synchronous Digital Hierarchy (SDH);
 - Plesiochronous Digital Hierarchy (PDH);
 - Asynchronous Transfer Mode (ATM);

such as: <https://standards.iteh.ai/catalog/standards/sist/594a5ede-24c9-4b2a-8441-262722a8c9e4/sist-en-300-386-v2-1-1-2016>

 - Digital Cross Connect systems;
 - network terminations;
 - transmission equipment used in the access network like xDSL.
- Power supply equipment. Such equipment includes:
 - central power plant;
 - end of suite power supplies;
 - uninterruptible power supplies;
 - stabilized AC power supplies; and
 - other dedicated telecommunication network power supplies;

but excludes equipment which is uniquely associated with or integrated in other equipment.
- Supervisory equipment. Such equipment includes:
 - network management equipment;
 - operator access maintenance equipment;
 - traffic measurement systems;
 - line test units;
 - functional test units.

NOTE: The function of *supervision* may either be performed by independent equipment or form part of other telecommunication network equipment. If the function of supervision forms part of a telecommunication network equipment, the performance may be evaluated simultaneously with other functions (such as switching and transmission) during EMC testing.

- Data centre equipment which is intended to be used within telecommunication network infrastructure:
 - Storage.
 - Processor.
 - Server.

The environmental classification locations used in the present document refers to ETSI TR 101 651 [i.22].

The requirements of the present document have been selected to ensure an adequate level of immunity for the apparatus covered by the scope of the present document. The levels do not, however, cover extreme cases which may occur at any location but with a low probability of occurrence. In special cases, situations may arise where the levels of disturbance may exceed the immunity test levels specified in the present document. In these instances, special mitigation measures may have to be employed.

General purpose equipment, which is used as a part of a telecommunication network, may be covered by the scope of other standards. For such equipment, if those other standards fully cover the requirements of the present document, no further assessment is necessary. Equipment which also fall within the scope of CENELEC EN 50083-2 [3] may require additional testing on the relevant RF ports. See clause 9.2 and annex D.

Equipment may provide different functions, i.e. switching equipment may also provide transmission functions and transmission equipment may provide storage capabilities etc. All available functions of the EUT are to be tested.

iTeh STANDARD PREVIEW

2 References (standards.iteh.ai)

2.1 Normative references

SIST EN 300 386 V2.1.1:2016

<http://standards.iteh.ai/catalog/standards/sist/594a5ede-24c9-4b2a-8441-262722a8c9e4/sist-en-300-386-v2-1-1-2016>

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CENELEC EN 55016-1-2 (2014): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-2: Radio disturbance and immunity measuring apparatus - Coupling devices for conducted disturbance measurements".
- [2] CENELEC EN 55016-2-3 (2010 + Amendment 1: 2010 + Amendment 2: 2014): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 2-3: Methods of measurement of disturbances and immunity - Radiated disturbance measurements".
- [3] CENELEC EN 50083-2 (2012): "Cable networks for television signals, sound signals and interactive services - Part 2: Electromagnetic compatibility for equipment".
- [4] CENELEC EN 55022 (2010): "Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement".

NOTE: The use of CENELEC EN 55022 is controlled by the dates defined in the Official Journal.

- [5] CENELEC EN 61000-3-2 (2014): "Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current \leq 16 A per phase)".
- [6] CENELEC EN 61000-3-3 (2013): "Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current \leq 16 A per phase and not subject to conditional connection".
- [7] CENELEC EN 61000-3-11 (2000): "Electromagnetic compatibility (EMC) - Part 3-11: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems - Equipment with rated current \leq 75 A and subject to conditional connection".
- [8] CENELEC EN 61000-3-12 (2011): "Electromagnetic compatibility (EMC) - Part 3-12: Limits - Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current $>$ 16 A and \leq 75 A per phase".
- [9] CENELEC EN 61000-4-2 (2009): "Electromagnetic compatibility (EMC) - Part 4-2: Testing and measurement techniques - Electrostatic discharge immunity test".
- [10] CENELEC EN 61000-4-3 (2006 + Amendment 1: 2008 + Amendment 2: 2010 + Interpretation Sheet: 2009): "Electromagnetic compatibility (EMC) - Part 4-3: Testing and measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test".
- [11] CENELEC EN 61000-4-4 (2012): "Electromagnetic compatibility (EMC) - Part 4-4: Testing and measurement techniques - Electrical fast transient/burst immunity test".
- [12] CENELEC EN 61000-4-5 (2006): "Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test".
- NOTE: The dated reference of CENELEC EN 61000-4-5 has not been updated to the latest version because of the significant technical changes in comparison with the referenced revision. For some test laboratories, updating equipment will be a significant additional cost hence more time is required for implementation.
- [13] CENELEC EN 61000-4-6 (2009): "Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields".
- NOTE: The dated reference of CENELEC EN 61000-4-6 has not been updated to the latest version because of the significant technical changes in comparison with the referenced revision. For some test laboratories, updating equipment will be a significant additional cost hence more time is required for implementation.
- [14] CENELEC EN 61000-4-11 (2004): "Electromagnetic compatibility (EMC) -- Part 4-11: Testing and measurement techniques - Voltage dips, short interruptions and voltage variations immunity tests".
- [15] ETSI ETS 300 132-1 (edition 1) (09-1996): "Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 1: Operated by alternating current (ac) derived from direct current (dc) sources".
- [16] ETSI EN 300 132-2 (V2.4.6) (12-2011): "Environmental Engineering (EE); Power supply interface at the input to telecommunications and datacom (ICT) equipment; Part 2: Operated by -48 V direct current (dc)".
- [17] IEC 60050-161 (1990): "International Electrotechnical Vocabulary. Chapter 161: Electromagnetic compatibility".
- [18] IEC 60050-714 (1992): "International Electrotechnical Vocabulary - Chapter 714: Switching and signalling in telecommunications".
- [19] Void.
- [20] Recommendation ITU-T O.41 (1994): "Psophometer for use on telephone-type circuits".
- [21] Void.
- [22] Void.

- [23] Void.
- [24] Void.
- [25] Void.
- [26] Void.
- [27] Void.
- [28] ETSI EN 300 132-3-1 (V2.1.1) (02-2012): "Environmental Engineering (EE); Power supply interface at the input to telecommunications and datacom (ICT) equipment; Part 3: Operated by rectified current source, alternating current source or direct current source up to 400 V; Sub-part 1: Direct current source up to 400 V".
- [29] Void.
- [30] Void.
- [31] CENELEC EN 55032 (2015): "Electromagnetic compatibility of multimedia equipment - Emission requirements".
- NOTE: The use of CENELEC EN 55032 is controlled by the dates defined in the Official Journal.
- [32] CENELEC EN 50083 series (2012): "Cable networks for television signals, sound signals and interactive services".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 011-1 (V1.2.2): "Integrated Services Digital Network (ISDN); Primary rate User Network Interface (UNI); Part 1: Layer 1 specification".
- [i.2] ETSI EN 300 012-1 (V1.2.2): "Integrated Services Digital Network (ISDN); Basic User-Network Interface (UNI); Part 1: Layer 1 specification".
- [i.3] ETSI EN 300 166 (V1.2.1): "Transmission and Multiplexing (TM); Physical and electrical characteristics of hierarchical digital interfaces for equipment using the 2 048 kbit/s - based plesiochronous or synchronous digital hierarchies".
- [i.4] ETSI ETS 300 232 (1993 + Amendment 1: 1996): "Transmission and Multiplexing (TM); Optical interfaces for equipments and systems relating to the Synchronous Digital Hierarchy (SDH) [ITU-T Recommendation G.957 (1995), modified]".
- [i.5] ISO/IEC/IEEE 8802-3 (2014): "Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications".
- [i.6] Void.
- [i.7] Void.
- [i.8] Recommendation ITU-T G.712 (2001): "Transmission performance characteristics of pulse code modulation channels".

- [i.9] Recommendation ITU-T G.812 (2004): "Timing requirements of slave clocks suitable for use as node clocks in synchronization networks".
- [i.10] Recommendation ITU-T G.813 (2003): "Timing characteristics of SDH equipment slave clocks (SEC)".
- [i.11] Void.
- [i.12] Recommendation ITU-T G.961 (1993 + Erratum 1: 2000): "Digital transmission system on metallic local lines for ISDN basic rate access".
- [i.13] Recommendation ITU-T O.150 (1996 + Corrigendum 1: 2002): "General requirements for instrumentation for performance measurements on digital transmission equipment".
- [i.14] Recommendation ITU-T Q.552 (2001): "Transmission characteristics at 2-wire analogue interfaces of digital exchanges".
- [i.15] Recommendation ITU-T V.10 (1993): "Electrical characteristics for unbalanced double-current interchange circuits operating at data signalling rates nominally up to 100 kbit/s".
- [i.16] Recommendation ITU-T V.11 (1996): "Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s".
- [i.17] Recommendation ITU-T V.24 (2000): "List of definitions for interchange circuits between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE)".
- [i.18] Recommendation ITU-T V.28 (1993): "Electrical characteristics for unbalanced double-current interchange circuits".
- [i.19] Recommendation ITU-T V.36 (1988): "Modems for synchronous data transmission using 60-108 kHz group band circuits".
- [i.20] Recommendation ITU-T X.24 (1988): "List of definitions for interchange circuits between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) on public data networks".
- [i.21] Recommendation ITU-T X.25 (1996 + Corrigendum 1: 1998): "Interface between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for terminals operating in the packet mode and connected to public data networks by dedicated circuit".
- [i.22] ETSI TR 101 651 (V2.1.1): "Electromagnetic compatibility and radio spectrum matters (ERM); Classification of the electromagnetic environment conditions for equipment in telecommunication networks".
- [i.23] Void.
- [i.24] Council Directive 2004/108/EC of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility and repealing Directive 89/336/EEC (EMC Directive).
- [i.25] Recommendation ITU-T G.783 (2006 + Erratum 1: 2006 + Amendment 1: 2008 + Amendment 2: 2010): "Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks".
- [i.26] Recommendation ITU-T G.798 (2012 + Amendment 1: 2014 + Amendment 2: 2015): "Characteristics of optical transport network hierarchy equipment functional blocks".
- [i.27] Void.
- [i.28] IEEE 1284™ (2000): "IEEE Standard Signalling Method for a Bidirectional Parallel Peripheral Interface for Personal Computers".
- [i.29] IEEE 1394™ (2008): "IEEE Standard for High Performance Serial Bus Bridges".

- [i.30] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.31] Directive 2014/30/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to electromagnetic compatibility (recast).
- [i.32] Recommendation ITU-T G.996.1 (2001 + Amendment 1: 2003): "Test procedures for digital subscriber line (DSL) transceivers".
- [i.33] ETSI TS 101 135 (V1.5.3): "Transmission and Multiplexing (TM); High bit-rate Digital Subscriber Line (HDSL) transmission systems on metallic local lines; HDSL core specification and applications for combined ISDN-BA and 2 048 kbit/s transmission".
- [i.34] ETSI TS 101 524-1 (V1.1.1): "Transmission and Multiplexing (TM); Access transmission system on metallic access cables; Symmetrical single pair high bitrate Digital Subscriber Line (SDSL); Part 1: Functional requirements".
- [i.35] ETSI TS 101 270-1 (V1.4.1): "Transmission and Multiplexing (TM); Access transmission systems on metallic access cables; Very high speed Digital Subscriber Line (VDSL); Part 1: Functional requirements".
- [i.36] Recommendation ITU-T G.992.1 (1999 + Annex H: 2000 + Corrigendum 1: 2001 + Corrigendum 2: 2002 + Amendment 1: 2003 + Corrigendum of Amendment 1: 2003): "Asymmetric digital subscriber line (ADSL) transceivers".
- [i.37] Recommendation ITU-T G.992.3 (2009 + Corrigendum 1: 2009 + Amendment 1: 2010 + Amendment 2: 2010 + Amendment 3: 2010 + Corrigendum 2: 2011 + Amendment 4: 2011 + Amendment 5: 2012 + Corrigendum 3: 2013): "Asymmetric digital subscriber line transceivers 2 (ADSL2)".
- [i.38] Recommendation ITU-T G.992.5 (2009 + Corrigendum 1: 2010): "Asymmetric digital subscriber line 2 transceivers (ADSL2) - Extended bandwidth ADSL2 (ADSL2plus)".
- [i.39] Recommendation ITU-T G.993.1 (2004): "Very high speed digital subscriber line transceivers (VDSL)".
- [i.40] Recommendation ITU-T G.993.2 (2015): "Very high speed digital subscriber line transceivers 2 (VDSL2)".
- [i.41] Recommendation ITU-T G.991.1 (1998): "High bit rate digital subscriber line (HDSL) transceivers".
- [i.42] Recommendation ITU-T G.991.2 (2013 + Amendment 1: 2004 + Amendment 2: 2005 + Amendment 2 Erratum 1: 2005 + Amendment 3: 2005): "Single-pair high-speed digital subscriber line (SHDSL) transceivers".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in IEC 60050-161 [17] and the following apply:

NOTE: The definitions taken from IEC 60050-161 [17] have reference in parentheses.

AC secondary interface: output port of an AC power supply

AC secondary voltage: output of the AC power supply at the AC secondary interface

NOTE: The AC secondary voltage may be either:

- a stabilized AC supply derived from a DC primary supply (e.g. where the power supply is an inverter); or
- derived from the AC primary supply (e.g. a stabilized power supply used where the quality of the primary supply is not sufficient to feed telecommunication equipment).

burst (161-02-07): sequence of a limited number of distinct pulses or an oscillation of limited duration

connection: temporary association of transmission channels or telecommunication circuits, switching or other functional units set up to provide for the transfer of information between two or more points in a telecommunication network (IEC 60050-714 [18])

continuous disturbance (161-02-11): electromagnetic disturbance the effects of which on a particular device or equipment cannot be resolved into a succession of distinct effects

data centre: structure, or group of structures, dedicated to the centralized accommodation, interconnection and operation of information technology and network telecommunications equipment providing data storage, processing and transport services together with all the facilities and infrastructures for power distribution and environmental control together with the necessary levels of resilience and security required to provide the desired service availability

DC secondary interface: output port of a DC power supply

DC secondary voltage: output of the DC power supply at the DC secondary interface

NOTE: The DC secondary voltage may be derived from the AC primary supply with or without a buffer battery.

duration (of a voltage change) (161-08-03): interval of time for the voltage to increase or decrease from the initial value to the final value

duration (of a pulse): interval of time between the instants at which the instantaneous value of a pulse reaches 50 % of the pulse magnitude for the first and last time

enclosure port: physical boundary of the Equipment Under Test (EUT) through which electromagnetic fields may emanate or on which they may impinge

environment, environmental conditions: electromagnetic conditions external to the equipment, to which it is subjected at a certain time

NOTE: The environmental conditions comprise a combination of single environmental parameters and their severity.

environmental parameters: present one or more properties of the electromagnetic environment

immunity (to a disturbance) (161-01-20): ability of a device, equipment or system to perform without degradation in the presence of an electromagnetic disturbance

impulsive disturbance (161-02-09): electromagnetic disturbance which, when incident on a particular device or equipment, manifests itself as a succession of distinct pulses or transients

interface "A": terminals at which a power supply is connected to the telecommunications equipment

interface A3: interface, physical point, at which power supply is connected in order to operate the telecommunications and datacom (ICT) equipment with input DC voltage between 260 V and 400 V

multimedia network equipment: multimedia network equipment containing broadcast and telecommunication functions

Network Termination Point (NTP): physical point at the boundary of the Public Switched Telecommunications Networks (PSTN) intended to accept the connection of a Terminal Equipment (TE)

nominal voltage: nominal value of voltage that designates the type of supply

normal service: service mode where telecommunications equipment operates within its specification