Final draft ETSI EN 302 264 V2.1.1 (2017-02)



Short Range Devices;
Transport and Traffic Telematics (TTT);
Short Range Radar equipment operating
in the 77 GHz to 81 GHz band;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU

Reference

REN/ERM-TGSRR-76

Keywords

harmonised standard, radar, radio, RTTT, SRD, testing, UWB

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT[™], **PLUGTESTS**[™], **UMTS**[™] and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**[™] and **LTE**[™] are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intelle	ectual Property Rights	5
Forew	vord	5
Moda	ll verbs terminology	5
Introd	luction	5
1	Scope	6
2	References	6
2.1	Normative references	6
2.2	Informative references.	7
3	Definitions, symbols and abbreviations	Q
3.1	Definitions	
3.2	Symbols	
3.3	Abbreviations	
4	Technical requirements specifications	
4.1	Environmental conditions	
4.2	General Background information Wanted performance criteria. Fixed and scanning antennas Transmitter Conformance Requirements. Operating Frequency Range Applicability. Description Limits Conformance Mean Power spectral density Applicability. Description Limits Conformance Mean Power spectral density Applicability. Description Limits Conformance Peak Power Applicability.	8
4.2.1	Background information	8
4.2.2	Wanted performance criteria	9
4.2.3	Fixed and scanning antennas	9
4.3	Transmitter Conformance Requirements	9
4.3.1	Operating Frequency Range	9
4.3.1.1	Applicability	9
4.3.1.2	2 Description	9
4.3.1.3	Conformation	9
4.3.1.4	Many Danier and James Agents and Many Danier a	9
4.3.2 4.3.2.1	Mean Power spectral density	9
4.3.2.1	Applicability	9
4.3.2.2 4.3.2.3	2 Description	9
4.3.2.3 4.3.2.4	1 Conformance	10
4.3.2.4 4.3.3	Pools Dower	10
4.3.3.1	1 Can I Owel	10
4.3.3.1 4.3.3.2		10
4.3.3.2 4.3.3.3		10
4.3.3.4		
4.3.4	Unwanted emissions in the out-of-band domain.	
4.3.4.1		
4.3.4.2	rr	
4.3.4.3	1	
4.3.4.4		
4.3.5	Unwanted emissions in the spurious domain	
4.3.5.1		
4.3.5.2	11 -	
4.3.5.3	<u>.</u>	
4.3.5.4		
4.4	Receiver Conformance Requirements	
4.4.1	Introduction.	
4.4.2	Receiver spurious emissions	
4.4.2.1	•	
4.4.2.2	11 2	
4.4.2.3	1	
4.4.2.4		
4.4.3	Receiver in-band, out-of-band and remote-band signals handling	
4.4.3.1	The state of the s	
4.4.3.2		

History			17
Annex A (informative): Annex B (informative):		Change History	16
		Relationship between the present document and the essential requirements of Directive 2014/53/EU	15
7 C	Conformance methods	s of measurement for transmitter and receiver	14
6 T	est setup and proced	ures	14
		s for performing the tests	
4.5.1.4	Conformance		14
4.5.1.3	Limits		14
4.5.1.2			
4.5.1.1	Applicability.		13
4.5.1		rements	
4.5		nd mitigation techniques	
4.4.4		ity	
4.4.3.4			
4.4.3.3	Limite		13

IT all ST AND ARD RELIEVED AND A SOUTH AND SOU

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This final draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.7] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document covers short range radar equipment operating in the 77 GHz to 81 GHz range.

The present document covers the essential requirements of article 3.2 of the Directive 2014/53/EU [i.2].

Proposed national transposition dates			
Date of latest announcement of this EN (doa).	3 months after ETSI publication		
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa		
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa		

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document, together with ETSI EN 303 396 [1], covers the assessment of certain types of equipment as defined herein.

1 Scope

The present document specifies the technical requirements and methods of measurement for Short Range Devices (SRD) working as broadband devices with at least 50 MHz occupied bandwidth in the 77 GHz to 81 GHz frequency range, intended for Transport and Traffic Telematics (TTT) applications. Applications include but are not limited to e.g. Short Range Radar (SRR) for obstacle detection, stop&go, blind spot detection, parking aid, backup aid and precrash.

The present document covers transmitters intended to operate in the frequency range as defined in the EC Decision 2004/545/EC [i.5] and the ECC Decision ECC/DEC/(04)03 [i.6].

The present document:

- a) contains the technical characteristics and test methods for short range radar equipment fitted with integral antennas operating in 77 GHz to 81 GHz range;
- b) covers short range radar vehicle applications in the 77 GHz to 81 GHz range. It covers integrated transceivers and separate transmit/receive modules;
- c) integrated multi-mode transceivers [i.9], transmitters and receivers in the 76 GHz to 77 GHz range which comply with ETSI EN 301 091-1 [i.8] and which use the 77 GHz to 81 GHz range for one or several operation modes, within one EUT cycle or in different vehicle operation modes.

For such sensors, the 77 GHz to 81 GHz operation modes should be available for testing separately from the 76 GHz to 77 GHz operation modes.

The present document does not necessarily include all the characteristics which may be required by a user, nor does it necessarily represent the optimum performance achievable.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and ETSI EN 303 396 [1], the provisions of the present document take precedence.

These radio equipment types are capable of operating in all or part of the frequency bands given in table 1.

Table 1: Permitted ranges of operation

Permitted ranges of operation		
Transmit 15 30	77 GHz to 81 GHz	
Receive A	77 GHz to 81 GHz	

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.2] under the conditions identified in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at https://docbox.etsi.org/Reference/.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

[1] ETSI EN 303 396 (V1.1.1) (12-2016): "Short Range Devices; Measurement Techniques for automotive and surveillance radar equipment".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1]	CEPT/ERC Recommendation 70-03: "Relating to the use of Short Range Devices (SRD)".
[i.2]	Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
[i.3]	CEPT/ERC/REC 74-01: "Unwanted emissions in the spurious domain".
[i.4]	ETSI EG 203 336: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
[i.5]	Commission Decision 2004/545/EC on the harmonisation of radio spectrum in the 79 GHz range for the use of automotive short-range radar equipment in the Community.
[i.6]	ECC Decision (04)/03: "The frequency band 77-81 GHz to be designated for the use of Automotive Short Range Radars".
[i.7]	Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
[i.8]	ETSI EN 301 091-1: "Short Range Devices; Transport and Traffic Telematics (TTT); Radar equipment operating in the 76 GHz to 77 GHz range; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU; Part 1: Ground based vehicular radar".
[i.9]	ETSI EG 203 367: "Guide to the application of harmonised standards covering articles 3.1b and 3.2 of the Directive 2014/53/EU (RED) to multi-radio and combined radio and non-radio equipment".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 303 396 [1] and the following apply:

ground based vehicles: vehicles using wheels or rails for movement

EXAMPLE: Includes but is not limited to passenger cars, busses, trucks, rail engines, trams, ships, constriction vehicle and aircraft while taxiing.

NOTE: For details see CEPT/ERC Recommendation 70-03 [i.1].

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI EN 303 396 [1] and the following apply:

D antenna scan duty factor

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 303 396 [1] and the following apply:

e.r.p. equivalent radiated power

4 Technical requirements specifications

4.1 Environmental conditions

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile. The normal and extreme test conditions are defined in clauses 4.4.3 and 4.4.4 of ETSI EN 303 396 [1].

4.2 General

4.2.1 Background information

In this clause general considerations for the testing of radar applications for automotive vehicular applications in the frequency range from 77 GHz to 81 GHz are given. The tests cover integrated transceivers and separate transmit/receive modules.

All operating bandwidths of the equipment (see clause 4.3.1) shall be declared by the equipment manufacturer (see clauses 4.2 and 4.3 of ETSI EN 303 396 [1]).

Where equipment has more than one operating bandwidths, sufficient number of operating bandwidths shall be chosen for testing so as to encompass the lower and higher limits of the operating frequency and the minimum and maximum bandwidth.

The meaning of EUT with scanning/steerable antenna is that the EUT TX antenna pattern is electronically or mechanically adjustable.

4.2.2 Wanted performance criteria

The wanted performance criterion is that the EUT shall indicate the properties of a given target at a given distance. Since EUT considered here typically are tailored to specific applications, no single wanted performance criterion can be defined here.

Therefore:

- The relevant properties (e.g. presence, range, relative speed, azimuth angle) shall be declared by the manufacturer.
- The type and RCS of the target and the distance shall be declared by the manufacturer.

4.2.3 Fixed and scanning antennas

The provisions of ETSI EN 303 396 [1], clause 4.3.5 apply.

4.3 Transmitter Conformance Requirements

4.3.1 Operating Frequency Range

4.3.1.1 Applicability

This requirement applies to all EUT.

4.3.1.2 Description

The description in ETSI EN 303 396 [1], clause 6.2.2 applies.

4.3.1.3 Limits

The upper and lower limits of the operating frequency range shall meet the following conditions:

- $f_H \le 81 \text{ GHz}.$
- $f_L \ge 77 \text{ GHz}.$

4.3.1.4 Conformance

The conformance test suite for operating frequency range shall be as defined in clause 6.3.2 of ETSI EN 303 396 [1].

Conformance shall be established under normal and extreme test conditions defined in clause 4.1.

The interpretation of the results for the measurements uncertainty shall be as given in clause 4.6 of ETSI EN 303 396 [1].

4.3.2 Mean Power spectral density

4.3.2.1 Applicability

This requirement applies to all EUT.

4.3.2.2 Description

The description in ETSI EN 303 396 [1], clause 6.2.6 applies.

4.3.2.3 Limits

The mean power shall not be greater than the limits in table 2.

Table 2: Mean power spectral density, CEPT/ERC Recommendation 70-03 [i.1]

Frequency in GHz	77 GHz to 81 GHz
Maximum radiated average power spectral density (e.i.r.p.)	-3 dBm/MHz
[dBm/MHz] of the EUT	

4.3.2.4 Conformance

The conformance test suite for mean power shall be as defined in clause 6.3.4 of ETSI EN 303 396 [1].

Conformance shall be established under normal and extreme test conditions defined in clause 4.1.

The interpretation of the results for the measurements uncertainty shall be as given in clause 4.6 of ETSI EN 303 396 [1].