



**Short Range Devices (SRD);
Tank Level Probing Radar (TLPR) equipment operating in the
frequency ranges 4,5 GHz to 7 GHz, 8,5 GHz to 10,6 GHz,
24,05 GHz to 27 GHz, 57 GHz to 64 GHz, 75 GHz to 85 GHz;
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU**

*https://standards.etsi.org/standard/etsi_en_302_372_v2.1.1_2016-10-159r2
4aa7-8ba0-97cfc4-9a2e-4a2d-860-f59f*

Reference

REN/ERM-TGUWB-131

KeywordsEHF, harmonised standard, radar, regulation,
SHF, short range, SRD, testing, UWB**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88*iTeh STANDARD (standards.itec.etsi.org)*
Full standard:
<http://standards.itec.etsi.org/catalog/sist/302-372-v2.1.1-2016-12>

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction	8
1 Scope	10
2 References	11
2.1 Normative references	11
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	12
3.1 Definitions	12
3.2 Symbols	13
3.3 Abbreviations	14
4 Technical requirements specifications	15
4.1 Environmental conditions.....	15
4.2 General	15
4.3 Transmitter conformance requirements.....	15
4.3.1 Permitted frequency range of operation.....	15
4.3.1.1 Applicability.....	15
4.3.1.2 Description	15
4.3.1.3 Limits	15
4.3.1.4 Conformance.....	16
4.3.2 Operating bandwidth.....	16
4.3.2.1 Applicability.....	16
4.3.2.2 Description	16
4.3.2.3 Limits	16
4.3.2.4 Conformance.....	16
4.3.3 Maximum value of mean power spectral density	17
4.3.4 Maximum value of peak power	17
4.3.4.1 Applicability.....	17
4.3.4.2 Description	17
4.3.4.3 Limits	17
4.3.4.4 Conformance.....	17
4.3.5 Exterior limits	17
4.3.6 Low duty cycle	17
4.3.7 Other emissions	17
4.3.8 Transmitter unwanted emissions.....	18
4.3.8.1 Applicability.....	18
4.3.8.2 Description	18
4.3.8.3 Limits	18
4.3.8.4 Conformance.....	18
4.4 Receiver conformance requirements	18
4.4.1 General.....	18
4.4.2 Receiver spurious emissions	18
4.4.2.1 Applicability.....	18
4.4.2.2 Description	19
4.4.2.3 Limits	19
4.4.2.4 Conformance.....	19
4.4.3 Interferer signal handling.....	19
4.4.3.1 Applicability.....	19
4.4.3.2 Description	19
4.4.3.3 Limits	20
4.4.3.4 Conformance.....	20
4.5 Requirements for spectrum access	20
4.5.1 Detect and avoid (DAA)	20

4.5.2	Listen-before-talk (LBT)	20
4.5.3	Low duty cycle (LDC)	21
4.6	Antenna requirements.....	21
4.7	Other requirements and mitigation techniques.....	21
4.7.1	General.....	21
4.7.2	Adaptive power control (APC)	21
4.7.3	Activity factor and duty cycle.....	21
4.7.3.1	Applicability.....	21
4.7.3.2	Description.....	21
4.7.3.3	Limits	22
4.7.3.4	Conformance.....	22
4.7.4	Frequency domain mitigation	23
4.7.4.1	Applicability.....	23
4.7.4.2	Description.....	23
4.7.4.3	Limits	23
4.7.4.4	Conformance.....	23
4.7.5	Shielding effects	23
4.7.5.1	Applicability.....	23
4.7.5.2	Description.....	23
4.7.5.3	Limits	23
4.7.5.4	Conformance.....	23
4.7.6	Thermal radiation.....	23
4.7.7	Site registration.....	23
4.7.8	Equivalent mitigation techniques.....	24
4.7.8.1	Applicability.....	24
4.7.8.2	Description	24
4.7.8.3	Limits	24
4.7.8.4	Conformance.....	24
4.7.9	Range of modulation parameters	24
4.7.9.1	Applicability.....	24
4.7.9.2	Description	24
4.7.9.3	Limits	24
4.7.9.4	Conformance.....	24
5	Testing for compliance with technical requirements.....	25
5.1	Environmental conditions for testing	25
5.2	General conditions for testing	25
5.2.1	Product information	25
5.2.2	Product information useful to facilitate testing.....	25
5.2.3	Requirements for the test modulation	25
5.2.4	Test conditions, power supply and ambient temperatures	25
5.2.5	Choice of equipment for test suites.....	25
5.2.6	Multiple operating bandwidths and multiband equipment.....	26
5.2.7	Testing of host connected equipment and plug-in radio devices	26
5.2.8	Radiated measurement arrangements.....	26
5.3	Interpretation of the measurement results	26
5.3.1	General.....	26
5.3.2	Conversion loss data and measurement uncertainty	27
5.3.3	Measurement uncertainty is equal to or less than maximum acceptable uncertainty.....	28
5.3.4	Measurement uncertainty is greater than maximum acceptable uncertainty.....	28
5.3.5	Emissions	28
6	Conformance test suite	28
6.1	Introduction	28
6.2	Initial measurement steps	28
6.3	Radiated measurements	29
6.3.1	General.....	29
6.3.2	Test sites and general arrangements for measurements involving the use of radiated fields	29
6.3.3	Guidance on the use of a radiation test site.....	29
6.3.4	Coupling of signals	29
6.3.5	Standard test methods	29
6.3.6	Standard calibration method	29

6.4	Conducted measurements	29
6.4.1	General Setup	29
6.4.2	Specific Setup	29
6.5	Conformance test suite for transmitter parameters	29
6.5.1	General	29
6.5.2	Method of measurements of the Ultra-Wideband emissions	30
6.5.3	Permitted frequency range of operation	30
6.5.4	Operating bandwidth	30
6.5.5	Mean power spectral density measurements	32
6.5.6	Peak power measurements	34
6.5.6.1	Description	34
6.5.6.2	Radiated test procedure	35
6.5.6.3	Conducted test procedure	35
6.5.7	Exterior limit measurement	35
6.5.8	Total Power	35
6.5.9	Other Emissions	35
6.6	Conformance test suite for receiver parameters	35
6.6.1	Receiver spurious emissions	35
6.6.2	Receiver sensitivity	35
6.6.3	Interferer signal handling	35
6.6.3.1	Description	35
6.6.3.2	Interferer frequencies and power levels	35
6.6.3.3	Real scenario	36
6.6.3.4	Equivalent scenario	37
6.6.3.5	Radiated test setup for the equivalent scenario	37
6.6.3.6	Conducted test setup for the equivalent scenario	40
6.6.3.7	Test procedure for the equivalent scenario	41
6.6.3.8	Alternative scenario	42
6.6.3.9	Radiated test setup for the alternative scenario	42
6.6.3.10	Conducted test setup for the alternative scenario	43
6.6.3.11	Test procedure for the alternative scenario	44
6.7	Conformance test suites for spectrum access	45
6.7.1	Detect and avoid mechanisms	45
6.7.2	Listen before talk	45
6.7.3	Low duty cycle	45
6.8	Conformance test suites for antenna requirements	45
6.9	Other test suites	45
6.9.1	Adaptive power control (APC)	45
6.9.2	Activity factor and duty cycle	45
6.9.3	Frequency domain mitigation	45
6.9.4	Shielding effects	45
6.9.5	Thermal radiations	46
6.9.6	Site registration	46

Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	47
-----------------------------	---	-----------

Annex B (informative):	Application form for testing	48
B.1	Introduction	48
B.2	General information as required by ETSI EN 302 372, clause 5.2	48
B.2.1	Type of equipment (stand-alone, combined, plug-in radio device, etc.)	48
B.2.2	The nominal voltages of the stand-alone radio equipment or the nominal voltages of the combined (host) equipment or test jig in case of plug-in devices	48
B.3	Signal related information as required by ETSI EN 302 372, clause 4.3	49
B.3.1	Introduction	49
B.3.2	Operational frequency range(s) of the equipment	49
B.3.3	Nominal channel bandwidth(s)	49
B.3.4	The type of modulation used by the equipment	49
B.3.5	The worst case mode for each of the following tests	49

B.4	RX test information as required by ETSI EN 302 372, clause 4.4.....	50
B.4.1	Worst case mode for RX tests	50
B.4.2	Performance criterion and level of performance	50
B.4.3	RX test setup	50
B.4.4	Definition of interfering signals	50
B.5	Information on mitigation techniques as required by ETSI EN 302 372, clause 4.7	51
B.5.1	Mitigation techniques	51
B.6	Additional information provided by the applicant	51
B.6.1	About the equipment under test.....	51
B.6.2	Additional items and/or supporting equipment provided	51
Annex C (normative):	Radiated measurement.....	53
C.1	Test sites and general arrangements for measurements involving the use of radiated fields	53
C.1.0	General	53
C.1.1	Anechoic chamber.....	53
C.1.2	Anechoic chamber with a conductive ground plane	54
C.1.3	Open area test site (OATS).....	56
C.1.4	Minimum requirements for test sites for measurements above 18 GHz.....	57
C.1.5	Test antenna.....	59
C.1.6	Substitution antenna	59
C.1.7	Measuring antenna	59
C.2	Guidance on the use of radiation test sites	59
C.2.0	General	59
C.2.1	Verification of the test site	59
C.2.2	Preparation of the EUT.....	60
C.2.3	Power supplies to the EUT.....	60
C.2.4	Range length.....	60
C.2.5	Site preparation	61
C.3	Coupling of signals.....	61
C.4	Standard test methods.....	61
C.4.0	General	61
C.4.1	Calibrated setup.....	62
C.4.2	Substitution method.....	62
Annex D (normative):	Conducted measurements	64
Annex E (normative):	Installation requirements of Tank Level Probing Radar (TLPR) equipment	65
Annex F (normative):	Requirements on test tank	66
Annex G (informative):	Electromagnetic leakage from a EUT	67
G.1	General	67
G.2	Survey of sources of leakage.....	67
Annex H (informative):	Measurement antenna and preamplifier specifications	69
Annex I (informative):	Practical test distances for accurate measurements	70
I.1	Introduction	70
I.2	Conventional near-field measurements distance limit	70
Annex J (informative):	Range of modulation parameters	71
J.1	Pulse modulation	71
J.1.1	Definition	71
J.2	Frequency modulated continuous wave	72

J.2.1	Definition	72
Annex K (informative):	Void	73
Annex L (informative):	General requirements for RF measurement equipment	74
L.1	RF cables	74
L.2	RF waveguides	74
L.3	External harmonic mixers	75
L.3.1	Introduction	75
L.3.2	Signal identification	76
L.3.3	Measurement hints	77
L.4	Preamplifier	77
L.5	Measuring receiver	77
Annex M (informative):	Radar targets for radiated measurements.....	78
M.1	Introduction	78
M.2	Radar cross sections of suitable radar targets.....	78
M.3	Boundary conditions of the RCS equations.....	81
Annex N (informative):	Boundary conditions for the radar equation.....	83
N.1	Introduction	83
N.2	Far-field condition.....	83
N.3	Point target condition	84
Annex O (informative):	Bibliography.....	86
Annex P (informative):	Change History	87
History	88

*Final STANDARD PREVIEW
https://standards.etsi.org/4aa78ba0-97cf-48fd-8fcd-302372-v2.1.1-2016-12
Full standard:
Catalogue:
Change History*

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This final draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.8] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.6].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

There have been no significant technical changes incorporated from the previous version of the present document.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

Clauses 1 and 3 provide a general description on the types of equipment covered by the present document and the definitions and abbreviations above.

Clause 2 provides the information on normative and informative reference documentation.

Clause 4 lists all technical requirements specifications. This includes transmitter and receiver conformance requirements as well as requirements for spectrum access, antennas and mitigation techniques.

Clause 5 addresses the conditions for testing. This includes the environmental conditions and product information of the equipment to be tested. It also gives advice on the interpretation of the measurement results and gives the maximum measurement uncertainty values.

Clause 6 provides the information on conformance test suites. This includes test suites for transmitter and receiver parameters as well as test suites for spectrum access, antenna requirements and others.

Annex A explains the relationship between the present document and the essential requirements of Directive 2014/53/EU [i.6].

Annex B provides an application form for facilitating the test preparation.

Annex C lists general requirements on radiated test setups.

Annex D provides information about the requirements of conducted measurements.

Annex E lists the installation requirements of a Tank Level Probing Radar (TLPR) on a tank.

Annex F establishes the requirements on the test tank.

Annex G deals with electromagnetic leakage from a tank with an installed TLPR.

Annex H gives recommendations on measurement antennas and preamplifiers.

Annex I deals with practically useful approximations of the far field conditions for radiated measurements.

Annex J describes the range of modulation parameters for TLPR instruments.

Annex K gives information on the atmospheric absorption of electromagnetic waves as a function of frequency.

Annex L gives practical information on RF measurements, especially in higher frequency bands.

Annex M gives information on radar targets for radiated measurements.

Annex N describes the boundary conditions for the Radar equation.

Annex O (bibliography) lists further related documents.

Annex P contains the change history of the present document.

1 Scope

The present document applies to the following equipment types:

Tank Level Probing Radar (TLPR) applications are based on pulse RF, FMCW or similar wideband techniques. TLPR radio equipment types are capable of operating in all or part of the frequency bands as specified in table 1.

Table 1: Tank Level Probing Radar (TLPR) permitted frequency bands [i.7]

	TLPR assigned frequency bands (GHz)
Transmit and Receive	4,5 to 7
Transmit and Receive	8,5 to 10,6
Transmit and Receive	24,05 to 27
Transmit and Receive	57 to 64
Transmit and Receive	75 to 85

The present document contains requirements to demonstrate that TLPR equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

Table 1 shows a list of the frequency bands as assigned to Tank Level Probing Radars in the EC Decision 2013/752/EU [i.7] and CEPT/ERC Recommendation 70-03 [i.1] as known at the date of publication of the present document.

TLPRs are used for tank level measurement applications in many industries concerned with process control to measure the amount of various substances (mostly liquids or granulates). TLPRs are used for a wide range of applications such as process control, custody transfer measurement (government legal measurements), water and other liquid monitoring, spilling prevention and other industrial applications. The main purposes of using TLPRs are:

- to increase reliability by preventing accidents;
- to increase industrial efficiency, quality and process control;
- to improve environmental conditions in production processes.

The present document applies to TLPRs radiating RF signals towards the surface of a substance contained in a closed tank. Any radiation outside of the tank is caused by leakage and is considered as unintentional emission. The present document does not necessarily include all the characteristics, which may be required by a user, nor does it necessarily represent the optimum performance achievable, it applies only to TLPRs fitted with dedicated antennas.

TLPRs always consist of a combined transmitter and receiver and are used with an integral or dedicated antenna. The TLPR equipment is for professional applications where installation and maintenance are performed by professionally trained individuals only.

The scope is limited to TLPRs operating as Short Range Devices (SRD), in which the devices are installed in closed metallic tanks or reinforced concrete tanks, or similar enclosure structures made of comparable attenuating material, holding a substance, liquid or powder.

The TLPR applications in the present document are not intended for communication purposes. Their intended usage excludes any intended radiation into free space.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [2] CISPR 16-1-1 (2015): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [3] ETSI TR 102 273 (all parts) (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [4] ANSI C63.5 (2006): "American National Standard for Electromagnetic Compatibility - Radiated Emission Measurements in Electromagnetic Interference (EMI) Control - Calibration of Antennas (9 kHz to 40 GHz)".
- [5] ETSI EN 303 883 (V1.1.1) (09-2016): "Short Range Devices (SRD) using Ultra Wide Band (UWB); Measurement Techniques".
- [6] ETSI TS 103 361 (V1.1.1) (03-2016): "Short Range Devices (SRD) using Ultra Wide Band technology (UWB); Receiver technical requirements, parameters and measurement procedures to fulfil the requirements of the Directive 2014/53/EU".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT/ERC/Recommendation 70-03: "Relating to the use of Short Range Devices (SRD)".
- [i.2] Recommendation ITU-R SM.1754: "Measurement techniques of Ultra-wideband transmissions".
- [i.3] ETSI TS 103 051: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Expanded measurement uncertainty for the measurement of radiated electromagnetic fields".
- [i.4] ETSI TS 103 052: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [i.5] Recommendation ITU-R P.676-10 (09-2013): "Attenuation by atmospheric gases".

- [i.6] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC, (OJ L153, 22.5.2014, p62).
- [i.7] European Commission Decision 2013/752/EU amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices and repealing Decision 2005/928/EC.
- [i.8] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.9] European Commission Decision 2009/343/EC amending Decision 2007/131/EC on allowing the use of the radio spectrum for equipment using ultra-wideband technology in a harmonised manner in the Community.
- [i.10] ETSI TR 102 215: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.11] CEPT/ERC Recommendation 74-01: "Unwanted emissions in the spurious domain" (Siófok 98, Nice 99, Sesimbra 02, Hradec Kralove 05, Cardiff 11).

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

ActivityFactor (AF): factor which is used to describe different modulation parameters and activity levels of TLPR devices and defined as the ratio of active measurement periods t_{meas} (bursts, sweeps, scans) within the overall repetitive measurement cycle $T_{\text{meas_cycle}}$, i.e. $t_{\text{meas}}/T_{\text{meas_cycle}}$

dedicated antenna: antenna that is designed as an indispensable part of the equipment

Device Under Test (DUT): TLPR under test without a test tank

Duty cycle (DC): ratio of the total on time of the transmitter to the total time in any one hour period reflecting normal operational mode

emissions: signals that leaked or are scattered into the air within the frequency range (that includes harmonics) which depend on equipment's operating bandwidth

NOTE: For TLPRs there is no intended emission outside the tank.

Equipment Under Test (EUT): TLPR under test mounted on a test tank

equivalent isotropically radiated power (e.i.r.p.): total power transmitted, assuming an isotropic radiator

NOTE: e.i.r.p. is conventionally the product of "power into the antenna" and "antenna gain". e.i.r.p. is used for both peak and average power.

equivalent radiated power (e.r.p.): total power transmitted, assuming a directional power transmitted from a theoretical half-wave dipole antenna radiator

Frequency Modulated Continuous Wave (FMCW) radar: radar where the transmitter power is fairly constant but possibly zero during periods giving a big duty cycle (such as 0,1 to 1)

NOTE: The frequency is modulated in some way giving a very wideband spectrum with a power versus time variation which is clearly not pulsed.

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

operating frequency (operating centre frequency): nominal frequency at which equipment is operated

power spectral density (psd): amount of the total power inside the measuring receiver bandwidth expressed in dBm/MHz

pulsed radar (or here simply "pulsed TLPR"): radar where the transmitter signal has a microwave power consisting of short RF pulses

Pulse Repetition Frequency (PRF): inverse of the Pulse Repetition Interval (PRI), averaged over a sufficiently long time to cover all PRF variations

Pulse Repetition Interval (PRI): time period between two consecutive transmit pulses in a pulsed TLPR

radiated measurements: measurements that involve the absolute measurement of a radiated field

radiation: signals emitted intentionally inside a tank for level measurements

step response time (of a TLPR): time span after a sudden distance change until the output value (distance value) reaches 90 % of the final value for the first time

3.2 Symbols

For the purposes of the present document, the following symbols apply:

AF	Activity factor
f	Frequency
f_C	Frequency at which the peak power of the emission is at maximum
f_H	Highest frequency of the operating bandwidth
f_L	Lowest frequency of the operating bandwidth
t	Time
t_{meas}	active measurement period
$T_{\text{meas_cycle}}$	overall repetitive measurement cycle
t_G	blanking time
k	Boltzmann constant
c	speed of light
T	Temperature
G	efficient antenna gain of radiating structure or gain of the TLPR antenna in the direction of main radiation (main lobe axis)
G_α	gain of the TLPR antenna in an angle α off the main lobe axis (see figure 5)
G_t	gain of the test antenna in the direction of main radiation (main lobe axis)
G_a	declared measurement antenna gain
d	Largest dimension of the antenna aperture of the TLPR or extent of the main lobe in slant distance R_T
d_1	Largest dimension of the TLPR antenna (m)
d_2	Largest dimension of the test antenna (m)
DC	Duty cycle
P_s	Output power of the signal generator measured by power meter
Δf	Bandwidth
BW_{ref}	reference bandwidth
BW_{measured}	measurement bandwidth
X	Minimum radial distance (m) between the DUT and the test antenna
λ	wavelength in general or wavelength of the TLPR transmit signal at centre frequency
dB	deciBel
dB _i	antenna gain in deciBel relative to an isotropic antenna
ϵ_r	relative permittivity of the surface material in the real measurement scenario
R_{max}	maximum measurement distance which the individual sensor is still able to reliably measure under the influence of an interferer
Δd	measurement value variation over time during a distance measurement