



**Short Range Devices (SRD);
Level Probing Radar (LPR) equipment operating in the
frequency ranges 6 GHz to 8,5 GHz, 24,05 GHz to 26,5 GHz,
57 GHz to 64 GHz, 75 GHz to 85 GHz;
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU**

STANDARD UNDER REVIEW
<https://standards.100.org/standards/etsi/en/302729-v211-201610>
456b-b27b-43728

Reference

REN/ERM-TGUWB-136

Keywords

EHF, harmonised standard, radar, SHF, short range, SRD, testing, UWB

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction	8
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	12
3.1 Definitions	12
3.2 Symbols.....	13
3.3 Abbreviations	15
4 Technical requirements specification.....	16
4.1 Environmental conditions.....	16
4.2 General	16
4.3 Transmitter conformance requirements.....	16
4.3.1 Permitted frequency range of operation.....	16
4.3.1.1 Applicability.....	16
4.3.1.2 Description.....	16
4.3.1.3 Limits	16
4.3.1.4 Conformance.....	16
4.3.2 Operating bandwidth.....	17
4.3.2.1 Applicability.....	17
4.3.2.2 Description	17
4.3.2.3 Limits	17
4.3.2.4 Conformance.....	17
4.3.3 Maximum value of mean power spectral density	17
4.3.3.1 Applicability.....	17
4.3.3.2 Description.....	17
4.3.3.3 Limits	18
4.3.3.4 Conformance.....	18
4.3.4 Maximum value of peak power	18
4.3.4.1 Applicability.....	18
4.3.4.2 Description	18
4.3.4.3 Limits	18
4.3.4.4 Conformance.....	19
4.3.5 Exterior limits	19
4.3.6 Low duty cycle	19
4.3.7 Other emissions	19
4.3.7.1 Applicability.....	19
4.3.7.2 Description.....	19
4.3.7.3 Limits	20
4.3.7.4 Conformance.....	20
4.3.8 Transmitter unwanted emissions.....	20
4.3.8.1 Applicability.....	20
4.3.8.2 Description	20
4.3.8.3 Limits	20
4.3.8.4 Conformance.....	21
4.4 Receiver conformance requirements	22
4.4.1 General.....	22
4.4.2 Receiver spurious emissions	22
4.4.2.1 Applicability.....	22
4.4.2.2 Description.....	22
4.4.2.3 Limits	22

4.4.2.4	Conformance	22
4.4.3	Interferer signal handling	22
4.4.3.1	Applicability	22
4.4.3.2	Description	23
4.4.3.3	Limits	23
4.4.3.4	Conformance	23
4.5	Requirements for spectrum access	24
4.5.1	Detect and avoid (DAA)	24
4.5.2	Listen-before-talk (LBT)	24
4.5.3	Low duty cycle (LDC)	24
4.6	Antenna requirements	24
4.6.1	Characteristics and orientation	24
4.6.1.1	Applicability	24
4.6.1.2	Description	24
4.6.1.3	Limits	25
4.6.1.4	Conformance	25
4.7	Other requirements and mitigation techniques	25
4.7.1	General	25
4.7.2	Adaptive power control (APC)	26
4.7.2.1	Applicability	26
4.7.2.2	Description and general requirements	26
4.7.2.3	Limits	26
4.7.2.4	Conformance	26
4.7.3	Activity factor and duty cycle	26
4.7.3.1	Applicability	26
4.7.3.2	Description	26
4.7.3.3	Limits	27
4.7.3.4	Conformance	27
4.7.4	Frequency domain mitigation	27
4.7.4.1	Applicability	27
4.7.4.2	Description	27
4.7.4.3	Limits	27
4.7.4.4	Conformance	28
4.7.5	Shielding effects	28
4.7.5.1	Applicability	28
4.7.5.2	Description and general requirement	28
4.7.5.3	Limits	28
4.7.5.4	Conformance	28
4.7.6	Equivalent mitigation techniques	28
4.7.6.1	Applicability	28
4.7.6.2	Description and general requirement	28
4.7.6.3	Limits	28
4.7.6.4	Conformance	29
4.7.7	Range of modulation parameters	29
4.7.7.1	Applicability	29
4.7.7.2	Description	29
4.7.7.3	Limits	29
4.7.7.4	Conformance	29
5	Testing for compliance with technical requirements	29
5.1	Environmental conditions for testing	29
5.2	General conditions for testing	29
5.2.1	Product information	29
5.2.2	Product information useful to facilitate testing	29
5.2.3	Requirements for the test modulation	30
5.2.4	Test conditions, power supply and ambient temperatures	30
5.2.5	Choice of equipment for test suites	30
5.2.6	Multiple operating bandwidths and multiband equipment	30
5.2.7	Testing of host connected equipment and plug-in radio devices	30
5.2.8	Radiated measurement arrangements	31
5.3	Interpretation of the measurement results	31
5.3.1	General	31

5.3.2	Conversion loss data and measurement uncertainty	32
5.3.3	Measurement uncertainty is equal to or less than maximum acceptable uncertainty.....	33
5.3.4	Measurement uncertainty is greater than maximum acceptable uncertainty.....	33
5.3.5	Emissions.....	33
6	Conformance test suite	33
6.1	Introduction	33
6.2	Initial measurement steps	33
6.3	Radiated measurements	34
6.3.1	General.....	34
6.3.2	Test sites and general arrangements for measurements involving the use of radiated fields	34
6.3.3	Guidance on the use of a radiation test site.....	34
6.3.4	Coupling of signals	34
6.3.5	Standard test methods	34
6.3.6	Standard calibration method	34
6.4	Conducted measurements.....	34
6.4.1	General Setup.....	34
6.4.2	Specific Setup	34
6.5	Conformance test suite for transmitter parameters.....	34
6.5.1	General.....	34
6.5.2	Method of measurements of the ultra-wideband emissions	35
6.5.3	Permitted frequency range of operation.....	35
6.5.4	Operating bandwidth.....	35
6.5.5	Mean power spectral density measurements.....	37
6.5.5.1	Description	37
6.5.5.2	Radiated mean power spectral density measurements	38
6.5.5.3	Conducted mean power spectral density measurements	38
6.5.6	Peak power measurements.....	39
6.5.6.1	Description.....	39
6.5.6.2	Radiated peak power measurements	40
6.5.6.3	Conducted peak power measurements	40
6.5.7	Exterior limit measurement.....	40
6.5.8	Total power	40
6.5.9	Other emissions	40
6.6	Conformance test suite for receiver parameters.....	41
6.6.1	Receiver spurious emissions	41
6.6.2	Receiver sensitivity.....	41
6.6.3	Interferer signal handling.....	41
6.6.3.1	Description and general requirement	41
6.6.3.2	Interferer frequencies and power levels	41
6.6.3.3	Real scenario.....	42
6.6.3.4	Equivalent scenario	43
6.6.3.5	Radiated test setup for the equivalent scenario	43
6.6.3.6	Conducted test setup for the equivalent scenario	46
6.6.3.7	Test procedure for the equivalent scenario.....	47
6.6.3.8	Alternative scenario	48
6.6.3.9	Radiated test setup for the alternative scenario	48
6.6.3.10	Conducted test setup for the alternative scenario	49
6.6.3.11	Test procedure for the alternative scenario	50
6.7	Conformance test suites for spectrum access	51
6.7.1	Detect and avoid mechanisms.....	51
6.7.2	Listen before talk	51
6.7.3	Low duty cycle	51
6.8	Conformance test suites for antenna requirements	51
6.9	Other test suites	53
6.9.1	Adaptive/transmit power control (APC/TPC).....	53
6.9.2	Activity factor and duty cycle.....	54
6.9.3	Frequency domain mitigation	54
6.9.4	Shielding effects	54
6.9.5	Thermal radiations	55
6.9.6	Site registration	55

Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	56
Annex B (informative):	Application form for testing.....	57
B.1	Introduction	57
B.2	General Information as required by ETSI EN 302 729, clause 5.2	57
B.2.1	Type of equipment (stand-alone, combined, plug-in radio device, etc.)	57
B.2.2	The nominal voltages of the stand-alone radio equipment or the nominal voltages of the combined (host) equipment or test jig in case of plug-in devices	57
B.3	Signal related Information as required by ETSI EN 302 729, clause 4.3.....	58
B.3.1	Introduction	58
B.3.2	Operational frequency range(s) of the equipment	58
B.3.3	Nominal channel bandwidth(s).....	58
B.3.4	The type of modulation used by the equipment.....	58
B.3.5	Antenna data.....	58
B.3.6	The worst case mode for each of the following tests.....	58
B.4	RX test information as required by ETSI EN 302 729, clause 4.4.....	59
B.4.1	Worst case mode for RX tests	59
B.4.2	Performance criterion and level of performance	59
B.4.3	RX test setup	59
B.4.4	Definition of interfering signals	59
B.5	Information on mitigation techniques as required by ETSI EN 302 729, clause 4.7	60
B.5.1	Mitigation techniques	60
B.6	Additional information provided by the applicant.....	60
B.6.1	About the equipment under test.....	60
B.6.2	Additional items and/or supporting equipment provided.....	60
Annex C (normative):	Radiated measurement.....	62
C.1	Test sites and general arrangements for measurements involving the use of radiated fields	62
C.1.0	General	62
C.1.1	Anechoic chamber.....	62
C.1.2	Anechoic chamber with a conductive ground plane	63
C.1.3	Open area test site (OATS).....	65
C.1.4	Minimum requirements for test sites for measurements above 18 GHz.....	66
C.1.5	Test antenna.....	68
C.1.6	Substitution antenna	68
C.1.7	Measuring antenna	68
C.2	Guidance on the use of radiation test sites	68
C.2.0	General	68
C.2.1	Verification of the test site	68
C.2.2	Preparation of the EUT.....	69
C.2.3	Power supplies to the EUT	69
C.2.4	Range length.....	69
C.2.5	Site preparation	70
C.3	Coupling of signals.....	70
C.4	Standard test methods.....	70
C.4.0	General	70
C.4.1	Calibrated setup.....	71
C.4.2	Substitution method.....	71
Annex D (normative):	Conducted measurements	73
Annex E (informative):	Installation of level probing Radar (LPR) equipment in the proximity of radio astronomy sites	74
Annex F (informative):	Measurement antenna and preamplifier specifications	75

Annex G (informative):	Practical test distances for accurate measurements	76
G.1	Introduction	76
G.2	Conventional near-field measurements distance limit	76
Annex H (informative):	Range of modulation parameters	77
H.1	Pulse modulation	77
H.1.1	Definition	77
H.2	Frequency modulated continuous wave	78
H.2.1	Definition	78
Annex I (informative):	Void	79
Annex J (normative):	General requirements for RF measurement equipment	80
J.1	RF cables	80
J.2	RF waveguides	80
J.3	External harmonic mixers	81
J.3.1	Introduction	81
J.3.2	Signal identification	82
J.3.3	Measurement hints	83
J.4	Preamplifier	83
J.5	Measuring receiver	83
Annex K (informative):	Radar targets for radiated measurements	85
K.1	Introduction	85
K.2	Radar cross sections of suitable radar targets	85
K.3	Boundary conditions of the RCS equations	87
Annex L (informative):	Boundary conditions for the Radar equation	89
L.1	Introduction	89
L.2	Far-field condition	89
L.3	Point target condition	90
Annex M (informative):	Bibliography	92
Annex N (informative):	Change History	93
History		94

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This final draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.15] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.12].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

- The present document cancels and replaces previous versions of the whole series.
- There have been no significant technical changes incorporated from the previous version of the present document.

Clauses 1 and 3 provide a general description on the types of equipment covered by the present document and the definitions and abbreviations above.

Clause 2 provides the information on normative and informative reference documentation.

Clause 4 lists all technical requirements specifications. This includes transmitter and receiver conformance requirements as well as requirements for spectrum access, antennas and mitigation techniques.

Clause 5 addresses the conditions for testing. This includes the environmental conditions and product information of the equipment to be tested. It also gives advice on the interpretation of the measurement results and gives the maximum measurement uncertainty values.

Clause 6 provides the information on conformance test suites. This includes test suites for transmitter and receiver parameters as well as test suites for spectrum access, antenna requirements and others.

Annex A explains the relationship between the present document and the essential requirements of Directive 2014/53/EU [i.12].

Annex B provides an application form for facilitating the test preparation.

Annex C lists general requirements on radiated test setups.

Annex D provides information about the requirements of conducted measurements.

Annex E lists the exact locations of radio astronomy sites. The installation of LPR instruments is restricted in the vicinity of these sites.

Annex F gives recommendations on measurement antennas and preamplifiers.

Annex G deals with practically useful approximations of the far field conditions for radiated measurements.

Annex H describes the range of modulation parameters for LPR instruments.

Annex I gives information on the atmospheric absorption of electromagnetic waves as a function of frequency.

Annex J gives practical information on RF measurements, especially in higher frequency bands.

Annex K gives information on radar targets for radiated measurements.

Annex L describes the boundary conditions for the Radar equation.

Annex M (bibliography) lists further related documents.

Annex N contains the change history of the present document.

1 Scope

The present document applies to the following equipment types:

Level Probing Radar (LPR) applications are based on pulse RF, FMCW, or similar wideband techniques. LPR radio equipment types are capable of operating in all or part of the frequency bands as specified in table 1.

Table 1: Level Probing Radar (LPR) permitted frequency bands [i.13]

	LPR assigned frequency bands (GHz)
Transmit and Receive	6 to 8,5
Transmit and Receive	24,05 to 26,5
Transmit and Receive	57 to 64
Transmit and Receive	75 to 85

The present document contains requirements to demonstrate that LPR equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

Table 1 shows a list of the frequency bands as assigned to Level Probing Radars in the European Commission Decision 2013/752/EU [i.13] on harmonised deployment conditions for industrial Level Probing Radars (LPR) as known at the date of publication of the present document.

Technical and regulatory requirements for LPR are provided in ECC Decision (11)02 [i.20], which are based on ECC Report 139 [i.8].

LPRs are used in many industries concerned with process control to measure the amount of various substances (mostly liquids or granulates). LPRs are used for a wide range of applications such as process control, custody transfer measurement (government legal measurements), water and other liquid monitoring, spilling prevention and other industrial applications. The main purposes of using LPRs are:

- to increase reliability by preventing accidents;
- to increase industrial efficiency, quality and process control;
- to improve environmental conditions in production processes.

LPRs always consist of a combined transmitter and receiver and are used with an integral or dedicated antenna. The LPR equipment is for professional applications where installation and maintenance are performed by professionally trained individuals only.

NOTE: LPR antennas are always specific directive antennas and no LPR omnidirectional antennas are used. This is also important in order to limit the illuminated surface area as well as to control and limit the scattering caused by the edges of the surface.

The scope is limited to LPRs operating as Short Range Devices (SRD).

The LPR applications in the present document are not intended for communications purposes.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [2] CISPR 16 (part 1-1:2015), (part 1-4:2010+AMD1:2012) and (part 1-5: 2014): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1: Radio disturbance and immunity measuring apparatus".
- [3] ETSI TR 102 273 (all parts) (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [4] ANSI C63.5 (2006): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electro Magnetic Interference".
- [5] ETSI EN 303 883 (V1.1.1) (07-2016): "Short Range Devices (SRD) using Ultra Wide Band (UWB); Measurement Techniques".
- [6] ETSI TS 103 361 (V1.1.1) (03-2016): "Short Range Devices (SRD) using Ultra Wide Band technology (UWB); Receiver technical requirements, parameters and measurement procedures to fulfil the requirements of the Directive 2014/53/EU".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT/ERC/REC 74-01 (2005): "Unwanted emissions in the spurious domain".
- [i.2] Recommendation ITU-R SM.1754: "Measurement techniques of Ultra-wideband transmissions".
- [i.3] ERA Report 2006-0713: "Conducted and radiated measurements for low level UWB emissions".
- [i.4] FCC: "Revision of part 15 of the Commission's Rules Regarding Ultra- Wideband Transmission Systems", ET Docket No. 98-153, First Report and Order, April 2002.
- [i.5] Recommendation ITU-R P.526-13 (11/2013): "Propagation by diffraction".
- [i.6] ETSI TS 103 052: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [i.7] Recommendation ITU-R P.676-10 (09/2013): "Attenuation by atmospheric gases".
- [i.8] CEPT ECC Report 139: "Impact of Level Probing Radars Using Ultra-Wideband Technology on Radiocommunications Services", Rottach-Egern, February 2010.
- [i.9] ETSI TR 102 601: "Electromagnetic compatibility and Radio spectrum Matters (ERM); System reference document; Short Range Devices (SRD); Equipment for Detecting Movement using Ultra Wide Band (UWB) radar sensing technology; Level Probing Radar (LPR)-sensor equipment operating in the frequency bands 6 GHz to 8,5 GHz; 24,05 GHz to 26,5 GHz; 57 GHz to 64 GHz and 75 GHz to 85 GHz".
- [i.10] European Commission Decision 2009/343/EC amending Decision 2007/131/EC on allowing the use of the radio spectrum for equipment using ultra-wideband technology in a harmonised manner in the Community.

- [i.11] ETSI TR 102 215: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.12] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC, (OJ L153, 22.5.2014, p62).
- [i.13] European Commission Decision 2013/752/EU amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices and repealing Decision 2005/928/EC.
- [i.14] FCC part 15.256: "Operation of level probing radars within the bands 5.925-7.250 GHz, 24.05-29.00 GHz, and 75-85 GHz".
- [i.15] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.16] ETSI TS 103 051: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Expanded measurement uncertainty for the measurement of radiated electromagnetic fields".
- [i.17] ETSI TR 103 181-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD) using Ultra Wide Band (UWB); Transmission characteristics Part 2: UWB mitigation techniques".
- [i.18] Committee on Radio Astronomy Frequencies, European Science Foundation.
- NOTE: Available at www.craf.eu.
- [i.19] Void.
- [i.20] ECC/DEC/(11)02: "ECC Decision of 11 March 2011 on industrial Level Probing Radars (LPR) operating in frequency bands 6 - 8.5 GHz, 24.05 - 26.5 GHz, 57 - 64 GHz and 75 - 85 GHz".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Activity Factor (AF): Factor which is used to describe different modulation parameters and activity levels of LPR devices and defined as the ratio of active measurement periods t_{meas} (bursts, sweeps, scans) within the overall repetitive measurement cycle $T_{\text{meas_cycle}}$, i.e. $t_{\text{meas}}/T_{\text{meas_cycle}}$.

Adaptive Power Control (APC): automatic function implemented to offer a dynamic power control that delivers maximum power only during deep fading; in this way for most of the time the interference is reduced

dedicated antenna: antenna that is designed as an indispensable part of the equipment

Duty Cycle (DC): product of the pulse repetition frequency (PRF) and the pulse duration

emissions: signals that leaked or are scattered into the air within the frequency range (that includes harmonics) which depend on equipment's operating bandwidth

Equipment Under Test (EUT): LPR under test

equivalent isotropically radiated power (e.i.r.p.): total power transmitted, assuming an isotropic radiator

NOTE: e.i.r.p. is conventionally the product of "power into the antenna" and "antenna gain". e.i.r.p. is used for both peak and average power.

Frequency Modulated Continuous Wave (FMCW) radar: radar where the transmitter power is fairly constant but possibly zero during periods giving a big duty cycle (such as 0,1 to 1)

NOTE: The frequency is modulated in some way giving a very wideband spectrum with a power versus time variation which is clearly not pulsed.

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

operating frequency (operating centre frequency): nominal frequency at which equipment is operated

power spectral density (psd): amount of the total power inside the measuring receiver bandwidth expressed in dBm/MHz

pulsed radar (or here simply "pulsed LPR"): radar where the transmitter signal has a microwave power consisting of short RF pulses

Pulse Repetition Frequency (PRF): inverse of the Pulse Repetition Interval (PRI), averaged over a sufficiently long time to cover all PRF variations

Pulse Repetition Interval (PRI): time period between two consecutive transmit pulses for example in a pulsed LPR

radiated measurements: measurements that involve the absolute measurement of a radiated field

radiation: signals emitted intentionally for level measurements

step response time (of an LPR): time span after a sudden distance change until the output value (distance value) reaches 90 % of the final value for the first time

3.2 Symbols

For the purposes of the present document, the following symbols apply:

AF	Activity factor
f	Frequency
f_C	Frequency at which the peak power of the emission is at maximum
f_H	Highest frequency of the operating bandwidth
f_L	Lowest frequency of the operating bandwidth
t	Time
t_{meas}	active measurement period
$T_{\text{meas_cycle}}$	overall repetitive measurement cycle
t_G	blanking time
k	Boltzmann constant
c	speed of light
T	Temperature
G	efficient antenna gain of radiating structure or gain of the TLPR antenna in the direction of main radiation (main lobe axis)
G_α	gain of the TLPR antenna in an angle α off the main lobe axis (see figure 5)
G_t	gain of the test antenna in the direction of main radiation (main lobe axis)
G_a	declared measurement antenna gain
d	Largest dimension of the antenna aperture of the TLPR or extent of the main lobe in slant distance R_T
d_1	Largest dimension of the TLPR antenna (m)