
Fiksni radijski sistemi - Večtočkovna oprema in antene - 2. del: Harmonizirani standard za dostop do radijskega spektra

Fixed Radio Systems - Multipoint Equipment and Antennas - Part 2: Harmonised Standard for access to radio spectrum

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: ETSI EN 302 326-2 V2.1.1 (2021-09)

SIST EN 302 326-2 V2.1.1:2021
<https://standards.iteh.ai/catalog/standards/sist/22e6d1e1-2b47-4487-85e5-e4250791b241/sist-en-302-326-2-v2-1-1-2021>

ICS:

33.060.30	Radiorelejni in fiksni satelitski komunikacijski sistemi	Radio relay and fixed satellite communications systems
33.120.40	Antene	Aerials

SIST EN 302 326-2 V2.1.1:2021 **en**

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 302 326-2 V2.1.1:2021

<https://standards.iteh.ai/catalog/standards/sist/22e6d1e1-2b47-4487-85e5-e4250791b241/sist-en-302-326-2-v2-1-1-2021>

ETSI EN 302 326-2 V2.1.1 (2021-09)



Fixed Radio Systems; Multipoint Equipment and Antennas; Part 2: Harmonised Standard for access to radio spectrum

[SIST EN 302 326-2 V2.1.1:2021](https://standards.iteh.ai/catalog/standards/sist/22e6d1e1-2b47-4487-85e5-e4250791b241/sist-en-302-326-2-v2-1-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/22e6d1e1-2b47-4487-85e5-e4250791b241/sist-en-302-326-2-v2-1-1-2021>

Reference

REN/ATTM-0436

Keywords

access, DFRS, DRRS, FWA, multipoint, radio, system

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.

All rights reserved.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	8
Introduction	8
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definition of terms, symbols and abbreviations.....	13
3.1 Terms.....	13
3.2 Symbols.....	17
3.3 Abbreviations	17
4 Framework for requirements	19
4.1 Generality	19
4.1.0 The "Manufacturer's declaration" concept.....	19
4.1.1 Applicability of requirements	20
4.1.1.1 Generality.....	20
4.1.1.2 The Equipment Classification (EqC)	20
4.1.2 Asymmetric MP implementations	21
4.2 RF reference architecture	21
4.2.1 Reference block diagram	21
4.2.2 Measure reference points and system loading	22
5 Technical requirements specifications	22
5.1 General requirements	22
5.2 Environmental profile.....	22
5.3 Transmitter requirements	22
5.3.1 General requirements.....	22
5.3.2 Transmitter output power.....	22
5.3.2.1 General	22
5.3.2.2 Transmitter maximum power and EIRP	23
5.3.2.3 Transmitter output power environmental variation	23
5.3.3 Transmitter Radio Frequency tolerance.....	24
5.3.4 Transmitter Radio Frequency spectrum mask and emissions	24
5.3.4.1 Transmitter Radio Frequency spectrum mask.....	24
5.3.4.2 Transmitter discrete CW components exceeding the transmitter Radio Frequency spectrum mask limits	27
5.3.5 Transmitter unwanted emissions in the spurious domain	28
5.3.6 Transmitter power control (ATPC and RTPC)	29
5.3.6.1 General	29
5.3.6.2 Automatic Transmitter Power Control (ATPC)	29
5.3.6.3 Remote Transmitter Power Control (RTPC).....	29
5.3.7 Transmitter Remote Frequency Control (RFC)	30
5.3.8 Transmitter Dynamic Change of Modulation Order	30
5.4 Receiver requirements	30
5.4.1 General.....	30
5.4.2 Receiver unwanted emissions in the spurious domain.....	30
5.4.3 BER as a function of Receiver input Signal Level (RSL).....	30
5.4.3.1 General	30
5.4.3.2 Single signal performance.....	31
5.4.3.3 Performance with maximum system loading (EqC-PET = D only).....	32
5.4.3.4 Receiver Dynamic range	33
5.4.4 Receiver selectivity.....	34
5.4.4.0 Introduction.....	34

5.4.4.1	Receiver co-channel interference sensitivity	34
5.4.4.2	Receiver first adjacent channel interference sensitivity	36
5.4.4.3	Receiver blocking (CW spurious interference sensitivity)	38
5.4.4.4	Receiver radio-frequency intermodulation and Receiver second adjacent channel interference sensitivity	39
5.4.4.4.1	Requirement background	39
5.4.4.4.2	Requirement limit	39
6	Testing for conformance with technical requirements	40
6.1	General	40
6.2	Environmental conditions for testing	40
6.2.1	Generality	40
6.2.2	Minimum profile for indoor use	41
6.2.3	Minimum profile for outdoor use	41
6.3	Transmitter requirements	41
6.3.1	General	41
6.3.1.1	Summary table for transmitter test conditions	41
6.3.1.2	Spectrum analyser settings	42
6.3.2	Transmitter output power	43
6.3.2.1	General	43
6.3.2.2	Transmitter maximum power and EIRP	43
6.3.2.3	Transmitter output power environmental variation	44
6.3.3	Transmitter Radio Frequency tolerance	44
6.3.4	Transmitter Radio Frequency spectrum mask and emissions	44
6.3.4.1	Transmitter Radio Frequency spectrum mask	44
6.3.4.2	Transmitter Discrete CW components exceeding the transmitter Radio Frequency spectrum mask limit	45
6.3.5	Transmitter unwanted emissions in the spurious domain	45
6.3.6	Transmitter power control (ATPC and RTPC)	45
6.3.6.1	General	45
6.3.6.2	Automatic Transmitter Power Control (ATPC)	46
6.3.6.3	Remote Transmitter Power Control (RTPC)	46
6.3.7	Transmitter Remote Frequency Control (RFC)	46
6.3.8	Transmitter dynamic Change of Modulation Order	47
6.4	Receiver requirements	47
6.4.1	General	47
6.4.2	Receiver unwanted emissions in the spurious domain	48
6.4.3	BER as a function of Receiver input Signal Level (RSL)	49
6.4.3.1	General	49
6.4.3.2	Single signal performance	49
6.4.3.3	Performance at maximum system loading (EqC-PET = D only)	49
6.4.3.4	Receiver dynamic range	49
6.4.4	Receiver selectivity	49
6.4.4.1	Receiver co-channel interference sensitivity	49
6.4.4.2	Receiver first adjacent channel interference sensitivity	50
6.4.4.3	Receiver blocking (CW spurious interference sensitivity)	50
6.4.4.4	Receiver radio-frequency intermodulation and receiver second adjacent channel interference sensitivity	50
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	52
Annex B (normative):	Test report in relation to flexible systems applications	54
B.1	Wide radio-frequency band covering units specification and tests	54
B.2	Multirate/Multiformat covering equipment specification and tests	56
Annex C (normative):	Equipment classification (EqC) and system capacity	57
C.1	General	57
C.2	EqC description	57
C.2.1	Void	57

C.2.2	Primary Equipment Type (EqC-PET)	57
C.2.3	Secondary Equipment Type (EqC-SET)	58
C.2.4	Equivalent Modulation Order (EqC-EMO)	58
C.2.5	Channel Separation (EqC-ChS)	59
C.2.6	Frequency Range (EqC-FR)	59
C.2.7	Station Type (EqC-STN)	59
C.3	System capacity	60
C.3.1	General	60
C.3.2	Capacity of equipment with EqC-PET = T, O or M	60
C.3.3	Capacity of equipment with EqC-PET = F	60
C.3.4	Capacity of equipment with EqC-PET = D	61
C.4	Classification of equipment	62
C.4.1	Equipment profiles in the scope of present document	62
Annex D (informative):	Transmitter Radio Frequency Spectrum mask background for ATPC and/or RTPC implementation	65
D.0	Introduction	65
D.1	ATPC impact	65
D.2	RTPC Impact	66
Annex E (informative):	Overview of technology features of multipoint systems	67
E.1	General	67
E.2	Network topology	67
E.3	Multiplexing methods	67
E.4	Multiple access methods	68
E.5	Duplex methods	68
E.6	Modulation methods	69
E.6.1	Modulation techniques	69
E.6.2	Equivalent Modulation Order (EMO)	69
E.7	Error correction	70
E.8	Other relevant system characteristics	70
Annex F (informative):	Frequency bands	71
F.1	Frequency ranges	71
F.2	Frequency ranges CEPT applications	72
Annex G (informative):	Summary Table of EqC subject to conformance declaration	74
G.1	The right to copy	74
Annex H (informative):	System architecture	75
H.1	General architecture	75
H.2	Point-to-MultiPoint (P-MP) architectures	75
H.3	Mesh (or MP-MP) architectures	77
Annex I (informative):	Mixed-mode operation	78
I.1	Introduction	78
I.2	General description of mixed-mode systems	78
I.3	Background for transmitter and receiver requirements operating in mixed-mode	78
I.3.1	Requirements summary	78

I.3.2	Transmitter Radio Frequency spectrum masks for mixed-mode systems	78
I.3.3	Receiver adjacent channel interference sensitivity	80
I.3.4	Receiver co-channel interference sensitivity	80
Annex J (informative):	Antennas	81
J.1	Antenna generality	81
J.2	Antenna profiles	81
Annex K (informative):	Typical reference model for BER, MGBR and EMO.....	82
K.1	General	82
K.2	Interface X'_1 to X'_N	83
K.3	Payload processing block	83
K.4	Multiple access block	84
K.5	Outer error correcting block	84
K.6	Inner error correcting block.....	84
K.7	Modulator	85
K.8	Choice of reference point for BER, MGBR and EMO	85
K.9	Examples	85
K.9.1	16 QAM TDMA system with 3/4 rate convolutional coding	85
K.9.2	16 QAM TDMA system with 1/2 rate convolutional coding and 204/188 Reed Solomon coding	86
K.9.3	16 QAM TDMA system with 1/2 rate turbo coding	86
K.9.4	16 QAM FDMA system with 1/2 rate convolutional coding	86
Annex L (informative):	Test interpretation and measurement uncertainty	87
Annex M (informative):	Bibliography	88
Annex N (informative):	Change History	89
History		90

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

IT-EN STANDARD PREVIEW
(standards.itech.ai)

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Access, Terminals, Transmission and Multiplexing (ATTM).
SIST EN 302 326-2 V2.1.1:2021
<https://standards.itech.ai/catalog/standards/sist/22c0d1e1-2047-4707-83e9-64250791b241/sist-en-302-326-2-v2-1-1-2021>

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.4] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document covers characteristics and requirements for fixed multipoint radio equipment using a variety of access and duplex methods and operating at a variety of bit rates in frequency bands as specified in the present document.

The present document is part 2 of a multi-part deliverable covering the Fixed Radio Systems; Multipoint Equipment and Antennas, as identified below:

Part 1: "Overview and Requirements for Digital Multipoint Radio Systems";

Part 2: "Harmonised Standard for access to radio spectrum";

Part 3: "Multipoint Antennas".

NOTE: Part 1 is no longer maintained and referenced in other parts of the series.

National transposition dates	
Date of adoption of this EN:	30 August 2021
Date of latest announcement of this EN (doa):	30 November 2021
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2022
Date of withdrawal of any conflicting National Standard (dow):	31 May 2023

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document defines the essential characteristics for multipoint radio equipment and up to 43,5 GHz to comply with article 3.2 of Directive 2014/53/EU [i.1].

For the purpose of the present document, multipoint radio systems can be considered as radio systems which interconnect a number of fixed stations (usually more than two). The topology of the systems may be Point-to-MultiPoint (P-MP), or MultiPoint-to-MultiPoint (MP-MP), known as "Mesh".

Depending on the application, MultiPoint Systems can be seen either as "Fixed Wireless Access" (FWA) systems to grant multiple access to different services with a variety of bit rates, or as "infrastructure" or "backhaul" applications when different stations in a network will be connected to support, e.g. duplex mobile telephony.

Either as narrowband or wideband system MultiPoint technology facilitates access to public and private networks (PSTN, Internet, PDN, etc.) to connect residential and business subscribers in urban, suburban and rural areas.

Access and infrastructure applications can be supported simultaneously.

In order to (technically) cover different market and network requirements, with an appropriate balance of performance to cost and effective use of the radio spectrum, the present document, together with ETSI EN 302 326-3 [i.2], offers a number of radio equipment types and antennas alternatives (integral or dedicated antennas).

Those options include:

- channel separation alternatives (as provided by the relevant CEPT Recommendation);
- spectral efficiency class alternatives (different modulation formats provided in radio equipment standards).

Antenna characteristics are not relevant for access to radio spectrum of MP fixed radio systems (see technical description in ETSI TR 101 506 [i.6]). For information, the most common types of antennas are standardized in Part 3 of this multi-part deliverable [i.2].

The applicability of this whole multi-part deliverable to MP equipment is governed by the definition of a number of equipment/system profiles that define the set of consistent requirements to which equipment would comply.

For compliance purposes, a specific type of equipment needs to be identified by an Equipment Classification (EqC) coherent set, as specified in annex C.

Based on this Equipment Classification, the appropriate clauses of the present document have to be applied.

The present document introduces new technical features compared to the previous version in terms of RX intermodulation requirements and ATPC functionality, mandatory for managing the different CS/RS link lengths where the system has to operate as intended. In addition, it covers equipment operating in the band 40,5 GHz to 43,5 GHz frequency band, previously separated and handled covered by ETSI EN 301 997-2 [i.27], under the regime of Directive 1999/5/EC [i.39].

For more background information on the antenna parameters, not relevant to article 3.2 of Directive 2014/53/EU [i.1], see ETSI EN 302 326-3 [i.2].

Following annexes are embedded in the present document:

- Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU [i.1]
- Annex B (normative): Test report in relation to flexible systems applications
- Annex C (normative): Equipment classification (EqC) and system capacity
- Annex D (informative): Transmitter Radio Frequency Spectrum mask background for ATPC and/or RTPC implementation
- Annex E (informative): Overview of technology features of multipoint systems
- Annex F (informative): Frequency bands
- Annex G (informative): Summary Table of EqC subject to conformance declaration
- Annex H (informative): System architecture
- Annex I (informative): Mixed-mode operation
- Annex J (informative): Antennas
- Annex K (informative): Typical reference model for BER, MGBR and EMO
- Annex L (informative): Test interpretation and measurement uncertainty
- Annex M (informative): Bibliography
- Annex N (informative): Change History

1 Scope

The present document specifies technical characteristics and methods of measurements applicable to radio equipment used in MultiPoint (MP) Digital Fixed Radio Systems (DFRS) (see note 2) designed for use in the following sub-ranges (see note 3):

- 30 MHz to 1 GHz.
- 1 GHz to 3 GHz.
- 3 GHz to 11 GHz.
- 24,25 GHz to 29,5 GHz.
- 31,0 GHz to 33,4 GHz.
- 40,5 GHz to 43,5 GHz.

NOTE 1: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in Annex A.

The present document is applicable to multipoint radio system equipment using any arbitrary access method. It applies to all equipment composing the MP systems, i.e. to Central Station (CS), Terminal Station (TS) and Repeater Station (RS).

Time Division Duplex (TDD) or Frequency Division Duplex (FDD or H-FDD) can be used on an equivalent basis.

Systems implementing an actual FH-CDMA access method with hopping period exceeding 400 ms are not considered within the scope of the present document.

NOTE 2: Applications intended for offering in the bands 3,4 GHz to 3,8 GHz the option of Nomadic Wireless Access (NWA), according to the NWA definition in Recommendation ITU-R F.1399 [i.14], are also considered in the scope of the present document.

NOTE 3: For more information on the applicable frequency bands, refer to Annex F.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- | | |
|-----|--|
| [1] | CEPT/ERC/REC 74-01 (2019): "Unwanted emissions in the spurious domain". |
| [2] | ETSI EN 301 390 (V1.3.1) (08-2013): "Fixed Radio Systems; Point-to-point and Multipoint Systems; Unwanted emissions in the spurious domain and receiver immunity limits at equipment/antenna port of Digital Fixed Radio Systems". |
| [3] | ETSI EN 301 126-2-1 (V1.1.1) (12-2000): "Fixed Radio Systems; Conformance testing; Part 2-1: Point-to-Multipoint equipment; Definitions and general requirements". |

- [4] ETSI EN 301 126-2-2 (V1.1.1) (11-2000): "Fixed Radio Systems; Conformance testing; Part 2-2: Point-to-Multipoint equipment; Test procedures for FDMA systems".
- [5] ETSI EN 301 126-2-3 (V1.2.1) (11-2004): "Fixed Radio Systems; Conformance testing; Part 2-3: Point-to-Multipoint equipment; Test procedures for TDMA systems".
- [6] ETSI EN 301 126-2-4 (V1.1.1) (11-2000): "Fixed Radio Systems; Conformance testing; Part 2-4: Point-to-Multipoint equipment; Test procedures for FH-CDMA systems".
- [7] ETSI EN 301 126-2-5 (V1.1.1) (11-2000): "Fixed Radio Systems; Conformance testing; Part 2-5: Point-to-Multipoint equipment; Test procedures for DS-SSMA systems".
- [8] ETSI EN 301 126-2-6 (V1.1.1) (02-2002): "Fixed Radio Systems; Conformance testing; Part 2-6: Point-to-Multipoint equipment; Test procedures for Multi Carrier Time Division Multiple Access (MC-TDMA) systems".
- [9] ETSI EN 300 019-1-3 (V2.4.1) (04-2014): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weatherprotected locations".
- [10] ETSI EN 300 019-1-4 (V2.2.1) (04-2014): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weatherprotected locations".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

[SIST EN 302 326-2 V2.1.1:2021](#)

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI EN 302 326-3: "Fixed Radio Systems; Multipoint Equipment and Antennas; Part 3: Multipoint Antennas".
- [i.3] ITU Radio Regulations (2016).
- [i.4] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.5] ETSI EG 203 336 (V1.2.1): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.6] ETSI TR 101 506 (V2.2.1): "Fixed Radio Systems; Generic definitions, terminology and applicability of essential requirements covering article 3.2 of Directive 2014/53/EU to Fixed Radio Systems".
- [i.7] Recommendation ITU-R SM.1539-1: "Variation of the boundary between the out-of-band and spurious domains required for the application of Recommendations ITU-R SM.1541 and ITU-R SM.329".
- [i.8] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

- [i.9] ETSI TR 102 215: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.10] ETSI TR 103 103 (V1.1.1): "Fixed Radio Systems; Point-to-point systems; ATPC, RTPC, Adaptive Modulation (mixed-mode) and Bandwidth Adaptive functionalities; Technical background and impact on deployment, link design and coordination".
- [i.11] ERC Report 25: "The European table of frequency allocations and applications in the frequency range 8.3 kHz to 3000 GHz".
- [i.12] ETSI TR 101 274: "Transmission and Multiplexing (TM); Digital Radio Relay Systems (DRRS); Point-to-multipoint DRRS in the access network: Overview of different access techniques".
- [i.13] Recommendation ITU-R F.746: "Radio-frequency arrangements for fixed service systems".
- [i.14] Recommendation ITU-R F.1399: "Vocabulary of terms for wireless access".
- [i.15] CEPT/ECC/DEC(05)01: "The use of the band 27.5-29.5 GHz by the Fixed Service and uncoordinated Earth stations of the Fixed-Satellite Service (Earth-to-space)".
- [i.16] CEPT/ERC/REC(01)02: "Preferred channel arrangement for digital fixed service systems operating in the frequency band 31.8 - 33.4 GHz".
- [i.17] CEPT/ECC/REC(04)05: "Guidelines for accommodation and assignment of multipoint Fixed Wireless Systems in frequency bands 3.4-3.6 GHz and 3.6-3.8 GHz".
- [i.18] CEPT/ECC/REC(11)01: "Guidelines for assignment of frequency blocks for fixed wireless systems in the bands 24.5-26.5 GHz, 27.5-29.5 GHz AND 31.8-33.4 GHz".
- [i.19] CEPT/ERC/REC 12-05: "Harmonized radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 10.0 - 10.68 GHz".
- [i.20] CEPT/ERC/REC 12-08: "Harmonized radio frequency channel arrangements and block allocations for low, medium and high capacity systems in the band 3 600 MHz to 4 200 MHz".
- [i.21] CEPT/ERC/REC T/R 13-02: "Preferred channel arrangements for the fixed services in the range 22.0 - 29.5 GHz".
- [i.22] CEPT/ERC/REC 14-03: "Harmonized radio frequency channel arrangements for low and medium capacity systems in the band 3 400 MHz to 3 600 MHz".
- [i.23] CEPT/ECC/REC(02)02: "Channel arrangements for digital fixed service systems (point-to-point and point-to-multipoint) operating in the frequency band 31 - 31.3 GHz".
- [i.24] ETSI EG 202 306: "Transmission and Multiplexing (TM); Access networks for residential customers".
- [i.25] ETSI ETS 300 019 (all parts): "Equipment engineering; Environmental conditions and environmental tests for telecommunications equipment".
- [i.26] ETSI EN 300 019 (all parts): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment".
- [i.27] ETSI EN 301 997-2: "Transmission and Multiplexing (TM); Multipoint equipment; Radio equipment for use in Multimedia Wireless Systems (MWS) in the frequency band 40,5 GHz to 43,5 GHz; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".
- [i.28] ETSI EN 301 126-3-2 (V1.2.1) (12-2003): "Fixed Radio Systems; Conformance testing; Part 3-2: Point-to-Multipoint antennas - Definitions, general requirements and test procedures".
- [i.29] Recommendation ITU-R P.525-4: "Calculation of free-space attenuation".

- [i.30] CEPT/ECC/REC(01)04: "Recommended guidelines for the accommodation and assignment of multimedia wireless systems (MWS) and point-to-point (P-P) fixed wireless systems in the frequency band 40.5 - 43.5 GHz".
- [i.31] Decision 2007/344/EC: "Commission Decision of 16 May 2007 on harmonised availability of information regarding spectrum use within the Community".
- [i.32] Directive (EU) 2015/1535 of the European Parliament and of the Council of 9 September 2015 laying down a procedure for the provision of information in the field of technical regulations and of rules on Information Society services.
- [i.33] Commission Implementing Decision (EU) 2019/784 of 14 May 2019 on the harmonisation of the 24,25-27,5 GHz frequency band for terrestrial systems capable of providing wireless broadband electronic communications services in the Union.
- [i.34] Decision 2008/411/EC: "Commission Decision of 21 May 2008 on the harmonisation of the 3 400 - 3 800 MHz frequency band for terrestrial systems capable of providing electronic communications services in the Community".
- [i.35] ECO Frequency Information System (EFIS).
- NOTE: Available at [ECO Frequency Information System \(cept.org\)](http://www.cept.org/eco).
- [i.36] ECO Report 04: "Fixed Service in Europe Implementation Status".
- [i.37] Technical Regulation Information System (TRIS).
- NOTE: Available at <https://ec.europa.eu/growth/tools-databases/tris/en>.
- [i.38] ISO/IEC 7498-1: "Information technology -- Open Systems Interconnection -- Basic Reference Model: The Basic Model"
- [i.39] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document , the following terms apply:

active antenna: antenna including one or more active electronic components that interact with the Radio Frequency (RF) signal as e.g. amplifier or diode

antenna: part of the transmitting or receiving system that is designed to transmit or receive electromagnetic radiation

assigned band: frequency block or the aggregation of all RF channels assigned to a MP system

NOTE: The assigned band may consist also of several non-contiguous RF channels (see Figure 1).