

ETSI EN 302 066 V2.1.1 (2017-01)



**Short Range Devices (SRD);
Ground- and Wall- Probing Radar applications (GPR/WPR)
imaging systems;
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU**

IPB 3F A140 P REVIEW
https://standards.iteh.ai/catalog/standards/si/296423-3601-4e0e-8673-b540417912e8/etsi-en-302-066-v2-1-1-2017-01

Reference

REN/ERM-TGUWB-138

Keywordsharmonised standard, radar, radio, SRD, testing,
UWB**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	8
3.1 Definitions.....	8
3.2 Symbols.....	9
3.3 Abbreviations	9
4 Technical requirements specifications	9
4.1 Environmental conditions.....	9
4.2 General	9
4.3 Transmitter Conformance Requirements.....	10
4.3.1 Operating Bandwidth.....	10
4.3.1.1 Applicability.....	10
4.3.1.2 Description	10
4.3.1.3 Limits	10
4.3.1.4 Conformance.....	10
4.3.2 Maximum value of mean power spectral density	10
4.3.3 Maximum value of peak power	10
4.3.4 Exterior Limits	10
4.3.4.1 Applicability.....	10
4.3.4.2 Description	10
4.3.4.3 Limits	10
4.3.4.4 Conformance.....	11
4.3.5 Total Power.....	11
4.3.6 Other Emissions.....	11
4.3.7 Transmitter unwanted emissions.....	11
4.4 Receiver Conformance Requirements.....	11
4.4.1 General.....	11
4.4.2 Receiver spurious emissions	11
4.4.3 Receiver interference handling	11
4.4.3.1 Applicability.....	11
4.4.3.2 Description	11
4.4.3.3 Limits	12
4.4.3.4 Conformance.....	12
4.5 Requirements for spectrum access	12
4.5.1 Detect and Avoid (DAA).....	12
4.5.2 Listen-before-talk (LBT)	12
4.5.3 Low Duty Cycle (LDC)	12
4.6 Antenna Requirements	12
4.7 Other Requirements and Mitigation techniques	12
4.7.1 Adaptive/Transmit Power Control (TPC).....	12
4.7.2 Activity factor	12
4.7.3 Frequency Domain Mitigation.....	12
4.7.4 Shielding effects	12
4.7.5 Thermal Radiation	12
4.7.6 Site registration	13
4.7.7 Deactivation mechanism.....	13
5 Testing for compliance with technical requirements.....	13
5.1 Environmental conditions for testing	13
5.2 General conditions for testing	13

5.2.1	Product information	13
5.2.2	Requirements for the test modulation	13
5.2.3	Test conditions, power supply and ambient temperatures	13
5.2.4	Choice of equipment for test suites.....	13
5.2.5	Multiple Operating bandwidths and multiband equipment.....	13
5.2.6	Testing of host connected equipment and plug-in radio devices	13
5.3	Interpretation of the measurement results	14
5.3.0	General.....	14
5.3.1	Measurement uncertainty is equal or less than maximum acceptable uncertainty.....	14
5.3.2	Measurement uncertainty is greater than maximum acceptable uncertainty.....	14
5.3.3	Emissions	14
6	Conformance test suites.....	14
6.1	Introduction	14
6.2	Initial Measurement steps.....	14
6.3	Radiated measurements	14
6.3.1	General.....	14
6.3.2	Test sites and general arrangements for measurements involving the use of radiated fields	15
6.3.3	Guidance on the use of a radiation test site.....	15
6.3.3.1	General	15
6.3.3.2	Range length	15
6.3.4	Coupling of signals	15
6.3.5	Standard test methods	15
6.3.5.1	Generic measurement method.....	15
6.3.5.1.1	Calibrated setup	15
6.3.5.1.2	Substitution method.....	15
6.3.6	Standard calibration method	15
6.4	Conducted measurements.....	16
6.4.1	General Setup.....	16
6.4.2	Specific Setup	16
6.5	Conformance methods of measurement for transmitter.....	16
6.5.1	General.....	16
6.5.2	Method of measurements of the Ultra Wideband Emissions from GPR/WPR.....	16
6.5.3	Operating Bandwidth(s)	16
6.5.4	Mean power spectral density measurements.....	17
6.5.5	Peak power measurements.....	17
6.5.6	Exterior limit measurement.....	17
6.5.7	Total Power.....	18
6.5.8	Transmitter unwanted emissions.....	18
6.6	Conformance methods of measurement for receiver.....	18
6.6.1	Receiver spurious emissions	18
6.6.2	Receiver interference handling	18
6.7	Conformance test suits for spectrum access	19
6.7.1	Detect and Avoid (DAA).....	19
6.7.2	Listen Before Talk	19
6.7.3	Low Duty Cycle.....	19
6.8	Conformance test suites for antenna requirements	19
6.9	Other test suites	19
6.9.1	Transmit Power control	19
6.9.2	Activity factor	19
6.9.3	Frequency domain mitigation	19
6.9.4	Shielding Effects.....	19
6.9.5	Thermal Radiations.....	19
6.9.6	Installation requirements/site registration	19
6.9.7	Deactivation mechanism.....	19
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	20
Annex B (informative):	Application form for testing.....	21
B.1	Introduction	21

B.2	General Information by ETSI EN 302 066, clause 5.2.1.....	21
B.2.1	Type of Equipment (stand-alone, combined, plug-in radio device, etc.).....	21
B.2.2	The nominal voltages of the stand-alone radio equipment or the nominal voltages of the combined (host) equipment or test jig in case of plug-in devices	21
B.3	Signal related Information by ETSI EN 302 066, clause 4.3	22
B.3.1	Introduction	22
B.3.2	Operational bandwidth(s) of the equipment	22
B.3.3	The worst case mode for each of the following tests.....	22
B.4	RX test Information by ETSI EN 302 066, clause 4.4	22
B.4.1	Introduction	22
B.4.2	Performance criterion and level of performance	22
B.4.3	Interfering signals.....	22
B.5	Additional information provided by the applicant	23
B.5.1	About the DUT	23
B.5.2	Additional items and/or supporting equipment provided	23
Annex C (normative):	Radiated measurements	24
C.1	Test sites and general arrangements for measurements involving the use of radiated fields	24
C.1.0	General	24
C.1.1	Test antenna.....	24
C.1.2	Measuring antenna	25
C.2	Guidance on the use of radiation test sites	25
C.2.0	General	25
C.2.1	Verification of the test site	25
C.2.2	Preparation of the DUT	25
C.2.3	Power supplies to the DUT.....	25
C.2.4	Range length.....	25
C.2.5	Site preparation	26
C.2.6	Conversion of field strength to power limits	26
Annex D (normative):	Deactivation mechanism.....	27
Annex E (informative):	Measurement antenna and preamplifier specifications	28
Annex F (normative):	Calculation of the Mean Power Density.....	29
F.0	General	29
F.1	Measurement of τ , transmit pulse width.....	30
Annex G (informative):	Bibliography.....	32
Annex H (informative):	Change History	33
History		34

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.5] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	23 December 2016
Date of latest announcement of this EN (doa):	31 March 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2017
Date of withdrawal of any conflicting National Standard (dow):	30 September 2018

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies the requirements for Ground- and Wall- Probing Radar imaging systems applications. Ground Probing Radars (GPR) and Wall Probing Radars (WPR) are used in survey and detection applications.

The scope is limited to GPR and WPR radars, in which the system is in close proximity to the materials being investigated. It does not include radars operated from aircraft or spacecraft.

The GPR/WPR applications in the present document are not intended for communications purposes, and the intended signal is not radiated into free space.

NOTE: Equipment covered by the present document is intended to be used by competent professional personnel.

The present document applies to:

- 1) Ground Probing Radars (GPR) operating in the frequency range 30 MHz to 12,4 GHz radiating directly downwards into the ground.
- 2) Wall Probing Radars (WPR) operating in the frequency range 30 MHz to 12,4 GHz radiating directly into a "wall". The "wall" is a building material structure, the side of a bridge, the wall of a mine or another physical structure that absorbs a significant part of the signal transmitted by the radar.

These equipment can either:

- 1) be fitted with integral antennas and without antenna connector; or
- 2) use different imaging heads (antennas) with an antenna connector, to allow operation at different operating bandwidths frequencies.

Equipment covered by the present document operates in accordance with ECC/DEC(06)08 "ECC Decision of 1 December 2006 on the conditions for use of the radio spectrum by Ground- and Wall- Probing Radar (GPR/WPR) imaging systems" [i.2].

These radio equipment types are capable of operating in all or part of the frequency bands given in table 1.

Table 1: Permitted ranges of operation

Permitted range of operation	
Transmit	30 MHz to 12,4 GHz
Receive	30 MHz to 12,4 GHz
NOTE 1: Limits in table 2, clause 4.3.4 are to be met.	
NOTE 2: The frequency usage conditions for GPR/WPR are not fully harmonised in the EU and CEPT. Some National Regulatory Authorities (NRAs) may not have a general frequency allocation for GPR/WPT and may have established individual licensing requirements (e.g. registration of the user). Annex 2 of [i.2] gives some guidance to administrations.	

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 303 883 (V1.1.1) (09-2016): "Short Range Devices (SRD) using Ultra Wide Band (UWB); Measurement Techniques".
- [2] ETSI TS 103 361 (V1.1.1) (03-2016): "Short Range Devices (SRD) using Ultra Wide Band technology (UWB); Receiver technical requirements, parameters and measurement procedures to fulfil the requirements of the Directive 2014/53/EU".
- [3] CISPR 16 (2014) (parts 1-1, 1-4 and 1-5): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1: Radio disturbance and immunity measuring apparatus".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ECC Decision of 1 December 2006 on the conditions for use of the radio spectrum by Ground- and Wall- Probing Radar (GPR/WPR) imaging systems, ECC/DEC/(06)08.
- [i.3] ANSI C63.5-2004: "American National Standard for Electromagnetic Compatibility-Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas (9 kHz to 40 GHz)".
- [i.4] ETSI TR 102 273 (V1.2.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.5] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 303 883 [1] and the following apply:

exterior limits: regulatory limits defined and measured around a specific setup or measurement scenario

Pulse Repetition Frequency (PRF): inverse of the Pulse Repetition Interval (PRI), averaged over a sufficiently long time to cover all PRI variations

radiated measurements: measurements which involve the absolute measurement of a radiated field

user manual: end user documentation to be included with the device

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI EN 303 883 [1] and the following apply:

dB	decibel
dBi	gain in decibels relative to an isotropic antenna
E	Electrical field strength
f_c	Frequency at which the emission is the peak power at maximum
λ	wavelength

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 303 883 [1] and the following apply:

CEPT	European Conference of Postal and Telecommunications Administrations
DT	DwellTime
DUT	Device Under Test
e.r.p.	effective radiated power
GPR	Ground Probing Radar, Ground Penetrating Radar
OATS	Open Area Test Site
PRF	Pulse Repetition Frequency
PRI	Pulse Repetition Interval
RNSS	Radio Navigation Satellite Service
SA	Spectrum Analyser
ST	ScanTime
WPR	Wall Probing Radar

4 Technical requirements specifications

4.1 Environmental conditions

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile. The normal test conditions are defined in clause 5.4.3 of ETSI EN 303 883 [1].

4.2 General

UWB devices in the scope of the present document can operate in a broad permitted range of frequencies from 30 MHz to 12,4 GHz, as defined in table 1.

In order to clearly identify the required limits and thus measurement procedures it is essential to define the operational bandwidth of the UWB equipment under test. The operating bandwidth of the UWB equipment under test shall be the -10 dBc bandwidth of the intended UWB signal under normal operational conditions as defined in clause 4.3.1.

A single UWB device can have more than one operational bandwidth. All UWB related emissions shall be measured in the identified operational bandwidth of the UWB device under test. The required mitigation techniques are only valid in the operational bandwidth.

The RX interference signal handling deals with the performance of the receiver and is focused on interference signals in the operational bandwidth and on some clearly identified frequencies outside the operational bandwidth(s), see clause 4.4.3.

4.3 Transmitter Conformance Requirements

4.3.1 Operating Bandwidth

4.3.1.1 Applicability

This requirement shall apply to all DUT.

4.3.1.2 Description

The operating bandwidth(s) of GPR/WPR is/are the -10 dBc bandwidth(s) of effective emissions radiated into the air by the equipment.

4.3.1.3 Limits

Any operating bandwidth of all the DUT shall lie within the permitted frequency range of operation of the device (see table 1) and shall be > 50 MHz.

4.3.1.4 Conformance

The conformance test suite for operating bandwidth shall be as defined in clause 6.5.3 of the present document.

Conformance shall be established under normal test conditions (see clause 4.1).

The interpretation of the results for the measurements uncertainty shall be as given in clause 5.3.

4.3.2 Maximum value of mean power spectral density

Intentional emissions can't be tested due to the nature of the GPR/WPR applications and thus only unintentional emissions into the air will be tested (see clause 4.3.4 on exterior limit).

4.3.3 Maximum value of peak power

Intentional emissions cannot be tested due to the nature of the GPR/WPR applications and thus only unintentional emissions into the air will be tested (see clause 4.3.4 on exterior limit).

4.3.4 Exterior Limits

4.3.4.1 Applicability

This requirement shall apply to all DUT.

4.3.4.2 Description

The emissions into the air resulting from the operation of GPR/WPR imaging systems are defined as those emissions radiated in all directions above the ground from the GPR/WPR equipment, including direct emissions from the housing/structure of the equipment and emissions reflected or passing through the media under inspection; they are therefore dependent on the operational conditions and are meaningful only if the GPR/WPR are coupled with the material being investigated.

4.3.4.3 Limits

The effective radiated power of any emission from GPR/WPR shall not exceed the values given in table 2.

Table 2: Power limits of radiated emissions [i.2]

Frequency range (MHz)	Peak power limit values for emission
30 to 230	-44,5 dBm/120 kHz (e.r.p)
> 230 to 1 000	-37,5 dBm/120 kHz (e.r.p)
> 1 000 to 18 000	-30 dBm/MHz (e.i.r.p.)

The maximum mean e.i.r.p. spectral density shall not exceed the values in table F.1 ([i.2]) and shall be calculated as set out in annex F.

4.3.4.4 Conformance

The conformance test suite for Exterior Limit shall be as defined in clause 6.5.6.

The maximum mean e.i.r.p. spectral density which is based on the peak values measured according to clause 6.5.6 shall be calculated as set out in annex F and shall not exceed the values in table F.1 ([i.2]).

Conformance shall be established under normal test conditions (see clause 4.1).

The interpretation of the results for the measurements uncertainty shall be as given in clause 5.3.

4.3.5 Total Power

This requirement does not apply to any DUT.

4.3.6 Other Emissions

This requirement does not apply to any DUT.

4.3.7 Transmitter unwanted emissions

This requirement does not apply to any DUT.

4.4 Receiver Conformance Requirements

4.4.1 General

Detailed description for related UWB receiver requirements, see ETSI TS 103 361 [2].

4.4.2 Receiver spurious emissions

Receiver spurious emissions are measured as part of the emissions resulting from the operation of GPR/WPR imaging systems, see clause 4.3.4.

4.4.3 Receiver interference handling

4.4.3.1 Applicability

This requirement shall apply to all DUT.

4.4.3.2 Description

Interferer signal handling, defined as the capability of the device to operate as intended in coexistence with interferers, is the receiver parameter for UWB applications.