



SLOVENSKI STANDARD

SIST EN 302 454-1 V1.2.1:2016

01-februar-2016

Meteorološki pripomočki (Met Aids) - Radiosonde za uporabo v frekvenčnem območju od 1668,4 MHz do 1690 MHz - 1. del: Tehnične karakteristike in preskusne metode

Meteorological Aids (Met Aids); Radiosondes to be used in the 1 668,4 MHz to 1 690 MHz frequency range; Part 1: Technical characteristics and test methods

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 454-1 V1.2.1:2016](https://standards.iteh.ai/catalog/standards/sist/6693f2e8-9bd6-4310-af70-1859d514182c/sist-en-302-454-1-v1-2-1-2016)

Ta slovenski standard je istoveten z: **EN 302 454-1 V1.2.1**

ICS:

07.060	Geologija. Meteorologija. Hidrologija	Geology. Meteorology. Hydrology
33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications

SIST EN 302 454-1 V1.2.1:2016

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 454-1 V1.2.1:2016

<https://standards.iteh.ai/catalog/standards/sist/6693f2e8-9bd6-4310-af70-1859d5f4182c/sist-en-302-454-1-v1-2-1-2016>

ETSI EN 302 454-1 V1.2.1 (2015-10)



**Meteorological Aids (Met Aids);
Radiosondes to be used in the
1 668,4 MHz to 1 690 MHz frequency range;
Part 1: Technical characteristics and test methods**

<https://standards.iteh.ai/catalog/standards/sist/6693f2e8-9bd6-4310-af70-1859d5f4182c/sist-en-302-454-1-v1-2-1-2016>

Reference

REN/ERM-JTFEA-23

Keywords

radio, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 454-1 V1.2.1:2016

<https://standards.iteh.ai/catalog/standards/sist/6693f2e8-9bd6-4310-af70-1859d5f18241/etsi-en-302-454-1-v1-2-1-2016>

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	7
3.1 Definitions	7
3.2 Symbols.....	8
3.3 Abbreviations	8
4 Technical requirement specifications.....	8
4.1 Presentation of equipment for testing purposes.....	8
4.1.1 General Considerations.....	8
4.1.2 Choice of model for testing	8
4.1.3 Testing of equipment with alternative power levels	9
4.1.4 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment).....	9
4.1.4.1 Equipment with an internal permanent or temporary antenna connector.....	9
4.1.4.2 Equipment with an internal permanent antenna.....	9
4.2 Mechanical and electrical design.....	9
4.2.1 Marking (equipment identification).....	9
4.2.1.1 Equipment identification.....	9
4.2.1.2 Marking.....	9
4.2.2 Auxiliary test equipment.....	9
5 Test conditions, power sources and ambient temperatures	9
5.1 Normal and extreme test conditions	9
5.2 Test power source.....	10
5.2.1 External test power source.....	10
5.2.2 Internal test power source	10
5.3 Normal test conditions.....	10
5.3.1 Normal temperature and humidity	10
5.3.2 Normal test power source	10
5.4 Extreme test conditions	10
5.4.1 General.....	10
5.4.2 Procedure for tests at extreme conditions	11
5.4.3 Special Radiosondes	11
5.4.4 Extreme test source voltages.....	11
5.4.4.1 Power sources using batteries	11
5.4.4.2 Other power sources.....	11
6 General conditions.....	12
6.1 Test signals and modulation	12
6.2 Artificial antenna.....	12
6.3 Test fixture	12
6.4 Test sites and general arrangements for radiated measurements	12
6.5 Modes of operation of the transmitter	12
6.6 Measuring receiver	13
7 Methods of measurement and limits for transmitter parameters	13
7.1 General	13
7.2 Frequency error	13
7.2.1 Definitions	13

7.2.2	Method of measurement	13
7.2.3	Limit	13
7.3	Carrier power (conducted).....	13
7.3.1	Definition.....	13
7.3.2	Method of measurement	14
7.3.3	Limits.....	14
7.4	Effective radiated power	14
7.4.1	Definition.....	14
7.4.2	Methods of measurement.....	14
7.4.3	Limit	15
7.5	Modulation bandwidth	15
7.5.1	Definition.....	15
7.5.2	Method of measurement	15
7.5.3	Limits.....	16
7.6	Spurious emissions	16
7.6.1	Definition.....	16
7.6.2	Methods of measurement.....	16
7.6.2.1	Method of measuring the power level in a specified load, clause 7.6.2 a) i).....	16
7.6.2.2	Method of measuring the effective radiated power, clause 7.6.2 a) ii)	17
7.6.2.3	Method of measuring the effective radiated power, clause 7.6.2 b).....	17
7.6.3	Limits.....	18
7.7	Frequency stability under low voltage conditions	18
7.7.1	Definition.....	18
7.7.2	Method of measurement	18
7.7.3	Limits.....	18
History	19

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 454-1 V1.2.1:2016](https://standards.iteh.ai/catalog/standards/sist/6693f2e8-9bd6-4310-af70-1859d5f4182c/sist-en-302-454-1-v1-2-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/6693f2e8-9bd6-4310-af70-1859d5f4182c/sist-en-302-454-1-v1-2-1-2016>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

For non-EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document is part 1 of a multi-part deliverable covering digitally modulated Radiosonde transmitters in the Meteorological Aids frequency band from 1 668,4 MHz to 1 690 MHz, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".

iTeh STANDARD PREVIEW

(standards.itih.ai)

Date of adoption of this EN:	22 October 2015
Date of latest announcement of this EN (doa):	31 January 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2016
Date of withdrawal of any conflicting National Standard (dow):	31 July 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

Meteorological aids, Radiosondes, are light weight, disposable precision measurement instruments mainly used for *in situ* upper air measurements of meteorological variables (pressure, temperature, relative humidity, wind speed and direction) in the atmosphere up to an altitude of 36 km. The measurements are vital to international weather forecasting capability (and hence severe weather warning services for the public involving protection of life and property). The Radiosonde systems provide simultaneous measurements of the vertical profile of temperature, relative humidity as well as wind speed and direction. The variation of these meteorological variables in the vertical contains the majority of the critical information for weather forecasting. These systems are the only meteorological observing systems able to regularly provide the vertical resolution that meteorologists need for all five variables.

Typically the Radiosonde observations are produced by Radiosondes measuring atmosphere for approximately 2 hours and carried by ascending balloons launched from land stations or ships. Radiosonde observations are carried out routinely by almost all countries, two to four times a day. The observation data is then circulated immediately to all other countries within a few hours via the WMO (World Meteorological Organization) Global Telecommunications System (GTS). The observing systems and data dissemination are all organized under the framework of the World Weather Watch Programme of WMO.

The observation stations are required, worldwide, at a horizontal spacing of less than or equal to 250 km, during the first decade of the twenty-first century, with a frequency of observation of from one to four times per day.

Remotely sensed measurements from satellites do not have the vertical resolution available from Radiosondes. Successful derivation of vertical temperature structure from these satellite measurements usually requires a computation initialized either directly from Radiosonde statistics or from the numerical weather forecast itself. In the latter case, the Radiosonde measurements ensure that the vertical structure in these forecasts remains accurate and stable with time. In addition, the Radiosonde measurements are used to calibrate satellite observations by a variety of techniques.

Radiosonde observations are thus seen to remain absolutely necessary for meteorological operations for the foreseeable future.

Other applications, independent of the main civilian meteorological organizations include environmental pollution, hydrology, radioactivity in the free atmosphere, significant weather phenomena (e.g. winter storms, thunderstorms, etc.) and investigation of a range of physical and chemical properties of the atmosphere.

About 150 000 Radiosondes are annually used in Europe, about 10 % of them are in 1 680 MHz band. This use is not decreasing with time, since with modern automation it is now much easier to successfully operate systems without highly skilled operators and a large amount of supporting equipment.

The Radiosondes use unidirectional transmission on two frequency bands: 403 MHz band covers primary and co-primary allocations from 400,15 MHz to 406 MHz and 1 680 MHz band from 1 668,4 MHz to 1 690 MHz. The 403 MHz Radiosonde technology applies GNSS (Global Navigation Satellite Systems) for wind measurement, whereas the 1 680 MHz systems may base the wind measurement on balloon tracking with a Radio Direction Finding antenna. Because the 403 MHz wind measurement depends on the availability of the GNSS signals, many operators do not consider this technology secure enough for critical applications (e.g. defence and national security), and consequently prefer 1 680 MHz systems.

According to Recommendation ITU-R SA.1745 [i.1] the Mobile Satellite Service (MSS) is allocated in the band from 1 670 MHz to 1 675 MHz, and the sub band from 1 683 MHz to 1 690 MHz is used for meteorological satellite. Thus all administrations should strive to implement MetAids systems that limit their operations to the band 1 675 - 1 683 MHz for Radiosondes.

National regulatory conditions may apply regarding the, channel/frequency separations, and the inclusion of an automatic transmitter shut-off feature as a condition of an individual or general license, or, as a condition of use under license exemption. The automatic transmitter shut-off facility of the Radiosonde may be based on elapsed time from the beginning of the sounding, or atmospheric pressure or height measured by the Radiosonde.

1 Scope

The present document defines the technical requirements for transmitters used in Radiosondes operating in the range from 1 668,4 MHz to 1 690 MHz.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CISPR 16-1-1: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [2] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [3] ETSI EN 300 440-1 (V1.6.1) (08-2010): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short range devices; Radio equipment to be used in the 1 GHz to 40 GHz frequency range; Part 1: Technical characteristics and test methods".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Recommendation ITU-R SA.1745: "Use of the band 1 668.4-1 710 MHz by the meteorological aids service and meteorological-satellite service (space-to-Earth)".
-

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

conducted measurements: measurements, which are made using a direct 50 Ω connection to the EUT

dedicated antenna: removable antenna supplied and tested with the radio equipment, designed as an indispensable part of the EUT

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

radiated measurements: measurements, which involve the absolute measurement of a radiated field

telemetry: use of radio communication for recording measurement or other data at a distance

3.2 Symbols

For the purposes of the present document, the following symbols apply:

dB	decibel
E	field strength
°C	Temperature in degrees Celsius
hPa	Atmospheric pressure in hecto Pascal
%RH	Air Relative Humidity in percentage
λ	Wavelength

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CISPR	International Special Committee on Radio Interference
EU	European Union
EUT	Equipment Under Test
FAR	Fully Anechoic Room
GNSS	Global Navigation Satellite Systems
GTS	Global Telecommunications System
ICAO	International Civil Aviation Organization
ITU-R	International Telecommunication Union - Radiocommunication Sector
MSS	Mobile Satellite Service
RF	Radio Frequency
RH	Relative Humidity
VSWR	Voltage Standing Wave Ratio
WMO	World Meteorological Organization

4 Technical requirement specifications

4.1 Presentation of equipment for testing purposes

4.1.1 General Considerations

Each equipment submitted for testing, where applicable, shall fulfil the requirements of the present document on all frequencies over which it is intended to operate.

Testing shall be carried out on the highest and lowest frequencies within the equipment's intended operating range.

If equipment is designed to operate with different carrier powers, measurement of each transmitter parameter shall be performed at the highest power level at which the transmitter is intended to operate.

To simplify and harmonize the testing procedures between the different testing laboratories, measurements shall be performed, according to the present document.

4.1.2 Choice of model for testing

The manufacturer shall provide one or more samples of the equipment, as appropriate, for testing.

If equipment has several optional features, considered not to affect the RF parameters then tests need only be performed on the equipment configured with that combination of features considered being the most complex, as proposed by the manufacturer and agreed by the test laboratory.

Where practicable, equipment offered for testing shall provide a 50 Ω connector for conducted RF power measurements.

In the case of integral antenna equipment, if the equipment does not have an internal permanent 50 Ω connector then it is permissible to supply a second sample of the equipment with a temporary 50 Ω antenna connector fitted to facilitate testing.

4.1.3 Testing of equipment with alternative power levels

If a family of equipment has alternative output power levels provided by the use of separate power modules or add on stages, then each module or add on stage shall be tested in combination with the equipment. The necessary samples and tests shall be proposed by the manufacturer and/or test laboratory, based on the requirements of clause 4.1.

4.1.4 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)

4.1.4.1 Equipment with an internal permanent or temporary antenna connector

The means to access and/or implement the internal permanent or temporary antenna connector shall be stated by the manufacturer and the access method shall be recorded in the test report.

No connection shall be made to any internal permanent or temporary antenna connector during the performance of radiated emissions measurements.

4.1.4.2 Equipment with an internal permanent antenna

Manufacturer shall state and describe the method to connect test equipment to antenna port and this method shall be recorded in the test report.

4.2 Mechanical and electrical design

4.2.1 Marking (equipment identification)

4.2.1.1 Equipment identification

The marking shall include as a minimum:

- the name of the manufacturer or his trademark;
- the type designation.

4.2.1.2 Marking

The equipment shall be marked in a visible place, unless the equipment is too small to carry the marking. This marking shall be legible and durable. Relevant information shall be provided in the user manual.

4.2.2 Auxiliary test equipment

All necessary auxiliary test equipment and set-up information shall accompany the EUT, when it is submitted for testing.

5 Test conditions, power sources and ambient temperatures

5.1 Normal and extreme test conditions

Testing shall be performed under normal test conditions, and also, where stated, under extreme test conditions.

The test conditions and procedures shall be as specified in clauses 5.2 to 5.4.