

SLOVENSKI STANDARD
oSIST prEN 305 550 V2.1.0:2017
01-december-2017

Naprave kratkega dosega (SRD) - Radijska oprema, ki se uporablja v frekvenčnem območju od 40 GHz do 246 GHz - Harmonizirani standard za dostop do radijskega spektra

Short Range Devices (SRD) - Radio equipment to be used in the 40 GHz to 246 GHz frequency range - Harmonised Standard for access to radio spectrum

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 305 550 V2.1.0:2017](#)

Ta slovenski standard je istoveten z: [ETSI EN 305 550 V2.1.0 \(2017-10\)](https://standards.iteh.ai/catalog/standards/sist/5b7a0c0e-7b27-4794-8009-a5503a5a74ba/osist-pren-305-550-v2.1.0-2017)

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

oSIST prEN 305 550 V2.1.0:2017 [en](#)

iTeh STANDARD PREVIEW (standards.iteh.ai)

oSIST prEN 305 550 V2.1.0:2017

<https://standards.iteh.ai/catalog/standards/sist/5b7a0c0e-7b27-4794-8009-a3503a5a74ba/osist-pren-305-550-v2-1-0-2017>

Draft ETSI EN 305 550 V2.1.0 (2017-10)



**Short Range Devices (SRD);
Radio equipment to be used
in the 40 GHz to 246 GHz frequency range;
Harmonised Standard for access to radio spectrum**

oSIST prEN 305 550 V2.1.0:2017
<https://standards.iteh.ai/catalog/standards/sist/5b7a0c0e-7b27-4794-8009-a3503a5a74ba/osist-pr-en-305-550-v2-1-0-2017>

Reference

REN/ERM-TG28-509

Keywords

harmonised standard, radio, SRD, testing, UWB

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

Important noticeoSIST prEN 305 550 V2.1.0:2017

<https://standards.iteh.ai/catalog/standards/sist/5b7a0c0e-7b27-4794-8009-a3503a224ba/0sist-pr-en-305-550-v2-1-10-2017>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Technical requirements specifications	11
4.1 Environmental conditions.....	11
4.2 General	11
4.2.1 Background information	11
4.2.2 Wanted performance criteria.....	11
4.3 Transmitter Conformance Requirements.....	12
4.3.1 Permitted range of operating frequencies	12
4.3.1.1 Applicability.....	12
4.3.1.2 Description.....	12
4.3.1.3 Limits	12
4.3.1.4 Conformance.....	12
4.3.2 Operating frequency range(s) (OFR)	12
4.3.2.1 Applicability.....	12
4.3.2.2 Description.....	12
4.3.2.3 Limits	13
4.3.2.4 Conformance.....	13
4.3.3 Mean Power	13
4.3.3.1 Applicability.....	13
4.3.3.2 Description	14
4.3.3.3 Limits	14
4.3.3.4 Conformance	14
4.3.4 Mean Power spectral density	14
4.3.4.1 Applicability.....	14
4.3.4.2 Description	14
4.3.4.3 Limits	14
4.3.4.4 Conformance	15
4.3.5 Unwanted emissions in the out-of-band domain.....	15
4.3.5.1 Applicability.....	15
4.3.5.2 Description	15
4.3.5.3 Limits	15
4.3.5.4 Conformance	16
4.3.6 Unwanted emissions in the spurious domain	16
4.3.6.1 Applicability.....	16
4.3.6.2 Description	16
4.3.6.3 Limits	16
4.3.6.4 Conformance	17
4.4 Receiver Conformance Requirements	17
4.4.1 General.....	17
4.4.2 Receiver spurious emissions	17
4.4.2.1 Applicability.....	17
4.4.2.2 Description	17
4.4.2.3 Limits	17
4.4.2.4 Conformance	18

4.4.3	Receiver interference signal handling.....	18
4.4.3.1	Applicability.....	18
4.4.3.2	Description.....	18
4.4.3.3	Limits.....	18
4.4.3.4	Conformance.....	19
5	Testing for compliance with technical requirements.....	19
5.1	Environmental conditions for testing	19
5.2	General conditions for testing	19
5.2.1	Product information	19
5.2.2	Requirements for the test modulation	20
5.2.2.1	Normal test signals and test modulation.....	20
5.2.2.2	Normal test signals for data.....	20
5.2.2.3	Testing of frequency agile or hopping equipment.....	20
5.2.3	Test conditions, power supply and ambient temperatures	20
5.2.4	Choice of equipment for test suites.....	20
5.2.5	Multiple Operating bandwidths and multiband equipment.....	21
5.2.6	Testing of host connected equipment and plug-in radio devices	21
5.2.6.1	General.....	21
5.2.6.2	The use of a host or test fixture for testing plug-In radio devices	21
5.3	Mechanical and electrical design.....	21
5.3.1	General.....	21
5.3.2	Controls	21
5.3.3	Transmitter shut-off facility	21
5.3.4	Receiver automatic switch-off	21
5.4	Auxiliary test equipment	22
5.5	Reference bandwidth of the measuring receiver	22
5.6	General requirements for RF cables.....	23
5.7	RF waveguides	23
5.8	External harmonic mixers	24
5.8.1	Introduction.....	24
5.8.2	Signal identification.....	25
5.8.3	Measurement hints.....	25
5.9	Interpretation of the measurement results a3505a5a740a/oSIST-prEN-305-550-v2.1-0-2017	26
5.9.0	General.....	26
5.9.1	For measurement above 110 GHz.....	26
5.9.2	Conversion loss data and measurement uncertainty	27
5.9.3	Measurement uncertainty is equal to or less than maximum acceptable uncertainty.....	27
5.9.4	Measurement uncertainty is greater than maximum acceptable uncertainty.....	27
6	Conformance test suits	28
6.1	Introduction	28
6.2	Initial Measurement steps.....	28
6.3	Radiated measurements	28
6.3.1	General.....	28
6.3.2	Test sites and general arrangements for measurements involving the use of radiated fields	28
6.3.3	Guidance on the use of a radiation test site.....	28
6.3.3.1	General	28
6.3.3.2	Minimum requirements for test sites for measurements above 18 GHz	28
6.3.3.3	Range length	29
6.3.4	Standard test and calibration methods	30
6.4	Test fixture	30
6.4.1	Requirements	30
6.4.2	Calibration	30
6.5	Conformance methods of measurement for transmitter	31
6.5.1	General.....	31
6.5.2	Operating frequency range(s) (OFR)	31
6.5.3	Mean Power	31
6.5.4	Mean power spectral density measurements	31
6.5.5	Transmitter unwanted emissions.....	32
6.6	Conformance methods of measurement for receiver	32
6.6.1	Receiver spurious emissions	32

6.6.2	Receiver interference signal handling.....	32
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU.....	33
Annex B (informative):	Measurement antenna, preamplifier, and cable specifications.....	34
Annex C (informative):	Atmospheric absorptions and material dependent attenuations	35
C.0	General	35
C.1	Atmospheric absorptions.....	35
C.2	Material dependent attenuations.....	37
Annex D (informative):	Bibliography.....	39
Annex E (informative):	Change history	40
History		41

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 305 550 V2.1.0:2017](#)
<https://standards.iteh.ai/catalog/standards/sist/5b7a0c0e-7b27-4794-8009-a3503a5a74ba/osist-pr-en-305-550-v2-1-0-2017>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.10] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.9].

<https://standards.iteh.ai/a3503a5a74ba/osit-pren-305-550-v2-1-0-2017>

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is covering Short Range Devices (SRD) Radio equipment to be used in the 40 GHz to 246 GHz frequency range.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies technical characteristics and methods of measurements for Non-specific Short Range Devices category equipment types.

Non specific SRDs category is defined by the EU Commission Decision 2013/752/EU [i.2] as:

- "The non-specific short-range device category covers all kinds of radio devices, regardless of the application or the purpose, which fulfil the technical conditions as specified for a given frequency band. Typical uses include telemetry, telecommand, alarms, data transmissions in general and other applications".

The present document covers equipment:

- capable of operating in frequency bands listed in table 1;
- intended for fixed, mobile or nomadic use;
- either with a Radio Frequency (RF) output connection and dedicated antenna or with an integral antenna;
- with all types of modulation.

Table 1: Short Range Devices within the 40 GHz to 246 GHz frequency range

Frequency Bands (Transmit and Receive)	Applications
57 GHz to 64 GHz	Non-specific SRD
61,0 GHz to 61,5 GHz	Non-specific SRD
122 GHz to 123 GHz	Non-specific SRD
244 GHz to 246 GHz	Non-specific SRD

(standards.iteh.ai)

NOTE 1: The frequency usage conditions for Non-specific SRDs are EU wide harmonised bands according to EC Decision 2013/752/EU [i.2] as known at the date of publication of the present document. In addition, it should be noted that other frequency bands may be available for short range devices in a country within the frequency range 40 GHz to 246 GHz covered by the present document. See the CEPT/ERC Recommendation 70-03 [i.1] or as implemented through National Radio Interfaces (NRI) and additional

NOTE 2: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.9] is given in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CISPR 16-1-1:2015: "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [2] Recommendation ITU-T O.153 (1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".

- [3] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [4] ETSI EN 303 396 (V1.1.1) (12-2016): "Short Range Devices; Measurement Techniques for Automotive and Surveillance Radar Equipment".
- [5] ETSI TS 103 361 (V1.1.1) (03-2016): "Short Range Devices (SRD) using Ultra Wide Band technology (UWB); Receiver technical requirements, parameters and measurement procedures to fulfil the requirements of the Directive 2014/53/EU".
- [6] Recommendation ITU T O.41 (1994): "Psophometer for use on telephone-type circuits".
- [7] CISPR 16-1-4:2010: "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".
- [8] CISPR 16-1-5:2014: "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1-5: Radio disturbance and immunity measuring apparatus - Antenna calibration sites and reference test sites for 5 MHz to 18 GHz".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT/ERC Recommendation 70-03: "Relating to the use of Short Range Devices (SRD)".
<https://standards.iteh.ai/catalog/standards/sist/5b7a0c0e-7b27-4794-8009>
- [i.2] European Commission Decision 2013/752/EU of 11 December 2013 (amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices and repealing Decision 2005/928/EC).
- [i.3] CEPT/ERC Recommendation 74-01: "Unwanted emissions in the spurious domain", Hradec Kralove, Cardiff 2011.
- [i.4] Recommendation ITU-R P.676-5 (2001): "Attenuation by atmospheric gases".
- [i.5] IEC 60153: "Hollow metallic waveguides".
- [i.6] ETSI TR 102 215: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.7] ETSI TR 102 273 (V1.2.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.8] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.9] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.10] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

alarm: use of radio communication for indicating an alarm condition at a distant location

artificial antenna: non-radiating dummy load equal to the nominal impedance specified by the manufacturer

assigned frequency band: frequency band within which the device is authorized to operate and to perform the intended function of the equipment

dedicated antenna: removable antenna supplied and tested with the radio equipment, designed as an indispensable part of the equipment

Direct Sequence Spread Spectrum (DSSS): form of modulation where a combination of data to be transmitted and a fixed code sequence (chip sequence) is used to directly modulate a carrier, e.g. by phase shift keying

NOTE: The code rate determines the occupied bandwidth.

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

fixed station: equipment intended for use in a fixed location

Frequency Hopping Spread Spectrum (FHSS): spread spectrum technique in which the transmitter signal occupies a number of frequencies in time, each for some period of time, referred to as the dwell time

NOTE: Transmitter and receiver follow the same frequency hop pattern. The number of hop positions and the bandwidth per hop position determine the occupied bandwidth.

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

mobile station: equipment normally fixed in a vehicle or used as a transportable station

necessary bandwidth: width of the emitted frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

NOTE: The necessary bandwidth including the frequency tolerances is accommodated within the assigned frequency band.

Occupied Bandwidth (OBW): width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to 0,5 % of the total mean power of a given emission

NOTE: This corresponds to the -23 dBc bandwidth of the signal.

operating frequency: nominal frequency at which equipment is operated; this is also referred to as the operating centre frequency

NOTE: Equipment may be able to operate at more than one operating frequency.

operating frequency range: range of operating frequencies over which the equipment can be adjusted through tuning, switching or reprogramming

portable station: equipment intended to be carried, attached or implanted

Power Spectral Density (PSD): ratio of the amount of power to the used radio measurement bandwidth

NOTE: It is expressed in units of dBm/Hz or as a power in unit dBm with respect to the used bandwidth. In case of measurement with a spectrum analyser the measurement bandwidth is equal to the RBW.

radiated measurements: measurements which involve the absolute measurement of a radiated field

spread spectrum: modulation technique in which the energy of a transmitted signal is spread throughout a large portion of the frequency spectrum

ultra low power equipment: equipment using transmit envelope power below the receiver and idle/standby transmitter limits given in CEPT/ERC Recommendation 74-01 [i.3], see table 8

unwanted emissions: emission on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information

NOTE: Unwanted emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

D _{ant}	Aperture dimension of the radiating antenna
dB	deciBel
dBi	gain in deciBels relative to an isotropic antenna
E	Electrical field strength
E ₀	Reference electrical field strength

NOTE: See annex B.

f	Frequency
P	Power
R	Distance
R ₀	Reference distance

NOTE: See annex B.

iTeh STANDARD PREVIEW (standards.iteh.ai)

t	Time
λ	wavelength

[oSIST prEN 305 550 V2.1.0:2017
https://standards.iteh.ai/catalog/standards/sist/5b7a0c0e-7b27-4794-8009-a3503a5a74ba/osist-pr-en-305-550-v2-1-0-2017](https://standards.iteh.ai/catalog/standards/sist/5b7a0c0e-7b27-4794-8009-a3503a5a74ba/osist-pr-en-305-550-v2-1-0-2017)

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CEPT	European Conference of Postal and Telecommunications administrations
CISPR	Comité International Spécial des Perturbations Radioélectriques
DC	Direct Current
DSSS	Direct Sequence Spread Spectrum
e.i.r.p.	equivalent isotropically radiated power
ECC	Electronic Communications Committee
EESS	Earth Exploration Satellite Service
EIA	Electronic Industries Alliance
EIRP	Equivalent Isotropic Radiated Power
EMC	Electro Magnetic Compatibility
emf	electromagnetic field
ERC	European Radiocommunication Committee
EUT	Equipment Under Test
FAR	Fully Anechoic Rooms
FH	Frequency Hopping
FHSS	Frequency Hopping Spread Spectrum
FMCW	Frequency Modulated Continuous-Wave radar
FSK	Frequency Shift Keying
FSL	Free Space Loss
IF	Intermediate Frequency
ITU-R	International Telecommunications Union, Radio sector
ITU-T	International Telecommunications Union, Telecommunications sector
LNA	Low Noise Amplifier

LO	Local Oscillator
NF	Noise Figure
NRI	National Radio Interfaces
OBW	Occupied BandWidth
OFR	Operating Frequency Range
OOB	Out-of-Band
P _{corr}	Power correcting
PRF	Pulse Repetition Frequency
PSD	Power Spectral Density
R&TTE	Radio and Telecommunications Terminal Equipment
RBW	Resolution BandWidth
RBW _{REF}	measuring receiver resolution bandwidth
RCS	Radar Cross Section
RCSC	Radio Components Standardization Committee
RF	Radio Frequency
RMS	Root Mean Square
RX	Receiver
SMA	SubMiniature version A - connector
SND/ND	Signal + Noise + Distortion / Noise + Distortion
SRD	Short Range Device
TX	Transmitter
UWB	Ultra WideBand
VSWR	Voltage Standing Wave Ratio

4 Technical requirements specifications

The STANDARD PREVIEW

4.1 Environmental conditions

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile. The normal and extreme test conditions are defined in clauses 4.4.3 and 4.4.4 of ETSI EN 303 396 [4].

4.2 General

4.2.1 Background information

In this clause general considerations for the testing of EUT in the frequency range listed in table 1 are given. The tests cover integrated transceivers and separate transmit/receive modules.

All operating bandwidths of the equipment shall be declared by the equipment manufacturer (see clause 4.3.1).

Where equipment has more than one operating bandwidths, sufficient number of operating bandwidths shall be chosen for testing so as to encompass the lower and higher limits of the operating frequency and the minimum and maximum bandwidth.

4.2.2 Wanted performance criteria

For the purpose of the receiver performance tests, the criterion that the EUT shall indicate the properties of a given scenario for which the EUT was foreseen to operate, e.g. target at a given distance or other possible use-cases as described in ETSI TS 103 361 [5]. Since EUT considered here typically are tailored to specific applications, no single wanted performance criterion can be defined here.