



---

Reference

REN/ERM-TG28-507

---

Keywords

harmonised standard, radio, RFID, SRD, testing

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction .....	8
1 Scope .....	10
2 References .....	11
2.1 Normative references .....	11
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations .....	12
3.1 Definitions.....	12
3.2 Symbols.....	13
3.3 Abbreviations .....	13
4 Technical requirements specifications .....	14
4.1 Environmental conditions.....	14
4.2 General .....	14
4.2.1 General performance criteria .....	14
4.2.2 Presentation of equipment for testing purposes .....	14
4.2.2.0 General .....	14
4.2.2.1 Choice of model for testing.....	15
4.2.2.2 Testing of equipment with alternative radiated H-field strengths .....	15
4.2.2.3 Testing of equipment that does not have an external 50 $\Omega$ RF connector (integral antenna equipment) .....	15
4.2.2.3.1 Equipment with an internal permanent or temporary antenna connector .....	15
4.2.2.3.2 Equipment with a temporary antenna connector .....	15
4.2.2.4 On-site testing .....	16
4.2.3 Mechanical and electrical design .....	16
4.2.3.1 General .....	16
4.2.3.2 Controls.....	16
4.2.3.3 Transmitter shut-off facility .....	16
4.2.3.4 Receiver mute or squelch.....	16
4.3 Transmitter conformance requirements.....	16
4.3.1 Permitted range of operating frequencies .....	16
4.3.1.1 Applicability.....	16
4.3.1.2 Description .....	16
4.3.1.3 Limits.....	16
4.3.1.4 Conformance.....	16
4.3.2 Operating frequency ranges .....	16
4.3.2.1 Applicability.....	16
4.3.2.2 Description .....	17
4.3.2.3 Limits.....	17
4.3.2.4 Conformance.....	17
4.3.3 Modulation bandwidth.....	17
4.3.3.1 Applicability.....	17
4.3.3.2 Description .....	17
4.3.3.3 Limits.....	17
4.3.3.4 Conformance.....	17
4.3.4 Transmitter H-field requirements .....	18
4.3.4.1 Applicability.....	18
4.3.4.2 Description .....	18
4.3.4.3 Limits.....	18
4.3.4.4 Conformance.....	19
4.3.5 Transmitter RF carrier current .....	19
4.3.5.1 Applicability.....	19
4.3.5.2 Description.....	19

4.3.5.3	Limits .....	19
4.3.5.4	Conformance .....	20
4.3.6	Transmitter radiated E-field .....	20
4.3.6.1	Applicability .....	20
4.3.6.2	Description .....	20
4.3.6.3	Limits .....	20
4.3.6.4	Conformance .....	20
4.3.7	Transmitter conducted spurious emissions .....	20
4.3.7.1	Applicability .....	20
4.3.7.2	Description .....	20
4.3.7.3	Limits .....	21
4.3.7.4	Conformance .....	21
4.3.8	Transmitter radiated spurious domain emission limits < 30 MHz .....	21
4.3.8.1	Applicability .....	21
4.3.8.2	Description .....	21
4.3.8.3	Limits .....	21
4.3.8.4	Conformance .....	21
4.3.9	Transmitter radiated spurious domain emission limits > 30 MHz .....	21
4.3.9.1	Applicability .....	21
4.3.9.2	Description .....	22
4.3.9.3	Limits .....	22
4.3.9.4	Conformance .....	22
4.3.10	Transmitter Frequency stability .....	22
4.3.10.1	Applicability .....	22
4.3.10.2	Description .....	22
4.3.10.3	Limits .....	22
4.3.10.4	Conformance .....	22
4.4	Receiver Conformance requirements .....	23
4.4.1	General .....	23
4.4.2	Receiver spurious emissions .....	23
4.4.2.1	Applicability .....	23
4.4.2.2	Description .....	23
4.4.2.3	Limits .....	23
4.4.2.4	Conformance .....	23
4.4.3	Adjacent channel selectivity .....	24
4.4.3.1	Applicability .....	24
4.4.3.2	Description .....	24
4.4.3.3	Limits .....	24
4.4.3.4	Conformance .....	24
4.4.4	Receiver blocking or desensitization .....	24
4.4.4.1	Applicability .....	24
4.4.4.2	Description .....	24
4.4.4.3	Limits .....	25
4.4.4.4	Conformance .....	25
5	Testing for compliance with technical requirements .....	25
5.1	Environmental conditions for testing .....	25
5.2	General conditions for testing .....	25
5.2.1	Product information .....	25
5.3	Normal and extreme test conditions .....	25
5.4	Test power source .....	26
5.4.0	General .....	26
5.4.1	External test power source .....	26
5.4.2	Internal test power source .....	26
5.5	Normal test conditions .....	26
5.5.1	Normal temperature and humidity .....	26
5.5.2	Normal test power source .....	26
5.5.2.1	Mains voltage .....	26
5.5.2.2	Regulated lead-acid battery power sources .....	27
5.5.2.3	Other power sources .....	27
5.6	Extreme test conditions .....	27
5.6.1	Extreme temperatures .....	27

5.6.1.1	Procedure for tests at extreme temperatures.....	27
5.6.1.1.0	General .....	27
5.6.1.1.1	Procedure for equipment designed for continuous operation .....	27
5.6.1.1.2	Procedure for equipment designed for intermittent operation .....	27
5.6.1.2	Extreme temperature ranges.....	28
5.6.2	Extreme test source voltages.....	28
5.6.2.1	Mains voltage .....	28
5.6.2.2	Regulated lead-acid battery power sources .....	28
5.6.2.3	Power sources using other types of batteries.....	28
5.6.2.4	Other power sources.....	28
5.7	Auxiliary test equipment .....	29
5.8	Normal test signals and test modulation.....	29
5.8.0	General.....	29
5.8.1	Normal test signals for analogue speech.....	29
5.8.2	Normal test signals for data .....	29
5.9	Artificial antenna.....	29
5.9.0	General.....	29
5.9.1	Artificial antenna for inductive transmitters (non 50 $\Omega$ ).....	29
5.9.2	Artificial antenna for transmitters with 50 $\Omega$ impedance connector.....	30
5.10	Test fixture .....	30
5.11	Test sites and general arrangements for radiated measurements .....	31
5.12	Measuring receiver .....	31
5.13	Measurement uncertainty .....	31
5.14	Interpretation of the measurement results .....	32
5.14.0	General.....	32
5.14.1	Measurement uncertainty is equal to or less than maximum acceptable uncertainty.....	32
6	Conformance methods of measurement for transmitters and receivers .....	32
6.1	Transmitter requirements .....	32
6.1.1	Transmitter definitions.....	32
6.1.2	Equipment Product Classes .....	33
6.1.3	Modes of operation of the transmitter.....	33
6.2	Conformance methods of measurement for transmitter .....	33
6.2.1	General.....	33
6.2.2	Operating frequency ranges .....	33
6.2.2.1	General .....	33
6.2.2.2	OFR measurement with spectrum analyser.....	34
6.2.3	Modulation bandwidth.....	34
6.2.4	Transmitter H-field .....	35
6.2.5	Transmitter RF carrier current.....	35
6.2.6	Transmitter radiated E-field.....	35
6.2.7	Transmitter conducted spurious emissions .....	35
6.2.7.1	Transmitter conducted spurious emissions < 30 MHz .....	35
6.2.7.2	Transmitter conducted spurious emissions $\geq$ 30 MHz .....	36
6.2.8	Transmitter radiated spurious domain emission limits < 30 MHz .....	36
6.2.9	Transmitter radiated spurious domain emission limits > 30 MHz .....	36
6.2.10	Transmitter Frequency stability under low voltage conditions.....	37
6.2.10.1	Test conditions .....	37
6.3	Conformance methods of measurement for receiver.....	37
6.3.1	Receiver spurious emissions .....	37
6.3.2	Adjacent channel selectivity .....	38
6.3.3	Receiver blocking or desensitization .....	38
6.3.3.1	Measurement for channelized, narrowband or broadband equipment.....	38
6.3.3.2	Measurement for tagging systems.....	39
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>40</b>
<b>Annex B (normative):</b>	<b>Transmitter definitions.....</b>	<b>42</b>
B.1	Transmitter definitions .....	42
B.1.0	General .....	42

B.1.1	The inductive loop coil transmitters .....	42
B.1.2	The large size loop transmitters .....	42
B.1.3	Other transmitters .....	42
B.2	Product Classes .....	42
B.2.0	General .....	42
B.2.1	Product Class 1 .....	43
B.2.2	Product Class 2 .....	43
B.2.3	Product Class 3 .....	43
B.2.4	Product Class 4 .....	44
<b>Annex C (normative): Radiated measurement.....</b>		<b>46</b>
C.0	General .....	46
C.1	Test sites and general arrangements for measurements involving the use of radiated fields .....	46
C.1.0	Test sites .....	46
C.1.1	Anechoic chamber .....	46
C.1.2	Anechoic chamber with a conductive ground plane .....	47
C.1.3	Open Area Test Site (OATS) .....	49
C.1.3.0	General for OATS .....	49
C.1.3.1	Measurements below 30 MHz .....	49
C.1.3.2	Measurements above 30 MHz .....	49
C.1.4	Test antenna .....	50
C.1.5	Substitution antenna .....	51
C.1.6	Measuring antenna .....	51
C.2	Guidance on the use of radiation test sites .....	51
C.2.0	General .....	51
C.2.1	Verification of the test site .....	51
C.2.2	Preparation of the EUT .....	51
C.2.3	Power supplies to the EUT .....	52
C.2.4	Range length .....	52
C.2.4.1	Far-field length above 30 MHz .....	52
C.2.4.2	Near-field and Far-field length below 30 MHz .....	52
C.2.5	Site preparation .....	53
C.3	Coupling of signals .....	53
C.3.1	General .....	53
C.3.2	Data signals .....	53
C.4	Standard test position .....	54
C.5	Test fixture .....	54
C.5.0	Usage Test fixture .....	54
C.5.1	Description .....	54
C.5.2	Calibration .....	55
C.5.3	Mode of use .....	56
C.6	Technical performance of the spectrum analyser .....	56
<b>Annex D (normative): H-field limit correction factor for generated E-fields.....</b>		<b>57</b>
<b>Annex E (normative): Customized loop antennas.....</b>		<b>58</b>
E.1	Product classes related to the antenna loop .....	58
E.2	Antenna loops below 1 MHz .....	58
E.3	Antenna loops above 1 MHz .....	59
<b>Annex F (informative): Artificial antenna for measuring inductive transmitter carrier and harmonic currents (Product Class 3 only).....</b>		<b>60</b>
<b>Annex G (informative): E-fields in the near field at low frequencies.....</b>		<b>62</b>

<b>Annex H (normative):</b>	<b>H-field measurements and limits at 3 m and 30 m .....</b>	<b>64</b>
H.0	General .....	64
H.1	Limits for measurements at 30 m distance .....	64
H.2	Limits for measurements at 3 m distance .....	65
<b>Annex I (normative):</b>	<b>Transmitter emission levels and spectrum mask measurements.....</b>	<b>67</b>
<b>Annex J (normative):</b>	<b>Generic inductive loop limits in the frequency range 148,5 kHz to 30 MHz .....</b>	<b>70</b>
J.1	Introduction .....	70
J.2	Radiated H-field strength .....	70
J.2.1	Methods of measurements .....	70
J.2.2	Radiated H-field strength limit .....	70
J.2.2.1	Radiated total H-field and H-field density limits according to the measurements in clause J.2.1 indent a) .....	70
J.2.2.2	Radiated bandwidth and H-field density limits according to the measurements in clause J.2.1 indent b) .....	71
<b>Annex K (informative):</b>	<b>Determination and use of the measurement bandwidth.....</b>	<b>72</b>
<b>Annex L (informative):</b>	<b>Bibliography .....</b>	<b>73</b>
<b>Annex M (informative):</b>	<b>Change History .....</b>	<b>76</b>
History .....		77

**iTeh STANDARD PREVIEW**  
 (standards.iteh.ai)  
 Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/c7651b9a-f78e-4089-925b-67701bd00d53/etsi-en-300-330-v2.1.1-2017-02>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This final draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.11] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.4].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document has been prepared to conform to the requirements of the new Radio Equipment Directive (RED) [i.4].

The present document is structured as follows:

- Clause 2 provides references.
- Clause 3 provides definitions, symbols and abbreviations.



- Clause 4 provides technical requirements specifications.
- Clause 5 provides the testing procedures for compliance with technical requirements.
- Clause 6 provides conformance methods of measurement for transmitters and receivers.
- Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU.
- Annex B (normative): Transmitter definitions.
- Annex C (normative): Radiated measurement.
- Annex D (normative): H-field limit correction factor for generated E-fields.
- Annex E (normative): Customized loop antennas.
- Annex F (informative): Artificial antenna for measuring inductive transmitter carrier and harmonic currents (Product Class 3 only).
- Annex G (informative): E-fields in the near field at low frequencies.
- Annex H (normative): H-field measurements and limits at 3 m and 30 m.
- Annex I (normative): Transmitter emission levels and spectrum mask measurements.
- Annex J (normative): Generic inductive loop limits in the frequency range 148,5 kHz to 30 MHz.
- Annex K (informative): Determination and use of the measurement bandwidth.
- Annex L (informative): Bibliography.
- Annex M (informative): Change History.

**PRE-REVIEW**  
iTech STANDARD  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/755e09-77ac-4089-925b-67701bd00d53/etsi-en-300-330-v2.1.1-2017-12>

# 1 Scope

The present document specifies technical characteristics and methods of measurements for the following Short Range Device major equipment types:

- 1) Generic Short range Devices including transmitters and receivers operating in the range from 9 kHz to 25 MHz; and
- 2) inductive loop transmitters and receivers operating from 9 kHz to 30 MHz including Radio Frequency Identification (RFID), Near Field Communication (NFC) and Electronic Article Surveillance (EAS) operating in LF and HF ranges.

Also the present document covers fixed, mobile and portable stations.

NOTE: If a system includes transponders, these are measured together with the transmitter.

These radio equipment types are capable of operating in the permitted frequency bands within the 9 kHz to 30 MHz range as specified in table 1.

**Table 1: Short Range Devices within the 9 kHz to 30 MHz permitted frequency bands**

	Frequency Bands/frequencies	Applications
Transmit and Receive	9 kHz to 90 kHz	Inductive devices, Generic use
Transmit and Receive	90 kHz to 119 kHz	Inductive devices, Generic use
Transmit and Receive	119 kHz to 140 kHz	Inductive devices, Generic use
Transmit and Receive	140 kHz to 148,5 kHz	Inductive devices, Generic use
Transmit and Receive	148,5 kHz to 5 MHz	Inductive devices, Generic use
Transmit and Receive	400 kHz to 600 kHz	RFID only
Transmit and Receive	5 MHz to 30 MHz	Inductive devices, Generic use
Transmit and Receive	3 155 kHz to 3 400 kHz	Inductive devices, Generic use
Transmit and Receive	984 kHz to 7 484 kHz (Note 3, Centre frequency is 4 234 kHz)	Inductive devices, Railway applications
Transmit and Receive	4 516 kHz	Inductive devices, Railway applications
Transmit and Receive	6 765 kHz to 6 795 kHz	Inductive devices, Generic use
Transmit and Receive	7 400 kHz to 8 800 kHz	Inductive devices, Generic use
Transmit and Receive	10 200 kHz to 11,000 MHz	Inductive devices, Generic use
Transmit and Receive	11,810 MHz to 15,310 MHz (Centre frequency is 13,56 MHz)	RFID only
Transmit and Receive	12,5 MHz to 20 MHz	Inductive devices, Wireless healthcare
Transmit and Receive	13,553 MHz to 13,567 MHz	Inductive devices, Generic use
Transmit and Receive	26,957 MHz to 27,283 MHz	Inductive devices, Generic use
Transmit and Receive	27,090 MHz to 27,100 MHz	Inductive devices, Railway applications
NOTE 1: In addition, it should be noted that other frequency bands may be available in a country within the frequency range 9 kHz to 30 MHz.		
NOTE 2: On non-harmonised parameters, national administrations may impose certain conditions such as the type of modulation, frequency, channel/frequency separations, maximum transmitter radiated power, duty cycle, and the inclusion of an automatic transmitter shut-off facility, as a condition for the issue of an Individual Rights for use of spectrum or General Authorization, or as a condition for use under "licence exemption" as it is in most cases for Short Range Devices.		
NOTE 3: Transmitting only on receipt of a Balise/Eurobalise tele-powering signal from a train.		

The frequency ranges and limits of the present document are based on the European Commission Decision for SRDs [i.10], CEPT/ERC/REC 70-03 [i.1].

When selecting parameters for new SRDs, which may have inherent safety of human life implications, manufacturers and users should pay particular attention to the potential for interference from other systems operating in the same or adjacent bands.

The radio equipment, covered by the present document is divided into several classes which are dependent on the antenna used (see annex B). Three types of measuring methods are defined in the present document due to the varied nature of the antenna types for equipment used in this band. One method measures the RF carrier current, another measures the radiated H-field and the third conducted power.

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.4] under the conditions identified in annex A.

## 2 References

### 2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] CISPR 16-1-4:2010+AMD1:2012: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements"

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT/ERC/REC 70-03: "Relating to the use of Short Range Devices (SRD)".
- [i.2] Recommendation ITU-T O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [i.3] ANSI C63.5: "American National Standard for Electromagnetic Compatibility-Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas (9 kHz to 40 GHz)".
- [i.4] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC Text with EEA relevance.
- [i.5] ETSI TR 102 273-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.6] ETSI TR 102 273-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.7] ETSI TR 102 273-4: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".

- [i.8] Void.
- [i.9] ETSI TR 103 059 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short-Range Devices (SRD) for operation in the 13,56 MHz band; System Reference Document for Radio Frequency Identification (RFID) equipment".
- [i.10] Commission Decision 2013/752/EC on harmonisation of the radio spectrum for use by short-range devices as amended by subsequent Commission Decisions.
- [i.11] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.12] Recommendation ITU-T O.41: "Psophometer for use on telephone-type circuits".
- [i.13] ITU Radio Regulations.
- [i.14] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**artificial antenna:** tuned reduced-radiating dummy load equal to the nominal impedance specified by the manufacturer

**assigned frequency band:** frequency band within which the device is authorized to operate

**co-location:** assembly where Transmitter and Receiver contained in one case or unit

NOTE: Co-location is usually defined as  $< 3$  m.

**conducted measurements:** measurements which are made using a direct connection to the equipment under test

**customized antenna:** antenna built according to manufacturers' antenna design rules inside tested limits

**dedicated antenna:** removable antenna supplied and type tested with the radio equipment, designed as an indispensable part of the equipment

NOTE: The antenna has been designed or developed for one or more specific types of equipment. It is the combination of dedicated antenna and radio equipment that is expected to be compliant with the regulations.

**fixed station:** equipment intended for use in a fixed location

**integral antenna:** antenna designed as a fixed part of the equipment, without the use of an external connector and as such which cannot be disconnected from the equipment by the user

**magnetic dipole moment:** product of (Number of coil turns)  $\times$  (coil area)  $\times$  (coil current)

NOTE: Air coils only.

**mobile station:** equipment normally installed in a vehicle

**portable station:** equipment intended to be carried, attached or implanted

**radiated measurements:** measurements which involve the absolute measurement of a radiated field

**spurious emissions:** emissions on a frequency or frequencies which are outside the occupied bandwidth and the level of which may be reduced without affecting the corresponding transmission of information

**tagging systems:** RFID, anti-theft, access control, location systems and NFC

NOTE: These kind of equipment consists of a transmitter(s), receiver(s) (or a combination of the two) and an antenna(s) to identify objects by means of a transponder.

**transponder:** device that responds to an interrogation signal

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

$\Omega$	ohm
A	loop antenna area
C	correction factor
E	electrical field strength
f	frequency
$f_A$	frequency generator A
$f_B$	frequency generator B
$f_C$	centre frequency of the OFR
$f_H$	highest frequency of the OFR
$f_L$	lowest frequency
$f_c$	carrier frequency in Hz
H	magnetic field strength
$H_{ef}$	H field-strength generated by an e-field antenna
$H_f$	H-field-strength limit
$H_c$	carrier H-field strength
$H_s$	H-field-strength limit for radiated spurious emissions
$I_c$	transmitter carrier output current
$I_s$	transmitter spurious output current
$\lambda$	Wave length
m	magnetic dipole moment
N	number of turns for a loop antenna
$N_B$	variable defined in table 10 to calculate the frequency for RX-blocking test, see clause 6.3.3.1
NIA	Product of $N$ (the number of turns of the loop coil) $\times I$ (current in the loop coil) $\times A$ (the area of the loop coil antenna)
P	Power
t	time

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ASK	Amplitude Shift Keying
BER	Bit Error Rate
CEPT	Conférence Européenne des Postes et Télécommunications
CISPR	Comité International Spécial des Perturbations Radioélectriques
e.r.p.	effective radiated power
EAS	Electronic Article Surveillance
EC	European Community
ECC	Electronic Communications Committee
EFTA	European Free Trade Association
EMC	ElectroMagnetic Compatibility
EMF/emf	ElectroMagnetic Field
ERC	European Radiocommunications Committee
EU	European Union