

SLOVENSKI STANDARD oSIST prEN 301 489-17 V3.1.0:2016

Standard elektromagnetne združljivosti (EMC) za radijsko opremo in storitve - 17. del: Posebni pogoji za širokopasovne sisteme za prenos podatkov - Harmonizirani standard, ki zajema bistvene zahteve člena 3.1(b) direktive 2014/53/EU

01-junij-2016

ElectroMagnetic Compatibility (EMC) standard for radio equipment and services - Part 17: Specific conditions for Broadband Data Transmission Systems - Harmonised Standard covering the essential requirements of article 3.1(b) of the Directive 2014/53/EU

(standards.iteh.ai)

<u>SIST EN 301 489-17 V3.1.1:2017</u> https://standards.iteh.ai/catalog/standards/sist/0c4b7a0c-2cc2-4fe5-8099-f8b4fa90453f/sist en-301-489-17-v3-1-1-2017

Ta slovenski standard je istoveten z: ETSI EN 301 489-17 V3.1.0 (2016-04)

ICS:

33.060.01 Radijske komunikacije na Radiocommunications in

splošno general

33.100.01 Elektromagnetna združljivost Electromagnetic compatibility

na splošno in general

oSIST prEN 301 489-17 V3.1.0:2016 en

oSIST prEN 301 489-17 V3.1.0:2016

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 301 489-17 V3.1.1:2017</u> https://standards.iteh.ai/catalog/standards/sist/0c4b7a0c-2cc2-4fe5-8099-f8b4fa90453f/sist-en-301-489-17-v3-1-1-2017 oSIST prEN 301 489-17 V3.1.0:2016

Draft ETSI EN 301 489-17 V3.1.0 (2016-04)



ElectroMagnetic Compatibility (EMC)
standard for radio equipment and services;
Part 17: Specific conditions for
Broadband Data Transmission Systems;
Harmonised Standard covering the essential requirements
of article 3.1(b) of the Directive 2014/53/EU

2

Reference

REN/ERM-EMC-335

Keywords

EMC, harmonised standard, radio

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

(standards.iteh.ai)

Important notice

Important notice

The present document can be downloaded from:

http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT[™], **PLUGTESTS**[™], **UMTS**[™] and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**[™] and **LTE**[™] are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intell	ectual Property Rights	5
Forev	word	5
Moda	al verbs terminology	5
1	Scope	6
2	References	6
2.1	Normative references	
2.2	Informative references	
3	Definitions and abbreviations	7
3.1	Definitions	
3.2	Abbreviations	
4	Test conditions	
4 4.1	General	
4.2	Arrangements for test signals	
4.2.0	General	
4.2.1	Arrangements for test signals at the input of transmitters	
4.2.2	Arrangements for test signals at the output of transmitters	
4.2.3	Arrangements for test signals at the input of receivers	
4.2.4	Arrangements for test signals at the output of receivers	9
4.2.5	Arrangements for testing transmitter and receiver together (as a system)	9
4.3	Exclusion bands.	
4.4	Narrow band responses on receivers or receivers which are part of transceivers	
4.5	Normal test modulation	
5	Performance assessment.	10
5.1	General	
5.2	Arrangements for the assessment of host dependant equipment and plug-in cards	
5.2.0	Introduction	
5.2.1	Alternative A: composite equipment	
5.2.2	Alternative B: use of a test jig or host	
5.3 5.4	Assessment procedures	
5.5	Equipment classification	
_	• •	
6	Performance criteria	
6.1	General performance criteria	
6.2	Performance table	
6.3 6.4	Performance criteria for Continuous phenomena applied to Transmitters (CT)	
6.5	Performance criteria for Continuous phenomena applied to Receivers (CR)	
6.6	Performance criteria for Transient phenomena applied to Receivers (TR)	
7	Applicability overview	
7.1 7.1.1	Emission	
7.1.1	Special conditions	
7.1.2	Immunity	
7.2.1	General	
7.2.2	Special conditions	
Anne	ex A (normative): Relationship between the present document and the essential	1 4
	requirements of Directive 2014/53/EU	14
Anne	ex B (informative): Examples of radio equipment in the scope of the present documen	nt16
B.1	Introduction	16

Draft ETSI EN 301 489-17 V3.1.0 (2016-04)

Histo	rv		18
Anno	ex C (informative):	Bibliography	17
B.6	Multi-Gigabit Wireless	S Systems (MGWS)	16
B.5	Broadband data transm	uitting/BWA Terminal Stations	16
B.4	Broadband data transmitting systems operating in the band 5 725 MHz to 5 875 MHz		
B.3	5 GHz high performan	ce RLAN systems	16
B.2		ems operating in the 2,4 GHz ISM band and using wide band modulatio	

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 301 489-17 V3.1.1:2017</u> https://standards.iteh.ai/catalog/standards/sist/0c4b7a0c-2cc2-4fe5-8099-f8b4fa90453f/sisten-301-489-17-v3-1-1-2017

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.12] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 17 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

Proposed national transposition dates				
Date of latest announcement of this EN (doa):301-489-17-v3-1-1-2017	3 months after ETSI publication			
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa			
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa			

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document, together with ETSI EN 301 489-1 [1], covers the assessment of Broadband Data Transmission System equipment, as detailed in annex B, in respect of ElectroMagnetic Compatibility (EMC).

Technical specifications related to the antenna port and emissions from the enclosure port of the radio equipment are not included in the present document. Such technical specifications are found in the relevant product standards for the effective use of the radio spectrum.

The present document specifies the applicable test conditions, performance assessment and performance criteria for wideband data communication systems.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and ETSI EN 301 489-1 [1], the provisions of the present document take precedence.

The environmental classification and the emission and immunity requirements used in the present document are as stated in ETSI EN 301 489-1 [1], except for any special conditions included in the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at http://docbox.etsi.org/Reference.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document. 146:490453 f/s/s

[1] ETSI EN 301 489-1 (V2.1.0) (04-2016): "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Harmonised Standard covering the essential requirements of article 3.1(b) of the Directive 2014/53/EU and the essential requirements of article 6 of the Directive 2014/30/EU; Part 1: Common technical requirements".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Void.
- [i.3] ETSI EN 301 893: "Broadband Radio Access Networks (BRAN); 5 GHz high performance RLAN; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

7

Draft ETSI EN 301 489-17 V3.1.0 (2016-04)

[i.4]	ETSI EN 302 502: "Broadband Radio Access Networks (BRAN); 5,8 GHz fixed broadband data transmitting systems; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".
[i.5]	ETSI EN 302 544-2: "Broadband Data Transmission Systems operating in the 2 500 MHz to 2 690 MHz frequency band; Part 2: TDD User Equipment Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".
[i.6]	ETSI EN 302 567: "WAS/RLAN systems; Multiple-Gigabit WAS/RLAN equipment operating in the 60 GHz band; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
[i.7]	ETSI EN 302 623: "Broadband Wireless Access Systems (BWA) in the 3 400 MHz to 3 800 MHz frequency band; Mobile Terminal Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".
[i.8]	ETSI EN 300 328: "Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
[i.9]	Void.
[i.10]	ETSI EN 301 908-19: "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 19: OFDMA TDD WMAN (Mobile WiMAXTM) TDD User Equipment (UE)".
[i.11]	ETSI EN 301 908-21: "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 21: OFDMA TDD WMAN (Mobile WiMAXTM) FDD User Equipment (UE)".
[i.12]	Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 301 489-1 [1] and the following apply:

Equipment Under Test (EUT): equipment under test and subject to the performance requirements of the present document

fixed station: equipment intended for use in a fixed location and fitted with one or more antennas

NOTE: The equipment may be fitted with either antenna socket(s) or integral antenna(s) or both.

hand-portable station: equipment normally used on a stand-alone basis and to be carried by a person

NOTE: The equipment may be fitted with one or more antennas. The equipment may be fitted with either antenna socket(s) or integral antenna(s) or both.

host: any equipment which has complete user functionality when not connected to the radio equipment part and to which the radio equipment part provides additional functionality and to which connection is necessary for the radio equipment part to offer functionality

plug-in radio device: equipment, including slide-in radio cards, intended to be used with or within a variety of host systems, using their control functions and power supply

stand-alone radio equipment: equipment that is intended primarily as communications equipment and that is normally used on a stand-alone basis

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC Alternating Current ACK ACKnowledgement

ARQ Automatic Retransmission reQuest BRAN Broadband Radio Access Networks

BWA Broadband Wireless Access

CR Continuous phenomena applied to Receivers
CT Continuous phenomena applied to Transmitters

DC Direct Current

EMC ElectroMagnetic Compatibility

ERM Electromagnetic compatibility and Radio Matters

EUT Equipment Under Test

HIPERLAN HIgh PErformance Radio Local Area Network

ISM Industrial, Scientific and Medical MGWS Multi-Gigabit Wireless Systems MUS Maximum Usable Sensitivity NACK Not ACKnowledgement

RF Radio Frequency

RLAN Radio Local Area Network

TR Transient phenomena applied to Receivers
TT Transient phenomena applied to Transmitters

4 Test conditions NDARD PREVIEW

4.1 General

For the purposes of the present document, the test conditions of ETSI EN 301 489-1 [1], clause 4, shall apply as appropriate. Further product related test conditions for wideband data communications systems are specified in clauses 4.2 to 4.5.

The radio equipment may take forms which may require special software and/or test fixtures. Equipment which requires connection to a host equipment to function shall use the test configuration as defined by the manufacturer. In all cases the EUT shall be exercised in a manner representative of normal intended use.

4.2 Arrangements for test signals

4.2.0 General

The provisions of ETSI EN 301 489-1 [1], clause 4.2 shall apply.

4.2.1 Arrangements for test signals at the input of transmitters

The provisions of ETSI EN 301 489-1 [1], clause 4.2.1 shall apply with the following modifications.

The wanted signals and/or controls required to establish a communications link shall be defined by the manufacturer. The transmitter shall be operated at maximum rated power.

4.2.2 Arrangements for test signals at the output of transmitters

The provisions of ETSI EN 301 489-1 [1], clause 4.2.2 shall apply with the following modifications.

The manufacturer may provide a suitable companion receiver that can be used to receive messages or to set up a communication link.

4.2.3 Arrangements for test signals at the input of receivers

The provisions of ETSI EN 301 489-1 [1], clause 4.2.3 shall apply with the following modifications.

The wanted signals required to establish a communications link shall be defined by the manufacturer.

The level of the wanted signal at the input of the receiver shall be at least 30 dB above the declared Maximum Usable Sensitivity (MUS).

4.2.4 Arrangements for test signals at the output of receivers

The measuring equipment for the output signal from the receiver under test shall be located outside the test environment.

It shall be possible to assess the performance of the equipment by appropriately monitoring the receiver output.

If the receiver has an output connector or port providing the wanted output signal, then this port shall be used via a cable, consistent with the standard cable used in normal operation, connected to the external measuring equipment outside the test environment. The measuring equipment may be supplied by the manufacturer.

Precautions shall be taken to ensure that any effect on the test due to the coupling means is minimized.

The manufacturer may provide a suitable companion transmitter that can be used to transmit messages or to set up a communication link.

4.2.5 Arrangements for testing transmitter and receiver together (as a system)

The provisions of ETSI EN 301 489-1 [1], clause 4.2.5 shall apply.

The manufacturer may provide a suitable companion transceiver or transmitter and receiver that can be used to send and receive messages or to set up a communication link.

Both the EUT and the companion equipment shall transmit the normal test modulation. Further, the output of the radio equipment under test shall be monitored by the test system. 0.2457a(0.22224fe5.8099-f854fa90)453f/sist

4.3 Exclusion bands

The frequencies on which the transmitter part of the EUT is intended to operate shall be excluded from radiated emission measurements when performed in transmit mode of operation.

There shall be no frequency exclusion band applied to emission measurements of the receiver part of transceivers or the stand alone receiver under test, and/or associated ancillary equipment.

The exclusion band for immunity testing of equipment operating in the 2,4 GHz band shall be:

- lower limit of exclusion band = lowest allocated band edge frequency -120 MHz, i.e. 2 280 MHz;
- upper limit of exclusion band = highest allocated band edge frequency +120 MHz, i.e. 2 603,5MHz.

The exclusion band for immunity testing of equipment operating in the 5 GHz WiFi band shall be:

- lower limit of exclusion band = lowest allocated band edge frequency -270 MHz, i.e. 4 880 MHz;
- upper limit of exclusion band = highest allocated band edge frequency +270 MHz, i.e. 5 995 MHz.

The exclusion band for immunity testing of equipment operating in the 5,8 GHz band shall be:

- lower limit of exclusion band = lowest allocated band edge frequency -270 MHz, i.e. 5 455 MHz;
- as the immunity requirements have an upper frequency range of 6 GHz and any upper edge exclusion band would be greater than this for the 5,8 GHz band. The above frequency shall also be regarded as the upper end of the test range.

NOTE: These receiver exclusion band ranges align with the relevant blocking test ranges.