

ETSI TS 102 384 V10.2.0 (2015-03)



**Smart Cards;
UICC-Terminal interface;
Card Application Toolkit (CAT) conformance specification
(Release 10)**

PREVIEW
Standard (ai)
https://standards.iteh.ai/standards/sist/a304b76b-1a30-4405-ad86-e47cfe5b0e7/etsi-ts-102-384-v10.2.0-2015-03-01

Reference

RTS/SCP-00014va20

Keywords

smart card**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	10
3 Definitions and abbreviations.....	10
3.1 Terminal definition and configurations	10
3.2 Applicability.....	10
3.2.1 Applicability of the present document	10
3.2.2 Applicability of the individual tests	11
3.2.3 Applicability to terminal equipment	11
3.2.4 Definitions	11
3.2.4.1 Format of the table of optional features	11
3.2.4.2 Format of the applicability table	11
3.2.4.3 Status and notations.....	12
3.3 Table of optional features.....	12
3.4 Applicability table.....	15
3.5 Conventions for mathematical notations	55
3.5.1 Mathematical signs	55
3.6 Abbreviations	55
4 Test equipment	55
5 Testing methodology in general.....	56
5.1 Testing of optional functions and procedures.....	56
5.2 Test interfaces and facilities	56
5.3 Information to be provided by the apparatus supplier.....	56
6 Void.....	57
7 Measurement uncertainty	57
8 Format of tests.....	57
9 Generic call set up procedures.....	59
10 to 26 Void.....	59
27 Testing of the UICC/Terminal interface	59
27.1 to 27.21 Void.....	59
27.22 Card Application Toolkit.....	59
27.22.1a General Test purpose	59
27.22.1b Definition of default values for Card Application Toolkit testing.....	60
27.22.1 Initialization of Card Application Toolkit Enabled UICC by Card Application Toolkit Enabled Terminal (Profile Download).....	63
27.22.1.1 Definition and applicability.....	63
27.22.1.2 Conformance requirement.....	63
27.22.1.3 Test purpose	63
27.22.1.4 Method of test	63
27.22.1.4.1 Initial conditions.....	63
27.22.1.4.2 Procedure.....	63
27.22.1.5 Test requirement	64
27.22.2 Contents of the TERMINAL PROFILE command.....	64
27.22.2.1 Definition and applicability.....	64
27.22.2.2 Conformance requirement.....	64

27.22.2.3	Test purpose	64
27.22.2.4	Method of test	64
27.22.2.4.1	Initial conditions	64
27.22.2.4.2	Procedure.....	64
27.22.2.5	Test requirement	64
27.22.3	Servicing of proactive UICC commands	65
27.22.3.1	Definition and applicability.....	65
27.22.3.2	Conformance requirement.....	65
27.22.3.3	Test purpose	65
27.22.3.4	Method of test	65
27.22.3.4.1	Initial conditions	65
27.22.3.4.2	Procedure.....	65
27.22.3.5	Test requirement	65
27.22.4	Proactive UICC commands	65
27.22.4.1	DISPLAY TEXT.....	65
27.22.4.1.1	DISPLAY TEXT (Normal)	65
27.22.4.1.2	DISPLAY TEXT (Support of "No response from user")	75
27.22.4.1.3	DISPLAY TEXT (Display of extension text).....	76
27.22.4.1.4	DISPLAY TEXT (Sustained text).....	78
27.22.4.1.5	DISPLAY TEXT (Display of icons)	82
27.22.4.1.6	DISPLAY TEXT (UCS2 display supported in Cyrillic)	87
27.22.4.1.7	DISPLAY TEXT (Variable Time out)	89
27.22.4.1.8	DISPLAY TEXT (Support of Text Attribute)	90
27.22.4.1.9	DISPLAY TEXT (UCS2 display in Chinese)	116
27.22.4.1.10	DISPLAY TEXT (UCS2 display in Katakana)	118
27.22.4.2	GET INKEY	119
27.22.4.2.1	GET INKEY(normal).....	119
27.22.4.2.2	GET INKEY (No response from User)	126
27.22.4.2.3	GET INKEY (UCS2 display in Cyrillic).....	128
27.22.4.2.4	GET INKEY (UCS2 entry in Cyrillic).....	130
27.22.4.2.5	GET INKEY ("Yes/No" Response).....	132
27.22.4.2.6	GET INKEY (display of Icon)	134
27.22.4.2.7	GET INKEY (Help Information).....	142
27.22.4.2.8	GET INKEY (Variable Time out).....	145
27.22.4.2.9	GET INKEY (Support of Text Attribute).....	147
27.22.4.2.10	GET INKEY (UCS2 display in Chinese)	180
27.22.4.2.11	GET INKEY (UCS2 entry in Chinese)	183
27.22.4.2.12	GET INKEY (UCS2 display in Katakana)	185
27.22.4.2.13	GET INKEY (UCS2 entry in Katakana)	187
27.22.4.3	GET INPUT	189
27.22.4.3.1	GET INPUT (normal).....	189
27.22.4.3.2	GET INPUT (No response from User).....	202
27.22.4.3.3	GET INPUT (UCS2 display in Cyrillic)	204
27.22.4.3.4	GET INPUT (UCS2 entry in Cyrillic).....	207
27.22.4.3.5	GET INPUT (default text).....	210
27.22.4.3.6	GET INPUT (display of Icon).....	214
27.22.4.3.7	GET INPUT (Help Information)	222
27.22.4.3.8	GET INPUT (Support of Text Attribute)	224
27.22.4.3.9	GET INPUT (UCS2 display in Chinese).....	261
27.22.4.3.10	GET INPUT (UCS2 entry in Chinese)	264
27.22.4.3.11	GET INPUT (UCS2 display in Katakana).....	268
27.22.4.3.12	GET INPUT (UCS2 entry in Katakana).....	271
27.22.4.4	MORE TIME	274
27.22.4.4.1	Definition and applicability	274
27.22.4.4.2	Conformance requirement	274
27.22.4.4.3	Test purpose	274
27.22.4.4.4	Method of test.....	274
27.22.4.4.5	Test requirement	275
27.22.4.5	PLAY TONE.....	275
27.22.4.5.1	PLAY TONE (Normal)	275
27.22.4.5.2	PLAY TONE (UCS2 display in Cyrillic).....	287
27.22.4.5.3	PLAY TONE (display of Icon)	290

27.22.4.5.4	PLAY TONE (Support of Text Attribute).....	298
27.22.4.5.5	PLAY TONE (UCS2 display in Chinese)	327
27.22.4.5.6	PLAY TONE (UCS2 display in Katakana)	330
27.22.4.6	POLL INTERVAL.....	333
27.22.4.6.1	Definition and applicability	333
27.22.4.6.2	Conformance requirement	333
27.22.4.6.3	Test purpose	333
27.22.4.6.4	Method of test.....	334
27.22.4.6.5	Test requirement	335
27.22.4.7	REFRESH	335
27.22.4.7.1	REFRESH (normal).....	335
27.22.4.8	SET UP MENU and ENVELOPE MENU SELECTION	338
27.22.4.8.1	SET UP MENU (normal) and ENVELOPE MENU SELECTION.....	338
27.22.4.8.2	SET UP MENU (help request support) and ENVELOPE MENU SELECTION.....	349
27.22.4.8.3	SET UP MENU (next action support) and ENVELOPE MENU SELECTION	351
27.22.4.8.4	SET UP MENU (display of icons) and ENVELOPE MENU SELECTION.....	353
27.22.4.8.5	SET UP MENU (soft keys support) and ENVELOPE MENU SELECTION.....	358
27.22.4.8.6	SET UP MENU (support of Text Attribute) and ENVELOPE MENU SELECTION	360
27.22.4.8.7	SET UP MENU (UCS2 display in Cyrillic) and ENVELOPE MENU SELECTION.....	396
27.22.4.8.8	SET UP MENU (UCS2 display in Chinese) and ENVELOPE MENU SELECTION	401
27.22.4.8.9	SET UP MENU (UCS2 display in Katakana) and ENVELOPE MENU SELECTION.....	405
27.22.4.9	SELECT ITEM	409
27.22.4.9.1	SELECT ITEM (mandatory features for Terminal supporting SELECT ITEM).....	409
27.22.4.9.2	SELECT ITEM (next action support).....	422
27.22.4.9.3	SELECT ITEM (default item support)	423
27.22.4.9.4	SELECT ITEM (help request support).....	425
27.22.4.9.5	SELECT ITEM (icons support).....	427
27.22.4.9.6	SELECT ITEM (presentation style)	431
27.22.4.9.7	SELECT ITEM (soft keys support).....	434
27.22.4.9.8	SELECT ITEM (Support of "No response from user").....	436
27.22.4.9.9	SELECT ITEM (Support of Text Attribute).....	437
27.22.4.9.10	SELECT ITEM (UCS2 display in Cyrillic).....	471
27.22.4.9.11	SELECT ITEM (UCS2 display in Chinese).....	476
27.22.4.9.12	SELECT ITEM (UCS2 display in Katakana).....	478
27.22.4.10	SEND SHORT MESSAGE.....	482
27.22.4.11	Void.....	482
27.22.4.12	Void.....	482
27.22.4.13	SET UP CALL	482
27.22.4.14	POLLING OFF	482
27.22.4.15	PROVIDE LOCAL INFORMATION	482
27.22.4.15.1	Definition and applicability	482
27.22.4.15.2	Conformance requirement	483
27.22.4.15.3	Test purpose	483
27.22.4.15.4	Method of tests	483
27.22.4.15.5	Test requirement	492
27.22.4.16	SET UP EVENT LIST	492
27.22.4.16.1	SET UP EVENT LIST (normal)	492
27.22.4.17	PERFORM CARD APDU	499
27.22.4.17.1	PERFORM CARD APDU (normal).....	499
27.22.4.18	POWER OFF CARD	517
27.22.4.18.1	POWER OFF CARD (normal).....	517
27.22.4.18.2	POWER OFF CARD (detachable card reader)	519
27.22.4.19	POWER ON CARD	520
27.22.4.19.1	POWER ON CARD (normal)	520
27.22.4.19.2	POWER ON CARD (detachable card reader).....	524
27.22.4.20	GET READER STATUS	525
27.22.4.20.1	GET READER STATUS (normal)	525
27.22.4.20.2	GET CARD READER STATUS (detachable card reader).....	535
27.22.4.21	TIMER MANAGEMENT and ENVELOPE TIMER EXPIRATION	537
27.22.4.21.1	TIMER MANAGEMENT (normal)	537
27.22.4.21.2	ENVELOPE TIMER EXPIRATION (normal)	575
27.22.4.22	SET UP IDLE MODE TEXT.....	580

27.22.4.22.1	SET UP IDLE MODE TEXT (normal)	580
27.22.4.22.2	SET UP IDLE MODE TEXT (Icon support)	589
27.22.4.22.3	SET UP IDLE MODE TEXT (UCS2 display in Cyrillic)	596
27.22.4.22.4	SET UP IDLE MODE TEXT (support of Text Attribute)	597
27.22.4.22.5	SET UP IDLE MODE TEXT (UCS2 display in Chinese)	625
27.22.4.22.6	SET UP IDLE MODE TEXT (UCS2 display in Katakana)	626
27.22.4.23	RUN AT COMMAND	628
27.22.4.23.1	RUN AT COMMAND (normal)	628
27.22.4.23.2	RUN AT COMMAND (Icon support)	630
27.22.4.23.3	RUN AT COMMAND (support of Text Attribute)	637
27.22.4.23.4	RUN AT COMMAND (UCS2 display in Cyrillic)	668
27.22.4.23.5	RUN AT COMMAND (UCS2 display in Chinese)	670
27.22.4.23.6	RUN AT COMMAND (UCS2 display in Katakana)	671
27.22.4.24	SEND DTMF	673
27.22.4.25	LANGUAGE NOTIFICATION	673
27.22.4.25.1	Definition and applicability	673
27.22.4.25.2	Conformance Requirement	673
27.22.4.25.3	Test purpose	673
27.22.4.25.4	Method of Test	673
27.22.4.25.5	Test requirement	675
27.22.4.26	LAUNCH BROWSER	676
27.22.4.27	OPEN CHANNEL	676
27.22.4.27.1	Void	676
27.22.4.27.2	Open Channel (related to GPRS)	676
27.22.4.27.3	Open Channel (default bearer)	676
27.22.4.27.4	Open Channel (Local Bearer)	676
27.22.4.27.5	Open Channel (GPRS, support of Text Attribute)	676
27.22.4.27.6	Open Channel (related to UICC Server Mode)	676
27.22.4.27.7	Open Channel (related to Terminal Server Mode)	679
27.22.4.28	CLOSE CHANNEL	684
27.22.4.28.1	CLOSE CHANNEL (related to GPRS)	684
27.22.4.28.2	CLOSE CHANNEL (support of Text Attribute)	684
27.22.4.28.3	CLOSE CHANNEL (related to UICC Server Mode)	684
27.22.4.28.4	CLOSE CHANNEL (related to Terminal Server Mode)	687
27.22.4.29	RECEIVE DATA	690
27.22.4.30	SEND DATA	690
27.22.4.31	GET CHANNEL STATUS	690
27.22.4.31.1	GET CHANNEL STATUS (related to GPRS)	690
27.22.4.31.2	GET CHANNEL STATUS (related to UICC server mode)	690
27.22.4.32	ACTIVATE	695
27.22.4.32.1	Definition and applicability	695
27.22.4.32.2	Conformance Requirement	695
27.22.4.32.3	Test purpose	695
27.22.4.32.4	Method of Test	695
27.22.4.32.5	Test requirement	697
27.22.4.33	CONTACTLESS STATE CHANGED	697
27.22.4.33.1	Definition and applicability	697
27.22.4.33.2	Conformance Requirement	697
27.22.4.33.3	Test purpose	697
27.22.4.33.4	Method of Test	697
27.22.4.33.5	Test requirement	699
27.22.5	Void	699
27.22.6	CALL CONTROL BY NAA	699
27.22.6.1	Procedure for Terminal Originated calls	699
27.22.6.2	Void	699
27.22.6.3	Interaction with Fixed Dialling Number (FDN)	699
27.22.7	EVENT DOWNLOAD	700
27.22.7.1	MT Call Event	700
27.22.7.2	Call Connected Event	700
27.22.7.2.1	Call Connected Event (MT and MO call)	700
27.22.7.3	Call Disconnected Event	700
27.22.7.4	Location Status Event	700

27.22.7.4.1	Location Status Event (normal).....	700
27.22.7.5	User Activity Event.....	700
27.22.7.5.1	User Activity Event (normal)	700
27.22.7.6	Idle screen available event	702
27.22.7.6.1	Idle Screen Available (normal).....	702
27.22.7.7	Card reader status event	704
27.22.7.7.1	Card Reader Status (normal)	704
27.22.7.7.2	Card Reader Status(detachable card reader).....	709
27.22.7.8	Language selection event	711
27.22.7.8.1	Language selection event (normal).....	711
27.22.7.9	Browser termination event	713
27.22.7.10	Data available event	713
27.22.7.10.1	Data available event (related to GPRS).....	713
27.22.7.10.2	Data available event (related to UICC server mode).....	713
27.22.7.11	Channel Status event.....	716
27.22.7.11.1	Channel Status event (related to GPRS).....	716
27.22.7.11.2	Channel Status event (related to UICC server mode).....	716
27.22.7.12	Access Technology Change event.....	720
27.22.7.13	Display parameter changed event	720
27.22.7.14	Local Connection event.....	720
27.22.7.15	Network search mode change event.....	720
27.22.7.16	Browsing status event	720
27.22.7.17	Frames Information changed event.....	720
27.22.7.18	HCI connectivity event	720
27.22.7.18.1	HCI connectivity event (normal).....	720
27.22.7.19	Contactless state request	722
27.22.7.19.1	Contactless state request (normal).....	722
27.22.8	Void.....	726
27.22.9	Handling of command number	726
27.22.9.1	Definition and applicability.....	726
27.22.9.2	Conformance requirement	726
27.22.9.3	Test purpose	726
27.22.9.4	Method of tests.....	726
27.22.9.4.1	Initial conditions	726
27.22.9.4.2	Procedure.....	726
27.22.9.5	Test requirement	729
27.22.10	TERMINAL APPLICATIONS	729
27.22.10.1	TERMINAL APPLICATIONS (one application).....	729
27.22.10.1.1	Definition and applicability	729
27.22.10.1.2	Conformance requirement	729
27.22.11.1.3	Test purpose	729
27.22.11.1.4	Method of test.....	729
27.22.11.2	TERMINAL APPLICATIONS (several applications).....	731
27.22.11.2.1	Definition and applicability	731
27.22.11.2.2	Conformance requirement	731
27.22.11.2.3	Test purpose	731
27.22.11.2.4	Method of test.....	731
Annex A (normative):	Details of Test-SIM (TestSIM).....	734
Annex B (normative):	Details of terminal profile support	736
Annex C (informative):	Bibliography	747
Annex D (informative):	Change history	748
History		750

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

It is based on work originally done in the 3GPP in TSG-terminals WG3.

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 0 early working draft;
 - 1 presented to TC SCP for information;
 - 2 presented to TC SCP for approval;
 - 3 or greater indicates TC SCP approved document under change control.
 - y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
 - z the third digit is incremented when editorial only changes have been incorporated in the document.
-

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document defines the Card Application Toolkit (CAT) test conformance for the Terminal.

The aim of the present document is to ensure interoperability between an UICC and a Terminal independently of the respective manufacturer, card issuer or operator.

Application specific tests for applications residing on an UICC are specified in ETSI TS 131 124 [9].

1 Scope

The present document describes the technical characteristics and methods of test for testing the Card Application Toolkit implemented in Terminals for the UICC, in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-7 [3] and ETS 300 406 [4].

The present document covers the minimum characteristics considered necessary in order to provide sufficient performance for Terminal and to prevent interference to other services or to other users.

It does not necessarily include all the characteristics which may be required by a user or subscriber, nor does it necessarily represent the optimum performance achievable.

The present document is part of the ETSI-series of technical specifications. The present document neither replaces any of the other ETSI technical specifications or ETSI related ETSs or ENs, nor is it created to provide full understanding of (or parts of) the NAA. The present document lists the requirements, and provides the methods of test for testing the Card Application Toolkit implemented in a Terminal for conformance to the ETSI standard.

For a full description of the system, reference should be made to all the ETSI technical specifications or ETSI related ETSs or ENs. Clause 2 provides a complete list of the ETSI technical specifications, ETSI related ETSs, ENs, and ETRs, on which this conformance test specifications is based.

If there is a difference between this present conformance document, and any other ETSI technical specification or ETSI related ETS or EN, then the other ETSI technical specification or ETSI related ETS or EN is to be considered the authoritative reference.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non specific reference implicitly refers to the latest version of that document in the same Release as the present document.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 223: "Smart Cards; Card Application Toolkit (CAT)".
- [2] ISO/IEC 10646 (2003): "Information technology -- Universal Multiple-Octet Coded Character Set (UCS)".
- [3] ISO/IEC 9646-7 (1995): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".
- [4] ETSI ETS 300 406 (1995): "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [5] ETSI TS 124 008: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Mobile radio interface Layer 3 specification; Core network protocols; Stage 3 (3GPP TS 24.008)".

- [6] ETSI TS 127 007: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; AT command set for User Equipment (UE) (3GPP TS 27.007)".
- [7] ISO/IEC 7816-3 (1997): "Information technology -- Identification cards -- Integrated circuit(s) cards with contacts -- Part 3: Electronic signals and transmission protocols".
- [8] ANSI TIA/EIA-41-D: "Cellular Radiotelecommunications Intersystem Operations (ANSI/TIA/EIA-41-D-97)".
- [9] ETSI TS 131 124: "Universal Mobile Telecommunications System (UMTS); LTE; Mobile Equipment (ME) conformance test specification; Universal Subscriber Identity Module Application Toolkit (USAT) conformance test specification (3GPP TS 31.124)".
- [10] Void.
- [11] ETSI TS 101 267: "Digital cellular telecommunications system (Phase 2+); Specification of the SIM Application Toolkit (SAT) for the Subscriber Identity Module - Mobile Equipment (SIM-ME) interface (3GPP TS 11.14)".
- [12] ETSI TS 100 607-4: "Digital cellular telecommunications system (Phase 2+); Mobile Station (MS) conformance specification; Part 4: Subscriber Identity Module (SIM) application toolkit conformance test specification (3GPP TS 11.10-4)".
- [13] ETSI TS 102 613: "Smart Cards; UICC - Contactless Front-end (CLF) Interface; Part 1: Physical and data link layer characteristics".
- [14] ETSI TS 102 622: "Smart Cards; UICC - Contactless Front-end (CLF) Interface; Host Controller Interface (HCI)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non specific reference implicitly refers to the latest version of that document in the same Release as the present document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".

3 Definitions and abbreviations

3.1 Terminal definition and configurations

The terminal definition and configurations specified in the present document apply.

3.2 Applicability

3.2.1 Applicability of the present document

The present document applies to a terminal equipment that supports the Card Application Toolkit optional feature according to ETSI TS 102 223 [1].

3.2.2 Applicability of the individual tests

Table A.1 lists the optional features for which the supplier of the implementation states the support.

3.2.3 Applicability to terminal equipment

The applicability to terminal equipment specified in table B.1 in clause 3.4 of the present document applies, unless otherwise specified.

Terminals, which require a specific NAA to be present on the UICC, are to be tested according to the specific Card Application Toolkit enabled NAA dependent test specification (e.g. ETSI TS 131 124 [9] for USIM application, ETSI TS 100 607-4 [12] for SIM application). If there is no test specification defined for a specific Card Application Toolkit enabled NAA, terminals may be tested according to the present document. In this case, the simulated UICC is to include the specific NAA application, but the configuration and additional requirements of the specific Card Application Toolkit enabled NAA are out of scope in the present document.

3.2.4 Definitions

Void.

3.2.4.1 Format of the table of optional features

Option

The optional feature supported or not by the implementation.

Support Answer notation

The support columns is to be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [3], are used for the support column in the tables below.

Y or y	supported by the implementation
N or n	not supported by the implementation
N/A, n/a or -	no answer required (allowed only if the status is N/A, directly or after evaluation of a conditional status)

Mnemonic column

The Mnemonic column contains mnemonic identifiers for each item.

3.2.4.2 Format of the applicability table

The applicability of every test in table B.1 is formally expressed by the use of Boolean expression defined in the following clause.

The columns in table B.1 have the following meaning:

- In the "Item" column a local entry number for the requirement in the table is given.
- In the "Description" column a short non-exhaustive description of the requirement is found.
- The "Release" column gives the Release applicable and onwards, for the item in the "Description" column.
- The "Test Sequence(s)" column gives a reference to the test sequence number(s) detailed in the present document and required to validate the implementation of the corresponding item in the "Description" column.
- For a given Release, the corresponding "Rel X Terminal" column lists the tests required for a Terminal to be declared compliant to this Release.
- The "Support" column is blank in the proforma, and is to be completed by the manufacturer in respect of each particular requirement to indicate the choices, which have been made in the implementation.

- The "Terminal Profile" column gives a reference to the corresponding bit that needs to be present in the Terminal Profile.

3.2.4.3 Status and notations

The "Release X Terminal" columns show the status of the entries as follows:

The following notations, defined in ISO/IEC 9646-7 [3], are used for the status column:

M	mandatory - the capability is required to be supported.
O	optional - the capability may be supported or not.
N/A	not applicable - in the given context, it is impossible to use the capability.
X	prohibited (excluded) - there is a requirement not to use this capability in the given context.
O.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table.
Ci	conditional - the requirement on the capability ("M", "O", "X" or "N/A") depends on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF... THEN (IF... THEN... ELSE...) ELSE..." is to be used to avoid ambiguities.

References to items

For each possible item answer (answer in the support column) there exists a unique reference, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are to be discriminated by letters (a, b, etc.), respectively.

EXAMPLE: A.1/4 is the reference to the answer of item 4 in table A.1.

3.3 Table of optional features

Support of Card Application Toolkit is optional for Terminal. However, if a Terminal states conformance with a specific SCP release, it is mandatory for the Terminal to support all functions of that release, as stated in table A.1.

The support of letter classes, which specify mainly Terminal hardware dependent features, is optional for the Terminal and may supplement the Card Application Toolkit functionality described in the present document. If a Terminal states conformance to a letter class, it is mandatory to support all functions within the respective letter class.

The supplier of the implementation is to state the support of possible options in table A.1.

Table A.1: Options

Item	Option	Status	Support	Mnemonic
1	Capability Configuration parameter	M		O_Cap_Conf
2	Sustained text	M		O_sust_text
3	UCS2 coding scheme for Entry	O		O_Ucs2_Entry
4	Extended Text String	M		O_Ext_Str
5	Help information	O		O_Help
6	Icons	O		O_Icons
7	Class A: Dual Slot	O		O_Dual_Slot
8	Detachable reader	O		O_Detach_Rdr
9	Class B: RUN AT	O		O_Run_At
10	Class C: LAUNCH BROWSER	O		O_LB
11	Class D: Soft keys	O		O_Soft_key
12	Class E: B.I.P related to CSD	O		O_BIP_CSD
13	Screen sizing parameters	O		O_Scr_Siz
14	Screen Resizing	O		O_Scr_Resiz
15	UCS2 coding scheme for Display	O		O_Ucs2_Displ
16	Terminal supporting GPRS	O		O_GPRS

Item	Option	Status	Support	Mnemonic
17	Terminal supporting UDP	O		O_UDP
18	Terminal supporting TCP	O		O_TCP
19	Redial in Set Up Call	O		O_Redial
20	Terminal decision to respond with "No response from user" in finite time	O		O_D_NoResp
21	Class E: B.I.P related to GPRS	O		O_BIP_GPRS
22	Terminal supporting Called Party Subaddress	O		O_CP_Subaddr
23	Immediate response	O		O_Imm_Resp
24	Variable Timeout	O		O_Duration
25	Void			
26	Class F: B.I.P related to local bearer	O		O_BIP_Local
27	BlueTooth Support	O		O_BT
28	IrDA Support	O		O_IrDA
29	RS232 Support	O		O_RS232
30	USB Support	O		O_USB
31	WML Browser Support	O		O_WML
32	XHTML Browser Support	O		O_XHTML
33	HTML Browser Support	O		O_HTML
34	CHTML Browser Support	O		O_CHTML
35	Class G: Battery Data	O		O_Batt
36	Class H: Multimedia Call support	O		O_Xmedia_Call
37	Class I: Frame support	O		O_Frames
38	Class J: Multimedia Support	O		O_MMS
39	Void			
40	Void			
41	UCS2 in Cyrillic	O		O_UCS2_Cyrillic
42	UCS2 in Chinese	O		O_UCS2_Chinese
43	UCS2 in Katakana	O		O_UCS2_Katakana
44	Text attributes - Alignment left	O		O_TAT_AL
45	Text attributes - Alignment center	O		O_TAT_AC
46	Text attributes - Alignment right	O		O_TAT_AR
47	Text attributes - Font size normal	O		O_TAT_FSN
48	Text attributes - Font size large	O		O_TAT_FSL
49	Text attributes - Font size small	O		O_TAT_FSS
50	Text attributes - Style normal	O		O_TAT_SN
51	Text attributes - Style bold	O		O_TAT_SB
52	Text attributes - Style italic	O		O_TAT_SI
53	Text attributes - Style underlined	O		O_TAT_SU
54	Text attributes - Style strikethrough	O		O_TAT_SS
55	Text attributes - Style text foreground colour	O		O_TAT_STFC
56	Text attributes - Style text background colour	O		O_TAT_STFB
57	Terminal supporting "+CGMI" in combination with Run AT Command	O		O_+CGMI
58	Class E: Terminal supports TCP, UICC in Server Mode	O		O_TCP_UICC_ServerMode
59	Terminal supports selection of default item in Select Item	O		O_Select_Item_Default_Item
60	Preferred buffer size supported by the terminal for Open Channel command is greater than 0 byte and less than 65535 bytes	O		O_BUFFER_SIZE
61	Class E: Terminal supports TCP, Terminal in Server Mode	O		O_TCP_Terminal_ServerMode
62	Class E: Terminal supports UDP, Terminal in Server Mode	O		O_UDP_Terminal_ServerMode
63	Class K: Terminal Applications	O		O_Terminal_Applications
64	Class L: Proactive command: ACTIVATE	O		O_Activate
65	Class M: Event download: HCI connectivity event	O		O_HCI_Connectivity_Event
66	Class O: Broadcast Network Information	O		O_Broadcast_Network
67	Terminal supports display capability	C001		O_No_Type_ND
68	Terminal supports keypad	C001		O_No_Type_NK
69	Terminal supports audio alerting	C001		O_No_Type_NA
70	Terminal supports speech call	C001		O_No_Type_NS
71	Terminal supports multiple languages	C001		O_No_Type_NL