



SLOVENSKI STANDARD

DSIST TBR 043 E1:% - -

01-oktober-% - -

GUHY]hg_Y'nYa Y'g_Y'dcghUY]b'g]ghYa]'fG9GL!'GUHY]hg_Y'nYa Y'g_Y'dcghUY'g
HYfa]bU]'n'nY'c'a U\ bc'UbHYbg_c'cXdfH]bc'fU G5 H'gUa c'nUcXXU'Ub'YžnUcXXU'Ub'Y
]b'gdfY'Ya Ub'Y'U]'gUa c'nUgdfY'Ya Ub'Yž_]XY'i Y'c'j 'ZY_j Yb b] 'dUgcj]' (' ; <n]b
*'; <n

Satellite Earth Stations and Systems (SES); Very Small Aperture Terminal (VSAT)
transmit-only, transmit-and-receive, receive-only satellite earth stations operating in the 4
GHz and 6 GHz frequency bands


Ta slovenski standard je istoveten z: TBR 043 E1.% - , !\$)

ICS:

33.060.30	Radiorelejni in fiksni satelitski komunikacijski sistemi	Radio relay and fixed satellite communications systems
-----------	--	--

DSIST TBR 043 E1:% - -

en



TECHNICAL **B**ASIS for **R**EGULATION

TBR 43

May 1998

Source: SES

Reference: DTBR/SES-00021

ICS: 33.020

Key words: Satellite, earth station, VSAT, type approval

**Satellite Earth Stations and Systems (SES);
Very Small Aperture Terminal (VSAT)
transmit-only, transmit-and-receive, receive-only
satellite earth stations operating in the
4 GHz and 6 GHz frequency bands**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE**Internet:** secretariat@etsi.fr - <http://www.etsi.fr> - <http://www.etsi.org>

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998. All rights reserved.

Contents

Foreword	7
Introduction	7
1 Scope	9
2 Normative references	10
3 Definitions and abbreviations	10
3.1 Definitions	10
3.2 Abbreviations	12
4 Requirements	12
4.1 Off-axis spurious radiation	12
4.1.1 Justification	12
4.1.2 Specification	13
4.1.2.1 Transmit VSAT	13
4.1.2.2 Receive-only VSAT	14
4.1.3 Conformance test	14
4.2 On-axis spurious radiation for transmit VSAT	14
4.2.1 Justification	14
4.2.2 Specification	14
4.2.2.1 Specification 1: Carrier-on state	14
4.2.2.2 Specification 2: Carrier-off state and transmission disabled state	15
4.2.3 Conformance test	15
4.3 Off-axis EIRP emission density (co-polar and cross-polar) within the band 5,850 GHz to 6,650 GHz	15
4.3.1 Justification	15
4.3.2 Specification	15
4.3.3 Conformance test	16
4.4 Transmit polarization discrimination (linear) or voltage axial ratio (circular)	16
4.4.1 Justification	16
4.4.2 Specification	16
4.4.2.1 Specification 1	16
4.4.2.2 Specification 2	16
4.4.3 Conformance test	16
4.5 Carrier suppression	16
4.5.1 Justification	16
4.5.2 Specification	16
4.5.3 Conformance test	17
4.6 ElectroMagnetic Compatibility (EMC)	17
4.7 Mechanical (antenna pointing) for transmit VSAT	17
4.7.1 Justification	17
4.7.2 Specification	17
4.7.3 Conformance test	17
4.8 Control and monitoring for transmit VSAT	17
4.8.1 General	17
4.8.1.1 Control and Monitoring Functions (CMF)	18
4.8.1.2 Specification of states	19
4.8.2 Control Channels (CC)	19
4.8.2.1 Justification	19
4.8.2.2 Specification	20
4.8.2.3 Conformance test	20
4.8.3 Self monitoring functions	20
4.8.3.1 Processor monitoring	21
4.8.3.1.1 Justification	21

	4.8.3.1.2	Specification	21
	4.8.3.1.3	Conformance test.....	21
4.8.3.2		Transmit subsystem monitoring	21
	4.8.3.2.1	Justification	21
	4.8.3.2.2	Specification	21
	4.8.3.2.3	Conformance test.....	21
4.8.3.3		VSAT transmission validation	21
	4.8.3.3.1	VSAT transmission validation by the CCMF	21
	4.8.3.3.1.1	Justification	21
	4.8.3.3.1.2	Specification	22
	4.8.3.3.1.3	Conformance test.....	22
	4.8.3.3.2	VSAT transmission validation by receiving station(s)	22
	4.8.3.3.2.1	Justification	22
	4.8.3.3.2.2	Specification	22
	4.8.3.3.2.3	Conformance test.....	22
	4.8.3.3.3	Transmission validation for VSAT using external CC(s)	22
	4.8.3.3.3.1	Purpose	22
	4.8.3.3.3.2	Specification	22
	4.8.3.3.3.3	Conformance test.....	22
4.8.4		Reception of commands from the CCMF	22
	4.8.4.1	Disable message	23
	4.8.4.1.1	Justification	23
	4.8.4.1.2	Specification	23
	4.8.4.1.3	Conformance test.....	23
	4.8.4.2	Enable message	23
	4.8.4.2.1	Justification	23
	4.8.4.2.2	Specification	23
	4.8.4.2.3	Conformance test.....	23
4.8.5		Power-on/Reset	23
	4.8.5.1	Justification	23
	4.8.5.2	Specification	23
	4.8.5.3	Conformance test.....	23
5		Test methods	24
	5.1	Off-axis spurious radiation	24
	5.1.1	Test method.....	25
	5.1.1.1	Up to 1 000 MHz	25
	5.1.1.1.1	Test site.....	25
	5.1.1.1.2	Measuring receivers	25
	5.1.1.1.3	Procedure.....	26
	5.1.1.2	Above 1 000 MHz	26
	5.1.1.2.1	Identification of the significant frequencies of spurious radiation	26
	5.1.1.2.1.1	Test site.....	26
	5.1.1.2.1.2	Procedure.....	26
	5.1.1.2.2	Measurement of radiated power levels of identified spurious radiation	27
	5.1.1.2.2.1	Test site.....	27
	5.1.1.2.2.2	Procedure.....	27
	5.1.1.2.3	Measurement of conducted spurious radiation at the antenna flange.....	28
	5.1.1.2.3.1	Test site.....	28
	5.1.1.2.3.2	Procedure.....	28
	5.2	On-axis spurious radiation for transmit VSAT	29
	5.2.1	Test method.....	29
	5.2.1.1	Test site	29
	5.2.1.2	Method of measurement	29
	5.2.1.2.1	General.....	29
	5.2.1.2.2	Method of measurement at the antenna flange.....	29

	5.2.1.2.3	Method of measurement with a test antenna	30
5.3	Off-axis EIRP emission density within the band		31
5.3.1	Test method		31
	5.3.1.1	Transmit output power density	31
	5.3.1.1.1	Test site	31
	5.3.1.1.2	Method of measurement	31
	5.3.1.2	Antenna transmit gain	32
	5.3.1.2.1	General	32
	5.3.1.2.2	Test site	32
	5.3.1.2.3	Method of measurement	32
	5.3.1.3	Antenna transmit radiation patterns	33
	5.3.1.3.1	General	33
	5.3.1.3.2	Test site	33
	5.3.1.3.3	Method of measurement	33
	5.3.1.3.4	Co-polar radiation pattern - azimuth	34
	5.3.1.3.5	Co-polar radiation pattern - elevation	34
	5.3.1.3.6	Cross-polar radiation pattern - azimuth	35
	5.3.1.3.7	Cross-polar radiation pattern - elevation	35
	5.3.2	Computation of results	36
5.4	Transmit polarization discrimination (linear) or voltage axial ratio (circular)		36
	5.4.1	General	36
	5.4.2	Test method	36
	5.4.2.1	Method of measurement	36
5.5	Carrier suppression		38
	5.5.1	Test method	38
5.6	Antenna pointing for transmit VSAT		38
	5.6.1	Test method	38
5.7	Control and monitoring for transmit VSAT		39
	5.7.1	Test arrangement	39
	5.7.2	Control channels	40
	5.7.2.1	Test method	40
	5.7.2.1.1	Test method for internal CC(s)	40
	5.7.2.1.2	Test method for external CC(s)	40
	5.7.3	Processor monitoring	41
	5.7.3.1	Test method	41
	5.7.4	Transmit subsystem monitoring	41
	5.7.4.1	Test method	41
	5.7.5	VSAT transmission validation	41
	5.7.5.1	Test method for VSAT validation by the CCMF for VSAT using internal CC(s)	41
	5.7.5.2	Test method for VSAT validation by receiving station(s) for VSAT using internal CC(s)	41
	5.7.5.3	Test method for transmission validation for VSAT using external CC(s)	41
	5.7.6	Reception of commands from the CCMF	42
	5.7.6.1	Test method	42
	5.7.7	Power-on/Reset	42
	5.7.7.1	Test method	42
6.	Test methods for modified VSAT		42
6.1	Antenna subsystem replacement		43
Annex A (normative):	The TBR Requirements Table (TBR-RT)		44
Annex B (informative):	Pointing stability methodology		45
Annex C (informative):	Bibliography		46
History			47

Blank page

Foreword

This Technical Basis for Regulation (TBR) has been produced by the Satellite Earth Stations and Systems (SES) Technical Committee of the European Telecommunications Standards Institute (ETSI).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 83/189/EEC (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Council Directive 93/97/EEC of 29 October 1993 supplementing Directive 91/263/EEC in respect of satellite earth station equipment (the "SES Directive").

A common technical regulation may be established by the European Commission in accordance with the Directive.

Introduction

The Satellite Earth Station (SES) Directive [1] which supplements the Telecommunications Terminal Equipment (TTE) Directive [2] concerns the harmonisation of conditions for the placing on the market of such equipment.

Two classes of standard are applicable to SES equipment. European Telecommunication Standards (ETS) give the full technical specifications for this equipment, whereas Technical Bases for Regulation (TBR) give the essential requirements under the SES Directive [1] and the TTE Directive [2] for placing such equipment on the market. Receive-only equipment, not intended for terrestrial connection to the public telecommunications network, may be put into use. Nothing in this TBR is construed to prevent the use of Community internal production control procedures as set out in the annexes to the two Directives for such receive-only equipment. This TBR is based on ETS 300 332, ETS 300 333, ETS 300 160 and ETS 300 456 (see annex C, Bibliography).

Blank page

1 Scope

This Technical Basis for Regulation (TBR) specifies the technical requirements that apply to Very Small Aperture Terminal (VSAT) for compliance with Articles 4.1 and 4.3 of the SES Directive [1].

The VSAT has the following characteristics:

- the VSAT is operating in the following bands allocated to the Fixed Satellite Service (FSS), shared with other services, e.g. the Fixed Service (FS) and the Mobile Service (MS):
 - 5,85 GHz to 6,65 GHz (earth-to-space);
 - 3,40 GHz to 4,20 GHz (space-to-earth);
- the VSAT uses linear or circular polarization;
- the VSAT operates through a geostationary satellite at least 3° away from any other geostationary satellite operating in the same frequency band and covering the same area;
- the VSAT antenna diameter does not exceed 7,3 m, or equivalent effective area;
- the VSAT is either:
 - transmit-only VSAT: designed for transmission-only of radio-communications signals in the frequency band specified above; or
 - transmit-and-receive VSAT: designed for transmission-and-reception of radio-communications signals in the frequency band specified above; or
 - receive-only VSAT: designed for reception-only of radio-communications signals in the frequency band specified above;
- the VSAT is designed usually for unattended operation;
- the VSAT is operating as part of a satellite network (e.g. star, mesh or point-to-point) used for the distribution and/or exchange of information between users;
- the transmit-only and transmit-and-receive VSAT is controlled and monitored by a Centralized Control and Monitoring Function (CCMF). The CCMF is outside the scope of this TBR.

This TBR applies to the VSAT (including its ancillary equipment and its various terrestrial ports) operated under the conditions which are within the ranges of humidity, temperature and supply voltage declared by the manufacturer.

The requirements have been selected to ensure an adequate level of compatibility with other radio services. The levels, however, do not cover extreme cases which may occur in any location but with a low probability of occurrence.

This TBR may not cover those cases where a potential source of interference which is producing individually repeated transient phenomena or a continuous phenomenon is present, e.g. a radar or broadcast site in the near vicinity. In such a case it may be necessary to use special protection applied to either the source of interference, or the interfered part or both.

This TBR does not contain any requirement, recommendation or information about the installation of the VSAT.

Compliance of a VSAT to the requirements of this TBR does not imply compliance to any requirement related to the use of the VSAT (e.g. licensing requirements).

2 Normative references

This TBR incorporates by dated or undated reference, provisions from other publications. These references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to, or revisions of any of these publications apply to this TBR only when incorporated into it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] SES Directive: "Council Directive 93/97/EEC (1993) supplementing Directive 91/263/EEC in respect of satellite earth station equipment".
- [2] TTE Directive: "Council Directive 91/263/EEC (1991) on the approximation of the laws of Member States concerning telecommunications terminal equipment, including the mutual recognition of their conformity".
- [3] ETS 300 673 (1996): "Radio Equipment and Systems (RES); ElectroMagnetic Compatibility (EMC) standard for 4/6 GHz and 11/12/14 GHz Very Small Aperture Terminal (VSAT) equipment and 11/12/13/14 GHz Satellite News Gathering (SNG) Transportable Earth Station (TES) equipment".
- [4] CISPR N 16-1 (1993): "Specification for radio interference measuring apparatus and measurements methods; Part 1: Radio disturbance and immunity measuring apparatus" (Annex G: Validation of the open area test site for the frequency range of 30 MHz to 1 000 MHz).

NOTE: This TBR also contains a number of informative references which have been included to indicate the sources from which various material has been derived, hence they do not have an associated normative reference number. Details of these publications are given in annex C (Bibliography).

3 Definitions and abbreviations

3.1 Definitions

For the purposes of this TBR, the following definitions apply:

ancillary equipment: Equipment used in connection with the VSAT is considered ancillary if the three following conditions are met:

- a) the equipment is intended for use in conjunction with the VSAT to provide additional operational and/or control features (e.g. to extend control to another position or location); and
- b) the equipment cannot be used on a stand alone basis, to provide user functions independently of the VSAT; and
- c) the absence of the equipment does not inhibit the operation of the VSAT.

carrier-off state: A VSAT is in this state when it is authorized by the Centralized Control and Monitoring Functions (CCMF) to transmit, but when it does not transmit any signal.

NOTE 1: The existence of a carrier-off state depends on the system of transmission used. For VSAT designed for continuous transmission mode there may be no carrier-off state.

carrier-on state: A VSAT is in this state when it is authorized by the CCMF to transmit and when it transmits a signal.

Centralized Control and Monitoring Functions (CCMF): A set of functional entities that, at system level, monitor and control the correct operation of all transmit VSAT in a network.

Control Channel (CC): A channel or channels by which VSAT receive control information from the CCMF.