



# SLOVENSKI STANDARD SIST EN 50126-1:2001

01-februar-2001

Železniška aplikacija - Specifikacija in dokazila zanesljivosti, razpoložljivosti, vzdržljivosti in varnosti (RAMS) - Del 1: Osnovne zahteve in splošni postopek

Railway applications - The specification and demonstration of Reliability, Availability, Maintainability and Safety (RAMS) - Part 1: Basic requirements and generic process

Bahnanwendungen - Spezifikation und Nachweis der Zuverlässigkeit, Verfügbarkeit, Instandhaltbarkeit, Sicherheit (RAMS) - Teil 1 Grundlegende Anforderungen und genereller Prozess

(standards.iteh.ai)

Applications ferroviaires - Spécification et démonstration de la fiabilité, de la disponibilité, de la maintenabilité et de la sécurité (FDMS) - Partie 1: Exigences de base et procédés génériques

Ta slovenski standard je istoveten z: EN 50126-1:1999

### ICS:

29.280	Električna vozila	Electric traction equipment
45.020	Železniška tehnika na splošno	Railway engineering in general

**SIST EN 50126-1:2001** en

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 50126-1:2001

<https://standards.iteh.ai/catalog/standards/sist/de607c98-c2ef-4454-8192-fb18c7bfa68/sist-en-50126-1-2001>



Corrigendum to EN 50126:1999

English version

---

Title page

**Replace** the reference of the standard by "EN 50126-1".

**Replace** the title by:

**Railway applications –  
The specification and demonstration of  
Reliability, Availability, Maintainability and Safety (RAMS)  
Part 1: Basic requirements and generic process**

iTeh STANDARD PREVIEW

Applications ferroviaires –  
Spécification et démonstration  
de la fiabilité, de la disponibilité,  
de la maintenabilité et de la sécurité  
(FDMS)  
Partie 1: Exigences de base et procédés  
génériques

Bahnanwendungen –  
Spezifikation und Nachweis  
der Zuverlässigkeit, Verfügbarkeit,  
Instandhaltbarkeit, Sicherheit (RAMS)  
Teil 1: Grundlegende Anforderungen und  
genereller Prozess

Foreword

**Add** after the implementation dates:

To assist the user in the application of this standard for safety and for managing RAM performance in the rolling stock procurement process, the following application guides have been produced:

- |                              |   |
|------------------------------|---|
| CLC/TR 50126-2 <sup>1)</sup> | Guide to the application of EN 50126-1 for safety             |
| CLC/TR 50126-3               | Guide to the application of EN 50126-1 for rolling stock RAMS |
- 

May 2006

---

<sup>1)</sup> In preparation.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 50126-1:2001

<https://standards.iteh.ai/catalog/standards/sist/de607c98-c2ef-4454-8192-fb18c7bfa68/sist-en-50126-1-2001>

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**EN 50126**

September 1999

ICS 29.280; 45.020

English version

**Railway applications - The specification and demonstration of Reliability,  
Availability, Maintainability and Safety (RAMS)**

Applications ferroviaires - Spécification  
et démonstration de la fiabilité, de la  
disponibilité, de la maintenabilité et de la  
sécurité (FDMS)

Bahnanwendungen - Spezifikation und  
Nachweis der Zuverlässigkeit,  
Verfügbarkeit, Instandhaltbarkeit,  
Sicherheit (RAMS)

This European Standard was approved by CENELEC on 1998-10-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

[SIST EN 50126-1:2001](https://standards.iteh.ai/catalog/standards/sist/de607c98-c2ef-4454-8192-fb18c7b6ca68/sist-en-50126-1-2001)

<https://standards.iteh.ai/catalog/standards/sist/de607c98-c2ef-4454-8192-fb18c7b6ca68/sist-en-50126-1-2001>

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Central Secretariat: rue de Stassart 35, B - 1050 Brussels**

## Foreword

This European Standard was prepared by the Technical Committee CENELEC TC 9X, Electrical and electronic applications in railways.

The text of the draft was submitted to the formal vote and was approved by CENELEC as EN50126 on 1998-10-01.

The following dates were fixed:

- latest date by which the EN has to be implemented  
at national level by publication of an identical  
national standard or by endorsement (dop) 2000-04-01
- latest date by which the national standards conflicting  
with the EN have to be withdrawn (dow) 2000-04-01

Annexes designated “normative” are part of the body of the standard.

Annexes designated “informative” are given for information only.

In this standard, annexes A to E are informative.



**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 50126-1:2001

<https://standards.iteh.ai/catalog/standards/sist/de607c98-c2ef-4454-8192-fb18c7bfa68/sist-en-50126-1-2001>

## Content

	Page
Introduction .....	5..
1 Scope .....	6..
2 Normative references .....	7..
3 Definitions .....	8..
4 Railway RAMS .....	11.
4.1 Introduction.....	11
4.2 Railway RAMS and quality of service .....	11
4.3 Elements of railway RAMS.....	12
4.4 Factors influencing railway RAMS .....	14
4.4.1 General.....	14
4.4.2 Categories of factors .....	14
4.4.3 Management of factors.....	18
4.5 The means to achieve railway RAMS requirements .....	19
4.5.1 General.....	19
4.5.2 RAMS specification: .....	19
4.6 Risk .....	20
4.6.1 Risk concept:.....	20
4.6.2 Risk analysis: .....	20
4.6.3 Risk evaluation and acceptance .....	21
4.7 Safety integrity .....	22
4.8 Fail-safe concept.....	24
5 Management of railway RAMS.....	25
5.1 General.....	25
5.2 System lifecycle .....	25
5.3 Application of this standard .....	31
6 RAMS lifecycle.....	34
6.1 Phase 1: Concept.....	34
6.2 Phase 2: System definition and application conditions .....	36
6.3 Phase 3: Risk analysis .....	39
6.4 Phase 4: System requirements .....	41
6.5 Phase 5: Apportionment of system requirements .....	45
6.6 Phase 6: Design and implementation .....	47
6.7 Phase 7: Manufacturing .....	50
6.8 Phase 8: Installation .....	52
6.9 Phase 9: System validation (including safety acceptance and commissioning) .....	54
6.10 Phase 10: System acceptance .....	56
6.11 Phase 11: Operation and maintenance.....	57
6.12 Phase 12: Performance monitoring.....	58
6.13 Phase 13: Modification and retrofit .....	59
6.14 Phase 14: Decommissioning and disposal .....	60
Annex A (informative) Outline of RAMS specification - example.....	61
Annex B (informative) RAMS programme.....	66
Annex C (informative) Examples of parameters for railway.....	71
Annex D (informative) Examples of some risk acceptance principles.....	73
Annex E (informative) Responsibilities within the RAMS process throughout the lifecycle.....	76

## Figures

Figure 1: Quality of Service and Railway RAMS.....	12
Figure 2: Inter-relation of Railway RAMS elements.....	12
Figure 3: Effects of Failures Within a System.....	13
Figure 4: Influences on RAMS.....	14
Figure 5: Factors Influencing Railway RAMS.....	16
Figure 6: Example of a Cause/Effect Diagram.....	18
Figure 7: Certified Products in Safety Systems.....	23
Figure 8: System Lifecycle.....	26
Figure 9: Project Phase Related Tasks (Sheet 1 of 2).....	27
Figure 9: Project Phase Related Tasks (Sheet 2 of 2).....	28
Figure 10: The V Representation .....	30
Figure 11: Verification and Validation.....	31
Figure 12:RAMS Eng. and Manag't Implemented within a System Realisation Process.....	33

## Tables

Table 1: RAM Failure Categories.....	19
Table 2: Frequency of Occurrence of Hazardous Events.....	20
Table 3: Hazard Severity Level.....	21
Table 4: Frequency - Consequence Matrix.....	21
Table 5: Qualitative Risk Categories.....	22
Table 6: Typical Example of Risk Evaluation and Acceptance.....	22
Table B.1: Example of a Basic RAMS Programme Outline.....	67
Table C.1: Examples of Reliability Parameters.....	71
Table C.2: Examples of Maintainability Parameters.....	71
Table C.3: Examples of Availability Parameters.....	72
Table C.4: Examples of Logistic Support Parameters.....	72
Table C.5: Examples of Safety Performance Parameters.....	72



## Introduction

This European Standard provides Railway Authorities and the railway support industry, throughout the European Union, with a process which will enable the implementation of a consistent approach to the management of reliability, availability, maintainability and safety, denoted by the acronym RAMS. Processes for the specification and demonstration of RAMS requirements are cornerstones of this standard. This European Standard aims to promote a common understanding and approach to the management of RAMS.

This European Standard can be applied systematically by a railway authority and railway support industry, throughout all phases of the lifecycle of a railway application, to develop railway specific RAMS requirements and to achieve compliance with these requirements. The systems-level approach defined by this European Standard facilitates assessment of the RAMS interactions between elements of complex railway applications.

This European Standard promotes co-operation between a railway authority and railway support industry, within a variety of procurement strategies, in the achievement of an optimal combination of RAMS and cost for railway applications. Adoption of this European Standard will support the principles of the European Single Market and facilitate European railway inter-operability.

The process defined by this European Standard assumes that railway authorities and railway support industry have business-level policies addressing Quality, Performance and Safety. The approach defined in this standard is consistent with the application of quality management requirements contained within the ISO 9000 series of International standards.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 50126-1:2001

<https://standards.iteh.ai/catalog/standards/sist/de607c98-c2ef-4454-8192-fb18c7bfa68/sist-en-50126-1-2001>

## 1 Scope

### 1.1 This European Standard:

- defines RAMS in terms of reliability, availability, maintainability and safety and their interaction;
- defines a process, based on the system lifecycle and tasks within it, for managing RAMS;
- enables conflicts between RAMS elements to be controlled and managed effectively;
- defines a systematic process for specifying requirements for RAMS and demonstrating that these requirements are achieved;
- addresses railway specifics;
- does not define RAMS targets, quantities, requirements or solutions for specific railway applications;
- does not specify requirements for ensuring system security;
- does not define rules or processes pertaining to the certification of railway products against the requirements of this standard;
- does not define an approval process by the safety regulatory authority.

### 1.2. This European Standard is applicable:

- to the specification and demonstration of RAMS for all railway applications and at all levels of such an application, as appropriate, from complete railway routes to major systems within a railway route, and to individual and combined sub-systems and components within these major systems, including those containing software; in particular:
  - to new systems;
  - to new systems integrated into existing systems in operation prior to the creation of this standard, although it is not generally applicable to other aspects of the existing system;
  - to modifications of existing systems in operation prior to the creation of this standard, although it is not generally applicable to other aspects of the existing system.
- at all relevant phases of the lifecycle of an application;
- for use by Railway Authorities and the railway support industry.

NOTE: Guidance on the applicability is given in the requirements of this standard.

<https://standards.iteh.ai/catalog/standards/sist/de607c98-c2ef-4454-8192-fb18c7b6ca68/sist-en-50126-1-2001>

## 2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this standard only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

EN ISO 9001	1994	Quality systems – Model for quality assurance in design, development, production, installation and servicing
EN ISO 9002	1994	Quality systems – Model for quality assurance in production, installation and servicing
EN ISO 9003	1994	Quality systems – Model for quality assurance in final inspection and test
EN 50128 (*)		Railway applications - Software for railway control and protection systems
ENV 50129	1998	Railway applications - Safety related electronic systems for signalling
IEC 60050(191)	1990	International Electrotechnical Vocabulary Chapter 191: Dependability and quality of service
IEC 61508	series	Functional safety of electrical/electronic/programmable electronic safety-related systems

## iTeh STANDARD PREVIEW (standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/de607c98-c2ef-4454-8192-fb18c7bfa68/sist-en-50126-1-2001>

---

(\*) In preparation

### 3 Definitions

For the purposes of this standard, the following definitions apply.

- 3.1 **apportionment:** A process whereby the RAMS elements for a system are sub-divided between the various items which comprise the system to provide individual targets.
- 3.2 **assessment:** The undertaking of an investigation in order to arrive at a judgement, based on evidence, of the suitability of a product.
- 3.3 **audit:** A systematic and independent examination to determine whether the procedures specific to the requirements of a product comply with the planned arrangements, are implemented effectively and are suitable to achieve the specified objectives.
- 3.4 **availability:** The ability of a product to be in a state to perform a required function under given conditions at a given instant of time or over a given time interval assuming that the required external resources are provided.
- 3.5 **commissioning:** A collective term for the activities undertaken to prepare a system or product prior to demonstrating that it meets its specified requirements.
- 3.6 **common cause failure:** A failure which is the result of an event(s) which causes a coincidence of failure states of two or more components leading to a system failing to perform its required function.
- 3.7 **compliance:** A demonstration that a characteristic or property of a product satisfies the stated requirements.
- 3.8 **configuration management:** A discipline applying technical and administrative direction and surveillance to identify and document the functional and physical characteristics of a configuration item, control change to those characteristics, record and report change processing and implementation status and verify compliance with specified requirements.
- 3.9 **corrective maintenance:** The maintenance carried out after fault recognition and intended to put a product into a state in which it can perform a required function.
- 3.10 **dependent failure:** The failure of a set of events, the probability of which cannot be expressed as the simple product of the unconditional probabilities of the individual events.
- 3.11 **down time:** The time interval during which a product is in a down state. (IEC 60050(191))
- 3.12 **failure cause:** The circumstances during design, manufacture or use which have led to a failure. (IEC 60050(191))
- 3.13 **failure mode:** The predicted or observed results of a failure cause on a stated item in relation to the operating conditions at the time of the failure.
- 3.14 **failure rate:** The limit, if this exists, of the ratio of the conditional probability that the instant of time,  $T$ , of a failure of a product falls within a given time interval  $(t, t+\Delta t)$  and the length of this interval,  $\Delta t$ , when  $\Delta t$  tends towards zero, given that the item is in an up state at the start of the time interval.
- 3.15 **fault mode:** One of the possible states of a faulty product for a given required function. (IEC 60050(191))
- 3.16 **fault tree analysis:** An analysis to determine which fault modes of the product, sub-products or external events, or combinations thereof, may result in a stated fault mode of the product, presented in the form of a fault tree.
- 3.17 **hazard:** A physical situation with a potential for human injury.

- 3.18 **hazard log:** The document in which all safety management activities, hazards identified, decisions made and solutions adopted are recorded or referenced. Also known as a "Safety Log". (ENV 50129)
- 3.19 **logistic support:** The overall resources which are arranged and organised in order to operate and maintain the system at the specified availability level at the required lifecycle cost.
- 3.20 **maintainability:** The probability that a given active maintenance action, for an item under given conditions of use can be carried out within a stated time interval when the maintenance is performed under stated conditions and using stated procedures and resources. (IEC 60050(191))
- 3.21 **maintenance:** The combination of all technical and administrative actions, including supervision actions, intended to retain a product in, or restore it to, a state in which it can perform a required function. (IEC 60050(191))
- 3.22 **maintenance policy:** A description of the inter-relationship between the maintenance echelons, the indenture levels and the levels of maintenance to be applied for the maintenance of an item. (IEC 60050(191))
- 3.23 **mission:** An objective description of the fundamental task performed by a system.
- 3.24 **mission profile:** Outline of the expected range and variation in the mission with respect to parameters such as time, loading, speed, distance, stops, tunnels, etc., in the operational phases of the lifecycle.
- 3.25 **preventive maintenance:** The maintenance carried out at pre-determined intervals or according to prescribed criteria and intended to reduce the probability of failure or the degradation of the functioning of an item. (IEC 60050(191))
- 3.26 **railway authority:** The body with the overall accountability to a Regulator for operating a railway system.
- NOTE: Railway authority accountabilities for the overall system or its parts and lifecycle activities are sometimes split between one or more bodies or entities. For example:
- the owner(s) of one or more parts of the system assets and their purchasing agents;
  - the operator of the system;
  - the maintainer(s) of one or more parts of the system;
  - etc.
- Such splits are based on either statutory instruments or contractual agreements. Such responsibilities should therefore be clearly stated at the earliest stages of a system lifecycle.
- 3.27 **railway support industry:** Generic term denoting supplier(s) of complete railway systems, their sub-systems or component parts.
- 3.28 **RAM programme:** A documented set of time scheduled activities, resources and events serving to implement the organisational structure, responsibilities, procedures, activities, capabilities and resources that together ensure that an item will satisfy given RAM requirements relevant to a given contract or project. (IEC 60050(191)).
- 3.29 **RAMS:** An acronym meaning a combination of Reliability, Availability, Maintainability and Safety.
- 3.30 **reliability:** The probability that an item can perform a required function under given conditions for a given time interval ( $t_1$ ,  $t_2$ ). (IEC 60050(191))
- 3.31 **reliability growth:** A condition characterised by a progressive improvement of a reliability performance measure of an item with time. (IEC 60050(191))

- 3.32 **repair:** That part of a corrective maintenance in which manual actions are performed on a item. (IEC 60050(191))
- 3.33 **restoration:** That event when an item regains the ability to perform a required function after a fault. (IEC 60050(191))
- 3.34 **risk:** The probable rate of occurrence of a hazard causing harm and the degree of severity of the harm.
- 3.35 **safety:** Freedom from unacceptable risk of harm.
- 3.36 **safety case:** The documented demonstration that the product complies with the specified safety requirements.
- 3.37 **safety integrity:** The likelihood of a system satisfactorily performing the required safety functions under all the stated conditions within a stated period of time.
- 3.38 **safety integrity level (SIL):** One of a number of defined discrete levels for specifying the safety integrity requirements of the safety functions to be allocated to the safety related systems. Safety Integrity Level with the highest figure has the highest level of safety integrity.
- 3.39 **safety plan:** A documented set of time scheduled activities, resources and events serving to implement the organisational structure, responsibilities, procedures, activities, capabilities and resources that together ensure that an item will satisfy given safety requirements relevant to a given contract or project.
- 3.40 **safety regulatory authority:** Often a national government body responsible for setting or agreeing the safety requirements for a railway and ensuring that the railway complies with the requirements.
- 3.41 **system lifecycle:** The activities occurring during a period of time that starts when a system is conceived and end when the system is no longer available for use, is decommissioned and is disposed.
- 3.42 **systematic failures:** Failures due to errors in any safety lifecycle activity, within any phase, which cause it to fail under some particular combination of inputs or under some particular environmental condition.
- 3.43 **tolerable risk:** The maximum level of risk of a product that is acceptable to the Railway Authority.
- 3.44 **validation:** Confirmation by examination and provision of objective evidence that the particular requirements for a specific intended use have been fulfilled.
- 3.45 **verification:** Confirmation by examination and provision of objective evidence that the specified requirements have been fulfilled.

NOTE For clarification between verification and validation see figure 11 and 5.2.9.

<https://standards.iteh.ai/SIST/EN-50126-1-2001>  
fb18c7bfa68/sist-en-50126-1-2001

## 4 Railway RAMS

### 4.1 Introduction

- 4.1.1 Clause 4 of this standard provides baseline information on the subject of RAMS and RAMS engineering. The purpose of this clause is to provide the reader with sufficient background information to enable the effective application of this standard to railway systems.
- 4.1.2 Railway RAMS is a major contributor to the Quality of Service provided by a Railway Authority. Railway RAMS is defined by several contributory elements; consequently, this clause of this European Standard is structured as follows:
- a) Subclause 4.2 examines the relationship between railway RAMS and quality of service.
  - b) Subclauses 4.3 to 4.8 examine aspects of railway RAMS, namely:
    - the elements of RAMS;
    - the factors which influence and means to achieve RAMS;
    - risk and safety integrity.
- 4.1.3 Where possible within this clause, internationally defined terms are used but where new terms are required or where recognised terms have been made specific in the railway context, these are defined in clause 3 of this standard.
- 4.1.4 Within this European Standard, the sequence "system, sub-system, component" is used to demonstrate the breakdown of any complete application into its constituent parts. The precise boundary of each term (system, sub-system and component) will depend upon the specific application.
- 4.1.5 A system can be defined as an assembly of sub-systems and components, connected together in an organised way, to achieve specified functionality. Functionality is assigned to sub-systems and components within a system and the behaviour and state of the system is changed if the sub-system or component functionality changes. A system responds to inputs to produce specified outputs, whilst interacting with an environment.

### 4.2 Railway RAMS and quality of service

- 4.2.1 This subclause introduces the link between RAMS and quality of service for an undertaking.
- 4.2.2 RAMS is a characteristic of a system's long term operation and is achieved by the application of established engineering concepts, methods, tools and techniques throughout the lifecycle of the system. The RAMS of a system can be characterised as a qualitative and quantitative indicator of the degree that the system, or the sub-systems and components comprising that system, can be relied upon to function as specified and to be both available and safe. System RAMS, in the context of this European Standard, is a combination of reliability, availability, maintainability and safety, RAMS.
- 4.2.3 The goal of a railway system is to achieve a defined level of rail traffic in a given time, safely. Railway RAMS describes the confidence with which the system can guarantee the achievement of this goal. Railway RAMS has a clear influence on the quality with which the service is delivered to the customer. Quality of Service is influenced by other characteristics concerning functionality and performance, for example frequency of service, regularity of service and fare structure. This relationship is shown in figure 1.