This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.

INTERNATIONAL

Designation:B348–05^{€1} Designation: B 348 – 06

Standard Specification for Titanium and Titanium Alloy Bars and Billets¹

This standard is issued under the fixed designation B 348; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

e¹Nore—Tensile strength for Grade 3 and Grade 4 in Table3 was corrected editorially in January 2006.

1. Scope

- 1.1 This specification² covers annealed titanium and titanium alloy bars and billets as follows:
- 1.1.1 Grade 1-Unalloyed titanium,
- 1.1.2 *Grade* 2—Unalloyed titanium,
- 1.1.3 Grade 3-Unalloyed titanium,
- 1.1.4 Grade 4-Unalloyed titanium,
- 1.1.5 Grade 5-Titanium alloy (6 % aluminum, 4 % vanadium),
- 1.1.6 Grade 6—Titanium alloy (5 % aluminum, 2.5 % tin),
- 1.1.7 Grade 7-Unalloyed titanium plus 0.12 to 0.25 % palladium,
- 1.1.8 Grade 9-Titanium alloy (3 % aluminum, 2.5 % vanadium),
- 1.1.9 Grade 11-Unalloyed titanium plus 0.12 to 0.25 % palladium,
- 1.1.10 Grade 12—Titanium alloy (0.3 % molybdenum, 0.8 % nickel),
- 1.1.11 Grade 13—Titanium alloy (0.5 % nickel, 0.05 % ruthenium),
- 1.1.12 Grade 14—Titanium alloy (0.5 % nickel, 0.05 % ruthenium),
- 1.1.13 Grade 15—Titanium alloy (0.5 % nickel, 0.05 % ruthenium),
- 1.1.14 Grade 16—Unalloyed titanium plus 0.04 to 0.08 % palladium,
- 1.1.15 Grade 17-Unalloyed titanium plus 0.04 to 0.08 % palladium,
- 1.1.16 Grade 18-Titanium alloy (3 % aluminum, 2.5 % vanadium) plus 0.04 to 0.08 % palladium,
- 1.1.17 Grade 19-Titanium alloy (3 % aluminum, 8 % vanadium, 6 % chromium, 4 % zirconium, 4 % molybdenum),

1.1.18 *Grade* 20—Titanium alloy (3 % aluminum, 8 % vanadium, 6 % chromium, 4 % zirconium, 4 % molybdenum) plus 0.04 %–0.08 % palladium,

- 1.1.19 Grade 21—Titanium alloy (15 % molybdenum, 3 % aluminum, 2.7 % niobium, 0.25 % silicon),
- 1.1.20 Grade 23-Titanium alloy (6 % aluminum, 4 % vanadium with extra low interstitial elements, ELI),
- 1.1.21 Grade 24—Titanium alloy (6 % aluminum, 4 % vanadium) plus 0.04 % to 0.08 % palladium,
- 1.1.22 Grade 25—Titanium alloy (6 % aluminum, 4 % vanadium) plus 0.3 % to 0.8 % nickel and 0.04 % to 0.08 % palladium,
- 1.1.23 Grade 26-Unalloyed titanium plus 0.08 to 0.14 % ruthenium,
- 1.1.24 Grade 27-Unalloyed titanium plus 0.08 to 0.14 % ruthenium,
- 1.1.25 Grade 28—Titanium alloy (3 % aluminum, 2.5 % vanadium plus 0.08–0.14 % ruthenium),
- 1.1.26 Grade 29-Titanium alloy (6 % aluminum, 4 % vanadium, extra low interstitial, ELI plus 0.08-0.14 % ruthenium),
- 1.1.27 Grade 30—Titanium alloy (0.3 % cobalt, 0.05 % palladium),
- 1.1.28 Grade 31—Titanium alloy (0.3 % cobalt, 0.05 % palladium),
- 1.1.29 Grade 32-Titanium alloy (5 % aluminum, 1 % tin, 1 % zirconium, 1 % vanadium, 0.8 % molybdenum),
- 1.1.30 Grade 33-Titanium alloy (0.4 % nickel, 0.015 % palladium, 0.025 % ruthenium, 0.15 % chromium),
- 1.1.31 Grade 34—Titanium alloy (0.4 % nickel, 0.015 % palladium, 0.025 % ruthenium, 0.15 % chromium),
- 1.1.32 Grade 35—Titanium alloy (4.5 % aluminum, 2 % molybdenum, 1.6 % vanadium, 0.5 % iron, 0.3 % silicon),
- 1.1.33 Grade 36-Titanium alloy (45 % niobium), and
- 1.1.34 Grade 37—Titanium Alloy (1.5% aluminum).

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.

¹ This specification is under the jurisdiction of ASTM Committee B10 on Reactive and Refractory Metals and Alloys and is the direct responsibility of Subcommittee B10.01 on Titanium.

Current edition approved Jan. 1, 2005. Published February 2005. Originally approved in 1959. Last previous edition approved in 2003 as B348–03. Current edition approved April 1, 2006. Published May 2006. Originally approved in 1959. Last previous edition approved in 2005 as B 348–05^{s1}

 $^{^{2}}$ For ASME Boiler and Pressure Vessel Code applications see related Specification SB-348 in Section II of that Code.

1.2 - Titanium alloy (1.5 % aluminum), and

1.1.35 Grade 38—Titanium alloy (4 % aluminum, 2.5 % vanadium, 1.5 % iron).

<u>1.2</u> The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

2. Referenced Documents

- 2.1 ASTM Standards: ³
- E 8 Test Methods for Tension Testing of Metallic Materials
- E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- E 120 Test Methods for Chemical Analysis of Titanium and Titanium Alloys
- E 1409 Test Method for Determination of Oxygen and Nitrogen in Titanium and Titanium Alloys by the Inert Gas Fusion Technique
- E 1447Test Method for Determination of Hydrogen in Titanium and Titanium Alloys by the Inert Gas Fusion Thermal Conductivity/Infrared Detection Method <u>Test Method for Determination of Hydrogen in Titanium and Titanium Alloys by the</u> Inert Gas Fusion Thermal Conductivity/Infrared Detection Method

TABLE 1	Chemical	Requirements ^A

Flowent		Composition, %										
Element	Grade 1	Grade 2	Grade 3	Grade 4	Grade 5	Grade 6	Grade 7	Grade 9	Grade 11	Grade 12		
Nitrogen, max Carbon, max Hydrogen, ^{B,C} max Iron, max	$ \begin{array}{r} 0.03 \\ 0.08 \\ 0.015 \\ 0.20 \\ 0.18 \end{array} $	$ \begin{array}{r} 0.03 \\ 0.08 \\ 0.015 \\ 0.30 \\ 0.25 \end{array} $	$ \begin{array}{r} 0.05 \\ 0.08 \\ 0.015 \\ 0.30 \\ 0.25 \end{array} $	$ \begin{array}{r} 0.05 \\ 0.08 \\ 0.015 \\ 0.50 \\ 0.40 \end{array} $	$ \begin{array}{r} 0.05 \\ 0.08 \\ 0.015 \\ 0.40 \\ 0.20 \end{array} $	0.03 0.08 0.015 0.50 0.20	0.03 0.08 0.015 0.30 0.25	0.03 0.08 0.015 0.25 0.15	0.03 0.08 0.015 0.20 0.18	0.03 0.08 0.015 0.30 0.25		
Aluminum Vanadium Tin Ruthenium	<u></u> 	<u></u> 			<u>5.5–6.75</u> <u>3.5–4.5</u> 	<u>4.0–6.0</u> <u></u> <u>2.0–3.0</u>	<u></u>	<u>2.5–3.5</u> 2.0–3.0	<u></u> 	<u></u>		
Palladium Cobalt Molybdenum Chromium	 		Doc			Evie	0.12-0.25 		0.12–0.25 	 0.2-0.4 		
Niobium Zirconium Silicon Residuals, ^{D,E,F}	 0.1	 0.1	 0.1	 	<u></u> <u></u> <u></u>	<u></u> <u></u> <u>0.1</u>	 0.1	 0.1	 0.1	<u>0.0-0.9</u> 0.1		
max each Residuals, ^{D,E,F} max total Titanium ^G	<u>0.4</u>	<u>0.4</u>	<u>0.4</u>	8 ac 8 - 1 a 8 0.4 balance	/-4c0/-a4 0.4	400-a5070 0.4 balance	0 00 e78dc <u>0.4</u>	/astm-b34 0.4	<u>0.4</u>	<u>0.4</u>		
<u>Internetine</u>	Composition, %											
Element	Grade 13	Grade 14	Grade 15	Grade 16	Grade 17	Grade 18	Grade 19	Grade 20	Grade 21	Grade 23		
Nitrogen, max Carbon, max Hydrogen, ^{B,C} max Iron, max Oxygen, max Aluminum Vanadium Tin Ruthenium Palladium Cobalt Molybdenum Chromium Nickel Niobium	0.03 0.08 0.015 0.20 0.10 0.04-0.06 0.4-0.6 	0.03 0.08 0.015 0.30 0.15 0.04-0.06 0.4-0.6 	0.05 0.08 0.015 0.30 0.25 0.04-0.06 0.4-0.6 	0.03 0.08 0.015 0.30 0.25 0.04–0.08 	0.03 0.08 0.015 0.20 0.18 0.04–0.08 	0.03 0.08 0.015 0.25 0.15 2.5–3.5 2.0–3.0 0.04–0.08 	$\begin{array}{c} 0.03 \\ \hline 0.05 \\ 0.02 \\ \hline 0.30 \\ \hline 0.12 \\ \hline 3.0-4.0 \\ \hline 7.5-8.5 \\ \hline \cdots \\ \hline \vdots \\ \hline \hline \hline \vdots \\ \hline \hline \hline \hline$	$\begin{array}{c} 0.03 \\ \hline 0.05 \\ \hline 0.02 \\ \hline 0.30 \\ \hline 0.12 \\ \hline 3.0-4.0 \\ \hline 7.5-8.5 \\ \hline \\ $	$\begin{array}{c} 0.03 \\ \hline 0.05 \\ \hline 0.015 \\ \hline 0.40 \\ \hline 0.17 \\ \hline 2.5-3.5 \\ \hline \\ $	0.03 0.08 0.0125 0.25 0.13 5.5-6.5 3.5-4.5 		

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.