



**White Space Devices (WSD);
Wireless Access Systems operating in the 470 MHz to 790 MHz
TV broadcast band;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU**

PREVIEW
https://standards.iteh.ai/catalog/standards/si/65949158-1909-4c86-80fe-0b855399a1b1/etsi-en-301-598-v2-2017-04

Reference

REN/BRAN-0060019

Keywords

access, broadband, CRS, FWA, LAN, M2M,
mobile, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
oneM2M logo is protected for the benefit of its Members
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction	7
1 Scope.....	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions.....	10
3.2 Symbols.....	12
3.3 Abbreviations	13
4 Technical requirements specifications	13
4.1 Environmental profile.....	13
4.2 Conformance requirements	14
4.2.1 Meeting the Directive requirements.....	14
4.2.2 Equipment types	14
4.2.2.1 Definition	14
4.2.2.2 Equipment Type A	14
4.2.2.3 Equipment Type B	14
4.2.3 Nominal Channel Bandwidth and Total Nominal Channel Bandwidth.....	14
4.2.3.1 Definitions.....	14
4.2.3.2 Requirements	14
4.2.3.3 Conformance.....	15
4.2.4 RF power and RF power spectral density	15
4.2.4.1 Definitions.....	15
4.2.4.1.1 RF power	15
4.2.4.1.2 RF power spectral density	15
4.2.4.2 Limits	15
4.2.4.3 Conformance.....	15
4.2.5 Transmitter unwanted emissions.....	15
4.2.5.1 Transmitter unwanted emissions outside the 470 MHz to 790 MHz band.....	15
4.2.5.1.1 Definition.....	15
4.2.5.1.2 Limits	16
4.2.5.1.3 Conformance	16
4.2.5.2 Transmitter unwanted emissions within the 470 MHz to 790 MHz band.....	16
4.2.5.2.1 Definition.....	16
4.2.5.2.2 Limits	16
4.2.5.2.3 Conformance	16
4.2.6 Transmitter Reverse Intermodulation Attenuation.....	17
4.2.6.1 Definition	17
4.2.6.2 Limits	17
4.2.6.3 Conformance.....	17
4.2.7 Control and monitoring.....	17
4.2.7.1 Control and monitoring mechanisms	17
4.2.7.2 TVWSDB identification.....	18
4.2.7.2.1 Applicability	18
4.2.7.2.2 Definition.....	18
4.2.7.2.3 Requirements	18
4.2.7.2.4 Conformance	18
4.2.7.3 Data exchange and compliance with parameters.....	18
4.2.7.3.1 Applicability	18
4.2.7.3.2 Device parameters, operational parameters and channel usage.....	18
4.2.7.3.3 Transmission in compliance with parameters.....	21

4.2.7.3.4	Reporting of device parameters	22
4.2.7.3.5	Reporting of channel usage parameters	22
4.2.7.3.6	Functionality of a master TVWSD to support slave TVWSDs	22
4.2.7.3.7	Conformance	23
4.2.7.4	Master TVWSD update	23
4.2.7.4.1	Definition	23
4.2.7.4.2	Requirements	23
4.2.7.4.3	Conformance	24
4.2.7.5	Slave TVWSD update	24
4.2.7.5.1	Applicability	24
4.2.7.5.2	Definition	24
4.2.7.5.3	Requirements	24
4.2.7.5.4	Conformance	24
4.2.8	Receiver Blocking	24
4.2.8.1	Applicability	24
4.2.8.2	Definition	25
4.2.8.3	Performance Criteria	25
4.2.8.4	Limits	25
4.2.8.5	Conformance	25
4.2.9	Receiver spurious emissions	25
4.2.9.1	Definition	25
4.2.9.2	Limits	25
4.2.9.3	Conformance	26
4.2.10	Geo-Location capability	26
4.2.10.1	Definition	26
4.2.10.2	Requirements	26
4.2.10.3	Conformance	26
4.2.11	Software, Firmware and User Access Restrictions	26
4.2.11.1	Definition	26
4.2.11.2	Requirement	27
4.2.11.3	Conformance	27
4.2.12	Security	27
4.2.12.1	Applicability	27
4.2.12.2	Definition	27
4.2.12.3	Requirements	27
4.2.12.4	Conformance	28
5	Testing for compliance with technical requirements	28
5.1	Introduction	28
5.2	Conditions for testing	28
5.2.1	Normal and extreme test conditions	28
5.2.2	Antennas	28
5.2.3	Transmit operating modes	28
5.2.4	Requirements for the test modulation	29
5.2.5	Communication between test TVWSDs, master and slave UUT	29
5.2.6	Operational Parameter set	30
5.3	Interpretation of measurement results	30
5.4	Essential test suites	31
5.4.1	Product Information	31
5.4.2	RF output power	32
5.4.2.1	Test conditions	32
5.4.2.2	Test method	32
5.4.2.2.1	Conducted measurements	32
5.4.2.2.2	Radiated measurements	33
5.4.3	Power Spectral Density and Transmitter unwanted emissions within the 470 MHz to 790 MHz band	34
5.4.3.1	Test conditions	34
5.4.3.2	Test method	34
5.4.3.2.1	Conducted measurement	34
5.4.3.2.2	Radiated measurement	36
5.4.4	Transmitter unwanted emissions outside the 470 MHz to 790 MHz bands	36
5.4.4.1	Purpose	36
5.4.4.2	Test conditions	37

5.4.4.3	Test method	37
5.4.4.3.1	Conducted measurements	37
5.4.4.3.2	Radiated measurements	39
5.4.5	Transmitter Intermodulation	39
5.4.5.1	Objective and Measurement Arrangement	39
5.4.5.2	Test Method	39
5.4.6	Master TVWSD update	40
5.4.6.1	Introduction and Test conditions	40
5.4.6.2	Test method	40
5.4.7	Lost connection between the master TVWSD and the TVWSDB	41
5.4.7.1	Test conditions	41
5.4.7.2	Test method	42
5.4.8	Slave TVWSD update - specific parameters invalidated	42
5.4.8.1	Test conditions	42
5.4.8.2	Test method	42
5.4.9	Slave TVWSD update - loss of communication with master TVWSD	43
5.4.9.1	Test conditions	43
5.4.9.2	Test method	43
5.4.10	Receiver Blocking	43
5.4.10.1	Test conditions	43
5.4.10.2	Test Method	44
5.4.10.2.1	Conducted measurements	44
5.4.11	Receiver spurious emission	45
5.4.11.1	Purpose	45
5.4.11.2	Test conditions	45
5.4.11.3	Test method	45
5.4.11.3.1	Conducted measurements	45
5.4.11.3.2	Radiated measurements	46
5.4.12	Control and monitoring functions	47
5.4.12.1	TVWSDB identification	47
5.4.12.1.1	Test condition	47
5.4.12.1.2	Test method 1	48
5.4.12.1.3	Test method 2	48
5.4.12.1.4	Test method 3	48
5.4.12.1.5	Test method 4	49
5.4.12.1.6	Test method 5	49
5.4.12.2	Transmission in compliance with parameters, provision of device parameters, provision of channel usage parameters and master TVWSD functionality in support of slave TVWSDs	50
5.4.12.2.1	Test condition	50
5.4.12.2.2	Test method 1	50
5.4.12.2.3	Test method 2	51
5.4.12.2.4	Test method 3	51
5.4.12.2.5	Test method 4	52
5.4.12.2.6	Test method 5	52
5.4.12.2.7	Test method 6	53
5.4.13	Geo-location capability	53
5.4.13.1	Purpose	53
5.4.13.2	Test conditions	53
5.4.13.3	Test method	54

Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	56
-------------------------------	---	-----------

Annex B (normative):	Test sites and arrangements for radiated measurement	58
-----------------------------	---	-----------

B.1	Introduction	58
B.2	Radiation test sites	58
B.2.1	Open Area Test Site (OATS)	58
B.2.2	Semi Anechoic Room	59
B.2.3	Fully Anechoic Room (FAR)	60
B.2.4	Measurement Distance	61

B.3	Antennas.....	62
B.3.1	Antenna types.....	62
B.3.2	Measurement antenna.....	62
B.3.3	Substitution antenna.....	62
B.4	Test fixture.....	63
B.4.1	Conducted measurements and use of test fixture.....	63
B.4.2	Description of the test fixture.....	63
B.4.3	Using the test fixture for relative measurements.....	63
B.5	Guidance on the use of radiation test sites.....	63
B.5.1	Test procedures, equipment and verification.....	63
B.5.2	Power supplies for the battery powered UUT.....	64
B.5.3	Site preparation.....	64
B.6	Coupling of signals.....	64
B.6.1	General.....	64
B.6.2	Data Signals.....	65
Annex C (normative):	General description of measurement.....	66
C.1	Introduction.....	66
C.2	Conducted measurements.....	66
C.3	Radiated measurements.....	66
C.4	Substitution measurement.....	67
Annex D:	Void.....	68
Annex E (informative):	Nominal Channel Bandwidth and Total Bandwidth.....	69
Annex F (informative):	Application form for testing.....	71
F.1	Introduction.....	71
F.2	Information as required by ETSI EN 301 598 V2.1.1.....	71
Annex G (informative):	Bibliography.....	75
Annex H (informative):	Change History.....	76
History.....		77

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.13] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.3].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document covers TV band high performance wireless access systems (WAS) including RLAN equipment which is used in wireless local area networks. Such networks provide high speed data communications in between devices connected to the wireless infrastructure. The present document also covers ad-hoc networking where devices communicate directly with each other, without the use of a wireless infrastructure.

The methods and principles used in the present document for the operation of TV White Space devices in the band 470 MHz to 790 MHz are taken from the ECC Report 186 [i.6], which explains the regulatory principles under which it is envisaged such devices will be permitted to operate in Europe. This approach is also explained in further detail in Chapter 9 of "Dynamic White Space Spectrum Access" [i.12].

A requirement to facilitate coexistence between TVWSDs is not considered essential with respect to compliance with article 3.2 of Directive 2014/53/EU [i.3] and therefore is not included in the current version of the present document. This may change in the future, resulting in the inclusion of mitigation techniques in a revision of the present document, to improve the coexistence among TVWSDs, if considered essential in order to comply with article 3.2 of Directive 2014/53/EU [i.3].

ITEH STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/649e3858-f909-4c86-80fe-0b855399a1bc/etsi-en-301-598-v2.1.1-2018-01>

1 Scope

The present document specifies technical characteristics and methods of measurements for TV white space devices (TVWSDs) controlled by a TV white space database (TVWSDB) and which operate in the TV broadcast band 470 MHz to 790 MHz.

The present document applies to the following radio equipment types:

- 1) Master TV white space device (TVWSD)
- 2) Slave TV white space device (TVWSD)

The present document applies to TVWSDs with integral, dedicated or external antennas, where TVWSDs using external antennas are intended only for fixed use.

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.3] under the conditions identified in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void
- [2] Void.
- [3] Void.
- [4] IETF RFC 4122 (05-2007): "A Universally Unique Identifier (UUID) URN Namespace".

NOTE: Available at <http://www.ietf.org/rfc/rfc4122.txt>.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] Void.

- [i.3] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.4] ETSI TR 100 028 (all parts) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics.
- [i.5] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.6] ECC Report 186: "Technical and operational requirements for the operation of white space devices under geo-location approach", January 2013.
- [i.7] ETSI TR 102 273-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.8] ETSI TR 102 273-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.9] ETSI TR 102 273-4: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".
- [i.10] ETSI TR 103 231: "White Space Devices (WSD); Wireless Access Systems operating in the 470 MHz to 790 MHz TV broadcast band; Information on weblisting of TV White Space Databases (TVWSDBs)".
- [i.11] ECC Report 159: "Technical and operational requirements for the possible operation of cognitive radio systems in the "white spaces" of the frequency band 470-790 MHz", January 2011.
- [i.12] William Webb and contributors: "Dynamic White Space Spectrum Access".
- NOTE: Available at <http://www.webbsearch.co.uk/publications/>.
- [i.13] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.14] NIMA Technical Report TR8350.2 (1984, including amendment 1 of 03 January 2000 and amendment 2 of 23 June 2004): "Department of Defense World Geodetic System 1984. Its Definition and Relationships with Local Geodetic Systems".

NOTE: Available at <http://earth-info.nga.mil/GandG/publications/tr8350.2/wgs84fin.pdf>.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ECC Report 159 [i.11], Directive 2014/53/EU [i.3] and the following apply:

Adjacent Channel Leakage Ratio (ACLR): ratio of the in-band transmit power measured in an 8 MHz TV channel, to the out-of-band emission measured in 100 kHz in an adjacent TV channel

altitude: height above the reference level defined by WGS84

association: process whereby a slave TVWSD provides its device parameters to a master TVWSD and initially identifies itself to its serving master TVWSD

authentication: ability to verify the identity of a server, and that a message was truly sent by the asserted sender

channel usage parameters: parameters sent by a TVWSD to inform the TVWSDB of the actual radio resources that will be used by both the master and the slave TVWSDs

dedicated antenna: removable antenna supplied and assessed with the radio equipment, designed as an indispensable part of the equipment

device emission class: classification declared by the manufacturer that identifies the level of ACLR for the device

device parameters: parameters that specify the technical characteristics of an individual TVWSD, and its location

Digital Terrestrial Television (DTT): platform for the delivery of digital TV content via terrestrial broadcasting

DTT channel: 8 MHz channel in accordance with the European harmonized DTT channel raster

external antenna: removable antenna which is designed for use with a broad range of radio equipment and has not been designed for use with a specific product

NOTE: An external antenna is not assessed together with the equipment against the requirements of the present document.

generic operational parameters: transmission parameters communicated by a master TVWSD to any slave TVWSD within the coverage area of that master TVWSD to allow the slave TVWSD to operate as required

geographic validity: geographic area within which the operational parameters for a geo-located TVWSD are valid

geo-location capability: capability of a TVWSD to determine and report the latitude, longitude and altitude coordinates of its antenna

geo-location uncertainty: 3D position error defined by the difference in metres between the point reported by the TVWSD device to the TVWSDB and the actual position of the TVWSD antenna

horizontal geo-location capability: capability of a TVWSD to determine and report the latitude and longitude coordinates of its antenna

in-block emissions: intended emissions that fall within a single or multiple DTT channel(s)

integral antenna: antenna designed as a fixed part of the equipment, without the use of an external connector, which cannot be disconnected from the equipment by a user with the intent to connect another antenna

NOTE: An integral antenna may be fitted internally or externally. In the case where the antenna is external, a non-detachable cable can be used.

integrity: capability to protect messages against accidental or malicious changes during transit

master operational parameters: transmission parameters communicated from a TVWSDB to a master TVWSD to allow the master TVWSD to operate as required

master TVWSD: geo-located TVWSD that is able to access a TVWSDB through either a direct or an indirect connection to the Internet and to communicate with TVWSDs

out-of-block emissions: unwanted emissions that fall within the 470 MHz to 790 MHz band

regulatory domains: geographical area where a set of regulatory rules applies

NOTE: This is normally a country.

reverse intermodulation attenuation: measure of the capability of the transmitter to inhibit the generation of intermodulation signals in its non-linear components caused by the presence of the transmitter wanted signal and an unwanted signal reaching the transmitter via the antenna

reverse intermodulation attenuation improvement: measure of the improvement in reverse intermodulation attenuation beyond the minimum value required, as a function of in-block transmitter power

slave operational parameters: transmission parameters communicated from a TVWSDB via a master TVWSD to enable a slave TVWSD to operate as required

slave TVWSD: TVWSD that is only able to communicate with other TVWSDs, when under the control of a master TVWSD

sleep mode: mode of operation for which the TVWSD is inactive but is not powered-down

specific operation parameters: transmission parameters communicated from a TVWSDB to a specific TVWSD (master or slave), taking account of the device parameters of that specific TVWSD

test equipment: equipment that provides the means to operate and control a UUT for the purposes of testing against the requirements contained in the present document

test master TVWSD: test equipment that emulates the functionalities of a master TVWSD for the purposes of testing a slave TVWSD against the requirements contained in the present document

test slave TVWSD: test equipment that emulates the functionalities of a slave TVWSD for the purposes of testing a master TVWSD against the requirements contained in the present document

test white space database: test equipment that emulates the functionalities of a TVWSDB for the purposes of testing a TVWSD against the requirements contained in the present document

time validity: period of time when a set of operational parameters is valid, determined by the $T_{ValStart}$ and T_{ValEnd} parameters contained in the said operational parameter set

TV white spaces: frequencies within the 470 MHz to 790 MHz band which have been identified by a TVWSDB for use by a TVWSD

TV White Space Database (TVWSDB): database system approved by the relevant national regulatory authority which can communicate with TVWSDs and provide information on TV white space availability

TV White Space Device (TVWSD): TVWSD controlled by a TVWSDB and which operates in TV white spaces

UHF TV band: 470 MHz to 790 MHz band

NOTE: This corresponds to DTT channels 21 to 60.

vertical geo-location capability: capability of a TVWSD to determine and report the altitude of its antenna

weblisting: publically available Internet listing of approved TVWSDB(s) relevant to a regulatory domain, and which is hosted by, or on behalf of the national regulatory authority for that regulatory domain

3.2 Symbols

For the purposes of the present document, the following symbols apply:

A_{ch}	Number of active transmit chains
dB	decibel
dBc	decibel relative to carrier
dBm	decibel relative to 1 milliwatt
f	Frequency of measurement
f_c	Centre frequency of the assigned channel
$f_{l,i}$	Frequency at the lower edge of the i^{th} channel
$f_{u,i}$	Frequency at the upper edge of the i^{th} channel
f_{un}	Centre frequency of the unwanted signal
f_w	Centre frequency of the wanted signal
$P_{0,i}$	Maximum mean EIRP in a given (i^{th}) 100 kHz channel
$P_{1,i}$	Maximum mean EIRP in a given (i^{th}) 8 MHz channel
P_{IB}	Measured in block EIRP spectral density over 8 MHz
P_{IBk}	An intermediate (k^{th}) value of P_{IB}
P_{IBMax}	Maximum value of P_{IB}
PIM3	Power of the third order intermodulation product at frequency $(2 \times f_w - f_{un})$, measured in a 100 kHz bandwidth
P_{OOB}	Mean out of block EIRP spectral density
$p_{0,i}$	In-block EIRP spectral density (dBm/100 kHz) which a TVWSD intends to use within each DTT channel

$p_{1,i}$	In-block EIRP which a TVWSD intends to use within each (8 MHz) DTT channel
RIM3	third order reverse intermodulation attenuation
Δ RIM3	Improvement in the third order reverse intermodulation attenuation (RIM3)
T_{Dur}	Time duration of the operational parameters
T_{ValEnd}	Absolute time of the end of the period of validity of the operational parameters
$T_{ValStart}$	Absolute time of the start of the period of validity of the operational parameters

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
ACLR	Adjacent Channel Leakage Ratio
BW	BandWidth
CW	Continuous Wave
DC	Direct Current
DHCP	Dynamic Host Configuration Protocol
DNS	Domain Name System
DTT	Digital Terrestrial Television
EIRP	Equivalent Isotropically Radiated Power
FAR	Fully Anechoic Room
GHz	GigaHertz
GNSS	Global Navigation Satellite System
IEEE	Institute of Electrical and Electronics Engineers
IETF	Internet Engineering Task Force
IP	Internet Protocol
LPDA	Logarithmic Periodic Dipole Antenna
MAC	Media Access Control
MHz	MegaHertz
OATS	Open Area Test Site
OUI	Organizationally Unique Identifier
PER	Packet Error Rate
RBW	Resolution BandWidth
RF	Radio Frequency
RLAN	Radio Local Area Network
RMS	Root Mean Square
SAR	Semi Anechoic Room
TE	Test Equipment
TV	TeleVision
TVWSD	TV White Space Device
TVWSDB	TV White Space Database
UE	User Equipment
UHF	Ultra High Frequency
UUID	Universally Unique Identifier
UUT	Unit Under Test
VSWR	Voltage Standing Wave Ratio

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile.