

ETSI EN 301 598 V2.1.1 (2018-01)



**White Space Devices (WSD);
Wireless Access Systems operating in the 470 MHz to 790 MHz
TV broadcast band;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU**

PREVIEW
https://standards.iteh.ai/en/standards/etsi/en-301-598-v2-1-1-2018-01-4c86-80fe-0b855399a1b/

Reference

REN/BRAN-60019

Keywords

access, broadband, CRS, FWA, LAN, M2M,
mobile, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

| | |
|---|----|
| Intellectual Property Rights | 7 |
| Foreword..... | 7 |
| Modal verbs terminology..... | 7 |
| Introduction | 8 |
| 1 Scope..... | 9 |
| 2 References | 9 |
| 2.1 Normative references | 9 |
| 2.2 Informative references..... | 9 |
| 3 Definitions, symbols and abbreviations | 10 |
| 3.1 Definitions..... | 10 |
| 3.2 Symbols..... | 12 |
| 3.3 Abbreviations | 13 |
| 4 Technical requirements specifications | 13 |
| 4.1 Environmental profile..... | 13 |
| 4.2 Conformance requirements | 14 |
| 4.2.1 Meeting the Directive requirements..... | 14 |
| 4.2.2 Equipment types | 14 |
| 4.2.2.1 Definition | 14 |
| 4.2.2.2 Equipment Type A | 14 |
| 4.2.2.3 Equipment Type B | 14 |
| 4.2.3 Nominal Channel Bandwidth and Total Nominal Channel Bandwidth..... | 14 |
| 4.2.3.1 Definitions..... | 14 |
| 4.2.3.2 Requirements | 14 |
| 4.2.3.3 Conformance..... | 15 |
| 4.2.4 RF power and RF power spectral density | 15 |
| 4.2.4.1 Definitions..... | 15 |
| 4.2.4.1.1 RF power | 15 |
| 4.2.4.1.2 RF power spectral density | 15 |
| 4.2.4.2 Limits | 15 |
| 4.2.4.3 Conformance..... | 15 |
| 4.2.5 Transmitter unwanted emissions..... | 15 |
| 4.2.5.1 Transmitter unwanted emissions outside the 470 MHz to 790 MHz band..... | 15 |
| 4.2.5.1.1 Definition..... | 15 |
| 4.2.5.1.2 Limits | 16 |
| 4.2.5.1.3 Conformance | 16 |
| 4.2.5.2 Transmitter unwanted emissions within the 470 MHz to 790 MHz band..... | 16 |
| 4.2.5.2.1 Definition..... | 16 |
| 4.2.5.2.2 Limits | 16 |
| 4.2.5.2.3 Conformance | 16 |
| 4.2.6 Transmitter Reverse Intermodulation Attenuation..... | 17 |
| 4.2.6.1 Definition | 17 |
| 4.2.6.2 Limits | 17 |
| 4.2.6.3 Conformance..... | 17 |
| 4.2.7 Control and monitoring..... | 17 |
| 4.2.7.1 Control and monitoring mechanisms | 17 |
| 4.2.7.2 TVWSDB identification..... | 18 |
| 4.2.7.2.1 Applicability | 18 |
| 4.2.7.2.2 Definition..... | 18 |
| 4.2.7.2.3 Requirements | 18 |
| 4.2.7.2.4 Conformance | 18 |
| 4.2.7.3 Data exchange and compliance with parameters..... | 18 |
| 4.2.7.3.1 Applicability | 18 |
| 4.2.7.3.2 Device parameters, operational parameters and channel usage..... | 18 |
| 4.2.7.3.3 Transmission in compliance with parameters..... | 21 |

| | | |
|-----------|--|----|
| 4.2.7.3.4 | Reporting of device parameters | 22 |
| 4.2.7.3.5 | Reporting of channel usage parameters | 22 |
| 4.2.7.3.6 | Functionality of a master TVWSD to support slave TVWSDs | 22 |
| 4.2.7.3.7 | Conformance | 23 |
| 4.2.7.4 | Master TVWSD update | 23 |
| 4.2.7.4.1 | Definition | 23 |
| 4.2.7.4.2 | Requirements | 23 |
| 4.2.7.4.3 | Conformance | 24 |
| 4.2.7.5 | Slave TVWSD update | 24 |
| 4.2.7.5.1 | Applicability | 24 |
| 4.2.7.5.2 | Definition | 24 |
| 4.2.7.5.3 | Requirements | 24 |
| 4.2.7.5.4 | Conformance | 24 |
| 4.2.8 | Receiver Blocking | 24 |
| 4.2.8.1 | Applicability | 24 |
| 4.2.8.2 | Definition | 25 |
| 4.2.8.3 | Performance Criteria | 25 |
| 4.2.8.4 | Limits | 25 |
| 4.2.8.5 | Conformance | 25 |
| 4.2.9 | Receiver spurious emissions | 25 |
| 4.2.9.1 | Definition | 25 |
| 4.2.9.2 | Limits | 25 |
| 4.2.9.3 | Conformance | 26 |
| 4.2.10 | Geo-Location capability | 26 |
| 4.2.10.1 | Definition | 26 |
| 4.2.10.2 | Requirements | 26 |
| 4.2.10.3 | Conformance | 26 |
| 4.2.11 | Software, Firmware and User Access Restrictions | 26 |
| 4.2.11.1 | Definition | 26 |
| 4.2.11.2 | Requirement | 27 |
| 4.2.11.3 | Conformance | 27 |
| 4.2.12 | Security | 27 |
| 4.2.12.1 | Applicability | 27 |
| 4.2.12.2 | Definition | 27 |
| 4.2.12.3 | Requirements | 27 |
| 4.2.12.4 | Conformance | 28 |
| 5 | Testing for compliance with technical requirements | 28 |
| 5.1 | Introduction | 28 |
| 5.2 | Conditions for testing | 28 |
| 5.2.1 | Normal and extreme test conditions | 28 |
| 5.2.2 | Antennas | 28 |
| 5.2.3 | Transmit operating modes | 28 |
| 5.2.4 | Requirements for the test modulation | 29 |
| 5.2.5 | Communication between test TVWSDs, master and slave UUT | 29 |
| 5.2.6 | Operational Parameter set | 30 |
| 5.3 | Interpretation of measurement results | 30 |
| 5.4 | Essential test suites | 31 |
| 5.4.1 | Product Information | 31 |
| 5.4.2 | RF output power | 32 |
| 5.4.2.1 | Test conditions | 32 |
| 5.4.2.2 | Test method | 32 |
| 5.4.2.2.1 | Conducted measurements | 32 |
| 5.4.2.2.2 | Radiated measurements | 33 |
| 5.4.3 | Power Spectral Density and Transmitter unwanted emissions within the 470 MHz to 790 MHz band | 34 |
| 5.4.3.1 | Test conditions | 34 |
| 5.4.3.2 | Test method | 34 |
| 5.4.3.2.1 | Conducted measurement | 34 |
| 5.4.3.2.2 | Radiated measurement | 36 |
| 5.4.4 | Transmitter unwanted emissions outside the 470 MHz to 790 MHz bands | 36 |
| 5.4.4.1 | Purpose | 36 |
| 5.4.4.2 | Test conditions | 37 |

| | | |
|------------|---|----|
| 5.4.4.3 | Test method | 37 |
| 5.4.4.3.1 | Conducted measurements | 37 |
| 5.4.4.3.2 | Radiated measurements | 39 |
| 5.4.5 | Transmitter Intermodulation | 39 |
| 5.4.5.1 | Objective and Measurement Arrangement | 39 |
| 5.4.5.2 | Test Method | 39 |
| 5.4.6 | Master TVWSD update | 40 |
| 5.4.6.1 | Introduction and Test conditions | 40 |
| 5.4.6.2 | Test method | 40 |
| 5.4.7 | Lost connection between the master TVWSD and the TVWSDB | 41 |
| 5.4.7.1 | Test conditions | 41 |
| 5.4.7.2 | Test method | 42 |
| 5.4.8 | Slave TVWSD update - specific parameters invalidated | 42 |
| 5.4.8.1 | Test conditions | 42 |
| 5.4.8.2 | Test method | 42 |
| 5.4.9 | Slave TVWSD update - loss of communication with master TVWSD | 43 |
| 5.4.9.1 | Test conditions | 43 |
| 5.4.9.2 | Test method | 43 |
| 5.4.10 | Receiver Blocking | 43 |
| 5.4.10.1 | Test conditions | 43 |
| 5.4.10.2 | Test Method | 44 |
| 5.4.10.2.1 | Conducted measurements | 44 |
| 5.4.11 | Receiver spurious emission | 45 |
| 5.4.11.1 | Purpose | 45 |
| 5.4.11.2 | Test conditions | 45 |
| 5.4.11.3 | Test method | 45 |
| 5.4.11.3.1 | Conducted measurements | 45 |
| 5.4.11.3.2 | Radiated measurements | 46 |
| 5.4.12 | Control and monitoring functions | 47 |
| 5.4.12.1 | TVWSDB identification | 47 |
| 5.4.12.1.1 | Test condition | 47 |
| 5.4.12.1.2 | Test method 1 | 48 |
| 5.4.12.1.3 | Test method 2 | 48 |
| 5.4.12.1.4 | Test method 3 | 48 |
| 5.4.12.1.5 | Test method 4 | 49 |
| 5.4.12.1.6 | Test method 5 | 49 |
| 5.4.12.2 | Transmission in compliance with parameters, provision of device parameters, provision of channel usage parameters and master TVWSD functionality in support of slave TVWSDs | 50 |
| 5.4.12.2.1 | Test condition | 50 |
| 5.4.12.2.2 | Test method 1 | 50 |
| 5.4.12.2.3 | Test method 2 | 51 |
| 5.4.12.2.4 | Test method 3 | 51 |
| 5.4.12.2.5 | Test method 4 | 52 |
| 5.4.12.2.6 | Test method 5 | 52 |
| 5.4.12.2.7 | Test method 6 | 53 |
| 5.4.13 | Geo-location capability | 53 |
| 5.4.13.1 | Purpose | 53 |
| 5.4.13.2 | Test conditions | 53 |
| 5.4.13.3 | Test method | 54 |

| | | |
|-------------------------------|---|-----------|
| Annex A (informative): | Relationship between the present document and the essential requirements of Directive 2014/53/EU | 56 |
|-------------------------------|---|-----------|

| | | |
|-----------------------------|---|-----------|
| Annex B (normative): | Test sites and arrangements for radiated measurement | 58 |
|-----------------------------|---|-----------|

| | | |
|-------|----------------------------|----|
| B.1 | Introduction | 58 |
| B.2 | Radiation test sites | 58 |
| B.2.1 | Open Area Test Site (OATS) | 58 |
| B.2.2 | Semi Anechoic Room | 59 |
| B.2.3 | Fully Anechoic Room (FAR) | 60 |
| B.2.4 | Measurement Distance | 61 |

| | | |
|-------------------------------|---|-----------|
| B.3 | Antennas..... | 62 |
| B.3.1 | Antenna types..... | 62 |
| B.3.2 | Measurement antenna..... | 62 |
| B.3.3 | Substitution antenna..... | 62 |
| B.4 | Test fixture..... | 63 |
| B.4.1 | Conducted measurements and use of test fixture..... | 63 |
| B.4.2 | Description of the test fixture..... | 63 |
| B.4.3 | Using the test fixture for relative measurements..... | 63 |
| B.5 | Guidance on the use of radiation test sites..... | 63 |
| B.5.1 | Test procedures, equipment and verification..... | 63 |
| B.5.2 | Power supplies for the battery powered UUT..... | 64 |
| B.5.3 | Site preparation..... | 64 |
| B.6 | Coupling of signals..... | 64 |
| B.6.1 | General..... | 64 |
| B.6.2 | Data Signals..... | 65 |
| Annex C (normative): | General description of measurement..... | 66 |
| C.1 | Introduction..... | 66 |
| C.2 | Conducted measurements..... | 66 |
| C.3 | Radiated measurements..... | 66 |
| C.4 | Substitution measurement..... | 67 |
| Annex D: | Void..... | 68 |
| Annex E (informative): | Nominal Channel Bandwidth and Total Bandwidth..... | 69 |
| Annex F (informative): | Application form for testing..... | 71 |
| F.1 | Introduction..... | 71 |
| F.2 | Information as required by ETSI EN 301 598 V2.1.1..... | 71 |
| Annex G (informative): | Bibliography..... | 75 |
| Annex H (informative): | Change History..... | 76 |
| History..... | | 77 |

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.13] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.3].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates

| | |
|--|-----------------|
| Date of adoption of this EN: | 8 January 2018 |
| Date of latest announcement of this EN (doa): | 30 April 2018 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 31 October 2018 |
| Date of withdrawal of any conflicting National Standard (dow): | 31 October 2019 |

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document covers TV band high performance wireless access systems (WAS) including RLAN equipment which is used in wireless local area networks. Such networks provide high speed data communications in between devices connected to the wireless infrastructure. The present document also covers ad-hoc networking where devices communicate directly with each other, without the use of a wireless infrastructure.

The methods and principles used in the present document for the operation of TV White Space devices in the band 470 MHz to 790 MHz are taken from the ECC Report 186 [i.6], which explains the regulatory principles under which it is envisaged such devices will be permitted to operate in Europe. This approach is also explained in further detail in chapter 9 of "Dynamic White Space Spectrum Access" [i.12].

A requirement to facilitate coexistence between TVWSDs is not considered essential with respect to compliance with article 3.2 of Directive 2014/53/EU [i.3] and therefore is not included in the current version of the present document. This may change in the future, resulting in the inclusion of mitigation techniques in a revision of the present document, to improve the coexistence among TVWSDs, if considered essential in order to comply with article 3.2 of Directive 2014/53/EU [i.3].

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/649e3858-f909-4c86-80fe-0b855399a1bc/etsi-en-301-598-v2.1.1-2018-01>

1 Scope

The present document specifies technical characteristics and methods of measurements for TV white space devices (TVWSDs) controlled by a TV white space database (TVWSDB) and which operate in the TV broadcast band 470 MHz to 790 MHz.

The present document applies to the following radio equipment types:

- 1) Master TV white space device (TVWSD)
- 2) Slave TV white space device (TVWSD)

The present document applies to TVWSDs with integral, dedicated or external antennas, where TVWSDs using external antennas are intended only for fixed use.

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.3] under the conditions identified in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] Void.
- [3] Void.
- [4] IETF RFC 4122 (07-2005): "A Universally Unique Identifier (UUID) URN Namespace".

NOTE: Available at <http://www.ietf.org/rfc/rfc4122.txt>.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] Void.

- [i.3] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.4] ETSI TR 100 028 (all parts) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.5] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.6] ECC Report 186: "Technical and operational requirements for the operation of white space devices under geo-location approach", January 2013.
- [i.7] ETSI TR 102 273-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.8] ETSI TR 102 273-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.9] ETSI TR 102 273-4: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".
- [i.10] ETSI TR 103 231: "White Space Devices (WSD); Wireless Access Systems operating in the 470 MHz to 790 MHz TV broadcast band; Information on weblistings of TV White Space Databases (TVWSDBs)".
- [i.11] ECC Report 159: "Technical and operational requirements for the possible operation of cognitive radio systems in the "white spaces" of the frequency band 470-790 MHz", January 2011.
- [i.12] William Webb and contributors: "Dynamic White Space Spectrum Access".
- NOTE: Available at <http://www.webbsearch.co.uk/publications/>.
- [i.13] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.14] NIMA Technical Report TR8350.2 (1984, including amendment 1 of 03 January 2000 and amendment 2 of 23 June 2004): "Department of Defense World Geodetic System 1984. Its Definition and Relationships with Local Geodetic Systems".

NOTE: Available at <http://earth-info.nga.mil/GandG/publications/tr8350.2/wgs84fin.pdf>.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ECC Report 159 [i.11], Directive 2014/53/EU [i.3] and the following apply:

Adjacent Channel Leakage Ratio (ACLR): ratio of the in-band transmit power measured in an 8 MHz TV channel, to the out-of-band emission measured in 100 kHz in an adjacent TV channel

altitude: height above the reference level defined by WGS84

association: process whereby a slave TVWSD provides its device parameters to a master TVWSD and initially identifies itself to its serving master TVWSD

authentication: ability to verify the identity of a server, and that a message was truly sent by the asserted sender

channel usage parameters: parameters sent by a TVWSD to inform the TVWSDB of the actual radio resources that will be used by both the master and the slave TVWSDs

dedicated antenna: removable antenna supplied and assessed with the radio equipment, designed as an indispensable part of the equipment

device emission class: classification declared by the manufacturer that identifies the level of ACLR for the device

device parameters: parameters that specify the technical characteristics of an individual TVWSD, and its location

Digital Terrestrial Television (DTT): platform for the delivery of digital TV content via terrestrial broadcasting

DTT channel: 8 MHz channel in accordance with the European harmonised DTT channel raster

external antenna: removable antenna which is designed for use with a broad range of radio equipment and has not been designed for use with a specific product

NOTE: An external antenna is not assessed together with the equipment against the requirements of the present document.

generic operational parameters: transmission parameters communicated by a master TVWSD to any slave TVWSD within the coverage area of that master TVWSD to allow the slave TVWSD to operate as required

geographic validity: geographic area within which the operational parameters for a geo-located TVWSD are valid

geo-location capability: capability of a TVWSD to determine and report the latitude, longitude and altitude coordinates of its antenna

geo-location uncertainty: 3D position error defined by the difference in metres between the point reported by the TVWSD device to the TVWSDB and the actual position of the TVWSD antenna

horizontal geo-location capability: capability of a TVWSD to determine and report the latitude and longitude coordinates of its antenna

in-block emissions: intended emissions that fall within a single or multiple DTT channel(s)

integral antenna: antenna designed as a fixed part of the equipment, without the use of an external connector, which cannot be disconnected from the equipment by a user with the intent to connect another antenna

NOTE: An integral antenna may be fitted internally or externally. In the case where the antenna is external, a non-detachable cable can be used.

integrity: capability to protect messages against accidental or malicious changes during transit

master operational parameters: transmission parameters communicated from a TVWSDB to a master TVWSD to allow the master TVWSD to operate as required

master TVWSD: geo-located TVWSD that is able to access a TVWSDB through either a direct or an indirect connection to the Internet and to communicate with TVWSDs

out-of-block emissions: unwanted emissions that fall within the 470 MHz to 790 MHz band

regulatory domains: geographical area where a set of regulatory rules applies

NOTE: This is normally a country.

reverse intermodulation attenuation: measure of the capability of the transmitter to inhibit the generation of intermodulation signals in its non-linear components caused by the presence of the transmitter wanted signal and an unwanted signal reaching the transmitter via the antenna

reverse intermodulation attenuation improvement: measure of the improvement in reverse intermodulation attenuation beyond the minimum value required, as a function of in-block transmitter power

slave operational parameters: transmission parameters communicated from a TVWSDB via a master TVWSD to enable a slave TVWSD to operate as required

slave TVWSD: TVWSD that is only able to communicate with other TVWSDs, when under the control of a master TVWSD

sleep mode: mode of operation for which the TVWSD is inactive but is not powered-down

specific operation parameters: transmission parameters communicated from a TVWSDB to a specific TVWSD (master or slave), taking account of the device parameters of that specific TVWSD

test equipment: equipment that provides the means to operate and control a UUT for the purposes of testing against the requirements contained in the present document

test master TVWSD: test equipment that emulates the functionalities of a master TVWSD for the purposes of testing a slave TVWSD against the requirements contained in the present document

test slave TVWSD: test equipment that emulates the functionalities of a slave TVWSD for the purposes of testing a master TVWSD against the requirements contained in the present document

test white space database: test equipment that emulates the functionalities of a TVWSDB for the purposes of testing a TVWSD against the requirements contained in the present document

time validity: period of time when a set of operational parameters is valid, determined by the $T_{ValStart}$ and T_{ValEnd} parameters contained in the said operational parameter set

TV white spaces: frequencies within the 470 MHz to 790 MHz band which have been identified by a TVWSDB for use by a TVWSD

TV White Space Database (TVWSDB): database system approved by the relevant national regulatory authority which can communicate with TVWSDs and provide information on TV white space availability

TV White Space Device (TVWSD): TVWSD controlled by a TVWSDB and which operates in TV white spaces

UHF TV band: 470 MHz to 790 MHz band

NOTE: This corresponds to DTT channels 21 to 60.

vertical geo-location capability: capability of a TVWSD to determine and report the altitude of its antenna

weblisting: publically available Internet listing of approved TVWSDB(s) relevant to a regulatory domain, and which is hosted by, or on behalf of the national regulatory authority for that regulatory domain

3.2 Symbols

For the purposes of the present document, the following symbols apply:

| | |
|-------------|---|
| A_{ch} | Number of active transmit chains |
| dB | decibel |
| dBc | decibel relative to carrier |
| dBm | decibel relative to 1 milliwatt |
| f | Frequency of measurement |
| f_c | Centre frequency of the assigned channel |
| $f_{l,i}$ | Frequency at the lower edge of the i^{th} channel |
| $f_{u,i}$ | Frequency at the upper edge of the i^{th} channel |
| f_{un} | Centre frequency of the unwanted signal |
| f_w | Centre frequency of the wanted signal |
| $P_{0,i}$ | Maximum mean EIRP in a given (i^{th}) 100 kHz channel |
| $P_{1,i}$ | Maximum mean EIRP in a given (i^{th}) 8 MHz channel |
| P_{IB} | Measured in block EIRP spectral density over 8 MHz |
| P_{IBk} | An intermediate (k^{th}) value of P_{IB} |
| P_{IBMax} | Maximum value of P_{IB} |
| PIM3 | Power of the third order intermodulation product at frequency $(2 \times f_w - f_{un})$, measured in a 100 kHz bandwidth |
| P_{OOB} | Mean out of block EIRP spectral density |
| $p_{0,i}$ | In-block EIRP spectral density (dBm/100 kHz) which a TVWSD intends to use within each DTT channel |

| | |
|----------------|--|
| $p_{1,i}$ | In-block EIRP which a TVWSD intends to use within each (8 MHz) DTT channel |
| RIM3 | third order reverse intermodulation attenuation |
| Δ RIM3 | Improvement in the third order reverse intermodulation attenuation (RIM3) |
| T_{Dur} | Time duration of the operational parameters |
| T_{ValEnd} | Absolute time of the end of the period of validity of the operational parameters |
| $T_{ValStart}$ | Absolute time of the start of the period of validity of the operational parameters |

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|--------|---|
| AC | Alternating Current |
| ACLR | Adjacent Channel Leakage Ratio |
| BW | BandWidth |
| CW | Continuous Wave |
| DC | Direct Current |
| DHCP | Dynamic Host Configuration Protocol |
| DNS | Domain Name System |
| DTT | Digital Terrestrial Television |
| EIRP | Equivalent Isotropically Radiated Power |
| FAR | Fully Anechoic Room |
| GHz | GigaHertz |
| GNSS | Global Navigation Satellite System |
| IEEE | Institute of Electrical and Electronics Engineers |
| IETF | Internet Engineering Task Force |
| IP | Internet Protocol |
| LPDA | Logarithmic Periodic Dipole Antenna |
| MAC | Media Access Control |
| MHz | MegaHertz |
| OATS | Open Area Test Site |
| OUI | Organizationally Unique Identifier |
| PER | Packet Error Rate |
| RBW | Resolution BandWidth |
| RF | Radio Frequency |
| RLAN | Radio Local Area Network |
| RMS | Root Mean Square |
| SAR | Semi Anechoic Room |
| TE | Test Equipment |
| TV | TeleVision |
| TVWSD | TV White Space Device |
| TVWSDB | TV White Space Database |
| UE | User Equipment |
| UHF | Ultra High Frequency |
| UUID | Universally Unique Identifier |
| UUT | Unit Under Test |
| VSWR | Voltage Standing Wave Ratio |

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile.