



SLOVENSKI STANDARD

oSIST prEN 303 363-1 V1.0.1:2021

01-februar-2021

Radarski senzorji za nadzor zračnega prometa - Sekundarni nadzorni radar (SSR) - Harmonizirani standard za dostop do radijskega spektra - 1. del: Bralnik SSR

Air Traffic Control Surveillance Radar Sensors - Secondary Surveillance Radar (SSR) - Harmonised Standard for access to radio spectrum - Part 1: SSR Interrogator

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **ETSI EN 303 363-1 V1.0.1 (2020-12)**

<https://standards.iteh.ai/catalog/standards/sist/e7bfd60e-8cd0-4d37-8640-9159e0237a7f/osist-pren-303-363-1-v1-0-1-2021>

ICS:

03.220.50	Zračni transport	Air transport
33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications

oSIST prEN 303 363-1 V1.0.1:2021 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 303 363-1 V1.0.1:2021](https://standards.iteh.ai/catalog/standards/sist/e7bfd60e-8cd0-4d37-8640-9159e0237a7f/osist-pren-303-363-1-v1-0-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/e7bfd60e-8cd0-4d37-8640-9159e0237a7f/osist-pren-303-363-1-v1-0-1-2021>

Draft **ETSI EN 303 363-1** V1.0.1 (2020-12)



**Air Traffic Control Surveillance Radar Sensors;
Secondary Surveillance Radar (SSR);
Harmonised Standard for access to radio spectrum;
Part 1: SSR Interrogator**

<https://standards.iteh.ai/catalog/standards/sist/e7bfd60e-8cd0-4d37-8640-9159e0237a7f/osist-pren-303-363-1-v1-0-1-2021>

Reference

DEN/ERM-TGAERO-30-1

Keywords

aeronautical, harmonised standard, radar, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Important notice

<https://standards.iteh.ai/catalog/standards/sist/e7bfd60e-8cd0-4d37-8640-9159c1237a4f/osist-prEN-303-363-1-V1.0.1-2021>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definition of terms, symbols and abbreviations.....	9
3.1 Terms.....	9
3.2 Symbols.....	12
3.3 Abbreviations	12
4 Technical requirements specifications	13
4.1 Environmental profile.....	13
4.2 Conformance requirements	13
4.2.1 Transmitter requirements	13
4.2.1.1 Maximum frequency deviation	13
4.2.1.1.1 Definition.....	13
4.2.1.1.2 Limits	13
4.2.1.1.3 Conformance	13
4.2.1.2 Transmitter power	13
4.2.1.2.1 Definition.....	13
4.2.1.2.2 Limits	13
4.2.1.2.3 Conformance	13
4.2.1.3 Transmitter power control	13
4.2.1.3.1 Definition.....	13
4.2.1.3.2 Limits	13
4.2.1.3.3 Conformance	14
4.2.1.4 Spectrum mask.....	14
4.2.1.4.1 Definition.....	14
4.2.1.4.2 Limits	14
4.2.1.4.3 Conformance	15
4.2.1.5 Emissions in idle mode	15
4.2.1.5.1 Definition.....	15
4.2.1.5.2 Limits	15
4.2.1.5.3 Conformance	15
4.2.1.6 Transmitted waveforms.....	15
4.2.1.6.1 Definition.....	15
4.2.1.6.2 Limits	16
4.2.1.6.3 Conformance	16
4.2.2 Receiver requirements	16
4.2.2.1 Receiver sensitivity and flatness	16
4.2.2.1.1 Definition.....	16
4.2.2.1.2 Limits	16
4.2.2.1.3 Conformance	17
4.2.2.2 Receiver Saturation Level and Dynamic Range.....	17
4.2.2.2.1 Definition.....	17
4.2.2.2.2 Limits	17
4.2.2.2.3 Conformance	17
4.2.2.3 Receiver blocking	18
4.2.2.3.1 Definition.....	18
4.2.2.3.2 Limits	18
4.2.2.3.3 Conformance	18

4.2.2.4	Receiver selectivity	18
4.2.2.4.1	Definition.....	18
4.2.2.4.2	Limits	18
4.2.2.4.3	Conformance	18
4.2.2.5	Inter-modulation response rejection.....	19
4.2.2.5.1	Definition.....	19
4.2.2.5.2	Limits	19
4.2.2.5.3	Conformance	19
4.2.2.6	Receiver co-channel rejection.....	19
4.2.2.6.1	Definition.....	19
4.2.2.6.2	Limits	19
4.2.2.6.3	Conformance	19
4.2.2.7	Receiver Noise Figure.....	19
4.2.2.7.1	Definition.....	19
4.2.2.7.2	Limits	19
4.2.2.7.3	Conformance	19
5	Testing for compliance with technical requirements.....	20
5.1	General requirements	20
5.1.1	Standard operation mode for testing	20
5.2	Environmental conditions for testing	20
5.2.1	Test Conditions	20
5.2.2	Normal temperature and humidity	20
5.2.3	Normal test power supply	20
5.3	Test specifications	21
5.3.1	Transmitter related tests	21
5.3.1.0	General requirements	21
5.3.1.1	Maximum frequency deviation	21
5.3.1.1.1	Test conditions	21
5.3.1.1.2	Procedure.....	21
5.3.1.2	Transmitter power	21
5.3.1.2.1	Test conditions	21
5.3.1.2.2	Procedure.....	21
5.3.1.3	Transmitter power control	22
5.3.1.3.1	Test conditions	22
5.3.1.3.2	Procedure.....	22
5.3.1.4	Spectrum mask	23
5.3.1.4.1	Test conditions	23
5.3.1.4.2	Procedure.....	23
5.3.1.5	Emissions in idle mode	24
5.3.1.5.1	Test conditions	24
5.3.1.5.2	Procedure.....	24
5.3.1.6	Transmitted Waveforms	25
5.3.1.6.1	Test conditions	25
5.3.1.6.2	Procedure.....	25
5.3.2	Receiver related tests	26
5.3.2.0	General requirements	26
5.3.2.1	Receiver sensitivity and flatness	26
5.3.2.1.1	Test conditions	26
5.3.2.1.2	Procedure.....	26
5.3.2.2	Receiver Saturation Level and Dynamic Range.....	27
5.3.2.2.1	Test conditions	27
5.3.2.2.2	Procedure.....	28
5.3.2.3	Receiver blocking	28
5.3.2.3.1	Test conditions	28
5.3.2.3.2	Procedure.....	28
5.3.2.4	Receiver selectivity	30
5.3.2.4.1	Test conditions	30
5.3.2.4.2	Procedure.....	30
5.3.2.5	Inter-modulation response rejection.....	31
5.3.2.5.1	Test conditions	31
5.3.2.5.2	Procedure.....	31

5.3.2.6	Receiver co-channel rejection	32
5.3.2.6.1	Test conditions	32
5.3.2.6.2	Procedure.....	33
5.3.2.7	Receiver Noise Figure.....	33
5.3.2.7.1	Test conditions	33
5.3.2.7.2	Procedure.....	33
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	34
Annex B (normative):	Measurement setups	36
B.1	Setup 1.....	36
B.2	Setup 2.....	37
B.3	Setup 3.....	38
B.4	Setup 4.....	39
B.5	Setup 5.....	40
Annex C (informative):	Checklist	42
Annex D (informative):	Maximum Measurement Uncertainty.....	43
History		44

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 303 363-1 V1.0.1:2021](https://standards.iteh.ai/catalog/standards/sist/e7bfd60e-8cd0-4d37-8640-9159e0237a7f/osist-pren-303-363-1-v1-0-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/e7bfd60e-8cd0-4d37-8640-9159e0237a7f/osist-pren-303-363-1-v1-0-1-2021>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 1 of a multi-part deliverable covering ATC Secondary Surveillance Radar systems for civil air navigation operating in the frequencies 1 030 MHz and 1 090 MHz, as identified below:

Part 1: "SSR Interrogator";

Part 2: "Far Field Monitor (FFM)".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The SSR system provides ground-based surveillance of transponder fitted aircraft and in addition may allow data link communication between ground stations and aircraft, where both are fitted with appropriate equipment.

Secondary Radar surveillance is exploited through two essential elements: the SSR interrogator, normally ground-based, and the aircraft SSR transponder. When aircraft are within the antenna beam of the ground station, its interrogations elicit replies from transponders.

Civil use systems have different modes of interrogation/reply: Mode A, Mode C, Mode S and intermode. Mode A, Mode C and Intermode interrogations consist of pulse amplitude modulated (PAM) signals, Mode-S interrogations have an additional pulse, with differential phase keying (DPSK) modulation.

Ground stations will be either Mode A/C ground stations, which can interrogate and receive replies on Mode A/C only, or Mode S ground stations, for which the present standard finds its applicability, which can interrogate and receive replies on all modes. On the other side, there are two classes of transponders: Mode A/C transponders, which can respond to Mode A, Mode C and Intermode interrogations only, and Mode S transponders, which can respond to all modes. Mode-S interrogation/replies have different data block depending on the information they have to support.

As far as Mode S is concerned, for the purpose of the present document it is assumed that the SSR can transmit interrogations at least in the uplink formats (UF) UF11, UF4 and UF5 and can process replies in the downlink formats (DF) DF11, DF4, DF20, DF5 and DF21. <https://standards.iteh.ai/catalog/standards/sist/e7bf160e-8cd0-4d37-8640-9139e0237a74/osist-prEN-303-363-1-V1-0-1-2021>

The replies to all modes of interrogation are used to determine aircraft 2D position by measurement of the range and bearing of the reply. The performance towards the radar parameters are determined on the basis of the number of correct and validated replies received and decoded, in the operating environment.

Performances are affected by interference effects, which can result in a degradation of the signal causing lost or wrong information. RF signals on either uplink or downlink can be distorted by other overlapping RF signals, which can make correct decoding of wanted signals impossible. The degree of degradation is a function of the channel loading.

The SSR system requires a 3 dB receiver bandwidth of approximately 8 MHz centered on 1 030 MHz and 1 090 MHz for the airborne transponder and ground SSR receiver respectively. This bandwidth is sufficient to permit significant co-channel interference from transmitters operating on adjacent frequencies.

This interference can be minimized by ensuring adequate frequency or spatial separation between the interfering transmitters and the SSR receivers. In this specific case, two air traffic service systems, DME and primary radars, can be the cause of interference.

1 Scope

The present document specifies technical characteristics and methods of measurements for the following equipment used in ground-based ATC Secondary Surveillance Radar systems for civil air navigation.

Secondary Surveillance Radar (SSR) with Mode S capabilities which includes mode A/C, transmitting in the 1 030 MHz band with a power not exceeding 4 kW (66 dBm), and receiving in the 1 090 MHz band, used for air traffic control and connected to a rotating antenna. The SSR Interrogator transmits interrogations to aircraft equipped with transponder, receives the corresponding replies, and operates in the frequency bands as indicated in Table 1.

Table 1: SSR interrogator service frequency bands

Signals	Service frequency bands
Transmitted signals	1 030 MHz
Received signals	1 090 MHz

NOTE 1: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in Annex A.

NOTE 2: Systems making use of an electronic scanned antenna are not covered by the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

Void.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

- [i.3] ECC/Recommendation (02)05 (2012): "Unwanted emissions".
- [i.4] ETSI EG 203 336: "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.5] ICAO Annex 10, Volume IV: "Surveillance and Collision Avoidance Systems", 5th edition, 16th July 2018, including amendments up to amendment 90.
- [i.6] Eurocontrol SUR/MODES/EMS/SPE-01: "European Mode S Station Functional Specification", edition 3.11, 9th May 2005.
- [i.7] ERC/Recommendation 74-01 (2019): "Unwanted emissions in spurious domain".
- [i.8] ITU-R Radio Regulations (2020).
- [i.9] ICAO DOC-9924: "Aeronautical Surveillance Manual", edition 2, 2017.

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

all-call: intermode interrogations (Mode A/C/S all-call) or Mode S interrogations (Mode S only all-call) or Mode S only all-call replies

Binary Pulse Position Modulation (BPPM): modulation used in the reply data block of a Mode S reply

NOTE: Within a Mode S reply data bit interval, a pulse transmitted in the first half of the interval represents a binary ONE and a pulse transmitted in the second half represents a binary ZERO.

carrier frequency: radio frequency, i.e. 1 030 MHz for an SSR Interrogator which has no "modulation" imposed on it (yet)

chip: carrier interval in a Mode S interrogation within the pulse P6 with a duration of 0,25 microseconds and located after the synchro phase reversal

control: RF path between the SSR interrogator and the SSR antenna allowing sidelobe suppression

NOTE: Control path is also called OMNI (as it is derived from an omnidirectional antenna beam) or OMEGA path and identified with Greek letter Ω .

difference: RF path between the SSR interrogator and the SSR antenna allowing the monopulse function

NOTE: Monopulse difference path is also called DELTA path and identified with Greek letter Δ .

Differential Phase Shift Keying (DPSK): phase modulation used in the P6 pulse of Mode S interrogations

NOTE: The aforementioned modulation uses phase reversal preceding chips to code binary ONES and the absence of phase reversal to code binary ZEROS.

downlink: direction of the signals transmitted on the 1 090 MHz frequency band from aircraft transponder or FFM to SSR

Downlink Format (DF): data coding format of a Mode S reply

NOTE: DF11 denotes the format of a Mode S all-call reply.
 DF4 denotes the format of a Mode S selective reply of type "surveillance altitude reply".
 DF5 denotes the format of a Mode S selective reply of type "surveillance identity reply".
 DF20 denotes the format of a Mode S selective reply of type "Comm-B altitude reply".
 DF21 denotes the format of a Mode S selective reply of type "Comm-B identity reply".
 Comm-B denotes a Mode S selective reply containing supplementary data.

Far Field Monitor (FFM): fixed ground based system allowing the monitoring of the uplink and/or downlink performance of an SSR system, located at a pre-determined position from the radar (far field)

NOTE: The FFM is interrogated by the SSR, and its replies are evaluated by the secondary radar for calibration and self-test purposes. A FFM with Mode S capability has Mode A and Mode C capabilities too.

fruits: replies received by an interrogator but not triggered by own interrogations. They overlap to requested replies and are to be considered as interfering signals

idle state: entire period between transmissions, less 10-microsecond transition periods preceding the first pulse and following the last pulse of the transmission

NOTE: The word "inactive" instead of "idle" is used in [i.5] and [i.6].

intermode: interrogation triggering replies from SSR transponders and eventually replies from Mode S transponders in case of Mode A/C/S all-call interrogations

NOTE: Two types of intermode interrogations exist. The first type consists of Mode A or Mode C only all-call interrogations to which transponders with Mode A and Mode C capabilities only reply and to which Mode S transponders do not reply. The second type consists of Mode A/C/S all-call interrogations to which all transponders reply. Intermode interrogations consist of P1, P3 and P4 pulses transmitted on the sum port of the SSR interrogator and a P2 pulse transmitted on the control port of the SSR interrogator.

mode A: interrogation triggering a Mode A reply allowing the identification of aircraft

NOTE 1: A Mode A interrogation consists of P1 and P3 pulses transmitted on the sum port of the SSR interrogator and a P2 pulse transmitted on the control port of the SSR interrogator (P2 is called a sidelobe suppression pulse). The interval between P1 and P3 determines the Mode A interrogation type.

NOTE 2: A Mode A reply consists of framing pulses (F1 and F2) and up to 12 pulses between F1 and F2. The absence or presence of each of the 12 pulses determines the Mode A code.

mode C: interrogation triggering a Mode C reply containing encoded pressure-altitude information

NOTE 1: A Mode C interrogation consists of P1 and P3 pulses transmitted on the sum port of the SSR interrogator and a P2 pulse transmitted on the control port of the SSR interrogator. The interval between P1 and P3 determines the Mode C interrogation type.

NOTE 2: A Mode C reply consists of framing pulses (F1 and F2) and up to 12 pulses between F1 and F2. The absence or presence of each of the 12 pulses determines the Mode C code.

mode S: enhanced SSR mode allowing the addressing of individual aircraft and the retrieving of information with higher integrity

NOTE 1: A Mode S interrogation consists of P1, P2 and P6 pulses transmitted on the sum port of the SSR interrogator and a P5 pulse transmitted on the control port of the SSR interrogator (P5 is called a sidelobe suppression pulse). A Mode S reply consists of a four-pulse preamble followed by a reply data block.

NOTE 2: Mode S stands for "Mode Select".

NOTE 3: The addressing method consists of a unique 24 bit Mode-S address for each individual aircraft transponder, assigned by ICAO and using a country prefix scheme. The Mode S address is used by SSR Interrogator in the interrogations, and by transponders and FFM in their correlated replies.

monopulse: technique used to determine the direction of a RF signal by comparison of different RF antenna paths

necessary bandwidth: width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

out-of-band domain: frequency range, immediately outside the necessary bandwidth but excluding the spurious domain, in which out-of-band emissions generally predominate

NOTE 1: Out-of-band emissions, defined based on their source, occur in the out-of-band domain and, to a lesser extent, in the spurious domain. Spurious emissions likewise may occur in the out-of-band domain as well as in the spurious domain.

NOTE 2: This definition is taken from ITU Radio Regulation [1.8].

out-of-band emissions: emission on a frequency or frequencies immediately outside the necessary bandwidth which results from the modulation process, but excluding spurious emissions

NOTE: This definition is taken from ITU Radio Regulation [1.8].

peak envelope power: average power supplied to the antenna transmission line by a transmitter during one radio frequency cycle at the crest of the modulation envelope taken under normal operating conditions

NOTE: This definition is taken from ITU Radio Regulation [1.8].

phase reversal: 180-degree change of the phase of the uplink frequency carrier

NOTE: Phase reversal is a characteristics of the Differential Phase Shift Keying (DPSK) modulation used for the uplink transmission of the Mode S signals.

Pulse Amplitude Modulation (PAM): modulation used for Mode A, Mode C, intermode interrogations, pulses P1 and P2 of Mode S interrogations as well as Mode A, Mode C replies and the preamble pulses of Mode S replies

pulse decay time: time taken for the trailing edge of the pulse to decrease from 90 % to 10 % of the maximum amplitude (voltage)

pulse duration: time between the 50 % amplitude (voltage) points on the leading and trailing edge of the pulse envelope

pulse rise time: time taken for the leading edge of the pulse to increase from 10 % to 90 % of the maximum amplitude (voltage)

roll-call: selective Mode S interrogations addressed to an individual aircraft or selective Mode S replies received from an individual aircraft

Secondary Surveillance Radar (SSR): radio-determination system based on the comparison of reference signals with radio signals retransmitted from the position to be determined

NOTE 1: This definition is taken from ITU Radio Regulation [1.8].

NOTE 2: The SSR provides ground-based radar surveillance of targets equipped with transponder, and of far field monitors.

spurious domain: frequency range beyond the out-of-band domain in which spurious emissions generally predominate

NOTE: This definition is taken from ITU Radio Regulation [1.8].

spurious emissions: emission on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information

NOTE 1: Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products, but exclude out-of-band emissions.

NOTE 2: This definition is taken from ITU Radio Regulation [1.8].

sum: RF path between the SSR interrogator and the SSR antenna allowing the transmission and reception of RF signals through the main directional beam of the SSR antenna

NOTE: Monopulse sum path is also called SIGMA path and identified with Greek letter Σ

uplink: direction of the signals transmitted on the 1 030 MHz frequency band from SSR interrogator to aircraft transponder or FFM

Uplink Format (UF): data coding format of a Mode S interrogation

NOTE: UF11 denotes the format of a Mode S only all-call interrogation.
 UF4 denotes the format of a Mode S selective interrogation of type "surveillance altitude request".
 UF5 denotes the format of a Mode S selective interrogation of type "surveillance identity request".