

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 428 V2.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/4217bf06-0479-4349-b3c1-aa11d4e4dc73/sist-en-301-428-v2-1-1-2016>

ETSI EN 301 428 V2.1.1 (2016-05)



**Satellite Earth Stations and Systems (SES);
Harmonised Standard for Very Small
Aperture Terminal (VSAT);
Transmit-only, transmit/receive or receive-only satellite
earth stations operating in the 11/12/14 GHz frequency bands
covering the essential requirements of
article 3.2 of the Directive 2014/53/EU**

Reference

REN/SES-00381

Keywords

regulation, satellite, VSAT

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 428 V2.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/4217bf06-0479-4349-b3c1-aa11d4e4d775/sist-en-301-428-v2-1-1-2016>

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction	7
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	13
3.2 Abbreviations	13
4 Technical requirements specifications	14
4.1 General	14
4.1.1 Environmental profile	14
4.1.2 Control and Monitoring Functions (CMF).....	14
4.1.3 Operational configurations	14
4.1.4 Transmit VSAT states and radio states	14
4.1.4.1 Definitions.....	14
4.1.4.2 Class A CMF.....	14
4.1.4.3 Class B CMF.....	15
4.1.4.4 Radio states	15
4.2 Conformance requirements	16
4.2.1 Off-axis spurious radiation	16
4.2.1.1 Justification.....	16
4.2.1.2 Specification.....	16
4.2.1.2.1 Transmit VSAT	16
4.2.1.2.2 Receive-only VSAT	17
4.2.1.3 Conformance tests.....	17
4.2.2 On-axis spurious radiation for transmit VSAT	17
4.2.2.1 Justification	17
4.2.2.2 Specification.....	17
4.2.2.2.1 Specification 1: "Carrier-on" radio state.....	17
4.2.2.2.2 Specification 2: "Carrier-off" and "Emissions disabled" radio states	18
4.2.2.3 Conformance tests.....	18
4.2.3 Off-axis e.i.r.p. emission density within the band.....	18
4.2.3.0 General	18
4.2.3.1 Justification	18
4.2.3.2 Specification.....	18
4.2.3.3 Conformance tests.....	20
4.2.4 Carrier suppression	20
4.2.4.1 Justification	20
4.2.4.2 Specification.....	20
4.2.4.3 Conformance tests.....	20
4.2.5 Mechanical (antenna pointing) for transmit VSAT	20
4.2.5.1 Justification	20
4.2.5.2 Specification.....	20
4.2.5.3 Conformance tests.....	20
4.2.6 Class A Control and Monitoring Functions	21
4.2.6.1 Control and Monitoring Functions (CMF).....	21
4.2.6.1.1 General	21
4.2.6.1.2 CMF state transition diagram	21
4.2.6.1.3 Specification of states.....	22
4.2.6.2 Control Channels (CC).....	22

4.2.6.2.1	Justification	22
4.2.6.2.2	Specification	22
4.2.6.2.3	Conformance tests	23
4.2.6.3	Self monitoring functions	23
4.2.6.3.1	General	23
4.2.6.3.2	Processor monitoring	23
4.2.6.3.3	Transmit subsystem monitoring	24
4.2.6.3.4	VSAT transmission validation	24
4.2.6.4	Reception of commands from the CCMF	25
4.2.6.4.1	General	25
4.2.6.4.2	Disable message	25
4.2.6.4.3	Enable Message	26
4.2.6.5	Power-on/Reset	26
4.2.6.5.1	Justification	26
4.2.6.5.2	Specification	26
4.2.6.5.3	Conformance tests	26
4.2.7	Class B Control and Monitoring Functions	26
4.2.7.0	General	26
4.2.7.1	Processor monitoring	27
4.2.7.1.1	Justification	27
4.2.7.1.2	Specification	27
4.2.7.1.3	Conformance tests	27
4.2.7.2	Transmit subsystem monitoring	28
4.2.7.2.1	Justification	28
4.2.7.2.2	Specification	28
4.2.7.2.3	Conformance tests	28
4.2.7.3	Power-on/Reset	28
4.2.7.3.1	Justification	28
4.2.7.3.2	Specification	28
4.2.7.3.3	Conformance tests	28
4.2.7.4	Control Channel (CC) reception	28
4.2.7.4.1	Justification	28
4.2.7.4.2	Specification	28
4.2.7.4.3	Conformance tests	28
4.2.7.5	Network control commands	29
4.2.7.5.1	Justification	29
4.2.7.5.2	Specification	29
4.2.7.5.3	Conformance test	29
4.2.7.6	Initial burst transmission	29
4.2.7.6.1	Justification	29
4.2.7.6.2	Specification	29
4.2.7.6.3	Conformance tests	29
4.2.8	Receive antenna off-axis gain pattern	29
4.2.8.1	Justification	29
4.2.8.2	Specification	30
4.2.8.3	Conformance tests	30
4.2.9	Blocking performance	30
4.2.9.1	Justification	30
4.2.9.2	Specification	30
4.2.9.3	Conformance tests	31
4.2.10	Adjacent Signal Selectivity	31
4.2.10.1	Justification	31
4.2.10.2	Specification	31
4.2.10.3	Conformance tests	31
5	Testing for compliance with technical requirements	31
5.1	Environmental conditions for testing	31
5.2	Essential radio test suites	31
6	Test methods for the complete VSAT	31
6.1	General	31
6.2	Off-axis spurious radiation	32

6.2.0	General.....	32
6.2.1	Test method	33
6.2.1.0	General.....	33
6.2.1.1	Up to 1 000 MHz	33
6.2.1.1.1	Test site.....	33
6.2.1.1.2	Measuring receivers.....	34
6.2.1.1.3	Procedure.....	34
6.2.1.2	Above 1 000 MHz.....	34
6.2.1.2.0	General	34
6.2.1.2.1	Identification of the significant frequencies of spurious radiation	34
6.2.1.2.2	Measurement of radiated power levels of identified spurious radiation	35
6.2.1.2.3	Measurement of conducted spurious radiation at the antenna flange	36
6.3	On-axis spurious radiation for transmit VSAT.....	37
6.3.1	Test method	37
6.3.1.1	Test site	37
6.3.1.2	Method of measurement.....	37
6.3.1.2.1	General	37
6.3.1.2.2	Method of measurement at the antenna flange	37
6.3.1.2.3	Method of measurement with a test antenna	38
6.4	Off-axis e.i.r.p. emission density within the band	39
6.4.0	General.....	39
6.4.1	Test method	39
6.4.1.1	General	39
6.4.1.2	Transmit output power density.....	39
6.4.1.2.1	General	39
6.4.1.2.2	Test site.....	39
6.4.1.2.3	Method of measurement.....	40
6.4.1.3	Antenna transmit gain	41
6.4.1.3.1	General	41
6.4.1.3.2	Test site.....	41
6.4.1.3.3	Method of measurement	41
6.4.1.4	Antenna transmit radiation patterns.....	42
6.4.1.4.1	General.....	42
6.4.1.4.2	Test site.....	42
6.4.1.4.3	Test arrangement	42
6.4.1.4.4	Co-polar radiation pattern-azimuth.....	42
6.4.1.4.5	Co-polar radiation pattern-elevation.....	43
6.4.1.4.6	Cross-polar radiation pattern-azimuth	44
6.4.1.4.7	Cross-polar radiation pattern-elevation	44
6.4.2	Computation of results.....	45
6.5	Carrier suppression.....	45
6.5.1	Test method	45
6.6	Antenna pointing for transmit VSAT	45
6.6.1	Test method	45
6.7	Class A Control and Monitoring Functions.....	46
6.7.1	General.....	46
6.7.2	Test arrangement	46
6.7.3	Control Channels (CC)	47
6.7.3.1	Test method.....	47
6.7.3.1.0	General	47
6.7.3.1.1	Test method for internal CC	47
6.7.3.1.2	Test method for external CC	47
6.7.4	Processor monitoring	48
6.7.4.1	Test method.....	48
6.7.5	Transmit subsystem monitoring.....	48
6.7.5.1	Test method.....	48
6.7.6	VSAT transmission validation.....	48
6.7.6.1	Test method for VSAT validation by the CCMF for VSAT using internal CC	48
6.7.6.2	Test method for VSAT validation by receiving station(s) for VSAT using internal CC.....	48
6.7.6.3	Test method for transmission validation for VSAT using external CC.....	48
6.7.7	Reception of commands from the CCMF	49
6.7.7.1	Test method.....	49

6.7.8	Power-on/Reset	49
6.7.8.1	Test method	49
6.8	Class B Control and Monitoring Functions	49
6.8.0	General	49
6.8.1	Test arrangement	50
6.8.2	Processor monitoring-Test method	50
6.8.3	Transmit subsystem monitoring-Test method	51
6.8.4	Power-on/Reset-Test method	51
6.8.5	Control Channel (CC) reception-Test method	51
6.8.6	Network Control commands-Test method	52
6.8.7	Initial burst transmission-Test method	54
6.9	Receive antenna off-axis gain pattern	54
6.9.1	Test method	54
6.9.1.1	Test site	54
6.9.1.2	Method of measurement	54
6.9.1.3	Computation	55
6.10	Blocking performance	55
6.10.1	Test method	55
6.11	Adjacent Signal Selectivity	56
6.11.1	Test method	56
7	Test methods for modified VSAT	56
7.1	General	56
7.2	Antenna subsystem replacement	57
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	58
Annex B (informative):	Pointing stability methodology	60
Annex C (informative):	Bibliography	61
History	SIST EN 301 428 V2.1.1:2016	62
	https://standards.iteh.ai/catalog/standards/sist/4217bf06-0479-4349-b3c1-aa11d4e4dc73/sist-en-301-428-v2-1-1-2016	

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [4].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

National transposition dates

Date of adoption of this EN:	SIST EN 301 428 V2.1.1:2016	16 May 2016
Date of latest announcement of this EN (doa):	4dc73/sist-en-301-428-v2-1-1-2016	31 August 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):		28 February 2017
Date of withdrawal of any conflicting National Standard (dow):		28 February 2018

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio equipment under the RE Directive [4]. The modular structure is shown in ETSI EG 201 399 [i.1].

Figure 1: Void

Remarks on the present document

The present document allows the choice of either a class A Control and Monitoring system or a class B Control and Monitoring system. The class B system is more suitable for networks comprising very many terminals.

The determination of the parameters of the user earth stations using a given geo-stationary satellite for the protection of the spectrum allocated to that satellite, is considered to be under the responsibility of the satellite operator or the satellite network operators. For this reason the requirement on the cross polarization discrimination which was in ETSI TBR 028 [i.4] has not been copied in the present document and inter-modulation limits inside the band 14,0 GHz to 14,5 GHz are to be determined by system design and are subject to satellite operator specifications.

The requirements have been selected to ensure an adequate level of compatibility with other radio services. The levels, however, do not cover extreme cases which may occur in any location but with a low probability of occurrence.

The present document may not cover those cases where a potential source of interference which is producing individually repeated transient phenomena or a continuous phenomenon is present, e.g. a radar or broadcast site in the near vicinity. In such a case it may be necessary to use special protection applied to either the source of interference, or the interfered part or both.

The present document does not contain any requirement, recommendation or information about the installation of the VSAT.

All parts of the indoor unit related to reception, processing and presentation of the received information except the control channel are not within the scope of the present document. The syntax of the control channel messages is outside the scope of the present document.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 428 V2.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/4217bf06-0479-4349-b3c1-aa11d4e4dc73/sist-en-301-428-v2-1-1-2016>

1 Scope

The present document applies to Very Small Aperture Terminals (VSATs) which have the following characteristics:

- The VSAT is operating in one or more frequency ranges in the part of the following bands allocated exclusively to the Fixed Satellite Services (FSS):
 - 14,00 GHz to 14,25 GHz (earth-to-space);
 - 12,50 GHz to 12,75 GHz (space-to-earth);or in the shared parts of the following bands, allocated to the FSS and Fixed Services (FS):
 - 14,25 GHz to 14,50 GHz (earth-to-space);
 - 10,70 GHz to 11,70 GHz (space-to-earth).
- The VSAT uses linear polarization.
- The VSAT operates through a geostationary satellite at least 3° away from any other geostationary satellite operating in the same frequency band and covering the same area.
- The VSAT antenna diameter does not exceed 3,8 m, or equivalent effective area.
- The VSAT is either:
 - a transmit only VSAT: designed for transmission only of radio-communications signals in any of the frequency bands (earth-to-space) specified above; or
 - a transmit and receive VSAT: designed for transmission and reception of radio-communications signals in any of the frequency bands specified above; or
 - a receive only VSAT: designed for reception only of radio-communications signals in any of the frequency bands (space-earth) specified above.
- The VSAT is designed usually for unattended operation.
- The VSAT is operating as part of a satellite network (e.g. star, mesh or point-to-point) used for the distribution and/or exchange of information between users.
- The transmit-only and transmit-and-receive VSAT is controlled and monitored by a Centralized Control and Monitoring Function (CCMF). The CCMF is outside the scope of the present document.

The present document applies to the VSAT with its ancillary equipment and its various terrestrial ports, and when operated within the boundary limits of the operational environmental profile declared by the applicant and when installed as required by the applicant by declaration or in the user documentation.

The present document is intended to cover the provisions of Directive 2014/53/EU [4] (RE Directive) article 3.2, which states that "... *radio equipment shall be so constructed that it both effectively uses and supports the efficient use of spectrum in order to avoid harmful interference*".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Directive 2014/53/EU (RE Directive) [4] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org/>.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] CISPR 16-1-5 (2014): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-5: Radio disturbance and immunity measuring apparatus - Antenna calibration sites and reference test sites for 5 MHz to 18 GHz".
- [3] Void.
- [4] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RE Directive).

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the Radio & Telecommunication Terminal Equipment Directive 1999/5/EC (R&TTE) and a first guide on the impact of the Radio Equipment Directive 2014/53/EU (RED) on Harmonized Standards".
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] ETSI TR 102 375: "Satellite Earth Stations and Systems (SES); Guidelines for determining the parts of satellite earth station antenna radiation patterns concerned by the geostationary satellite orbit protection".
- [i.4] ETSI TBR 028: "Satellite Earth Stations and Systems (SES); Very Small Aperture Terminal (VSAT); Transmit-only, transmit/receive or receive-only satellite earth stations operating in the 11/12/14 GHz frequency bands".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [4] and the following apply:

ancillary equipment: equipment used in connection with a VSAT is considered as ancillary if the three following conditions are met:

- a) the equipment is intended for use in conjunction with the VSAT to provide additional operational and/or control features (e.g. to extend control to another position or location); and
- b) the equipment cannot be used on a stand alone basis, to provide user functions independently of the VSAT; and
- c) the absence of the equipment does not inhibit the operation of the VSAT.

applicant: manufacturer or his authorized representative within the European Community or the person responsible for placing the apparatus on the market

carrier-off radio state: radio state in which the VSAT may transmit and does not transmit any carrier

NOTE 1: The phrase "the VSAT may transmit" means that all the conditions for transmission are satisfied (e.g. in a state where transmissions are permitted and no failure detected).

NOTE 2: The existence of a "Carrier-off" radio state depends on the system of transmission used. For VSATs designed for continuous transmission mode there may be no "Carrier-off" radio state.

carrier-on radio state: radio state in which the VSAT may transmit and transmits a carrier

Centralized Control and Monitoring Functions (CCMF): set of functional entities that, at system level, monitor and control the correct operation of all transmit VSAT in a network

Control Channel (CC): channel or channels by which VSAT receive control information from the CCMF

EIRP_{max}: maximum e.i.r.p. capability of the VSAT as declared by the applicant

EIRP_{nom}: either:

- i) EIRP_{max}; or
- ii) when uplink power control is implemented, the maximum required e.i.r.p. of the VSAT under clear sky condition as declared by the applicant.

NOTE: The applicant may declare different values of EIRP_{max} and EIRP_{nom} for each combination of occupied bandwidth and transmission parameters (see clause 4.1.3).

emissions disabled radio state: radio state in which the VSAT is not transmitting a carrier

NOTE: This radio state only applies in certain CMF states as defined in clause 4.1.4. (e.g. before system monitoring pass, before the control channel is received, when a failure is detected, when the VSAT is commanded to disable). The "Emissions disabled" radio state requires lower unwanted emissions than the "Carrier-off" radio state.

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

external control channel: control channel which is either:

- i) carried by the VSAT network via the same or another satellite, but not within the internal protocol of the VSAT system; or
- ii) carried by the PSTN or some other means.

external response channel: response channel which is either:

- i) carried by the VSAT network via the same or another satellite, but not within the internal protocol of the VSAT system; or
- ii) carried by the PSTN or some other means.

indoor unit: modules of the VSAT that are not declared by the applicant, or as indicated in the user documentation as outdoor unit are defined as indoor unit

integral antenna: antenna which may not be removed during the tests according to the applicant's statement

internal control channel: control channel which is carried by the VSAT network via the same satellite as used for transmission of user data and within the internal protocol structure of the VSAT system

internal response channel: response channel which is carried by the VSAT network via the same satellite as used for transmission of user data and within the internal protocol structure of the VSAT system

network: in the present document, any network configuration including star, mesh and point-to-point configurations

nominal antenna diameter: antenna diameter declared by the manufacturer that is a parameter in performance characteristics and that allows reference to a certain performance

NOTE: An antenna with circular aperture of diameter equal to the nominal diameter does typically have the performance specified.

Network operators might request antennas of a certain diameter. Then an antenna that is compliant with the requirement for nominal antenna diameter equal to the requested antenna diameter can be used. Manufacturers can mark their equipment with antenna diameters used in the requirements during compliance test.

nominated bandwidth: bandwidth of the VSAT radio frequency transmission nominated by the applicant

NOTE 1: The nominated bandwidth is centred on the transmit frequency and does not exceed 5 times the occupied bandwidth. <https://standards.iteh.ai/catalog/standards/sist/4217bf06-0479-4349-b3c1-aa1d4e4dc73/sist-en-301-428-v2-1-1-2016>

NOTE 2: The nominated bandwidth is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified spurious radiation limits. The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. This definition is chosen to allow flexibility regarding adjacent channel interference levels which will be taken into account by operational procedures depending on the exact transponder carrier assignment situation.

occupied bandwidth: bandwidth of the VSAT radio frequency transmission nominated by the manufacturer

NOTE: The nominated bandwidth is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified unwanted emissions limits. The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. The nominated bandwidth is within the transmit frequency band within which the VSAT operates.

outdoor unit: modules of the VSAT intended to be installed outdoor, as declared by the applicant, or as indicated in the user documentation

NOTE 1: The outdoor unit usually comprises three main parts:

- a) the antenna sub-system which converts the incident radiation field into a guided wave and vice versa;
- b) the Low Noise Block (LNB) down converter, which is a device that amplifies, with very low internal noise, the received signals in the Radio Frequency (RF) band and converts them to intermediate frequencies;
- c) the up-converter and the power amplifier which convert from the intermediate frequency to RF and amplify the low level RF signals for transmission through the antenna subsystem.

NOTE 2: The installation equipment (means of attachment) is outside the scope of the present document. However, the antenna structures and other components directly mounted on the antenna and forming an integral part of it, are subject to the specifications of the present document

removable antenna: antenna which may be removed during the tests according to the applicant's statement

Response Channel (RC): channel by which VSAT transmit monitoring information to the CCMF

spurious radiation: any radiation outside the nominated bandwidth

NOTE: For a receive-only VSAT there is no nominated bandwidth therefore any radiation is a spurious radiation.

transmission disabled state: state in which the VSAT is not authorized by the CCMF to transmit.

transmit VSAT: VSAT capable of being used either for transmission only, or for transmission and reception

uplink power density control: control of the e.i.r.p. and/or occupied bandwidth and/or other transmission parameters (e.g. FEC, modulation, symbol rate) of the transmitted signal in order to adjust the e.i.r.p. in a given measurement bandwidth

NOTE: Uplink power density control may be used to respond to uplink fade conditions.

VSAT: complete VSAT equipment, comprising the outdoor unit and the indoor unit including the connection cable(s) between the units

3.2 Symbols

For the purposes of the present document, the following symbols apply:

dBsd Ratio expressed in decibels relative to the spectral density

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BW	Wanted signal occupied Bandwidth
CC	Control Channel
CCF	Control Channel reception Failure
CCMF	Centralized Control and Monitoring Functions
CISPR	Comité International Spécial des Perturbations Radioélectriques (International Special Committee on Radio Interference)
CMF	Control and Monitoring Function
CCR	Control Channel correctly Received
CV	Control Variable
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power
EN	European Standard
EUT	Equipment Under Test
FEC	Forward Error Correction
FS	Fixed Service
FSS	Fixed Satellite Service
GSO	Geostationary Satellite Orbit
HPA	High Power Amplifier
IDU	Indoor Unit
ITU	International Telecommunications Union
LNA	Low Noise Amplifier
LNB	Low Noise Block
LO	Local Oscillator
MODEM	MODulator/DEMODulator
PSTN	Public Switched Telephone Network
R&TTE	Radio and Telecommunications Terminal Equipment
RC	Response Channel
RE	Reset Event
RE	Radio Equipment
RED	Radio Equipment Directive