



**Satellite Earth Stations and Systems (SES);  
Harmonised Standard for Mobile Earth Stations (MES),  
including handheld earth stations, for Satellite Personal  
Communications Networks (S-PCN) operating in the  
1,6 GHz/2,4 GHz frequency band under the Mobile Satellite  
Service (MSS) covering the essential requirements  
of article 3.2 of the Directive 2014/53/EU**

*PREVIEW*  
<https://standards.etsi.org/standards-search/301441-v211-2016-06>  
4fc1-b967-4e55-4660-301441-v211-2016-06

---

Reference

REN/SES-00383

---

Keywords

earth station, MES, MSS, regulation, satellite,  
S-PCN

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction .....	6
1 Scope .....	8
2 References .....	8
2.1 Normative references .....	8
2.2 Informative references.....	9
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations .....	11
4 Technical requirement specifications .....	12
4.1 Environment profile .....	12
4.1.1 General.....	12
4.1.2 Temperature.....	12
4.1.3 Voltage.....	12
4.1.4 Vibration.....	12
4.2 Conformance requirements .....	12
4.2.1 Unwanted emissions outside the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on).....	12
4.2.1.1 Justification .....	12
4.2.1.2 Technical requirements .....	12
4.2.1.3 Conformance test .....	13
4.2.2 Unwanted emissions within the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on).....	13
4.2.2.1 Justification .....	13
4.2.2.2 Technical requirements .....	13
4.2.2.3 Conformance test .....	14
4.2.3 EIRP density within the operational band.....	15
4.2.3.1 Justification .....	15
4.2.3.2 Technical requirements.....	15
4.2.3.3 Conformance test .....	15
4.2.4 Unwanted emissions in carrier-off state.....	15
4.2.4.1 Justification .....	15
4.2.4.2 Technical requirements .....	15
4.2.4.3 Conformance test .....	15
4.2.5 MES Control and Monitoring Functions (CMF) .....	16
4.2.5.1 Self-monitoring functions / Processor monitoring .....	16
4.2.5.1.1 Justification .....	16
4.2.5.1.2 Technical requirements.....	16
4.2.5.1.3 Conformance test.....	16
4.2.5.2 Self-monitoring functions / Transmit frequency generation sub-system monitoring.....	16
4.2.5.2.1 Justification .....	16
4.2.5.2.2 Technical requirements.....	16
4.2.5.2.3 Conformance test.....	16
4.2.5.3 Network control authorization .....	16
4.2.5.3.1 Justification .....	16
4.2.5.3.2 Technical requirements.....	16
4.2.5.3.3 Conformance test.....	17
4.2.5.4 Network control reception.....	17
4.2.5.4.1 Transmission disable/enable.....	17
4.2.5.4.2 Transmit frequency control .....	17
4.2.5.5 Fellow radio stations in a dual-mode or multi-mode terminal .....	18
4.2.5.5.1 Justification .....	18

4.2.5.5.2	Technical requirements.....	18
4.2.5.5.3	Conformance test.....	18
4.2.6	Equipment identity.....	18
4.2.6.1	Justification.....	18
4.2.6.2	Technical requirements.....	18
4.2.6.3	Conformance test.....	18
4.2.7	Protection of the radio astronomy service operation in the band 1 610,6 MHz to 1 613,8 MHz.....	18
4.2.7.1	Justification.....	18
4.2.7.2	Technical requirements.....	18
4.2.7.3	Conformance test.....	18
4.2.8	Receiver Adjacent Channel Selectivity.....	19
4.2.8.1	Justification.....	19
4.2.8.2	Technical requirements.....	19
4.2.8.3	Conformance test.....	19
4.2.9	Receiver Blocking Characteristics.....	19
4.2.9.1	Justification.....	19
4.2.9.2	Technical requirements.....	19
4.2.9.3	Conformance test.....	20
5	Testing for compliance with technical requirements.....	20
5.1	Environmental conditions for testing.....	20
5.1.1	Specification of the environmental test conditions.....	20
5.1.2	Tests under extreme voltage conditions.....	20
5.2	Essential radio test suites.....	20
5.2.1	General.....	20
5.2.1.1	Presentation of equipment for testing purposes.....	20
5.2.1.2	Description of equipment.....	21
5.2.1.3	Testing of host-connected equipment and plug-in modules.....	21
5.2.1.3.1	Alternative approaches.....	21
5.2.1.3.2	Alternative A: combined equipment.....	21
5.2.1.3.3	Alternative B: use of a test jig.....	22
5.2.1.4	CMF / Special Test Equipment (STE).....	22
5.2.1.5	General test requirements.....	22
5.2.1.5.1	MES test modes.....	22
5.2.1.5.2	Special Test Equipment (STE).....	23
5.2.1.5.3	Laboratory Test Equipment (LTE).....	23
5.2.1.5.4	Methods of test for MES RF emissions according to the equipment type.....	24
5.2.1.5.5	Procedures for measurement of radiated emissions.....	24
5.2.1.5.6	Procedures for measurement of conducted emissions.....	29
5.2.1.5.7	Interpretation of the measurement results.....	30
5.2.1.5.8	Test report.....	30
5.2.2	Unwanted emissions outside the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on).....	30
5.2.2.1	Method of test.....	30
5.2.2.2	Peak measurement.....	31
5.2.2.3	Average measurement.....	31
5.2.2.4	Test requirements.....	32
5.2.3	Unwanted emissions within the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on).....	32
5.2.3.1	Method of test.....	32
5.2.3.2	Measurement method.....	32
5.2.3.3	Test requirements.....	33
5.2.4	EIRP density within the operational band.....	33
5.2.4.1	Method of test.....	33
5.2.4.2	Peak limit test.....	33
5.2.4.3	Mean limit test.....	34
5.2.4.4	Test requirements.....	34
5.2.5	Unwanted emissions in carrier-off state.....	34
5.2.5.1	Method of test.....	34
5.2.5.2	Measurement method.....	35
5.2.5.3	Test requirements.....	35
5.2.6	MES Control and Monitoring Functions (CMF).....	35

5.2.6.1	Self-monitoring functions / Processor monitoring .....	35
5.2.6.2	Self-monitoring functions / Transmit frequency generation sub-system monitoring .....	35
5.2.6.3	Network control authorization .....	35
5.2.6.3.1	Method of test.....	35
5.2.6.3.2	Test procedure .....	35
5.2.6.3.3	Test requirement .....	36
5.2.6.4	Network control reception.....	36
5.2.6.4.1	Transmission disable/enable.....	36
5.2.6.4.2	Transmit frequency control .....	37
5.2.6.5	Fellow radio stations in a dual-mode or multi-mode terminal .....	37
5.2.6.5.1	Method of test.....	37
5.2.6.5.2	Test procedure .....	38
5.2.6.5.3	Test requirements .....	38
5.2.7	Equipment identity.....	38
5.2.7.1	Method of test .....	38
5.2.7.2	Test procedure.....	38
5.2.7.3	Test requirements.....	38
5.2.8	Receiver Adjacent Channel Selectivity.....	38
5.2.8.1	General .....	38
5.2.8.2	Test set-up.....	38
5.2.8.3	Test procedure.....	39
5.2.9	Receiver Blocking Characteristics.....	39
5.2.9.1	General .....	39
5.2.9.2	Test set-up.....	39
5.2.9.3	Test procedure.....	39
<b>Annex A (normative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>41</b>
<b>Annex B (informative):</b>	<b>Explanation of nominated bandwidth.....</b>	<b>43</b>
B.1	Introduction .....	43
B.2	Interpretation of Parameters $[B_n, f_c, a, b]$ .....	43
B.3	Choice of nominated bandwidth.....	43
B.4	Maximum value for nominated bandwidth .....	45
<b>Annex C (informative):</b>	<b>Bibliography.....</b>	<b>48</b>
History .....		49

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [10].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	16 May 2016
Date of latest announcement of this EN (doa):	31 August 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	28 February 2017
Date of withdrawal of any conflicting National Standard (dow):	28 February 2018

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

## Introduction

ETSI has designed a modular structure for the standards. Each standard is a module in the structure. The modular structure is shown in ETSI EG 201 399 [i.1]

Figure 1: Void

The present document is based on ETSI TBR 041 [4].

The technical requirements in the present document are applied under articles 3.2 of the Directive 2014/53/EU [10], concerning the effective uses of the spectrum allocated to terrestrial/space radio communication and orbital resources so as to avoid harmful interference.

These requirements are in two major categories:

**emissions limits:** to protect other radio services from harmful interference generated by the MES in normal use.

**MES Control and Monitoring Functions (CMF):** to protect other radio services from unwanted transmissions from the MES. The CMF in each MES is capable of answering to commands from the Network Control Facilities (NCF) for its S-PCN.

**Receiver performance specifications:** to enable reception of a wanted signal in the presence of other high power signals in the adjacent channel and/or adjacent band.

NOTE: The requirements for Network Control Facilities (NCF) for S-PCN are contained in ETSI ETS 300 735 [5].

The determination of the parameters of the user earth stations using a given satellite constellation for the protection of the spectrum allocated to that satellite constellation, is considered to be under the responsibility of the satellite operator or the satellite network operators.

**ITEH STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/13303614-703e-4fc1-b967-c91ec55c3360/etsi-en-301-441-v2.1.1-2016-06>

# 1 Scope

The present document applies to Mobile Earth Station (MES) radio equipment which have the following characteristics:

- these MES have both transmit and receive capabilities and operate in a Satellite-Personal Communications Network (S-PCN). An S-PCN MES may be a handheld, portable, vehicle-mounted, host connected, semi-fixed or fixed equipment, or may be an element in a multi-mode terminal. It may consist of a number of modules with associated connections and user interface, or may be a self-contained single unit;
- if the MES is an element in a multi-mode terminal, unless otherwise stated in the present document, its requirements apply only to the S-PCN MES element of the terminal;
- these MES are capable in operating in all or part of the frequency bands shown in table 1.

**Table 1: Mobile Satellite Service frequency bands**

MES	MSS frequency bands
Transmit	1 610 MHz to 1 626,5 MHz
Receive	1 613,8 MHz to 1 626,5 MHz
Receive	2 483,5 MHz to 2 500,0 MHz

The present document is intended to cover the provisions of Directive 2014/53/EU [10] (RE Directive) article 3.2 which states that "...radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference."

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Directive 2014/53/EU [10] may apply to equipment within the scope of the present document.

NOTE 1: A list of such ENs is included on the ETSI web site.

NOTE 2: These LMESs are controlled and monitored by a Network Control Facility (NCF). The NCF is outside the scope of the present document.

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] Recommendation ITU-T O.153 (10/92): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [3] Void.
- [4] ETSI TBR 041 (Edition 1) (02-1998): "Satellite Personal Communications Networks (S-PCN); Mobile Earth Stations (MES), including handheld earth stations, for S-PCN in the 1,6/2,4 GHz bands under the Mobile Satellite Service (MSS); Terminal essential requirements".



- [5] ETSI ETS 300 735 (Edition 1) (10-1997): "Satellite Personal Communications Networks (S-PCN); Network Control Facilities (NCF) for Mobile Earth Stations (MES), including handheld earth stations, for S-PCN in the 1,6/2,4 GHz and the 2,0 GHz bands, providing voice and/or data communications under the Mobile Satellite Service (MSS)".
- [6] Final Acts of the World Radio Conference (WRC '95); Geneva 1995.
- [7] IEC 60068-2-1 (2007): "Environmental testing - Part 2: Tests. Tests A: Cold".
- [8] IEC 60068-2-2 (2007): "Environmental testing - Part 2: Tests. Tests B: Dry heat".
- [9] IEC 60068-2-64 (2008): "Environmental testing. Part 2-64: Tests. Test Fh: Vibration, broadband random and guidance".
- [10] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EG 201 399 (V3.1.1): " Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the Radio & Telecommunication Terminal Equipment Directive 1999/5/EC (R&TTE) and a first guide on the impact of the Radio Equipment Directive 2014/53/EU (RED) on Harmonized Standards".
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in the Directive 2014/53/EU [10] and the following apply:

**applicant:** manufacturer or his authorized representative within the European Community or the person responsible for placing the apparatus on the market

**carrier-on state (allocated a channel):** MES is in this state when it is transmitting a signal in a continuous or non-continuous mode

**carrier-off state (idle mode):** MES is in this state when it is powered-on but not transmitting a signal, i.e. not in the carrier-on state

**conducted measurement:** measurement of emissions from an antenna port of the MES made by direct wired connection to the port

**environmental profile:** range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

**Equivalent Isotropically Radiated Power (EIRP):** product of transmitter power and maximum antenna gain, equivalent to an isotropic source radiating uniformly in all directions

**handheld:** PE MES which is self-contained and is small enough and light enough to be carried and used during a call with one hand

**host-connected:** MES for which connection to or integration with host equipment is necessary to offer functionality

**host equipment:** any equipment which has a complete user functionality when not connected to the MES, and to which the MES provides additional functionality, and to which connection is necessary for the MES to offer functionality

**in-band signals:** signals which are located in the operating band plus an offset of 10 MHz outside this operating band

**Installable Equipment (IE), Internally Mounted Equipment (IME) And Externally Mounted Equipment (EME):** Installable Equipment (IE) is an equipment which is intended to be installed in a vehicle

NOTE: An IE may consist of one or several interconnected modules. The IE is composed of modules intended to be externally mounted as declared by the applicant, and defined as Externally Mounted Equipment (EME) and the remaining modules(s) as Internally Mounted Equipment (IME).

**Laboratory Test Equipment (LTE):** logical grouping that contains the standard test equipment provided by a test laboratory

**MSS band:** continuous range of frequencies allocated by the ITU to the MSS

**multi-mode:** equipment that accommodates radio stations of different radio networks

**narrow-band system:** narrow-band system is one in which the nominal carrier frequency spacing for MESs in the earth-to-space direction is less than 300 kHz

**NCF control message:** message, normally originating from a network, to a specified terminal or set of terminals of the network which indicates to the terminal or set of terminals that it/they should carry out some specific action or should enter or maintain some specific state

NOTE: For test purposes NCF control messages may originate from Special Test Equipment (STE).

**network control channel:** channel by which an MES receives general control information from the NCF of its S-PCN

**nominated bandwidth (Bn):** Bn of the Mobile Earth Station (MES) radio frequency transmission is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified levels of unwanted emissions

NOTE 1: The Bn is defined relative to the MES actual carrier frequency  $f_c$ .

Bn is the width of the frequency interval ( $f_c - a$ ,  $f_c + b$ ), where a and b, which should be specified by the applicant, may vary with  $f_c$ .

The frequency interval ( $f_c - a$ ,  $f_c + b$ ) should not encompass more than either:

- i) when  $a = b$ , 4 nominal carrier frequencies for narrow-band systems;
- ii) when  $a \neq b$ , 1 nominal carrier frequency for narrow-band systems; or
- iii) 1 nominal carrier frequency for wide-band systems.

The frequency interval ( $f_c - a$ ,  $f_c + b$ ) should be within the operational band of the MES.

NOTE 2: Explanation of nominated bandwidth is presented in annex B.

**operational band:** sub-portion of the 1 610 MHz to 1 626,5 MHz band which has been assigned in the earth-to-space direction to the MSS network within which the MES is operating

**Portable Equipment (PE):** generally intended to be self-contained, free standing and portable. A PE would normally consist of a single module, but may consist of several interconnected modules

**radiated measurement:** measurement of an actual radiated field

**Special Test Equipment (STE):** equipment which allows a test laboratory to control the MES so that the tests required by the present document can be performed

**test laboratory:** laboratory which performs the conformance testing of the MES against the present document

NOTE: The test laboratory may be the applicant's laboratory.

**test load:** test load is a substantially non-reactive, non-radiating power attenuator which is capable of safely dissipating the power from the transmitter(s)

**unwanted emissions:** unwanted emissions are those falling outside the nominated bandwidth in the carrier-on state, and those generated in the carrier-off state

**wide-band system:** wide-band system is one in which the nominal carrier frequency spacing for MESs in the Earth-to-Space direction is equal to or greater than 300 kHz

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AK-R	Air Kerma Rate
ASD	Accelerated Spectral Density
BE <sub>L</sub>	Lower Band Edge of the operating band
BE <sub>U</sub>	Upper Band Edge of the operating band
B <sub>n</sub>	nominated Bandwidth
BW	Bandwidth
CDMA	Code Division Multiple Access
CMF	Control and Monitoring Functions
CW	Continuous Wave
dBW	decibels relative to 1 Watt
EIRP	Equivalent Isotropically Radiated Power
EMC	Electro-Magnetic Compatibility
EME	Externally Mounted Equipment
ERM	Electromagnetic compatibility and Radio spectrum Matters
ETS	European Telecommunication Standard
EUT	Equipment Under Test
IE	Installable Equipment
IEC	International Electrotechnical Commission/Committee
IME	Internally Mounted Equipment
ITU	International Telecommunications Union
LTE	Laboratory Test Equipment
MES	Mobile Earth Station
MIC	MES unique Identification Code (within its S-PCN)
MSS	Mobile Satellite Service
NCF	Network Control Facility
PCN	Personal Communication Network
PE	Portable Equipment
R&TTE	Radio and Telecommunications Terminal Equipment
RE	Radio Equipment
RED	Radio Equipment Directive
RF	Radio Frequency
SNR	Signal to Noise Ratio
S-PCN	Satellite Personal Communications Network
STE	Special Test Equipment
TBR	Technical Basis for Regulation
WARC	World Administrative Radio Conference
WRC	World Radio Conference
ZVEI	Zentralverband Elektrotechnik- und Elektronik-industrie

## 4 Technical requirement specifications

### 4.1 Environment profile

#### 4.1.1 General

The technical requirements of the present document apply under the environmental profile specified below for operation of the equipment. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the specified operational environmental profile.

#### 4.1.2 Temperature

The MES shall fulfil all the requirements in the full temperature ranges of:

- -10 °C to +55 °C;

taken from IEC publications 60068-2-1 [7] and 60068-2-2 [8].

#### 4.1.3 Voltage

The applicant shall declare the nominal, lower and the higher extreme voltages.

The MES shall fulfil all the requirements in the full voltage range between the extreme voltages.

#### 4.1.4 Vibration

The MES shall fulfil all the requirements when vibrated at the frequency/amplitudes given in table 2.

**Table 2: Vibration characteristics**

Frequency range	ASD (Acceleration Spectral Density) random vibration
5 Hz to 20 Hz	0,96 m <sup>2</sup> /s <sup>3</sup> (+0/-5 %)
20 Hz to 500 Hz	0,96 m <sup>2</sup> /s <sup>3</sup> (+0/-5 %) at 20 Hz, thereafter -3 dB/Octave (+0/-5 %) (taken from IEC Publication 60068-2-64 [9])

## 4.2 Conformance requirements

### 4.2.1 Unwanted emissions outside the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on)

#### 4.2.1.1 Justification

Protection of other radio services operating outside the band 1 610 MHz to 1 628,5 MHz from emissions caused by S-PCN MESs operating within the band 1 610 MHz to 1 626,5 MHz.

#### 4.2.1.2 Technical requirements

The maximum EIRP density of the unwanted emissions from the MES outside the band 1 610,0 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz shall not exceed the limits in table 3.

In table 3, whenever a change of limit between adjacent frequency bands occurs, the lower of the two limits shall apply at the transition frequency.