



SLOVENSKI STANDARD

SIST EN 301 444 V2.1.2:2017

01-januar-2017

Satelitske zemeljske postaje in sistemi (SES) - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU, za kopenske mobilne zemeljske postaje (LMES), ki zagotavljajo govorne in/ali podatkovne komunikacije in delujejo v frekvenčnih pasovih 1,5 GHz in 1,6 GHz

Satellite Earth Stations and Systems (SES) - Harmonised Standard for Land Mobile Earth Stations (LMES) providing voice and/or data communications, operating in the 1,5 GHz and 1,6 GHz frequency bands covering the essential requirements of article 3.2 of the Directive 2014/53/EU

(standards.iteh.ai)

[SIST EN 301 444 V2.1.2:2017](https://standards.iteh.ai/catalog/standards/sist/391c584b-d82c-43cd-bf22-39de16e7d0e2/sist-en-301-444-v2-1-2-2017)

<https://standards.iteh.ai/catalog/standards/sist/391c584b-d82c-43cd-bf22-39de16e7d0e2/sist-en-301-444-v2-1-2-2017>

Ta slovenski standard je istoveten z: ETSI EN 301 444 V2.1.2 (2016-11)

ICS:

33.060.30 Radiorelejni in fiksni satelitski komunikacijski sistemi Radio relay and fixed satellite communications systems

SIST EN 301 444 V2.1.2:2017 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 444 V2.1.2:2017

<https://standards.iteh.ai/catalog/standards/sist/391c584b-d82c-43cd-bf22-39de16e7d0e2/sist-en-301-444-v2-1-2-2017>

ETSI EN 301 444 V2.1.2 (2016-11)



**Satellite Earth Stations and Systems (SES);
Harmonised Standard for Land Mobile Earth Stations (LMES)
providing voice and/or data communications,
operating in the 1,5 GHz and 1,6 GHz frequency bands
covering the essential requirements of article 3.2
of the Directive 2014/53/EU**

Reference

REN/SES-00386

Keywords

earth station, LMES, regulation, satellite

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)SIST EN 301 444 V2.1.2:2017<https://standards.iteh.ai/catalog/standards/sist/391c584b-d82c-43cd-bf22-39de16e7d01c/sist-en-301-444-v2-1-2-2017>
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	8
3 Definitions and abbreviations.....	8
3.1 Definitions.....	8
3.2 Abbreviations	9
4 Technical requirement specifications	10
4.1 Environmental profile.....	10
4.2 Conformance requirements	10
4.2.0 Maximum EIRP	10
4.2.0.1 Justification	10
4.2.0.2 Specification.....	10
4.2.0.3 Conformance test	10
4.2.1 Unwanted emissions outside the 1 625,8 MHz to 1 661,2 MHz and outside the band 1 667,3 MHz to 1 675,7 MHz	10
4.2.1.1 Justification	10
4.2.1.2 Specification.....	10
4.2.1.3 Conformance test	12
4.2.2 Maximum unwanted emissions within the 1 625,8 MHz to 1 661,2 MHz band and within the 1 667,3 MHz to 1 675,7 MHz band	12
4.2.2.1 Justification	12
4.2.2.2 Specifications	13
4.2.2.3 Conformance test	13
4.2.3 Control and Monitoring Functions (CMF).....	14
4.2.3.1 General	14
4.2.3.2 Processor monitoring	14
4.2.3.2.1 Justification	14
4.2.3.2.2 Specification	14
4.2.3.2.3 Conformance test.....	14
4.2.3.3 Transmit subsystem monitoring.....	14
4.2.3.3.1 Justification	14
4.2.3.3.2 Specification	14
4.2.3.3.3 Conformance test.....	14
4.2.3.4 Power-on/reset	14
4.2.3.4.1 Justification	14
4.2.3.4.2 Specification	14
4.2.3.4.3 Conformance test.....	15
4.2.3.5 Control Channel (CC) reception	15
4.2.3.5.1 Justification	15
4.2.3.5.2 Specification	15
4.2.3.5.3 Conformance test.....	15
4.2.3.6 Network control commands	15
4.2.3.6.1 Justification	15
4.2.3.6.2 Specification	15
4.2.3.6.3 Conformance test.....	15
4.2.3.7 Initial burst transmission	16
4.2.3.7.1 Justification	16
4.2.3.7.2 Specification	16
4.2.3.7.3 Conformance test.....	16

4.2.4	Protection of the radio astronomy service operation in the band 1 660,0 MHz to 1 660,5 MHz and in the band 1 668,0 MHz to 1 670,0 MHz	16
4.2.4.1	Purpose.....	16
4.2.4.2	Technical requirements	16
4.2.4.3	Conformance test	16
4.2.5	Receiver Adjacent Channel Selectivity.....	16
4.2.5.1	Justification	16
4.2.5.2	Specification.....	16
4.2.5.3	Conformance test	17
4.2.6	Receiver Blocking Characteristics	17
4.2.6.1	Justification	17
4.2.6.2	Specification.....	17
4.2.6.3	Conformance test	17
5	Testing for compliance with technical requirements.....	17
5.1	Environmental conditions for testing	17
5.2	Radio test suites.....	17
5.2.1	General.....	17
5.2.2	Measurement of unwanted emissions	18
5.2.2.1	General	18
5.2.2.2	Test site	19
5.2.2.3	Test method.....	19
5.2.2.3.1	Installation	19
5.2.2.3.2	Receive test equipment.....	19
5.2.2.4	Procedure	20
5.2.2.4.1	Test arrangements.....	20
5.2.2.4.2	Unwanted emissions up to 1 000 MHz.....	21
5.2.2.4.3	Unwanted emissions above 1 000 MHz.....	21
5.2.3	LMES Control and Monitoring Functions (CMF)	22
5.2.3.1	General	22
5.2.3.2	Test arrangement.....	22
5.2.3.3	Processor monitoring	23
5.2.3.3.1	Test method.....	23
5.2.3.4	Transmit subsystem monitoring.....	23
5.2.3.4.1	Test method	23
5.2.3.5	Power-on/Reset	24
5.2.3.5.1	Test method	24
5.2.3.6	Control Channel (CC) reception	24
5.2.3.6.1	Test method	24
5.2.3.7	Network control commands	25
5.2.3.7.1	Test method	25
5.2.3.8	Initial burst transmission	26
5.2.3.8.1	Test method	26
5.2.4	Receiver Adjacent Channel Selectivity.....	26
5.2.4.1	General	26
5.2.4.2	Test arrangement.....	26
5.2.4.3	Test procedures	27
5.2.5	Receiver Blocking Characteristics	27
5.2.5.1	General	27
5.2.5.2	Test arrangement.....	27
5.2.5.3	Test procedures	27
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	29
Annex B (informative):	Bibliography.....	31
History		32

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.6].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

(standards.iteh.ai)

National transposition dates	
Date of adoption of this EN:	12 September 2016
Date of latest announcement of this EN (doa):	31 December 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2017
Date of withdrawal of any conflicting National Standard (dow):	30 June 2018

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The requirements defined in the present document have been selected to ensure an adequate level of compatibility with other radio services. The levels, however, do not cover extreme cases, which may occur in any location but with a low probability of occurrence.

The present document may not cover those cases where a potential source of interference which is producing individually repeated transient phenomena or a continuous phenomenon is present, e.g. a radar or broadcast site in the near vicinity. In such a case it may be necessary to use special protection applied to either the source of interference, or the interfered part or both.

The present document does not contain any requirement, recommendation or information about the installation of the LMES.

The determination of the parameters of the user earth stations using a given geo-stationary satellite for the protection of the spectrum allocated to that satellite, is considered to be under the responsibility of the satellite operators or the satellite network operators. Applicants for LMESs operating in satellite networks which provide radio navigation service and/or other safety services should note that such satellite network operators may require testing in addition to the present document to prove correct interworking in order to avoid the LMES causing harmful interference which endangers the functioning of these services.

Following the WRC-03 decision [i.4] to allocate to MSS the bands 1 518 MHz to 1 525 MHz (space to Earth) and 1 668 MHz to 1 675 MHz (Earth to space) and the conclusions of WRC-07 [i.5], a new set of emission requirements for LMESs that are capable of transmitting in the frequency band from 1 668,0 MHz to 1 675,0 MHz is specified.

The two parts of the L-band frequency allocations are treated as two sub-bands which may be used separately or in any combination. The standard L-band allocation is referenced in the present document as "sub-band 1" and the extended L-band is referenced as "sub-band 2".

Table 2c is applicable for LMESs that are capable of transmitting in any combination of either or both of these sub-bands. Table 2c is recommended for all new LMESs including LMES that can only operate in sub-band 1.

The applicant may choose between tables 2b and 2c for new LMESs that are capable of transmitting in only the sub-band 1. The applicant has to declare which alternative is used.

The present document specifies a new set of receiver performance requirements for LMESs under the new Radio Equipment Directive 2014/53/EU [i.6].

Figure 1: Void

The present document is intended to cover the provisions of Directive 2014/53/EU [i.6] (RE Directive) article 3.2 which states that "...radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference".

Recital 10 of Directive 2014/53/EU [i.6] states that "*in order to ensure that radio equipment uses the radio spectrum effectively and supports the efficient use of radio spectrum, radio equipment should be constructed so that: in the case of a transmitter, when the transmitter is properly installed, maintained and used for its intended purpose it generates radio waves emissions that do not create harmful interference, while unwanted radio waves emissions generated by the transmitter (e.g. in adjacent channels) with a potential negative impact on the goals of radio spectrum policy should be limited to such a level that, according to the state of the art, harmful interference is avoided; and, in the case of a receiver, it has a level of performance that allows it to operate as intended and protects it against the risk of harmful interference, in particular from shared or adjacent channels, and, in so doing, supports improvements in the efficient use of shared or adjacent channels*".

Recital 11 of Directive 2014/53/EU [i.6] states that "*although receivers do not themselves cause harmful interference, reception capabilities are an increasingly important factor in ensuring the efficient use of radio spectrum by way of an increased resilience of receivers against harmful interference and unwanted signals on the basis of the relevant essential requirements of Union harmonisation legislation*".

As a consequence, the present document includes both transmitting and receiving parameters aiming to maximize the efficient use of radio spectrum.

1 Scope

The present document applies to Land Mobile Earth Stations (LMESs) radio equipment with an EIRP less than or equal to 33 dBW and which have the following characteristics:

- the LMES could be either vehicle mounted or portable equipment;
- these LMESs are controlled and monitored by a Network Control Facility (NCF). The NCF is outside the scope of the present document;
- the LMES operate through geostationary satellites as part of a network providing voice and/or data communications;
- the LMES is capable of operating in any combination of all or any part of the frequency ranges sub-band 1 and sub-band 2 defined in table 1a.

Table 1a: Land Mobile Satellite Service frequency bands

Sub-Band	Direction of transmission	LMSS frequency bands
1	Transmit 1 (Earth to space)	1 626,5 MHz to 1 660,5 MHz
	Receive 1 (space to Earth)	1 525,0 MHz to 1 559,0 MHz
2	Transmit 2 (Earth to space)	1 668,0 MHz to 1 675,0 MHz
	Receive 2 (space to Earth)	1 518,0 MHz to 1 525,0 MHz

The present document is intended to cover the provisions of Directive 2014/53/EU [i.6] (RE Directive) article 3.2 which states that "...radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Directive 2014/53/UE [i.6] may apply to equipment within the scope of the present document.

SIST EN 301 444 V2.1.2:2017

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- | | |
|-----|---|
| [1] | Void. |
| [2] | CISPR 16-1-4 (2010): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements". |
| [3] | Void. |
| [4] | Void. |

- [5] Void.
- [6] ETSI EN 301 444 (V1.2.2) (06-2013): "Satellite Earth Stations and Systems (SES); Harmonized EN for Land Mobile Earth Stations (LMES) operating in the 1,5 GHz and 1,6 GHz bands providing voice and/or data communications covering essential requirements of article 3.2 of the R&TTE directive".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] Void.
- [i.3] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.4] World Radiocommunication Conference 2003 (WRC-03) Final Acts.
- [i.5] World Radiocommunication Conference 2007 (WRC-07) Finals Acts.
- [i.6] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RED Directive).

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [i.6] and the following apply:

antenna transmit gain: ratio, expressed in decibels, of the power that would have to be supplied to an isotropic radiator to the power supplied to the antenna being considered, so that they produce the same field strength at the same distance in the same direction

applicant: manufacturer or his authorized representative within the European Community or the person responsible for placing the apparatus on the market

carrier-off state: state in which the LMES is not transmitting a carrier

carrier-on state: state in which the LMES is transmitting a carrier

Control Channel (CC): channel or channels by which LMES receive control information from the NCF for their network

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

Externally Mounted Equipment (EME): equipment consisting of those of the modules of the Installable Equipment (IE) which are intended to be mounted externally to the vehicle as stated by the manufacturer

in-band signals: signals which are located in the operating band plus an offset of 10 MHz outside this operating band

Installable Equipment (IE): equipment which is intended to be fitted to a vehicle

NOTE: An IE may consist of one or several interconnected modules.

Internally Mounted Equipment (IME): those of the modules of the IE which are not declared by the applicant as EME are defined as Internally Mounted Equipment (IME)

nominated bandwidth: bandwidth of the LMES radio frequency transmission nominated by the manufacturer

NOTE: The nominated bandwidth is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified unwanted emissions limits. The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. The nominated bandwidth is within the transmit frequency band within which the LMES operates.

Portable Equipment (PE): equipment generally intended to be self-contained, free standing and portable

NOTE: A PE would normally consist of a single module, but may consist of several interconnected modules.

sub-band: contiguous portion of the operating band

NOTE: Two sub-bands are defined (see table 1a).

unwanted emissions: emissions falling outside the nominated bandwidth

3.2 Abbreviations

ITeH STANDARD PREVIEW
(standards.iteh.ai)

For the purposes of the present document, the following abbreviations apply:

BW	BandWidth	SIST EN 301 444 V2.1.2:2017
CC	Control Channel	https://standards.iteh.ai/catalog/standards/sist/391c584b-d82c-43cd-bf22-39de16e7d9e2/sist-en-301-444-v2-1-2-2017
CISPR	International Special Committee on Radio Interference	
CMF	Control and Monitoring Functions	
CW	Continuous Wave	
EIRP	Equivalent Isotropically Radiated Power	
EMC	ElectroMagnetic Compatibility	
EME	Externally Mounted Equipment	
ETS	European Telecommunication Standard	
EUT	Equipment Under Test	
IE	Installable Equipment	
IME	Internally Mounted Equipment	
LMES	Land Mobile Earth Station	
LMSS	Land Mobile Satellite Service	
LTE	Long Term Evolution	
MES	Mobile Earth Station	
MSS	Mobile Satellite Service	
NCF	Network Control Facility	
PE	Portable Equipment	
R&TTE	Radio and Telecommunications Terminal Equipment	
RA	Radio Astronomy	
RE	Radio Equipment	
RED	Radio Equipment Directive	
RF	Radio Frequency	
SNR	Signal to Noise Ratio	
STE	Special Test Equipment	
TBR	Technical Basis for Regulation	
TTE	Telecommunications Terminal Equipment	
WRC	World Radiocommunication Conference	

4 Technical requirement specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the applicant. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile. The environmental profile for operation of the equipment shall include the ranges of humidity, temperature and supply voltage.

4.2 Conformance requirements

4.2.0 Maximum EIRP

4.2.0.1 Justification

Not needed.

4.2.0.2 Specification

The maximum EIRP of the LMES shall not exceed 33 dBW.

4.2.0.3 Conformance test

Declaration of maximum EIRP by the applicant.

NOTE: No conformance test is defined for this requirement.

<https://standards.iteh.ai/catalog/standards/sist/391c584b-d82c-43cd-bf22-31d16e710451/en-301-444-v2-1-2-2017>

4.2.1 Unwanted emissions outside the band 1 625,8 MHz to 1 661,2 MHz and outside the band 1 667,3 MHz to 1 675,7 MHz

4.2.1.1 Justification

The technical requirements presented in this clause shall apply to all LMESs that are capable of transmitting either in sub-band 1 or sub-band 2, or in both sub-bands as defined in table 1a for the purpose of:

- protection of terrestrial and satellite services from emissions caused by LMES outside the band 1 625,8 MHz to 1 661,2 MHz; and
- protection of terrestrial and satellite services from emissions caused by LMES outside the band 1 667,3 MHz to 1 675,7 MHz.

4.2.1.2 Specification

Unwanted emissions from Land Mobile Earth Stations (LMESs) outside the band 1 625,8 MHz to 1 661,2 MHz and outside the band 1 667,3 MHz to 1 675,7 MHz shall be below the following limits.

Unless otherwise stated the specification in this clause shall apply to all types of LMESs notwithstanding their transmitting capabilities within the frequency bands as defined in table 1a.

The lower limit shall apply at the transition frequency.

- 1) The unwanted emissions over the frequency range 30 MHz to 1 000 MHz shall not exceed the limits in table 1b.