

SLOVENSKI STANDARD
SIST EN 301 473 V2.1.2:2017
01-januar-2017

Satelitske zemeljske postaje in sistemi (SES) - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU, za letalske zemeljske postaje (AES), ki zagotavljajo letalsko mobilno satelitsko storitev (AMSS) in mobilno satelitsko storitev (MSS) oziroma letalsko mobilno satelitsko storitev na poti (AMS(R)S) in mobilno satelitsko storitev (MSS) ter delujejo v frekvenčnem pasu pod 3 GHz

Satellite Earth Stations and Systems (SES) - Harmonised Standard for Aircraft Earth Stations (AES) providing Aeronautical Mobile Satellite Service (AMSS)/Mobile Satellite Service (MSS) and/or the Aeronautical Mobile Satellite on Route Service (AMS(R)S)/Mobile Satellite Service (MSS), operating in the frequency band below 3 GHz covering the essential requirements of article 3.2 of the Directive 2014/53/EU

<https://standards.iteh.ai/catalog/standards/sist/0797fef7-1394-4644-b646-d030fc0b3bbc/sist-en-301-473-v2-1-2-2017>

Ta slovenski standard je istoveten z: ETSI EN 301 473 V2.1.2 (2016-11)

ICS:

33.060.30 Radiorelejni in fiksni satelitski komunikacijski sistemi Radio relay and fixed satellite communications systems

SIST EN 301 473 V2.1.2:2017 en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 473 V2.1.2:2017

<https://standards.iteh.ai/catalog/standards/sist/0797fef7-1394-4644-b646-d030fc0b3bbc/sist-en-301-473-v2-1-2-2017>

ETSI EN 301 473 V2.1.2 (2016-11)



**Satellite Earth Stations and Systems (SES);
Harmonised Standard for Aircraft Earth Stations (AES)
providing Aeronautical Mobile Satellite Service (AMSS)/
Mobile Satellite Service (MSS) and/or the
Aeronautical Mobile Satellite on Route Service (AMS(R)S)/
Mobile Satellite Service (MSS), operating in the frequency band
below 3 GHz covering the essential requirements
of article 3.2 of the Directive 2014/53/EU**

Reference

REN/SES-00389

Keywords

aeronautical, AMSS, earth station, mobile, MSS,
satellite***ETSI***650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse 06 N° 7303/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)

[SIST EN 301 473 V2.1.2:2017](#)
<https://standards.iteh.ai/catalog/standards/sist/0797fef7-1394-4644-b646-d030fc0b300000000000000000000000>
Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	9
Foreword.....	9
Modal verbs terminology.....	9
Introduction	9
1 Scope	11
2 References	12
2.1 Normative references	12
2.2 Informative references.....	12
3 Definitions and abbreviations.....	13
3.1 Definitions	13
3.2 Abbreviations	14
4 General	15
4.1 Presentation of equipment for testing purposes.....	15
4.2 Aircraft earth stations	15
4.3 Description of equipment	16
5 Requirements for AES transmitting in the band 1 610 MHz to 1 626,5 MHz	17
5.1 Unwanted emissions limits outside the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on)	17
5.1.1 Purpose	17
5.1.2 Conformance requirements.....	17
5.1.3 Method of test	17
5.1.4 Peak measurement	18
5.1.5 Average measurement.....	18
5.1.6 Test requirements.....	18
5.2 Unwanted emissions limits within the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on)	19
5.2.1 Purpose	19
5.2.2 Conformance requirements.....	19
5.2.3 Method of test	20
5.2.4 Measurement method.....	21
5.2.5 Test requirements.....	21
5.3 EIRP density limits within the operational band	21
5.3.1 Purpose	21
5.3.2 Conformance requirements.....	21
5.3.3 Method of test	22
5.3.4 Peak Limit Test.....	22
5.3.5 Mean Limit Test	22
5.3.6 Test requirements.....	23
5.4 Unwanted emissions limits (carrier-off).....	23
5.4.1 Purpose	23
5.4.2 Conformance requirements.....	23
5.4.3 Method of test	23
5.4.4 Peak measurement	24
5.4.5 Average measurement.....	24
5.4.6 Test requirements.....	24
5.5 AES Control and Monitoring Functions (CMF).....	24
5.5.1 Special test equipment	24
5.5.2 Self-monitoring functions	25
5.5.2.1 Processor monitoring	25
5.5.2.1.1 Purpose	25
5.5.2.1.2 Conformance requirements.....	25
5.5.2.1.3 Method of test.....	25
5.5.2.2 Transmit frequency generation sub-system monitoring	25

5.5.2.2.1	Purpose	25
5.5.2.2.2	Conformance requirements.....	25
5.5.2.2.3	Method of test.....	25
5.5.3	Network control authorization and reception.....	25
5.5.3.1	Network control authorization	25
5.5.3.1.1	Purpose	25
5.5.3.1.2	Conformance requirements.....	26
5.5.3.1.3	Method of test.....	26
5.5.3.1.4	Test procedure	26
5.5.3.1.5	Test requirement.....	26
5.5.3.2	Network control reception transmit frequency control.....	26
5.5.3.2.1	Purpose	26
5.5.3.2.2	Conformance requirements.....	27
5.5.3.2.3	Method of test.....	27
5.5.3.2.4	Test procedure	27
5.5.3.2.5	Test requirement.....	27
5.6	Equipment identity	27
5.6.1	Purpose	27
5.6.2	Conformance requirements.....	27
5.6.3	Method of test	28
5.6.4	Test procedure	28
5.6.5	Test requirements.....	28
6	Requirements for AES transmitting in the band 1 626,5 MHz to 1 660,5 MHz and the band 1 668,0 MHz to 1 675,0 MHz	28
6.1	Unwanted emissions limits outside the band 1 626,5 MHz to 1 660,5 MHz and the band 1 660,5 MHz to 1 662,5 MHz and also outside the band 1 666,0 MHz to 1 668,0 MHz, the band 1 668,0 MHz to 1 675,0 MHz and the band 1 675,0 MHz to 1 677,0 MHz	28
6.1.1	Purpose	28
6.1.2	Conformance requirements.....	29
6.1.3	Testing for carrier on state	35
6.1.3.1	Method of test	35
6.1.3.2	Measurement method.....	36
6.1.3.3	Test requirements.....	36
6.1.4	Testing for carrier off state	36
6.1.4.1	Method of test	36
6.1.4.2	Peak measurement method.....	36
6.1.4.3	Average measurement	37
6.1.4.4	Test requirements	37
6.2	Unwanted emissions limits within the band 1 626,5 MHz to 1 660,5 MHz and the band 1 660,5 MHz to 1 662,5 MHz and also within the band 1 666,0 MHz to 1 668,0 MHz, the band 1 668,0 MHz to 1 675,0 MHz and the band 1 675,0 MHz to 1 677,0 MHz	37
6.2.1	Purpose	37
6.2.2	Conformance requirements	38
6.2.2.1	General	38
6.2.2.2	Specification 1: Carrier-on state.....	38
6.2.2.3	Specification 2: Carrier-off state	40
6.2.3	Testing for carrier on state	41
6.2.3.1	Method of test	41
6.2.3.2	Measurement method	41
6.2.3.3	Test requirements	41
6.2.4	Testing for carrier off state	42
6.2.4.1	Method of test	42
6.2.4.2	Peak measurement method.....	42
6.2.4.3	Average measurement	42
6.2.4.4	Test requirements	42
6.3	AES Control and Monitoring Functions (CMF).....	43
6.3.1	Special test equipment	43
6.3.2	Self-monitoring functions	43
6.3.2.1	Processor monitoring	43
6.3.2.1.1	Purpose	43
6.3.2.1.2	Conformance requirements.....	43

6.3.2.1.3	Method of test.....	43
6.3.2.2	Transmit frequency generation sub-system monitoring	43
6.3.2.2.1	Purpose	43
6.3.2.2.2	Conformance requirements.....	43
6.3.2.2.3	Method of test.....	44
6.3.3	Network control authorization and reception.....	44
6.3.3.1	Network control authorization	44
6.3.3.1.1	Purpose	44
6.3.3.1.2	Conformance requirements.....	44
6.3.3.1.3	Method of test.....	44
6.3.3.1.4	Test procedure	44
6.3.3.1.5	Test requirement.....	45
6.3.3.2	Network control reception transmit frequency control.....	45
6.3.3.2.1	Purpose	45
6.3.3.2.2	Conformance requirements.....	45
6.3.3.2.3	Method of test.....	45
6.3.3.2.4	Test procedure	45
6.3.3.2.5	Test requirement.....	46
6.4	Equipment identity	46
6.4.1	Purpose	46
6.4.2	Conformance requirements.....	46
6.4.3	Method of test	46
6.4.4	Test procedure	46
6.4.5	Test requirements.....	46
7	Requirements for NGSO AES transmitting in the band 1 980 MHz to 2 010 MHz	47
7.0	General	47
7.1	Unwanted emissions limits outside the band 1 980,1 MHz to 2 009,9 MHz (carrier-on)	47
7.1.1	Purpose	47
7.1.2	Conformance requirements	47
7.1.3	Method of test	48
7.1.4	Peak measurement	48
7.1.5	Average measurement	48
7.1.6	Test requirements.....	49
7.2	Unwanted emissions limits within the bands 1 980,1 MHz to 2 009,9 MHz, 1 978,1 MHz to 1 980,1 MHz and 2 009,9 MHz to 2 011,9 MHz (carrier-on).....	49
7.2.1	Purpose	49
7.2.2	Conformance requirements	49
7.2.3	Method of test	50
7.2.4	Measurement method.....	50
7.2.5	Test requirements.....	51
7.3	Unwanted emissions limits (carrier-off).....	51
7.3.1	Purpose	51
7.3.2	Conformance requirements	51
7.3.3	Method of test	51
7.3.4	Peak measurement	52
7.3.5	Average measurement.....	52
7.3.6	Test requirements.....	52
7.4	AES Control and Monitoring Functions (CMF).....	52
7.4.1	Special test equipment	52
7.4.2	Self-monitoring functions	53
7.4.2.1	Processor monitoring	53
7.4.2.1.1	Purpose	53
7.4.2.1.2	Conformance requirements.....	53
7.4.2.1.3	Method of test.....	53
7.4.2.2	Transmit frequency generation sub-system monitoring	53
7.4.2.2.1	Purpose	53
7.4.2.2.2	Conformance requirements.....	53
7.4.2.2.3	Method of test.....	53
7.4.3	Network control authorization and reception.....	53
7.4.3.1	Network control authorization	53
7.4.3.1.1	Purpose	53

7.4.3.1.2	Conformance requirements.....	54
7.4.3.1.3	Method of test.....	54
7.4.3.1.4	Test procedure	54
7.4.3.1.5	Test requirement.....	54
7.4.3.2	Network control reception.....	55
7.4.3.2.1	Transmit frequency control	55
7.5	Equipment identity	55
7.5.1	Purpose	55
7.5.2	Conformance requirements	56
7.5.3	Method of test	56
7.5.4	Test procedure	56
7.5.5	Test requirements.....	56
8	Protection of the global navigation satellite service operating in the band 1 559 MHz to 1 610 MHz.....	56
8.1	1 559 MHz to 1 605 MHz	56
8.1.1	Purpose	56
8.1.2	Conformance requirements.....	56
8.2	1 605 MHz to 1 610 MHz	57
8.2.1	Purpose	57
8.2.2	Conformance requirements.....	57
8.3	Method of test.....	57
8.4	Average measurement	58
8.5	Test requirements	58
9	Protection of the radio astronomy services operating in the band 1 610,6 MHz to 1 613,8 MHz and in the band 1 660 MHz to 1 670 MHz.....	58
9.1	Purpose	58
9.2	Conformance requirements	58
9.2.1	Alternative 1	58
9.2.2	Alternative 2	59
9.2.3	Protection of the radio astronomy service in the 1 660,0 MHz to 1 670,0 MHz band.....	59
9.3	Method of test - unwanted emissions (alternative 1).....	60
9.4	Test procedure - unwanted emissions (alternative 1).....	60
9.5	Test requirement - unwanted emissions (alternative 1).....	60
9.6	Method of test - CMF function (alternative 2)	61
9.7	Test procedure- CMF function (alternative 2).....	61
9.8	Test requirement- CMF function (alternative 2)	61
10	Requirements for GSO AES transmitting in the band 1 980 MHz to 2 010 MHz	61
10.0	General	61
10.1	Unwanted emissions limits outside the band 1 980 MHz to 2 010 MHz (carrier-on)	62
10.1.1	Purpose	62
10.1.2	Conformance requirements	62
10.1.3	Method of test	62
10.1.4	Peak measurement	63
10.1.5	Average measurement.....	63
10.1.6	Test requirements.....	63
10.2	Unwanted emissions limits within the bands 1 980 MHz to 2 010 MHz, 1 978,1 MHz to 1 980 MHz and 2 010 MHz to 2 011,9 MHz (carrier-on)	64
10.2.1	Purpose	64
10.2.2	Conformance requirements	64
10.2.3	Method of test	64
10.2.4	Measurement method.....	65
10.2.5	Test requirements.....	65
10.3	Unwanted emissions limits (carrier-off).....	65
10.3.1	Purpose	65
10.3.2	Conformance requirements	65
10.3.3	Method of test	66
10.3.4	Peak measurement	66
10.3.5	Average measurement.....	66
10.3.6	Test requirements.....	67
10.4	AES Control and Monitoring Functions (CMF).....	67

10.4.1	Special test equipment	67
10.4.2	Self-monitoring functions	67
10.4.2.1	Processor monitoring	67
10.4.2.1.1	Purpose	67
10.4.2.1.2	Conformance requirements	67
10.4.2.1.3	Method of test	67
10.4.2.2	Transmit frequency generation sub-system monitoring	68
10.4.2.2.1	Purpose	68
10.4.2.2.2	Conformance requirements	68
10.4.2.2.3	Method of test	68
10.4.3	Network control authorization and reception	68
10.4.3.1	Network control authorization	68
10.4.3.1.1	Purpose	68
10.4.3.1.2	Conformance requirements	68
10.4.3.1.3	Method of test	68
10.4.3.1.4	Test procedure	68
10.4.3.1.5	Test requirement	69
10.4.3.2	Network control reception	69
10.4.3.2.1	Transmit frequency control	69
10.5	Equipment identity	70
10.5.1	Purpose	70
10.5.2	Conformance requirements	70
10.5.3	Method of test	70
10.5.4	Test procedure	70
10.5.5	Test requirements	71
11	Receiver Performance Requirements	71
11.1	General	71
11.2	Receiver Adjacent Channel Selectivity	71
11.2.1	Purpose	71
11.2.2	Conformance requirements	71
11.2.3	Conformance test	71
11.3	Receiver Blocking Characteristics	71
11.3.1	Purpose	71
11.3.2	Conformance requirements	72
11.3.3	Conformance test	72
11.4	Method of testing	72
11.4.1	Receiver Adjacent Channel Selectivity	72
11.4.1.1	General	72
11.4.1.2	Test arrangement	72
11.4.1.3	Test procedures	73
11.4.2	Receiver Blocking Characteristics	73
11.4.2.1	General	73
11.4.2.2	Test arrangement	73
11.4.2.3	Test procedures	73
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	74
Annex B (normative):	General test requirements	76
B.1	AES test modes	76
B.2	Special Test Equipment	76
B.2.1	STE description	76
B.2.2	Use of STE for control and monitoring functions tests	77
B.2.3	Test modulating signal	77
B.3	Laboratory Test Equipment	77
B.4	Interpretation of the measurement results	78
B.5	Test report	78

Annex C (normative):	Environmental conditions	79
C.1	General	79
C.2	Environmental conformance requirements.....	79
C.3	Environmental test conditions	79
Annex D (normative):	Arrangements for measurement of emissions from AES	80
D.1	General	80
D.2	Carrier-on emissions.....	80
D.2.1	Equipment required	80
D.2.2	Equipment arrangement	81
D.2.3	Emissions from 4 GHz to 18 GHz.....	81
D.2.4	Emissions from 10 kHz to 4 GHz.....	81
D.3	Carrier-off emissions.....	82
D.3.1	Equipment required	82
D.3.2	Equipment arrangement	82
D.3.3	Carrier-off emissions from 4 GHz to 18 GHz	82
D.3.4	Carrier-off emissions from 10 kHz to 4 GHz	83
Annex E (informative):	Explanation of nominated bandwidth.....	84
E.1	Introduction	84
E.2	Interpretation of Parameters [B _n , f _c , a, b].....	84
E.3	Choice of nominated bandwidth.....	84
E.4	Maximum value for nominated bandwidth	86
Annex F (informative):	Bibliography.....	88
History	SIST EN 301 473 V2.1.2:2017 https://standards.iteh.ai/catalog/standards/sist/0797fcf7-1394-4644-b646-d030fc0b3bbc/sist-en-301-473-v2-1-2-2017	89

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.4].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

THE STANDARD REVIEW (standards.iteh.ai)

National transposition dates <small>SIST EN 301 473 V2.1.2:2017</small>	
Date of adoption of this EN:	12 September 2016 <small>https://standards.iteh.ai/catalog/standards/sist/0797fef7-1394-4611-1646-d030fc0b3bbc/sist-en-301-473-v2-1-2-2017</small>
Date of latest announcement of this EN (doa):	31 December 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2017
Date of withdrawal of any conflicting National Standard (dow):	30 June 2018

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

An AES to be effectively used on board an aircraft will also be subject to airworthiness approval. This approval will refer to additional requirements (e.g. ISO 7137 equivalent to EUROCAE ED-14D and RTCA DO-160D [1]). Foreseeable evolution of the GNSS (i.e. Galileo or GPS L5) would result in the coming years in specific requirements to protect the use of the GNSS signals on board aircraft. Therefore these new GNSS frequency bands may require different protection than currently stated in the present document.

The present document is therefore intended to cover the provisions of Directive 2014/53/EU [i.4] (RE Directive) article 3.2 which states that "*....radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*".

Recital 10 of Directive 2014/53/EU [i.4] states that "*In order to ensure that radio equipment uses the radio spectrum effectively and supports the efficient use of radio spectrum, radio equipment should be constructed so that: in the case of a transmitter, when the transmitter is properly installed, maintained and used for its intended purpose it generates radio waves emissions that do not create harmful interference, while unwanted radio waves emissions generated by the transmitter (e.g. in adjacent channels) with a potential negative impact on the goals of radio spectrum policy should be limited to such a level that, according to the state of the art, harmful interference is avoided; and, in the case of a receiver, it has a level of performance that allows it to operate as intended and protects it against the risk of harmful interference, in particular from shared or adjacent channels, and, in so doing, supports improvements in the efficient use of shared or adjacent channels.*"

Recital 11 of Directive 2014/53/EU [i.4] states that "*Although receivers do not themselves cause harmful interference, reception capabilities are an increasingly important factor in ensuring the efficient use of radio spectrum by way of an increased resilience of receivers against harmful interference and unwanted signals on the basis of the relevant essential requirements of Union harmonisation legislation.*"

As a consequence, the present document includes both transmitting and receiving parameters aiming to maximise the efficient use of radio spectrum.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 473 V2.1.2:2017](#)

<https://standards.iteh.ai/catalog/standards/sist/0797fef7-1394-4644-b646-d030fc0b3bbc/sist-en-301-473-v2-1-2-2017>

1 Scope

The present document specifies certain minimum technical performance requirements of Aircraft Earth Station (AES) equipment with both transmit and receive capabilities for operation in the Aeronautical Mobile Satellite Service (AMSS)/Mobile Satellite Service (MSS), and/or in the Aeronautical Mobile Satellite on Route Service (AMS(R)S)/Mobile Satellite Service (MSS), in the frequency bands given in table 1.

Table 1: Aeronautical Mobile Satellite Service (AMSS)/Mobile Satellite Service (MSS), and/or Aeronautical Mobile Satellite on Route Service (AMS(R)S)/Mobile Satellite Service (MSS) frequency bands

	AMSS/MSS and/or AMS(R)S/MSS frequency bands
AES transmit	1 610 MHz to 1 626,5 MHz
AES receive	1 613,8 MHz to 1 626,5 MHz
AES receive	2 483,5 MHz to 2 500 MHz
AES transmit	1 626,5 MHz to 1 660,5 MHz
AES receive	1 525 MHz to 1 559 MHz
AES transmit	1 668 MHz to 1 675 MHz
AES receive	1 518 MHz to 1 525 MHz
AES transmit	1 980 MHz to 2 010 MHz
AES receive	2 170 MHz to 2 200 MHz

The technical requirements in the present document are in three major categories:

- **emission limits:** to protect other radio services and systems from harmful interference generated by the AES in normal use;
- **AES Control and Monitoring Functions (CMF):** to protect other radio services and systems from unwanted transmissions from the AES. The CMF in each AES is capable of answering to commands from the Network Control Facilities (NCF) for its supporting satellite network;
- **receiver performance specifications:** to enable reception of a wanted signal in presence of other high power signals on the adjacent channel and/or adjacent band.

NOTE 1: The requirements for Network Control Facilities (NCF) for S-PCN MES transmitting in the 1 610 MHz to 1 626,5 MHz band or the 1 980 MHz to 2 010 MHz band are contained in ETSI ETS 300 735 [4]; these requirements are also applicable to AES transmitting in those bands.

An AES may be subject to additional or alternative requirements in other standards depending on its functionality, in particular if it supports a service which is considered a justified case for regulation of terminal equipment interworking via the public telecommunications network. An AES will also be subject to additional airworthiness certification requirements.

The present document is intended to cover the provisions of Directive 2014/53/EU [i.4] (RE Directive) article 3.2 which states that "*Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the RE Directive [i.4] may apply to equipment within the scope of the present document.

NOTE 2: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ISO 7137 (1995) equivalent to EUROCAE ED-14D and RTCA DO-160D: "Aircraft - Environmental conditions and test procedures for airborne equipment".
- [2] Recommendation ITU-T O.153 (1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [3] RTCA DO-210D (04-2000): "Minimum Operational Performance Standards (MOPS) for Geosynchronous Orbit Aeronautical Mobile Satellite Services (AMSS) Avionics".
- [4] ETSI ETS 300 735 (edition 1) (10-1997): "Satellite Personal Communications Networks (S-PCN); Network Control Facilities (NCF) for Mobile Earth Stations (MES), including handheld earth stations, for S-PCN in the 1,6/2,4 GHz and the 2,0 GHz bands, providing voice and/or data communications under the Mobile Satellite Service (MSS)".
- [5] ITU Radio Regulations (2008). <https://standards.iteh.ai/catalog/standards/sist/0797ef7-1394-4644-b646-40306-0b21bce0ist-en-301-473-v2-1-2-2017>

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ECC/DEC (04)09: "ECC Decision of 12 November 2004 on the designation of the band 1518 to 1525 MHz and 1670 to 1675 MHz for the Mobile-Satellite Service".
- [i.2] ICAO Annex 10 Volume I: "Radio Navigation Aids" (Aeronautical Telecommunications) to the convention on International Civil Aviation.
- [i.3] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.4] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RE Directive).

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

antenna subsystem: includes all those RF components from the physical aperture of the antenna(s) to a single antenna port where the interconnecting cable to the transceiver is to be attached; and related ancillary components; e.g. beam-steering units and RF relays, if present

applicant: party seeking an approval, or to place an AES on the European market, i.e. the manufacturer of the equipment, or his authorized representative, or an equipment supplier to the European market

carrier-off state (idle mode): state when AES is powered on but not transmitting a signal, i.e. not in the carrier-on state

carrier-on state (allocated a channel): state when AES is transmitting a signal in a continuous or non-continuous mode

conducted measurement: measurement of emissions from an antenna port of the AES made by direct wired connection to the port

Effective Isotropically Radiated Power (EIRP): product of transmitter power and maximum antenna gain, equivalent to an isotropic source radiating uniformly in all directions

Externally Mounted Equipment (EME): IE module which is intended to be externally mounted, as declared by the manufacturer

iTeh STANDARD PREVIEW

in-band signals: signals which are located in the operating band plus an offset of 10 MHz outside this operating band

(standards.iteh.ai)

Installable Equipment (IE): equipment which is intended to be fitted to an aircraft

Internally Mounted Equipment (IME): IE module which is not defined as Externally Mounted Equipment (EME)
<https://standards.iteh.ai/catalog/standards/sist/0797ef7-1394-4644-b646>

Laboratory Test Equipment (LTE): logical grouping that contains the standard test equipment provided by a test laboratory

MSS band: continuous range of frequencies allocated by the ITU to the MSS

narrow-band system: system in which the nominal carrier frequency spacing for AESs in the Earth-to-Space direction is less than 300 kHz

network control channel: channel by which an AES receives general control information from the NCF of its network

NCF control message: message, normally originating from a network, to a specified terminal or set of terminals of the network which indicates to the terminal or set of terminals that it/they should carry out some specific action or should enter or maintain some specific state

NOTE: For test purposes NCF control messages may originate from Special Test Equipment.

nominated Bandwidth (Bn): bandwidth of the Aircraft Earth Station (AES) radio frequency transmission

NOTE 1: Bn is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified levels of unwanted emissions. See annex D.

NOTE 2: The Bn is defined relative to the AES actual carrier frequency f_c .

Bn is the width of the frequency interval $[f_c - a, f_c + b]$, where a and b, which is specified by the terminal manufacturer and may vary with f_c .

The frequency interval $[f_c - a, f_c + b]$ does not encompass more than either:

- i) when $a = b$, 4 nominal carrier frequencies for narrow-band systems;
- ii) when $a \neq b$, 1 nominal carrier frequency for narrow-band systems; or