
Reference

REN/SES-00393

Keywords

earth station, ESV, maritime, regulation, satellite

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction	7
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	13
3.3 Abbreviations	13
4 Technical requirements specifications	14
4.1 General	14
4.1.1 Environmental profile	14
4.1.2 Operational configurations	14
4.1.3 ESV states and radio states	14
4.2 Conformance requirements	15
4.2.1 Off-axis spurious radiation	15
4.2.1.1 Justification	15
4.2.1.2 Specification.....	16
4.2.1.3 Conformance tests.....	17
4.2.2 On-axis spurious radiation for ESV.....	17
4.2.2.1 Justification	17
4.2.2.2 Specification.....	17
4.2.2.2.1 "Carrier-on" radio state.....	17
4.2.2.2.2 "Carrier-off" and "Emissions disabled" radio states	18
4.2.2.3 Conformance tests.....	18
4.2.3 Maximum ESV emissions towards the horizon	18
4.2.3.1 Justification	18
4.2.3.2 Specification.....	18
4.2.3.2.1 Specification 1: Maximum e.i.r.p. spectral density towards the horizon	18
4.2.3.2.2 Specification 2: Maximum e.i.r.p. towards the horizon.....	18
4.2.3.3 Conformance tests.....	18
4.2.4 Off-axis e.i.r.p. emission density within the band.....	18
4.2.4.0 General	18
4.2.4.1 Justification	18
4.2.4.2 Specification.....	19
4.2.4.3 Conformance tests.....	20
4.2.5 Carrier suppression	20
4.2.5.1 Justification	20
4.2.5.2 Specification.....	20
4.2.5.3 Conformance tests.....	21
4.2.6 Antenna pointing and polarization alignment for ESVs	21
4.2.6.1 Justification	21
4.2.6.2 Specification.....	21
4.2.6.3 Conformance tests.....	22
4.2.7 Cessation of emissions of the ESV	22
4.2.7.1 Justification	22
4.2.7.2 Specification.....	22
4.2.7.2.1 Specification 1: Mode of cessation of emissions	22
4.2.7.2.2 Specification 2: Conditions under which the ESV shall cease emissions.....	22
4.2.7.2.3 Specification 3: Cessation of emissions	23
4.2.7.2.4 Specification 4: Fault conditions	23

4.2.7.3	Conformance tests.....	23
4.2.8	Identification of ESV.....	23
4.2.8.1	Justification.....	23
4.2.8.2	Specification.....	23
4.2.8.3	Conformance tests.....	23
4.2.9	Control and Monitoring Functions (CMFs).....	24
4.2.9.1	CMF state diagram.....	24
4.2.9.2	Processor monitoring.....	25
4.2.9.2.1	Justification.....	25
4.2.9.2.2	Specification.....	25
4.2.9.2.3	Conformance tests.....	25
4.2.9.3	Transmit subsystem monitoring.....	25
4.2.9.3.1	Justification.....	25
4.2.9.3.2	Specification.....	25
4.2.9.3.3	Conformance tests.....	25
4.2.9.4	Power-on/Reset.....	25
4.2.9.4.1	Justification.....	25
4.2.9.4.2	Specification.....	25
4.2.9.4.3	Conformance tests.....	25
4.2.9.5	Control Channel (CC) and Response Channel (RC).....	26
4.2.9.5.1	Justification.....	26
4.2.9.5.2	Specification.....	26
4.2.9.5.3	Conformance tests.....	26
4.2.9.6	Network control commands.....	27
4.2.9.6.1	Justification.....	27
4.2.9.6.2	Specification.....	27
4.2.9.6.3	Conformance test.....	27
4.2.9.7	Initial burst transmission.....	27
4.2.9.7.1	Justification.....	27
4.2.9.7.2	Specification.....	27
4.2.9.7.3	Conformance tests.....	28
4.2.10	Receive antenna off-axis gain pattern.....	28
4.2.10.1	Justification.....	28
4.2.10.2	Specification.....	28
4.2.10.3	Conformance tests.....	28
4.2.11	Blocking performance.....	28
4.2.11.1	Justification.....	28
4.2.11.2	Specification.....	28
4.2.11.3	Conformance tests.....	29
4.2.12	Adjacent Signal Selectivity.....	29
4.2.12.1	Justification.....	29
4.2.12.2	Specification.....	29
4.2.12.3	Conformance tests.....	29
5	Testing for compliance with technical requirements.....	29
5.1	Environmental conditions for testing.....	29
5.2	Essential radio test suites.....	30
6	Test methods for the complete ESV.....	30
6.1	General.....	30
6.2	Off-axis spurious radiation.....	31
6.2.0	General.....	31
6.2.1	Test method.....	31
6.2.1.a	General.....	31
6.2.1.0	Multi-carrier operation.....	31
6.2.1.1	Up to 2 000 MHz.....	32
6.2.1.1.1	Test site.....	32
6.2.1.1.2	Procedure.....	32
6.2.1.2	Above 2 000 MHz.....	32
6.2.1.2.0	General.....	32
6.2.1.2.1	Identification of the significant frequencies of spurious radiation.....	33
6.2.1.2.2	Measurement of radiated power levels of identified spurious radiation.....	33

6.2.1.2.3	Measurement of conducted spurious radiation at the antenna flange	35
6.3	On-axis spurious radiation.....	35
6.3.1	Test method	35
6.3.1.1	Test site	35
6.3.1.2	Method of measurement.....	36
6.3.1.2.1	General	36
6.3.1.2.2	Method of measurement at the antenna flange	36
6.3.1.2.3	Method of measurement with a test antenna	37
6.4	Maximum ESV emissions towards the horizon.....	38
6.4.1	Test method	38
6.4.1.1	Maximum e.i.r.p. towards the horizon	38
6.4.1.2	Maximum e.i.r.p. spectral density towards the horizon.....	38
6.5	Off-axis e.i.r.p. emission density within the band	38
6.5.0	General.....	38
6.5.1	Test method	39
6.5.1.1	General	39
6.5.1.2	Transmit output power density.....	39
6.5.1.2.1	General	39
6.5.1.2.2	Test site.....	39
6.5.1.2.3	Method of measurement	39
6.5.1.3	Antenna transmit gain	40
6.5.1.3.1	General	40
6.5.1.3.2	Test site.....	40
6.5.1.3.3	Method of measurement	41
6.5.1.4	Antenna transmit radiation patterns	42
6.5.1.4.1	General	42
6.5.1.4.2	Test site.....	42
6.5.1.4.3	Test arrangement	42
6.5.1.4.4	Co-polar radiation pattern-azimuth.....	42
6.5.1.4.5	Co-polar radiation pattern-elevation.....	43
6.5.1.4.6	Cross-polar radiation pattern-azimuth.....	43
6.5.1.4.7	Cross-polar radiation pattern-elevation.....	44
6.5.2	Computation of results.....	44
6.6	Carrier suppression.....	45
6.6.1	Test method	45
6.7	Antenna pointing for ESV	45
6.7.1	General.....	45
6.7.2	Test method	45
6.8	Antenna mechanical stability.....	46
6.8.1	Test method	46
6.9	Polarization angle alignment capability	46
6.9.1	Test method	46
6.10	Cessation of emissions of the ESV.....	47
6.10.1	Test arrangement	47
6.10.2	Test Method.....	48
6.10.2.1	Required documentation	48
6.10.2.2	Cessation of emissions from the "Transmission enabled" state	48
6.10.2.3	Cessation of emission from the "Transmission disabled" state	48
6.10.2.4	Cessation of emission from the "Initial Phase" state.....	48
6.10.2.4.1	EUTs transmitting initial bursts.....	48
6.10.2.4.2	EUTs not transmitting initial bursts.....	49
6.10.2.5	"Single action" means of cessation of emissions.....	49
6.10.2.6	Fault conditions.....	50
6.11	Identification of ESV.....	50
6.11.1	Test arrangement	50
6.11.2	Test method	50
6.12	Control and monitoring functions	50
6.12.0	General.....	50
6.12.1	Test arrangement	50
6.12.2	Processor monitoring- Test method.....	50
6.12.3	Transmit subsystem monitoring-Test method.....	51
6.12.4	Power-on/Reset-Test method.....	51

6.12.5	Control Channel and Response Channel -Test method.....	52
6.12.6	Network Control commands-Test method.....	53
6.12.7	Initial burst transmission-Test method.....	54
6.13	Receive antenna off-axis gain pattern	54
6.13.1	Test Method.....	54
6.13.1.1	Test site	54
6.13.1.2	Method of measurement.....	54
6.14	Blocking performance	55
6.14.1	Test method	55
6.15	Adjacent Signal Selectivity	56
6.15.1	Test method	56
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	57
Annex B (normative):	Mechanical stability methodology	59
Annex C (informative):	Bibliography.....	61
History		62

iTeh STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/db7dabe-0719-4361-b151-942700926a26/etsi-en-302-340-v2.1.1-2016-05>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.5] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [9].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	16 May 2016
Date of latest announcement of this EN (doa):	31 August 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	28 February 2017
Date of withdrawal of any conflicting National Standard (dow):	28 February 2018

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio equipment within the scope of the Directive 2014/53/EU [9]. The modular structure is shown in ETSI EG 201 399 [i.1].

Figure 1: Void

Remarks on the present document

The determination of the parameters of the user earth stations using a given geo-stationary satellite for the protection of the spectrum allocated to that satellite, is considered to be under the responsibility of the satellite operator or the satellite network operators.

The requirements have been selected to ensure an adequate level of compatibility with other radio services. The levels, however, do not cover extreme cases which may occur in any location but with a low probability of occurrence.

The present document is based on the application of ITU-R Resolution 902 (WRC-03) [i.2].

The present document may not cover those cases where a potential source of interference which is producing individually repeated transient phenomena or a continuous phenomenon is present, e.g. a radar or broadcast site in the near vicinity. In such a case it may be necessary to use special protection applied to either the source of interference, or the interfered part or both.

The present document does not contain any requirement, recommendation or information about the installation of the ESV.

All parts of the below-deck unit related to reception, processing and presentation of the received information except the control channel are not within the scope of the present document. The syntax of the control channel messages is outside the scope of the present document.

The present document is based upon the standard for environmental conditions for marine navigational equipment, CENELEC EN 60945 [7]. In addition, attention should be paid to clause 11.1 (Acoustic noise and signals), and clause 11.2 (Compass safe distance).

PREVIEW
iTech STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/db7dabe-0771-4361-b151-942700926a26/etsi-en-302-340-v2.1.1-2016-05>

1 Scope

The present document applies to Earth Stations located on board Vessels (ESVs) which have the following characteristics:

- The ESV is comprised of all the equipment, electrical and mechanical, from the antenna itself to the interface with other communications equipment on board (usually referred to as the terrestrial interface).
- The ESV transmits in the frequency range from 14,00 GHz to 14,50 GHz allocated to the Fixed Satellite Services (FSS) (earth-to-space).
- The ESV receives in one or more frequencies within the range from 10,70 GHz to 12,75 GHz in the bands allocated to the Fixed Satellite Services (FSS) (space-to-earth), depending on the ITU Region where the ESV is located.
- The ESV uses linear polarization.
- The ESV operates through a geostationary satellite at least 2° to 3° away from any other geostationary satellite operating in the same frequency band and covering the same area.

NOTE 1: The satellite spacing is mainly equal to 3° in ITU Regions 1 and 3 and 2° in ITU Region 2.

The ESV transmits at elevations greater or equal to the minimum elevation angle declared by the applicant.

- The ESV antenna diameter is not smaller than 0,6 m.

NOTE 2: Operation within 125 km of non-CEPT countries with antenna diameter smaller than 1,2 m may be subject to specific agreement with concerned administrations as stated in ITU-R Resolution 902 (WRC-03).

- The ESV is designed for transmission and reception of radio-communications signals in accordance with any of the frequency bands specified above.
- The ESV is usually designed for unattended operation.
- The ESV is operating as part of a satellite network (e.g. star, mesh or point-to-point) used for the distribution and/or exchange of information between users.
- The ESV is controlled and monitored by a Network Control Facility (NCF). The NCF is outside the scope of the present document.

The present document applies to the ESV with its ancillary equipment and its various telecommunication ports, and when operated within the boundary limits of the operational environmental profile declared by the applicant and when installed as required by the applicant by declaration or in the user documentation.

The present document is intended to cover the provisions of Directive 2014/53/EU [9] (RE Directive) article 3.2, which states that "... radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference".

The present document incorporates the technical limitations listed in annex 2 of ITU-R Resolution 902 (WRC-03) [i.2].

NOTE 3: According to ITU-R Resolution 902 (WRC-03), any transmission from ESVs within the 125 km minimum distance of each country where the ESV transmit frequency band is used by the Fixed Service will be subject to the prior agreement of the concerned administration(s) or to the relevant ECC Decision and may specify additional operational requirements.

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Directive 2014/53 [9] (RE Directive) may apply to equipment within the scope of the present document.

NOTE 4: A list of such ENs is included on the web site <http://www.newapproach.org/>.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] Void.
- [3] Void.
- [4] Void.
- [5] CISPR 16-1 (2003): "Specification for radio disturbance and immunity measuring apparatus and methods".
- [6] CISPR 16-1-5 (2003): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1-5: Radio disturbance and immunity measuring apparatus - Antenna calibration test sites for 30 MHz to 1 000 MHz".
- [7] CENELEC EN 60945 (2002): "Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results".
- [8] ITU-R Radio Regulations (2004).
- [9] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RE Directive).

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the Radio & Telecommunication Terminal Equipment Directive 1999/5/EC (R&TTE) and a first guide on the impact of the Radio Equipment Directive 2014/53/EU (RED) on Harmonized Standards".
- [i.2] ITU-R Resolution 902 (WRC-03): "Provisions relating to earth stations located on board vessels which operate in fixed-satellite service networks in the uplink bands 5 925-6 425 MHz and 14-14.5 GHz".
- [i.3] ETSI TR 102 215: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".

- [i.4] ETSI TR 102 375: "Satellite Earth Stations and Systems (SES); Guidelines for determining the parts of satellite earth station antenna radiation patterns concerned by the geostationary satellite orbit protection".
- [i.5] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [9] and the following apply:

above-deck unit: part of the ESV intended to be installed above deck, as declared by the applicant, or as indicated in the user documentation

The above-deck unit usually comprises the following main parts:

- a) The antenna sub-system which converts the incident radiation field into a guided wave and vice versa.
- b) The Low Noise Block (LNB) down converter, which is a device that amplifies, with very low internal noise, the received signals in the Radio Frequency (RF) band and converts them to intermediate frequencies.
- c) The up-converter and the power amplifier which convert from the intermediate frequency to RF and amplify the low level RF signals for transmission through the antenna subsystem.
- d) The stabilization and tracking subsystems that ensure pointing of the antenna main beam towards the satellite within the required accuracy.

NOTE: The installation equipment (means of attachment) is outside the scope of the present document. However, the antenna structures and other components directly mounted on the antenna and forming an integral part of it, are subject to the specifications of the present document.

ancillary equipment: equipment used in connection with an ESV is considered as ancillary if the three following conditions are met:

- a) the equipment is intended for use in conjunction with the ESV to provide additional operational and/or control features (e.g. to extend control to another position or location); and
- b) the equipment cannot be used on a stand alone basis, to provide user functions independently of the ESV; and
- c) the absence of the equipment does not inhibit the operation of the ESV.

applicant: manufacturer or his authorized representative within the European Community or the person responsible for placing the apparatus on the market

below-deck unit: part of the ESV equipment which is installed inside the vessel (i.e. below deck) and its connection cables with the above deck units

carrier-off radio state: radio state in which the ESV may transmit and does not transmit any carrier

NOTE 1: The phrase "the ESV may transmit" means that all the conditions for transmission are satisfied (e.g. in a state where transmissions are permitted, no failure detected, and the ESV is correctly pointed towards the satellite).

NOTE 2: The existence of a "Carrier-off" radio state depends on the system of transmission used. For ESVs designed for continuous transmission mode there may be no "Carrier-off" state.

carrier-on radio state: radio state in which the ESV may transmit and transmits a carrier

Control Channel (CC): channel or channels by which ESVs receive control information from the NCF

EIRP_{max}: maximum e.i.r.p. capability of the ESV as declared by the applicant

EIRP_{nom}:

- (i) either EIRP_{max};
- (ii) or, when uplink power control is implemented, the maximum required e.i.r.p. of the ESV under clear sky condition as declared by the applicant.

emissions disabled radio state: radio state in which the ESV does not emit

NOTE: Examples of cases where the ESV is in this radio state: before system monitoring pass, before the control channel is received, when a failure is detected, when an ESV is commanded to disable, and when the ESV is in a location requiring cessation of emissions.

environmental profile: range of environmental conditions under which equipment within the scope of ETSI EN 302 340 (the present document) is required to comply with the provisions of ETSI EN 302 340

external control channel: control channel which is either (i) carried by the ESV network via the same or another satellite, but not within the internal protocol of the ESV system, or (ii) carried by any other radio communication system

external response channel: response channel which is either (i) carried by the ESV network via the same or another satellite, but not within the internal protocol of the ESV system, or (ii) carried by any other radio communication system

integral antenna: antenna which may not be removed during the tests according to the applicant's statement

internal control channel: control channel which is carried by the ESV network via the same satellite as used for transmission of user data and within the internal protocol structure of the ESV system

internal response channel: response channel which is carried by the ESV network via the same satellite as used for transmission of user data and within the internal protocol structure of the ESV system

network: any network configuration including star, mesh and point-to-point configurations

Network Control Facility (NCF): set of functional entities that, at system level, monitor and control the correct operation of all ESVs in a network

nominal antenna diameter: antenna diameter declared by the manufacturer that is a parameter in performance characteristics and that allows reference to a certain performance

NOTE: An antenna with circular aperture of diameter equal to the nominal diameter does typically have the performance specified.

Network operators might request antennas of a certain diameter. Then an antenna that is compliant with the requirement for nominal antenna diameter equal to the requested antenna diameter can be used. Manufacturers can mark their equipment with antenna diameters used in the requirements during compliance test.

nominated bandwidth: bandwidth of the ESV radio frequency transmission nominated by the applicant. The nominated bandwidth is centred on the transmit frequency and does not exceed 5 times the occupied bandwidth

NOTE: The nominated bandwidth is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified spurious radiation limits. The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. This definition is chosen to allow flexibility regarding adjacent channel interference levels which will be taken into account by operational procedures depending on the exact transponder carrier assignment situation.

off-axis angle: angle between the direction of the axis of the antenna main beam and the considered direction

removable antenna: antenna which may be removed during the tests according to the applicant's statement

Response Channel (RC): channel by which ESV transmit monitoring information to the NCF

spurious radiation: any radiation outside the nominated bandwidth

Transmission disabled state: ESV is in this state when it is not authorized by the NCF to transmit

Transmission enabled state: ESV is in this state when it is authorized by the NCF to transmit

Wanted signal occupied bandwidth (BW):

- for a digital modulation scheme: the width of the signal spectrum 10 dB below the maximum in-band density;
- for an analogue modulation scheme: the width of a frequency band such that, below the lower and above the upper frequency limits, the mean power emitted is equal to 0,5 % of the total mean power of the emission.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

dBc	Ratio expressed in decibels relative to the e.i.r.p. of the unmodulated carrier
dBi	Ratio of an antenna gain to the gain of an isotropic antenna, expressed in decibels
dBsd	Ratio expressed in decibels relative to the spectral density
dBW	Ratio of a power to 1 watt, expressed in decibels
dBpW	Ratio of a power to 1 pico watt, expressed in decibels
dB μ V/m	Ratio of an electric field to 1 μ V/m, expressed in decibels (20 log(electric field / 1 μ V/m))

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BW	Wanted signal occupied Bandwidth
BDU	Below Deck Unit
CC	Control Channel
CCF	Control Channel reception Failure
CCR	Control Channel correctly Received
CENR	Cessation of Emissions Not Requested
CEPT	Conférence Européenne des Postes et Télécommunications (European Conference of Postal and Telecommunications Administrations)
CER	Cessation of Emissions Requested
CISPR	Comité International Spécial des Perturbations Radioélectriques (International Special Committee on Radio Interference)
CMF	Control and Monitoring Functions
e.i.r.p.	equivalent isotropically radiated power
ECC	Electronic Communications Committee (of CEPT)
EMC	Electro-Magnetic Compatibility
EN	European Standard
ESV	Earth Station on board a Vessel
EUT	Equipment Under Test
FEC	Forward Error Correction
FS	Fixed Service
FSS	Fixed Satellite Service
GEUT	Gain of EUT
GSO	Geostationary Satellites Orbit
HPA	High Power Amplifier
IPR	Intellectual Property Rights
ITU	International Telecommunications Union
ITU-R	Internail Telecommunication Union - Radiocommunication Sector
LNB	Low Noise Block
LO	Local Oscillator
LV	Low Voltage
NCF	Network Control Facility
R&TTE	Radio and Telecommunications Terminal Equipment
RC	Response Channel
RE	Radio Equipment
RED	RE Directive
RF	Radio Frequency
SMF	System Monitoring Fail
SMP	System Monitoring Pass