



SLOVENSKI STANDARD
SIST EN 300 219 V2.1.1:2016
01-november-2016

Storitev kopenskih mobilnih komunikacij - Oddajni signali radijske opreme za vzbujanje specifičnega odziva v sprejemniku - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU

Land Mobile Service - Radio equipment transmitting signals to initiate a specific response in the receiver - Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 219 V2.1.1:2016
https://standards.iteh.ai/catalog/standards/sist/0d2ab404-704d-4c75-add5-49d7aa307b33/sist-en-300-219-v2-1-1-2016](https://standards.iteh.ai/catalog/standards/sist/0d2ab404-704d-4c75-add5-49d7aa307b33/sist-en-300-219-v2-1-1-2016)

Ta slovenski standard je istoveten z: ETSI EN 300 219 V2.1.1 (2016-08)

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.01	Mobilni servisi na splošno	Mobile services in general

SIST EN 300 219 V2.1.1:2016 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 219 V2.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/0d2ab404-704d-4c75-add5-49d7aa307b33/sist-en-300-219-v2-1-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/0d2ab404-704d-4c75-add5-49d7aa307b33/sist-en-300-219-v2-1-1-2016>

ETSI EN 300 219 V2.1.1 (2016-08)



Land Mobile Service;
Radio equipment transmitting signals to initiate
a specific response in the receiver;
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU

STANDARD PREVIEW
(strictly confidential)

SIST EN 300 219 V2.1.1:2016
49d7aa307b33/sist-en-300-219-v2-1-1-2016

Reference

REN/ERM-TGDMR-349

Keywords

analogue, mobile, PMR, radio, signalling

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 219 V2.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/0d2ab404-704d-4c75-add5-49d7aa3077b7/sist-en-300-219-v2-1-1-2016>
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Speech equipment with signalling.....	11
4.1 Applicability.....	11
4.1.1 General.....	11
4.1.2 Equipment with speech and signalling functions.....	11
4.1.3 Equipment with an add-on signalling unit	11
5 General and operational requirements.....	12
5.1 General	12
5.1.1 Environmental profile.....	12
5.1.2 Choice of model for testing	12
5.2 Mechanical and electrical design.....	12
5.2.1 General.....	12
5.2.2 Controls	12
5.2.3 Transmitter shut-off facility (time-out).....	12
6 Test conditions, power sources and ambient temperatures	12
6.1 Normal and extreme test conditions	12
6.2 Test power source.....	12
6.3 Normal test conditions.....	13
6.3.1 Normal temperature and humidity	13
6.3.2 Normal test power source	13
6.3.2.1 Mains voltage.....	13
6.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	13
6.3.2.3 Other power sources.....	13
6.4 Extreme test conditions	13
6.4.1 Extreme temperatures	13
6.4.2 Extreme test source voltages.....	14
6.4.2.1 Mains voltage.....	14
6.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	14
6.4.2.3 Power sources using other types of batteries.....	14
6.4.2.4 Other power sources.....	14
6.5 Procedure for tests at extreme temperatures.....	14
6.5.0 Thermal balance.....	14
6.5.1 Procedure for equipment designed for continuous transmission.....	15
6.5.2 Procedure for equipment designed for intermittent transmission	15
7 General conditions of measurement	15
7.1 Arrangements for test signals at the input of the receiver	15
7.2 Receiver mute or squelch facility	15
7.3 Normal test signals, (wanted and unwanted signals).....	15
7.4 Encoder for receiver measurements	16
7.5 Test Load (artificial antenna)	16
7.6 Test sites and general arrangements for radiated measurements	16
7.7 Transmitter automatic shut-off facility (time-out).....	16

7.8	Modes of operation of the transmitter	16
7.9	Facilities for access between the receiver demodulator output and its decoder	16
7.10	Calling indicator	17
7.11	Reset	17
7.12	Reset time	17
7.13	Test of equipment with a duplex filter	17
8	Technical characteristic of the transmitter	17
8.1	Frequency error	17
8.1.0	Applicability	17
8.1.1	Definition	17
8.1.2	Method of measurement	17
8.1.3	Limits	18
8.2	Carrier power (conducted)	18
8.2.0	Applicability	18
8.2.1	Definitions	18
8.2.2	Method of measurement	19
8.2.3	Limits	19
8.3	Effective radiated power (field strength)	19
8.3.0	Applicability	19
8.3.1	Definition	19
8.3.2	Method of measurement	19
8.3.3	Limits	21
8.4	Adjacent and alternate channel power	22
8.4.0	Applicability	22
8.4.1	Definition	22
8.4.2	Method of measurement	22
8.4.3	Limits	24
8.5	Transmitter spurious emissions	24
8.5.0	Applicability	24
8.5.1	Definition	24
8.5.2	Method of measuring the power level	24
8.5.3	Method of measuring the effective radiated power	25
8.5.4	Transmitter spurious emissions	26
8.6	Intermodulation attenuation	27
8.6.0	Applicability	27
8.6.1	Definition	27
8.6.2	Method of measurement	28
8.6.3	Limits	29
8.7	Transmitter Attack Time	29
8.7.0	Applicability	29
8.7.1	Definition	29
8.7.2	Method of measurement	29
8.7.3	Limits	30
8.8	Transmitter release time	30
8.8.0	Applicability	30
8.8.1	Definition	30
8.8.2	Method of measurement	30
8.8.3	Limits	31
8.9	Transient frequency behaviour of the transmitter	31
8.9.0	Applicability	31
8.9.1	Definitions	31
8.9.2	Method of measurement	31
8.9.3	Limits	35
9	Technical characteristics of the receiver	35
9.1	Reference sensitivity (responses)	35
9.1.1	Definition	35
9.1.2	Reference sensitivity (response)	35
9.2	Maximum usable sensitivity (responses, conducted)	35
9.2.0	Applicability	35
9.2.1	Definition	35

9.2.2	Method of measurement ("up-down method")	36
9.2.3	Limits	36
9.3	Average usable sensitivity (field strength, responses)	36
9.3.0	Applicability	36
9.3.1	Definition	37
9.3.2	Method of measurement under normal test conditions	37
9.3.3	Method of measurement of the average usable sensitivities under extreme test conditions	38
9.3.4	References for degradation measurements	39
9.3.4.1	Definition	39
9.3.4.2	Procedures for measurements using the test fixture	39
9.3.4.3	Procedures for measurements using the test site	40
9.3.5	Limits	40
9.4	Co-channel rejection	41
9.4.0	Applicability	41
9.4.1	Definition	41
9.4.2	Method of measurement	41
9.4.3	Limits	42
9.5	Adjacent channel selectivity	42
9.5.0	Applicability	42
9.5.1	Definition	42
9.5.2	Method of measurement	43
9.5.3	Limits	44
9.6	Spurious response rejection	44
9.6.0	Applicability	44
9.6.1	Definition	44
9.6.2	Introduction to the method of measurement	44
9.6.3	Method of search over the "limited frequency range"	45
9.6.4	Method of measurement	46
9.6.5	Limits	47
9.7	Intermodulation response	47
9.7.0	Applicability	47
9.7.1	Definition	47
9.7.2	Method of measurement	47
9.7.3	Limits	48
9.8	Blocking or desensitization	48
9.8.0	Applicability	48
9.8.1	Definition	48
9.8.2	Method of measurement	49
9.8.3	Limits	50
9.9	Receiver spurious radiations	50
9.9.0	Applicability	50
9.9.1	Definition	50
9.9.2	Method of measuring the power level	50
9.9.3	Method of measuring the effective radiated power	51
9.9.4	Limits	52
10	Duplex operation	52
10.0	Applicability	52
10.1	Receiver desensitization (with simultaneous transmission and reception)	52
10.1.1	Definition	52
10.1.2	Method of measurement when the equipment operates with a duplex filter	53
10.1.3	Method of measurement when the equipment operates with separate Tx and Rx antennas	54
10.1.4	Limits	54
10.2	Receiver spurious response rejection (with simultaneous transmission and reception)	55
10.2.1	Definition	55
10.2.2	Method of measurement	55
10.2.3	Limits	56
11	Testing for compliance with technical requirements	56
11.1	Test conditions, power supply and ambient temperatures	56
11.2	Interpretation of the measurement results	56
Annex A (normative): Radiated measurement		58

A.1	Test sites and general arrangements for measurements involving the use of radiated fields	58
A.1.0	General	58
A.1.1	Anechoic chamber	58
A.1.2	Anechoic chamber with a conductive ground plane	59
A.1.3	Open Area Test Site (OATS)	60
A.1.4	Test antenna	61
A.1.5	Substitution antenna	61
A.1.6	Measuring antenna	62
A.2	Guidance on the use of radiation test sites	62
A.2.0	General	62
A.2.1	Verification of the test site	62
A.2.2	Preparation of the EUT	62
A.2.3	Power supplies to the EUT	62
A.2.4	Volume control setting for analogue speech tests	62
A.2.5	Range length	63
A.2.6	Site preparation	63
A.3	Coupling of signals	64
A.3.1	General	64
A.3.2	Data signals	64
A.3.3	Speech and analogue signals	64
A.3.3.0	General	64
A.3.3.1	Acoustic coupler description	64
A.3.3.2	Calibration	65
A.4	Test fixture	65
A.4.1	Description	65
A.4.2	Calibration	65
A.4.3	Mode of use	66
Annex B (normative): Specification for some particular measurement arrangements		67
B.1	Power measuring receiver specification	67
B.1.0	General	67
B.1.1	IF filter	67
B.1.2	Attenuation indicator	69
B.1.3	RMS value indicator	69
B.1.4	Oscillator and amplifier	69
B.2	Spectrum analyser specification	69
B.2.1	Adjacent and alternate channel power measurement	69
B.2.2	Unwanted emissions measurement	70
B.3	Integrating and power summing device	70
Annex C (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU		71
History		73

iTech STANDARD PREVIEW
(standards.itech.ai)

SIST EN 300 219 V2.1.1:2016

[https://standards.itech.ai/catalog/standards/sist/0d2ab404-704d-4c75-add5-](https://standards.itech.ai/catalog/standards/sist/0d2ab404-704d-4c75-add5-49d7aa307b33/sist-en-300-219-v2-1-1-2016)

49d7aa307b33/sist-en-300-219-v2-1-1-2016

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.7] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.5].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table C.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

(standards.iteh.ai)

National transposition dates	
Date of adoption of this EN:	21 March 2016
Date of latest announcement of this EN (doa):	30 June 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2016
Date of withdrawal of any conflicting National Standard (dow):	31 December 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document applies to constant envelope angle modulation systems for use in the land mobile service, using the available bandwidth, operating on radio frequencies between 30 MHz and 1 GHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz intended for transmission and/or reception of signals used to initiate a specific response in the receiver.

Table 1: Radiocommunications service frequency bands

Radiocommunications service frequency bands	
Transmit	30 MHz to 1 000 MHz
Receive	30 MHz to 1 000 MHz

The present document applies to non-speech and to the non-speech part of combined speech/non-speech analogue equipment. In the present document, non-speech radio equipment is defined as a radio equipment transmitting a signal to initiate a specific response in the receiver. The equipment shall comprise a transmitter and associated encoder and/or a receiver and associated decoder. The encoder and/or decoder may be a separate piece of equipment, in which case compliance to the present document covers the encoder and/or decoder in connection with the transmitter and/or receiver equipment.

In the present document different requirements are given for the different radio frequency bands, channel separations, environmental conditions and types of equipment, where appropriate.

The types of equipment covered by the present document are as follows:

- Base Station: equipment fitted with an antenna socket;
- Mobile Station: equipment fitted with an antenna socket;
- Handportable stations:
 - a) fitted with an antenna socket; or
 - b) without an external antenna socket (integral antenna equipment) but fitted with a permanent internal or a temporary internal 50 Ω Radio Frequency (RF) connector which allows access to the transmitter output and the receiver input.

Handportable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document. Integral antenna equipment is covered by ETSI EN 300 341 [i.1] (see the corresponding scope).

The present document contains requirements to demonstrate that "... *Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*" and that "...*radio equipment supports certain features ensuring access to emergency services*" [i.5].

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Radio Equipment Directive [i.5] may apply to equipment within the scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Recommendation ITU-T O.41 (1994): "Psophometer for use on telephone-type circuits".
- [2] ETSI TR 100 028 (V1.4.1) (12-2001) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [3] ETSI EN 300 086 (V2.1.2) (08-2016): "Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [4] IEC 60489-3 (1988): "Methods of measurement for radio equipment used in the mobile services. Part 3: Receivers for A3E or F3E emissions".
- [5] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 341 (V1.4.1) (07-2015): "Land Mobile Service; Radio equipment using an integral antenna transmitting signals to initiate a specific response in the receiver; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
<https://standards.iteh.ai/catalog/standards/sist/0d2ab404-704d-4c75-add5-4614-4170-8251-000000000000/etsi-en-300-341-v1-4-1-2015>
- [i.2] ETSI EN 300 793 (1998): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Presentation of equipment for type testing".
- [i.3] ETSI TR 102 273 (V1.2.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.4] ANSI C63.5 (2006): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas (9 kHz to 40 GHz)".
- [i.5] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.6] CEPT/ERC/REC 74-01E: "Unwanted emissions in the spurious domain" (Siófok 1998, Nice 1999, Sesimbra 2002; Hradec Kralove 2005).
- [i.7] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

angle modulation: either phase modulation (G3) or frequency modulation (F3)

base station: equipment fitted with an antenna socket, for use with an external antenna, and intended for use in a fixed location

conducted measurements: measurements which are made using a direct 50 Ω connection to the equipment under test

handportable station: equipment either fitted with an antenna socket or an integral antenna, or both, normally used on a stand-alone basis, to be carried on a person or held in the hand

integral antenna: antenna designed to be connected to the equipment without the use of a 50 Ω external connector and considered to be part of the equipment

NOTE: An integral antenna may be fitted internally or externally to the equipment.

mobile station: mobile equipment fitted with an antenna socket, for use with an external antenna, normally used in a vehicle or as a transportable station

psophometric weighting network: psophometric weighting network is described in Recommendation ITU-T O.41 [1]

radiated measurements: measurements which involve the absolute measurement of a radiated field

3.2 Symbols

For the purposes of the present document, the following symbols apply:

t_a	transmitter attack time
P_c	transmitter steady state carrier power
F_c	transmitter steady state frequency
t_{am}	transmitter measured attack time
t_{al}	transmitter attack time limit
df_e	transmitter steady state frequency error
t_r	transmitter release time
t_{rm}	transmitter measured release time
t_{rl}	transmitter release time limit

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
bit	binary digit
dB	decibel
dB μ V	decibel relative to 1 μ V
dBm	decibel relative to 1 mW
emf	electro-motive force
IF	Intermediate Frequency
OATS	Open Area Test Site
RF	Radio Frequency
rms	root mean square
Rx	Receiver
SINAD	(Signal + Noise + Distortion)/(Noise + Distortion)

SR Switching Range
Tx Transmitter

4 Speech equipment with signalling

4.1 Applicability

4.1.1 General

Where several harmonised standards are applicable to the equipment then the following shall be followed to avoid double testing of the same parameters.

4.1.2 Equipment with speech and signalling functions

In the case of combined speech/non-speech equipment the speech part shall be tested to ETSI EN 300 086 [3] and additionally the tests described in the following clauses of the present document shall be carried out:

- clause 8.4: Adjacent channel power;
- clause 9.2: Maximum usable sensitivity (responses, conducted);
- clause 9.3: Average usable sensitivity (responses, field strength) in the case of equipment having an integral antenna.

These requirements also apply for equipment with an analogue output facility provided for test purposes only.

Additionally, the measurement of the spurious emissions (clause 8.5) shall be performed when an equipment, previously tested to ETSI EN 300 086 [3] is being tested to the present document with an add-on signalling unit. If the equipment has been originally combined for analogue and signalling operation, the measurement of the spurious emissions need not to be performed again if the signalling port(s) (and the signalling circuits/modules) were active while making this measurement for the test ETSI EN 300 086 [3].

4.1.3 Equipment with an add-on signalling unit

In the case where an equipment has already been tested according to the present document and is re-tested with an add-on-signalling unit using another type of modulation without affecting any other characteristic of the equipment, only some additional measurements shall be performed; they shall ensure that the equipment fulfils the requirements of the following clauses:

- clause 8.4: adjacent channel power;
- clause 8.5: spurious emissions;
- clause 9.2: maximum usable sensitivity (responses, conducted);
- clause 9.3: average usable sensitivity (responses, field strength).

In the case where signalling is transmitted simultaneously with analogue speech, the speech part of the equipment is tested according to ETSI EN 300 086 [3], and it shall also be checked that the signalling does not cause the adjacent channel power and spurious emissions to exceed the appropriate limits.

5 General and operational requirements

5.1 General

5.1.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer, but as a minimum, shall be that specified in the test conditions contained in the present document.

5.1.2 Choice of model for testing

All necessary setting up instructions and other product information shall be made available with the equipment to be tested, in accordance with article 10.8 of Directive 2014/53/EU [i.5].

NOTE: Guidance on the presentation of equipment is also given in ETSI EN 300 793 [i.2].

5.2 Mechanical and electrical design

5.2.1 General

Equipment shall be designed, constructed and manufactured in accordance with sound engineering practice, and with the aim of minimizing harmful interference to other equipment and services.

5.2.2 Controls

Those controls which if maladjusted might increase the interfering potentialities of the equipment shall not be accessible to the user.

5.2.3 Transmitter shut-off facility (time-out)

When a timer for an automatic shut-off facility is operative, at the moment of the time-out the transmitter shall automatically be switched off. (The activation of the transmitter key shall reset the timer). A shut off facility shall be inoperative for the duration of the measurements unless it has to remain operative to protect the equipment.

6 Test conditions, power sources and ambient temperatures

6.1 Normal and extreme test conditions

Measurements shall be made under normal test conditions and also, where stated, under extreme test conditions.

The test conditions and procedures shall be as specified in clauses 6.2 and 6.5.

6.2 Test power source

During measurements the power source of the equipment shall be replaced by a test power source capable of producing normal and extreme test voltages as specified in clauses 6.3.2 and 6.4.2. The internal impedance of the test power source shall be low enough for its effect on the test results to be negligible. For the purpose of tests, the voltage of the power source shall be measured at the input terminals of the equipment.

If the equipment is provided with a permanently connected power cable, the test voltage shall be that measured at the point of connection of the power cable to the equipment.

For battery operated equipment, the batteries shall be removed and the test power source shall be applied as close to the battery terminals as practicable.

During the tests the power source voltages shall be maintained within a tolerance of $< \pm 1$ % relative to the voltage at the beginning of each test. The value of this tolerance is critical to power measurements, using a smaller tolerance will provide better measurement uncertainty values.

6.3 Normal test conditions

6.3.1 Normal temperature and humidity

The normal temperature and humidity conditions for the tests shall be any convenient combination of temperature and humidity within the following ranges:

- temperature: +15 °C to +35 °C;
- relative humidity: 20 % to 75 %.

When it is impracticable to carry out the tests under these conditions, the ambient temperature and relative humidity during the tests shall be recorded.

6.3.2 Normal test power source

6.3.2.1 Mains voltage

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage or any of the declared voltages for which the equipment was designed. <https://standards.iteh.ai/catalog/standards/sist/0d2ab404-704d-4c75-add5-49d7aa307b33/sist-en-300-219-v2-1-1-2016>

The frequency of the test power source, corresponding to the AC mains, shall be between 49 Hz and 51 Hz.

6.3.2.2 Regulated lead-acid battery power sources used on vehicles

When the radio equipment is intended for operation from the usual types of regulated lead-acid battery power source used on vehicles, the normal test voltage shall be 1,1 x the nominal voltage of the battery (for nominal voltages of 6 V and 12 V, these are 6,6 V and 13,2 V respectively).

6.3.2.3 Other power sources

For operation from other power sources or types of battery (primary or secondary), the normal test voltage shall be that declared by the equipment manufacturer.

6.4 Extreme test conditions

6.4.1 Extreme temperatures

For tests at extreme temperatures, measurements shall be made in accordance with the procedures specified in clause 6.5, at the upper and lower temperatures of one of the following range:

- -20 °C to +55 °C:
 - all mobile and handportable equipment;
 - base stations for outdoor/uncontrolled climate conditions.