



# SLOVENSKI STANDARD

## SIST EN 303 980 V1.1.1:2018

01-februar-2018

---

**Satelitske zemeljske postaje in sistemi (SES) - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU, za fiksne in premične zemeljske postaje, ki komunicirajo z negeostacionarnimi satelitskimi sistemi (NEST) v frekvenčnih pasovih od 11 GHz do 14 GHz**

Satellite Earth Stations and Systems (SES) - Harmonised Standard for fixed and in-motion Earth Stations communicating with non-geostationary satellite systems (NEST) in the 11 GHz to 14 GHz frequency bands covering essential requirements of article 3.2 of the Directive 2014/53/EU

**(standards.iteh.ai)**

[SIST EN 303 980 V1.1.1:2018](https://standards.iteh.ai/catalog/standards/sist/00e1fa4e-8ad1-4cf5-840c-4c238189e3a5/sist-en-303-980-v1-1-1-2018)

<https://standards.iteh.ai/catalog/standards/sist/00e1fa4e-8ad1-4cf5-840c-4c238189e3a5/sist-en-303-980-v1-1-1-2018>

**Ta slovenski standard je istoveten z: ETSI EN 303 980 V1.1.1 (2017-12)**

**ICS:**

33.060.30      Radiorelejni in fiksni satelitski komunikacijski sistemi      Radio relay and fixed satellite communications systems

**SIST EN 303 980 V1.1.1:2018                      en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 303 980 V1.1.1:2018](https://standards.iteh.ai/catalog/standards/sist/00e1fa4e-8ad1-4cf5-840c-4c238189e3a5/sist-en-303-980-v1-1-1-2018)

<https://standards.iteh.ai/catalog/standards/sist/00e1fa4e-8ad1-4cf5-840c-4c238189e3a5/sist-en-303-980-v1-1-1-2018>

# ETSI EN 303 980 V1.1.1 (2017-12)



**Satellite Earth Stations and Systems (SES);  
Harmonised Standard for fixed and in-motion Earth Stations  
communicating with non-geostationary satellite systems  
(NEST) in the 11 GHz to 14 GHz frequency bands  
covering essential requirements of article 3.2 of  
Directive 2014/53/EU**

---

**Reference**DEN/SES-00402

---

**Keywords**broadband, earth station, mobile, regulation,  
satellite**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

---

**Important notice**

<https://standards.iteh.ai/catalog/standards/sist/00e1fa4e-8ad1-4cf5-840c-4c78189e3a/sist-en-303-980-v1-1-1-2018>  
The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M** logo is protected for the benefit of its Members.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction .....	8
1 Scope .....	9
2 References .....	10
2.1 Normative references .....	10
2.2 Informative references.....	10
3 Definitions, symbols and abbreviations .....	11
3.1 Definitions.....	11
3.2 Symbols.....	13
3.3 Abbreviations .....	13
4 Technical requirements specifications .....	14
4.1 General .....	14
4.1.1 Environmental profile .....	14
4.1.2 Mechanical and electrical design .....	14
4.1.2.1 General.....	14
4.1.3 Operating configurations .....	14
4.1.4 Presentation of equipment for testing purposes .....	14
4.1.5 Choice of model for testing .....	15
4.2 Conformance requirements .....	15
4.2.1 EIRP density mask.....	15
4.2.1.1 Justification .....	15
4.2.1.2 Specification.....	15
4.2.1.3 Conformance tests.....	15
4.2.2 Antenna beam pointing .....	15
4.2.2.1 Pointing accuracy.....	15
4.2.2.1.1 Purpose .....	15
4.2.2.1.2 Antenna Beam Pointing error .....	15
4.2.2.2 Pointing error detection.....	15
4.2.2.2.1 Purpose .....	15
4.2.2.2.2 Pointing error detection specification .....	16
4.2.2.3 Conformance tests.....	16
4.2.3 Off-axis spurious radiation .....	16
4.2.3.1 Justification .....	16
4.2.3.2 Specification.....	16
4.2.3.3 Conformance tests.....	17
4.2.4 On-axis spurious radiation .....	17
4.2.4.1 Justification .....	17
4.2.4.2 Specification.....	17
4.2.4.2.1 "Carrier-on" radio state.....	17
4.2.4.2.2 "Carrier-off" and "Emissions disabled" radio states .....	18
4.2.4.3 Conformance tests.....	18
4.2.5 Carrier suppression .....	18
4.2.5.1 Justification .....	18
4.2.5.2 Specification.....	18
4.2.5.3 Conformance tests.....	18
4.2.6 Cessation of emissions.....	18
4.2.6.1 Justification .....	18
4.2.6.2 Specification.....	18
4.2.6.2.1 Specification 1: Mode of cessation of emissions .....	18
4.2.6.2.2 Specification 2: Conditions under which the NEST shall cease emissions .....	19
4.2.6.2.3 Specification 3: Cessation of emissions .....	19
4.2.6.2.4 Specification 4: Fault conditions .....	20

4.2.6.3	Conformance tests.....	20
4.2.7	Identification of the NEST and its location .....	20
4.2.7.1	Justification .....	20
4.2.7.2	Specification.....	20
4.2.7.3	Conformance tests.....	20
4.2.8	Control and Monitoring Functions (CMFs).....	21
4.2.8.1	NEST States .....	21
4.2.8.1.1	General .....	21
4.2.8.1.2	CMF state diagram .....	22
4.2.8.2	Processor monitoring .....	23
4.2.8.2.1	Justification .....	23
4.2.8.2.2	Specification.....	23
4.2.8.2.3	Conformance tests .....	24
4.2.8.3	Transmit subsystem monitoring.....	24
4.2.8.3.1	Justification .....	24
4.2.8.3.2	Specification.....	24
4.2.8.3.3	Conformance tests .....	24
4.2.8.4	Power-on/Reset .....	24
4.2.8.4.1	Justification .....	24
4.2.8.4.2	Specification.....	24
4.2.8.4.3	Conformance tests .....	24
4.2.8.5	Control Channel (CC) and Response Channel (RC).....	24
4.2.8.5.1	Justification .....	24
4.2.8.5.2	Specification.....	25
4.2.8.5.3	Conformance tests .....	25
4.2.8.6	Network control commands .....	25
4.2.8.6.1	Justification.....	25
4.2.8.6.2	Specification.....	26
4.2.8.6.3	Conformance tests .....	26
4.2.8.7	Initial burst transmission.....	26
4.2.8.7.1	Justification .....	26
4.2.8.7.2	Specification.....	26
4.2.8.7.3	Conformance tests .....	26
4.2.8.8	Inhibition of transmissions.....	27
4.2.8.8.1	Justification .....	27
4.2.8.8.2	Specification.....	27
4.2.8.8.3	Conformance tests .....	27
4.2.9	Receive antenna off-axis gain pattern.....	27
4.2.9.1	Justification .....	27
4.2.9.2	Specification.....	27
4.2.9.3	Conformance tests.....	28
4.2.10	Blocking performance.....	28
4.2.10.1	Justification .....	28
4.2.10.2	Specification.....	28
4.2.10.3	Conformance tests.....	28
4.2.11	Adjacent Signal Selectivity.....	28
4.2.11.1	Justification .....	28
4.2.11.2	Specification.....	28
4.2.11.3	Conformance tests.....	29
5	Testing for compliance with technical requirements.....	29
5.1	Environmental conditions for testing .....	29
5.2	Essential radio test suites.....	29
6	Test methods for all aspects of the NEST .....	29
6.1	General .....	29
6.1.1	General requirements.....	29
6.1.2	Interpretation of measurement results.....	30
6.1.3	Measuring receiver .....	31
6.2	Off-axis spurious radiation.....	31
6.2.1	General.....	31
6.2.2	Test method .....	31

6.2.2.1	General .....	31
6.2.2.2	Multi-carrier operation .....	32
6.2.3	Measurements up to 1 000 MHz .....	32
6.2.3.1	Test site .....	32
6.2.3.2	Measuring receivers .....	33
6.2.3.3	Procedure .....	33
6.2.4	Measurements above 1 000 MHz .....	33
6.2.4.1	General .....	33
6.2.4.2	Identification of the significant frequencies of spurious radiation .....	33
6.2.4.2.1	Test site .....	33
6.2.4.2.2	Procedure .....	34
6.2.4.3	Measurement of radiated power levels of identified spurious radiation .....	34
6.2.4.3.1	Test site .....	34
6.2.4.3.2	Procedure .....	34
6.2.4.4	Measurement of conducted spurious radiation at the antenna flange .....	35
6.2.4.4.1	Test site .....	35
6.2.4.4.2	Procedure .....	36
6.3	On-axis spurious radiation .....	36
6.3.1	Test method .....	36
6.3.1.1	General .....	36
6.3.1.2	Test site .....	36
6.3.1.3	Method of measurement .....	36
6.3.1.3.1	General .....	36
6.3.1.3.2	Method of measurement at the antenna flange .....	37
6.3.1.3.3	Method of measurement for an EUT with antenna .....	39
6.4	EIRP density .....	40
6.4.1	General .....	40
6.4.2	Test method A radiated measurement .....	40
6.4.3	Test method B conducted measurement .....	40
6.5	Carrier suppression .....	40
6.5.1	Test method .....	40
6.6	Antenna beam pointing .....	40
6.6.1	General .....	40
6.6.2	Test methods .....	41
6.7	Cessation of emissions of the NEST .....	41
6.7.1	General .....	41
6.7.2	Test Method .....	41
6.7.2.1	Required documentation .....	41
6.7.2.2	Cessation of emissions from the "Transmission enabled" state .....	41
6.7.2.3	Cessation of emission from the "Transmission disabled" state .....	42
6.7.2.4	Cessation of emission from the "Initial Phase" state .....	42
6.7.2.4.1	EUTs transmitting initial bursts .....	42
6.7.2.4.2	EUTs not transmitting initial bursts .....	42
6.7.2.5	"Single action" means of cessation of emissions .....	43
6.7.2.6	Fault conditions .....	43
6.8	Identification of NEST and location determination .....	44
6.8.1	Test arrangement .....	44
6.8.2	Test method .....	44
6.9	Control and monitoring functions .....	44
6.9.1	General .....	44
6.9.2	Test arrangement .....	44
6.9.3	Processor monitoring- Test method .....	44
6.9.4	Transmit subsystem monitoring-Test method .....	45
6.9.5	Power-on/Reset-Test method .....	45
6.9.6	Control Channel and Response Channel -Test method .....	45
6.9.7	Network Control commands-Test method .....	46
6.9.8	Initial burst transmission-Test method .....	47
6.9.9	Inhibition of transmission-Test method .....	48
6.10	Antenna off-axis gain pattern .....	48
6.10.1	Test Method .....	48
6.10.1.1	Test site .....	48
6.10.1.2	Method of measurement for EUT antenna with linear polarization .....	48

6.10.1.3	Method of measurement for antennas with circular polarization .....	49
6.11	Blocking performance .....	49
6.11.1	Test method .....	49
6.12	Adjacent Signal Selectivity .....	50
6.12.1	Test method .....	50
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>51</b>
<b>Annex B (informative):</b>	<b>Bibliography .....</b>	<b>53</b>
<b>Annex C (informative):</b>	<b>Change history .....</b>	<b>54</b>
History .....		55

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 303 980 V1.1.1:2018

<https://standards.iteh.ai/catalog/standards/sist/00e1fa4e-8ad1-4cf5-840c-4c238189e3a5/sist-en-303-980-v1-1-1-2018>



---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.8]. <https://standards.iteh.ai/catalog/standards/sist/00e1fa4e-8ad1-4cf5-840c-4c238189e3a5/sist-en-303-980-v1-1-1-2018>

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	20 October 2017
Date of latest announcement of this EN (doa):	31 January 2018
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2018
Date of withdrawal of any conflicting National Standard (dow):	31 July 2019

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the RE Directive [i.8]. The modular structure is shown in ETSI EG 201 399 [i.2].

The present document is largely based on ETSI EN 303 979 [i.5], for ESOMPs operating with NGSO satellites.

The present document may also be applicable to the frequency band 14,0 GHz to 14,50 GHz (Earth-to-space) and 10,70 GHz to 12,75 GHz (space-to-Earth) subject to national regulation.

Annex A (informative) provides HS Requirements specifications.

Annex B (informative) Bibliography covers other supplementary information.

Recital 10 of Directive 2014/53/EU [i.8] states that "*in order to ensure that radio equipment uses the radio spectrum effectively and supports the efficient use of radio spectrum, radio equipment should be constructed so that: in the case of a transmitter, when the transmitter is properly installed, maintained and used for its intended purpose it generates radio waves emissions that do not create harmful interference, while unwanted radio waves emissions generated by the transmitter (e.g. in adjacent channels) with a potential negative impact on the goals of radio spectrum policy should be limited to such a level that, according to the state of the art, harmful interference is avoided; and, in the case of a receiver, it has a level of performance that allows it to operate as intended and protects it against the risk of harmful interference, in particular from shared or adjacent channels, and, in so doing, supports improvements in the efficient use of shared or adjacent channels*".

Recital 11 of Directive 2014/53/EU [i.8] states that "*although receivers do not themselves cause harmful interference, reception capabilities are an increasingly important factor in ensuring the efficient use of radio spectrum by way of an increased resilience of receivers against harmful interference and unwanted signals on the basis of the relevant essential requirements of Union harmonisation legislation*".

As a consequence, the present document includes both transmitting and receiving parameters aiming to maximize the efficient use of radio spectrum.

[SIST EN 303 980 V1.1.1:2018](https://standards.iteh.ai/catalog/standards/sist/00e1fa4e-8ad1-4cf5-840c-4c238189e3a5/sist-en-303-980-v1-1-1-2018)

<https://standards.iteh.ai/catalog/standards/sist/00e1fa4e-8ad1-4cf5-840c-4c238189e3a5/sist-en-303-980-v1-1-1-2018>

# 1 Scope


The present document specifies technical characteristics and methods of measurements for fixed and in-motion Earth Stations communicating with non-geostationary satellite systems (NEST) in the 11 GHz to 14 GHz FSS frequency bands, which have the following characteristics:

- The NEST is designed for both in-motion and stationary operation.
- The NEST operates in-motion on various platforms such as trains, maritime vessels, aircraft and other vehicles and, therefore, may be subject to occasional disturbances and interruptions in the satellite link.
- The NEST is operating as part of a satellite system used for the provision of broadband communications.
- The NEST is comprised of all the equipment, electrical and mechanical, from the antenna itself to the interface with other communications equipment on a mobile platform.
- The NEST comprises one or more emitters and the system overview as given in figure 1 should be interpreted accordingly.
- The transmit and receive frequencies are shown in table 1.

**Table 1: Frequency bands**

	Frequency Bands
Transmit (Earth-to-space)	14,0 GHz to 14,50 GHz
Receive (space-to-Earth)	10,70 GHz to 12,75 GHz

- iTeh STANDARD PREVIEW**  
(standards.iteh.ai)
- The NEST transmits within the frequency range from 14,0 GHz to 14,50 GHz.
  - The NEST receives within the range from 10,70 GHz to 12,75 GHz.
  - The NEST transmits at elevation angles of 50° or greater, relative to the horizontal plane.
  - The NEST uses linear or circular polarization.
  - The NEST communicates with non-geostationary satellites.
  - The NEST is designed for unattended operation.
  - The NEST is controlled and monitored by a Network Control Facility (NCF). The NCF is outside the scope of the present document.



**Figure 1: NEST System Overview**

The present document applies to the NEST with its ancillary equipment and its various telecommunication ports, and when operated within the boundary limits of the operational environmental profile as declared by the applicant and when installed as required by the applicant's declaration or in the user documentation.

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.8] under the conditions identified in annex A.

## 2 References

### 2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CISPR 16-1-1 Edition 4.0 (2015): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [2] CISPR 16-1-4 Edition 3.0 (2010): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Commission Implementing Decision C(2015) 5376 final of 04.08.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the Radio & Telecommunication Terminal Equipment Directive 1999/5/EC (R&TTE) and a first guide on the impact of the Radio Equipment Directive 2014/53/EU (RED) on Harmonized Standards".
- [i.3] ETSI TS 103 052: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [i.4] ITU Radio Regulations (edition 2016).
- [i.5] ETSI EN 303 979 (V2.1.2): "Satellite Earth Stations and Systems (SES); Harmonised Standard for Earth Stations on Mobile Platforms (ESOMP) transmitting towards satellites in non-geostationary orbit, operating in the 27,5 GHz to 29,1 GHz and 29,5 GHz to 30,0 GHz frequency bands covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [i.6] Recommendation ITU-R S.1503-2, Section 3.1: "Generation of Earth Station e.i.r.p density masks".

- [i.7] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.8] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [i.8] and the following apply:

**ancillary equipment:** equipment used in connection with a NEST

NOTE: Equipment is considered as ancillary if the three following conditions are met:

- the equipment is intended for use in conjunction with the NEST to provide additional operational and/or control features (e.g. to extend control to another position or location); and
- the equipment cannot be used on a standalone basis, to provide user functions independently of the NEST; and
- the absence of the equipment does not inhibit the operation of the NEST.

**antenna controller:** equipment used to maintain antenna stabilization and tracking accuracy based on inputs from the Control and Monitoring Function

**applicant:** manufacturer or his authorized representative within the European Community or the person responsible for placing the apparatus on the market

**carrier-off radio state:** radio state in which the NEST may transmit and does not transmit any carrier

NOTE 1: The phrase "the NEST may transmit" means that all the conditions for transmission are satisfied (e.g. in a state where transmissions are permitted, no failure detected, and the NEST is correctly pointed towards the satellite).

NOTE 2: The existence of a "Carrier-off" radio state depends on the system of transmission used. For NESTs designed for continuous transmission mode there may be no "Carrier-off" state.

**carrier-on radio state:** radio state in which the NEST may transmit and transmits a carrier

**Control Channel (CC):** channel or channels by which NESTs receive and send control information from and to the NCF

**EIRP<sub>max</sub>:** maximum EIRP capability of the NEST as declared by the applicant

**EIRP density mask:** EIRP density mask (dBW/40 kHz) declared by the applicant for the simulation described in the Recommendation ITU-R S.1503-2 [i.6] to demonstrate compliance with ITU Radio Regulations Article 22 limits [i.4]

**emissions disabled radio state:** radio state in which the NEST may not emit

NOTE: Examples of cases where the NEST is in this radio state:

- before system monitoring pass, before the control channel is received,
- when a failure is detected,
- when an NEST is commanded to disable, and
- when the NEST is in a location requiring cessation of emissions.

**external control channel:** control channel which is either:

- (i) carried by the NEST network via the same or another satellite, but not within the internal protocol of the NEST system; or
- (ii) carried by any other radio communication system

**external response channel:** response channel which is either:

- (i) carried by the NEST network via the same or another satellite, but not within the internal protocol of the NEST system; or
- (ii) carried by any other radio communication system

**integral antenna:** antenna which may not be removed during the tests according to the applicant's statement

**internal control channel:** control channel which is carried by the NEST network via the same satellite as used for transmission of user data and within the internal protocol structure of the NEST system

**internal response channel:** response channel which is carried by the NEST network via the same satellite as used for transmission of user data and within the internal protocol structure of the NEST system

**Network Control Facility (NCF):** set of functional entities that, at system level, monitor and control the correct operation of the NEST and, if appropriate, all of the NESTs in a network

**nominated bandwidth:** bandwidth of the NEST radio frequency transmission declared by the manufacturer

NOTE 1: The nominated bandwidth is wide enough to encompass all spectral elements of the transmission that have a level greater than the specified spurious radiation limits. The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. This definition is chosen to allow flexibility regarding adjacent channel interference levels that will be taken into account by operational procedures depending on the exact transponder carrier assignment situation.

NOTE 2: The nominated bandwidth is centred on the transmit frequency and is larger than the occupied bandwidth. However, the manufacturer should be aware that the larger the declared nominated bandwidth, the fewer channels will be available within the assigned band.

**off-axis angle:** angle between the direction of the axis of the antenna main beam and the considered direction

**removable antenna:** antenna which may be removed during the tests according to the applicant's statement

**Response Channel (RC):** channel by which the NEST transmit monitoring information to the NCF

**spurious radiation:** in the present document, any radiation outside the nominated bandwidth

**transmission disabled state:** radio state in which the NEST is not authorized to transmit by the NCF

**transmission enabled state:** radio state in which the NEST is authorized to transmit by the NCF

**wanted signal occupied bandwidth (BW):**

- for a digital modulation scheme: the width of the signal spectrum 10 dB below the maximum in-band power density;
- for an analogue modulation scheme: the width of a frequency band such that, below the lower and above the upper frequency limits, the mean power emitted is equal to 0,5 % of the total mean power of the emission

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

dB <sub>i</sub>	ratio of an antenna gain to the gain of an isotropic antenna, expressed in decibels
dB <sub>sd</sub>	ratio expressed in decibels relative to the spectral density
dBW	ratio of a power to 1 watt, expressed in decibels
dBpW	ratio of a power to 1 picowatt, expressed in decibels
dB <sub>μ</sub> V/m	ratio of an electric field to 1 μV/m, expressed in decibels (20 log(electric field / 1 μV/m))

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BW	Wanted signal occupied Bandwidth
CC	Control Channel
CCF	Control Channel reception Failure
CCR	Control Channel correctly Received
CENR	Cessation of Emissions Not Required
CER	Cessation of Emissions Required
CISPR	Comité International Spécial des Perturbations Radioélectriques (International Special Committee on Radio Interference)
CMF	Control and Monitoring Functions
DC	Direct Current
EIRP	Effective Isotropic Radiated Power
EIRP <sub>max</sub>	Maximum EIRP transmitted by the NEST
EMC	Electro-Magnetic Compatibility
epfd <sub>↑</sub>	Uplink equivalent power flux-density
EUT	Equipment Under Test
FEC	Forward Error Correction
FSS	Fixed Satellite Service
GEUT	Gain of EUT
GSO	Geostationary Satellite Orbit
HPA	High Power Amplifier
IPR	Intellectual Property Rights
IT <sub>max</sub>	maximum Inhibit Time
LNB	Low-Noise Block down converter
LO	Local Oscillator
LV	Low Voltage
NCF	Network Control Facility
NEST	Earth Station communicating with NGSO satellite system
NGSO	Non Geostationary Satellite Orbit
R&TTE	Radio and Telecommunications Terminal Equipment
RBW	Reference BandWidth
RC	Response Channel
RE	Radio Equipment
RED	Radio Equipment Directive
RF	Radio Frequency
RMS	Root Mean Square
SMF	System Monitoring Fail
SMP	System Monitoring Pass
STE	Special Test Equipment
T <sub>trans</sub>	time to transition from "Carrier off" to "Carrier on" radio state
TxD	Transmission Disable command
TxE	Transmission Enable command
VBW	Video BandWidth