ETSI TS 144 018 V11.9.0 (2015-07)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0984ed7-5fe0-4d7a-9367-13ad79055243/etsi-ts-144-018-v11.9.0-2015-07

Digital cellular telecommunications system (Phase 2+);
Mobile radio interface layer 3 specification;
Radio Resource Control (RRC) protocol
(3GPP TS 44.018 version 11.9.0 Release 11)

3GPP A GLOBAL INITIATIVE
GSM® GLOBAL SYSTEM FOR MOBILE COMMUNICATIONS

Reference
RTS/TSGG-0244018vb90

Keywords
GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0e84ed7-5f50-4dee-b767-1e4d79054443/etsi-ts-144018-v11.9.0-2015-07

Important notice

The present document can be downloaded from:
http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services:
https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.
The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, **PLUGTESTS**™, **UMTS**™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE**™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d098bed7-5fe0-4d7a-9367-15d79054a3e/etsi-ts-144-018-v11.9.0-2015-07

Contents

Intellectual Property Rights 2
Foreword 2
Modal verbs terminology 2
Foreword 18
1 Scope 19
1.1 Scope of the Technical Specification 19
1.2 Application to the interface structures 19
1.3 Structure of layer 3 procedures 19
1.4 Test procedures 19
1.5 Use of logical channels 20
1.6 Overview of control procedures 20
1.6.1 List of procedures 20
1.7 Applicability of implementations 21
1.7.1 Voice Group Call Service (VGCS) and Voice Broadcast Service (VBS) 21
1.7.2 General Packet Radio Service (GPRS) 22
1.7.3 Multimedia Broadcast/Multicast Service (MBMS) 22
1.8 Restrictions 22
2 References 22
2.1 Abbreviations 26
2.1.1 Random values 26
2.1.2 Vocabulary 26
3 Radio Resource management procedures 29
3.1 Overview/General 29
3.1.1 General 29
3.1.2 Services provided to upper layers 29
3.1.2.1 Idle mode 29
3.1.2.2 Dedicated mode 30
3.1.2.3 Group receive mode 30
3.1.2.4 Group transmit mode 30
3.1.2.5 Packet idle mode 31
3.1.2.6 Packet transfer mode 31
3.1.2.7 Dual transfer mode (DTM) 31
3.1.3 Services required from data link and physical layers 31
3.1.4 Change of dedicated channels 31
3.1.4.1 Change of dedicated channels using SAPI = 0 31
3.1.4.2 Change of dedicated channels using other SAPIs than 0 32
3.1.5 Procedure for Service Request and Contention Resolution 32
3.1.6 Preemption 33
3.2 Idle mode procedures and general procedures in packet idle and packet transfer modes 34
3.2.1 Mobile Station side 34
3.2.2 Network side 35
3.2.2.1 System information broadcasting 35
3.2.2.2 Paging 37
3.2.2.3 Sending of ETWS Primary Notification 38
3.2.3 Inter-RAT cell re-selection based on priority information 38
3.2.3.1 General 38
3.2.3.2 Common priorities information 39
3.2.3.3 Provision of individual priorities information 39
3.2.4 (void) 39
3.3 RR connection establishment 39
3.3.1 RR connection establishment initiated by the mobile station 39
3.3.1.1 Entering the dedicated mode : immediate assignment procedure 40
3.3.1.1.1 Permission to access the network 40

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/dd0981ed7-5fe0-4d7a-9367-13ad7905144 3/etsi-ts-144-018-v11.9.0-2015-07

3.3.1.1.1a Implicit reject indication from the network 40
3.3.1.1.2 Initiation of the immediate assignment procedure 41
3.3.1.1.3 Answer from the network 42
3.3.1.1.3.1 On receipt of a CHANNEL REQUEST message 42
3.3.1.1.3.2 Assignment rejection 43
3.3.1.1.3.2a Implicit Reject procedure 43
3.3.1.1.4 Assignment completion 43
3.3.1.1.4.1 Early classmark sending 44
3.3.1.1.4.2 Service information sending 45
3.3.1.1.5 Abnormal cases 45
3.3.1.2 Entering the group transmit mode: uplink access procedure 46
3.3.1.2.1 Mobile station side 46
3.3.1.2.1.1 Uplink investigation procedure - talker priority not supported by the network 46
3.3.1.2.1.1a Uplink investigation procedure - talker priority supported by the network 46
3.3.1.2.1.2 Uplink access procedure with talker priority not supported by the network 47
3.3.1.2.1.2a Uplink access procedure - with talker priority supported by the network using uplink access procedure 47
3.3.1.2.1.2a.1 Talker priority normal, privileged or emergency 47
3.3.1.2.1.2a.2 Emergency mode reset request 48
3.3.1.2.1.2b Priority uplink request procedure 49
3.3.1.2.1.2b.1 Talker priority privileged or emergency 49
3.3.1.2.1.2b.2 Emergency mode reset request 49
3.3.1.2.1.2b.3 Validation of priority uplink requests for ciphered voice group calls 50
3.3.1.2.1.2c Uplink access procedure for sending application-specific data 50
3.3.1.2.1.2c.1 General 50
3.3.1.2.1.2c.2 Using the Voice Group Call Channel 50
3.3.1.2.1.2c.3 Using the RACH 50
3.3.1.2.2 Network side - talker priority not supported by the network 51
3.3.1.2.2a Network side - network supports talker priority using uplink access procedure 51
3.3.1.2.2a.1 Uplink FREE 51
3.3.1.2.2a.1.1 Uplink Access cause - Normal, Privileged, or Emergency priority request 51
3.3.1.2.2a.1.2 Uplink Access cause - Emergency mode reset request 51
3.3.1.2.2a.2 Uplink BUSY 52
3.3.1.2.2a.2.1 Uplink Access with cause priority less than or equal to current talker priority 52
3.3.1.2.2a.2.2 Uplink Access with cause priority higher than current talker priority 52
3.3.1.2.2a.2.3 Uplink Access with cause Emergency mode reset request 52
3.3.1.2.2b Network side - network supports talker priority using priority uplink procedure 52
3.3.1.2.2b.1 Uplink FREE 52
3.3.1.2.2b.1.1 Uplink Access cause - Normal, Privileged, or Emergency priority request 52
3.3.1.2.2b.1.2 Uplink Access cause - Emergency mode reset request 52
3.3.1.2.2b.2 Uplink BUSY 53
3.3.1.2.2b.2.1 Priority Uplink Request with cause priority less than or equal to current talker priority 53
3.3.1.2.2b.2.2 Priority Uplink Request with cause priority higher than current talker priority 53
3.3.1.2.2b.2.3 Priority Uplink Request with cause Emergency mode reset request 53
3.3.1.2.2b.2.4 Validation of Priority Uplink Requests for ciphered voice group calls 53
3.3.1.2.2c Network side – network supports sending application-specific data by mobile station 54
3.3.1.2.2c.1 General 54
3.3.1.2.2c.2 Using the Voice Group Call Channel 54
3.3.1.2.2c.3 Using the RACH 54
3.3.1.2.3 Abnormal cases 54
3.3.1.3 Dedicated mode and GPRS 54
3.3.1.4 Preliminary Access Barring Check 54
3.3.2 Paging procedure for RR connection establishment 55
3.3.2.1 Paging initiation by the network 55
3.3.2.1.1 Paging initiation using paging subchannel on CCCH 55
3.3.2.1.2 Paging initiation using paging subchannel on PCCCH 56
3.3.2.1.3 Paging initiation using PACCH 56
3.3.2.2 Paging response 57
3.3.2.3 Abnormal cases 57
3.3.3 Notification procedure 57
3.3.3.1 Notification of a call 57
3.3.3.2 Joining a VGCS or VBS call 58

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0e8e4d7-5f10-4f7a-b367-1aa07905443/etsi-ts-144-018-v11.9.0-2015-07

3.3.3.2.1 General 58
3.3.3.2.2 Segmentation of notifications 59
3.3.3.2.2.1 General 59
3.3.3.2.2.2 Segmentation of notifications on NCH 59
3.3.3.2.2.4 Segmentation of notifications on PCH 61
3.3.3.3 Reduced NCH monitoring mechanism 62
3.3.3.4 Notification response procedure 63
3.4 Procedures in dedicated mode and in group transmit mode 63
3.4.1 SACCH procedures 63
3.4.1.1 General 63
3.4.1.2 Measurement Report and Enhanced Measurement Report 64
3.4.1.2.1 Parameters for Measurements and Reporting 65
3.4.1.2.1.1 Deriving the 3G Neighbour Cell list from the 3G Neighbour Cell Description sent on BCCH or on SACCH 66
3.4.1.2.1.1a Deriving the E-UTRAN Neighbour Cell list from the Repeated E-UTRAN Neighbour Cell information sent on BCCH or on SACCH 67
3.4.1.2.1.1b Deriving the E-UTRAN Neighbour Cell list from the Repeated E-UTRAN Neighbour Cell information sent on BCCH or on SACCH (abnormal cases) 68
3.4.1.2.1.2 Deriving the GSM Neighbour Cell list from the BSICs and the BA (list) 68
3.4.1.2.1.3 Deriving the Neighbour Cell list from the GSM Neighbour Cell list and the 3G Neighbour Cell list 68
3.4.1.2.1.4 Real Time Differences 69
3.4.1.2.1.5 Report Priority Description 69
3.4.1.2.1.6 GPRS Parameters 69
3.4.1.2.1.7 The 3G Cell Reselection list 69
3.4.1.2.1.7a (void) 70
3.4.1.2.1.7b Closed Subscriber Group Information 70
3.4.1.2.1.7c The 3G Frequency list 70
3.4.1.2.1.8 CCN Support description 71
3.4.1.2.1.9 3G_CCN_ACTIVE Description 71
3.4.1.2.1.9a E-UTRAN_CCN_ACTIVE Description 71
3.4.1.2.1.10 GSM Neighbour Cell Selection parameters 71
3.4.1.2.1.11 Fast Acquisition of System Information 71
3.4.1.2.1.12 Reporting of CSG Cells and Hybrid Cells 72
3.4.1.3 Extended measurement report $(MAFA)$ 73
3.4.2 Transfer of messages and link layer service provision 73
3.4.3 Channel assignment procedure 73
3.4.3.1 Channel assignment initiation 74
3.4.3.2 Assignment completion 76
3.4.3.3 Abnormal cases 76
3.4.4 Handover procedure 77
3.4.4.1 Handover initiation 77
3.4.4.2 Physical channel establishment 81
3.4.4.2.1 Finely synchronized cell case 81
3.4.4.2.2 Non synchronized cell case 81
3.4.4.2.3 Pseudo-synchronized cell case 82
3.4.4.2.4 Pre-synchronized cell case 82
3.4.4.3 Handover completion 82
3.4.4.4 Abnormal cases 83
3.4.4a Handover to UTRAN procedure 84
3.4.4a.1 Handover to UTRAN initiation 84
3.4.4a.2 Handover to UTRAN completion 84
3.4.4a.3 Abnormal cases 85
3.4.4b Handover to CDMA2000 procedure 85
3.4.4b.1 Handover to CDMA2000 initiation 86
3.4.4b.2 Handover to CDMA2000 completion 86
3.4.4b.3 Abnormal cases 86
3.4.4c Intermode handover to GERAN *Iu mode* procedure 86
3.4.4c.1 General 86
3.4.4c.2 Initiation of the handover to GERAN *Iu mode* procedure 87
3.4.4c.3 Completion of the Handover to GERAN *Iu Mode* procedure 87
3.4.4c.4 Abnormal cases 87

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0984ed7-5fe0-4d7a-830f-3ad9054c443/etsi-ts-144-018-v11.9.0-2015-07

3.4.4d CS to PS SRVCC procedure 87
3.4.4d.1 CS to PS SRVCC procedure initiation 88
3.4.4d.2 CS to PS SRVCC procedure completion 88
3.4.4d.3 Abnormal cases 88
3.4.5 Frequency redefinition procedure 89
3.4.5.1 Abnormal cases 89
3.4.6 Channel mode modify procedure 90
3.4.6.1 Normal channel mode modify procedure 90
3.4.6.1.1 Initiation of the channel mode modify procedure 90
3.4.6.1.2 Completion of channel mode modify procedure 90
3.4.6.1.3 Abnormal cases 90
3.4.6.2 Channel mode modify procedure for a voice group call talker 91
3.4.6.2.1 Initiation of the channel mode modify procedure 91
3.4.6.2.2 Completion of mode change procedure 91
3.4.6.2.3 Abnormal cases 91
3.4.7 Ciphering mode setting procedure 91
3.4.7.1 Ciphering mode setting initiation 91
3.4.7.2 Ciphering mode setting completion 92
3.4.7a Selective Ciphering of Downlink SACCH 92
3.4.8 Additional channel assignment procedure 93
3.4.8.1 Additional assignment procedure initiation 93
3.4.8.2 Additional assignment procedure completion 93
3.4.8.3 Abnormal cases 93
3.4.9 Partial channel release procedure 94
3.4.9.1 Partial release procedure initiation 94
3.4.9.2 Abnormal cases 94
3.4.10 Classmark change procedure 94
3.4.11 Classmark interrogation procedure 95
3.4.11.1 Classmark interrogation initiation 95
3.4.11.2 Classmark interrogation completion 95
3.4.12 Indication of notifications and paging information 95
3.4.13 RR connection release procedure 96
3.4.13.1 Normal release procedure 96
3.4.13.1.1 Channel release procedure initiation in dedicated mode and in group transmit mode 96
3.4.13.1.1a Channel release procedure initiation in dual transfer mode 98
3.4.13.1.2 Abnormal cases 98
3.4.13.2 Radio link failure in dedicated mode or dual transfer mode 98
3.4.13.2.1 Mobile side 98
3.4.13.2.2 Network side 99
3.4.13.3 RR connection abortion in dedicated mode or dual transfer mode 99
3.4.13.4 Uplink release procedure 99
3.4.13.5 Radio link failure in group transmit mode 99
3.4.13.5.1 Mobile side 100
3.4.13.5.2 Network side 100
3.4.13.6 RR connection abortion requested by upper layers 100
3.4.14 Receiving a RR STATUS message by a RR entity 100
3.4.15 Group receive mode procedures 100
3.4.15.1 Mobile station side 100
3.4.15.1.1 Reception of the VGCS or VBS channel 100
3.4.15.1.1.1 General 100
3.4.15.1.1.2 Reception on ciphered VGCS or VBS channel 101
3.4.15.1.2 Monitoring of downlink messages and related procedures 101
3.4.15.1.2.1 (void) 101
3.4.15.1.2.2 (void) 101
3.4.15.1.2.3 Channel mode modify procedure 101
3.4.15.1.2.4 Notification and paging information 101
3.4.15.1.2.4.1 Use of Reduced NCH monitoring 102
3.4.15.1.2.5 Uplink status messages 102
3.4.15.1.2.6 Channel release message 102
3.4.15.1.2.7 Information on paging channel restructuring 102
3.4.15.1.3 Uplink reply procedure 102
3.4.15.1.4 Leaving the group receive mode 102

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0984ed7-5fea-4d3a-9307-1ad7905443/etsi-ts-144-018-v11.9.0-2015-07

3.4.15.1.4.1 Returning to idle mode 102
3.4.15.1.4.2 Going to group transmit mode 103
3.4.15.2 Network side 103
3.4.15.2.1 Provision of messages on the VGCS or VBS channel downlink 103
3.4.15.2.1.1 General 103
3.4.15.2.1.2 Provision of general information messages 104
3.4.15.2.1.3 Provision of messages related to the voice group call uplink channel 104
3.4.15.2.1.4 Provision of messages related to the voice broadcast uplink channel 105
3.4.15.2.2 Release of the VGCS or VBS Channels 105
3.4.15.2a VBS/VGCS reconfiguration procedure 105
3.4.15.2a.1 Normal behaviour 105
3.4.15.2a.2 Abnormal cases 106
3.4.15.3 Failure cases 106
3.4.15.3a Additional Information procedure 106
3.4.15.3b SMS to on going group call procedure 106
3.4.16 Configuration change procedure 107
3.4.16.1 Configuration change initiation 108
3.4.16.2 Configuration change completion 108
3.4.16.3 Abnormal cases 108
3.4.17 Mapping of user data substreams onto timeslots in a multislot configuration 108
3.4.18 Handling of classmark information at band change 109
3.4.19 (void) 109
3.4.20 (void) 109
3.4.21 Application Procedures 109
3.4.21.1 General 109
3.4.21.2 Location Services (LCS) 109
3.4.21.2A Earthquake and Tsunami Warning System (ETWS) 109
3.4.21.3 Application Information Transfer 109
3.4.21.3.1 Normal Procedure without Segmentation 109
3.4.21.3.2 Normal Procedure with Segmentation 110
3.4.21.3.3 Abnormal Cases 111
3.4.22 RR procedures related to packet resource establishment while in dedicated mode 111
3.4.22.1 Packet request procedure while in dedicated mode 111
3.4.22.1.1 Entering the dual transfer mode 111
3.4.22.1.1.1 Permission to access the network 112
3.4.22.1.1.2 Initiation of establishment of the packet request procedure 112
3.4.22.1.1.3 Answer from the network 112
3.4.22.1.1.3.1 Packet assignment 112
3.4.22.1.1.3.2 RR reallocation only 114
3.4.22.1.1.3.3 Packet request rejection 114
3.4.22.1.1.4 Packet request completion 114
3.4.22.1.1.5 Abnormal cases 114
3.4.22.2 Packet notification procedure in dedicated mode 115
3.4.22.2.1 Packet notification initiation by the network 116
3.4.22.2.2 Packet notification response 116
3.4.22.3 Packet downlink assignment in dedicated mode 116
3.4.22.3.1 Initiation of the packet downlink assignment procedure in dedicated mode 116
3.4.22.3.2 Packet downlink assignment completion 117
3.4.22.3.3 Abnormal cases 117
3.4.22.4 Modification of packet resources while in DTM 118
3.4.23 RR procedures related to packet resource maintenance while in dual transfer mode 118
3.4.23.1 General 118
3.4.23.2 RR and packet resource reallocation whilst in dual transfer mode 119
3.4.23.2.1 General 119
3.4.23.2.2 Normal resource reallocation case 119
3.4.23.2.3 Abnormal cases 120
3.4.24 RR procedures related to packet resource release while in dual transfer mode 122
3.4.25 GPRS suspension procedure 122
3.4.25.1 General 122
3.4.25.2 MS in class B mode of operation 122
3.4.25.3 Dual transfer mode not supported 122
3.4.26 GPRS Transparent Transport Procedure 123

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0098ed7-d1b-4d7a-b3f7-13a6b9b54435/etsi-ts-144-018-v11.9.0-2015-07

3.4.27 RR procedures related to dedicated mode MBMS notification 123
3.4.27.1 General 123
3.4.27.2 MBMS announcement procedure in dedicated mode 123
3.4.27.2.1 General 123
3.4.27.2.2 MBMS announcement initiation by the network 123
3.4.27.2.3 MBMS notification response 123
3.4.28 Transmission of application-specific data by the talker 124
3.4.28.1 General 124
3.5 RR procedures on CCCH related to temporary block flow establishment 124
3.5.1 Packet paging procedure using CCCH 124
3.5.1.1 Packet paging initiation by the network 124
3.5.1.2 On receipt of a packet paging request 125
3.5.1.3 Packet Paging for MBMS notification on CCCH 125
3.5.1.3.1 General 125
3.5.1.3.2 MBMS pre-notification 126
3.5.1.3.3 MBMS notification 126
3.5.1.3.4 Response to MBMS notification 127
3.5.2 Packet access procedure using CCCH 128
3.5.2.1 Entering the packet transfer mode: packet access procedure 128
3.5.2.1.1 Permission to access the network 128
3.5.2.1.2 Initiation of the packet access procedure: channel request 128
3.5.2.1.3 Packet immediate assignment 131
3.5.2.1.3.1 On receipt of a CHANNEL REQUEST or EGPRS PACKET CHANNEL REQUEST message 131
3.5.2.1.3.2 One phase packet access 133
3.5.2.1.3.3 Single block packet access 134
3.5.2.1.3.3a Multiblock packet access 135
3.5.2.1.3.4 Packet access rejection 136
3.5.2.1.4 Packet access completion 136
3.5.2.1.5 Abnormal cases 136
3.5.2.2 Sending an RLC/MAC control message: single block packet access procedure 137
3.5.3 Packet downlink assignment procedure using CCCH 137
3.5.3.1 Entering the packet transfer mode: packet downlink assignment procedure 137
3.5.3.1.2 Initiation of the packet downlink assignment procedure 137
3.5.3.1.3 Packet downlink assignment completion 139
3.5.3.1.4 Abnormal cases 140
3.5.3.2 Sending an RLC/MAC control message: single block packet downlink assignment procedure 140
3.5.3.2a Sending an RLC/MAC control message: multiple blocks packet downlink assignment procedure 140
3.5.4 MBMS packet access procedure using CCCH 141
3.5.4.1 General 141
3.5.4.2 On receipt of a CHANNEL REQUEST message 141
3.5.4.3 On receipt of an IMMEDIATE ASSIGNMENT message 142
3.5.4.4 On receipt of an IMMEDIATE ASSIGNMENT REJECT message 142
3.5.4.5 On receipt of an MBMS ASSIGNMENT message 142
3.5.4.6 Abnormal cases 142
3.6 RR Procedures in packet transfer mode 142
3.6.1 RR Connection establishment using enhanced DTM CS establishment 142
3.6.2 Completion of RR Connection establishment 143
3.6.2.1 Connection established in response to an encapsulated IMMEDIATE ASSIGNMENT message 143
3.6.2.2 Connection established in response to an encapsulated DTM ASSIGNMENT COMMAND message 143
3.7 DTM Handover procedure 143
3.7.1 General 143
3.7.2 DTM Handover from GERAN *A/Gb mode* to GERAN *A/Gb mode* procedure 143
3.7.2.1 Abnormal cases 144
3.7.3 DTM Handover from GERAN *A/Gb mode* to UTRAN procedure 145
3.8 Network sharing 145
3.8.1 General 145
3.8.2 Network side 145
3.8.3 Mobile station side 146
3.8.4 Abnormal cases 147

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0098447-1f7-5bb4-d7a-9307-15ad0905d443/etsi-ts-144-018-v11.9.0-2015-07

4 Elementary procedures for Mobility Management 147
5 Elementary procedures for circuit-switched Call Control 148
6 Support for packet services 148
7 Examples of structured procedures 148
8 Handling of unknown, unforeseen, and erroneous protocol data 148
8.1 General 148
8.2 Message too short 149
8.3 (void) 149
8.4 Unknown or unforeseen message type 149
8.5 Non-semantical mandatory information element errors 149
8.5.1 Radio resource management 150
8.6 Unknown and unforeseen IEs in the non-imperative message part 150
8.6.1 IEIs unknown in the message 150
8.6.2 Out of sequence IEs 150
8.6.3 Repeated IEs 150
8.7 Non-imperative message part errors 150
8.7.1 Syntactically incorrect optional IEs 150
8.7.2 Conditional IE errors 151
8.8 Messages with semantically incorrect contents 151
8.9 Incomplete rest octets 151
9 Message functional definitions and contents 152
9.1 Messages for Radio Resources management 153
9.1.1 Additional assignment 154
9.1.1.1 Mobile Allocation 155
9.1.1.2 Starting Time 155
9.1.2 Assignment command 155
9.1.2.1 Mode of the First Channel (Channel Set 1) and Mode of Channel Set "X" (2=<X=<8) 156
9.1.2.2 Description of the Second Channel 156
9.1.2.3 Mode of the Second Channel 157
9.1.2.4 Mobile Allocation and Frequency List, after the starting time 157
9.1.2.5 Starting Time 157
9.1.2.6 Reference cell frequency list 157
9.1.2.7 Cell Channel Description 158
9.1.2.8 Cipher Mode Setting 158
9.1.2.9 VGCS target mode Indication 158
9.1.2.10 Description of the multislot allocation 158
9.1.2.11 Multi Rate configuration 158
9.1.2.12 VGCS Ciphering Parameters 159
9.1.3 Assignment complete 159
9.1.4 Assignment failure 159
9.1.5 Channel mode modify 159
9.1.5.1 Channel Description 160
9.1.5.2 VGCS target mode Indication 160
9.1.5.3 Multi Rate configuration 160
9.1.5.4 VGCS Ciphering Parameters 160
9.1.6 Channel mode modify acknowledge 161
9.1.7 Channel release 161
9.1.7.1 Group Channel Description / Group Channel Description 2 162
9.1.7.2 Group Cipher Key Number 162
9.1.7.3 UTRAN Freq List 163
9.1.7.4 Cell Channel Description 163
9.1.7.5 VGCS Ciphering Parameters 163
9.1.7.6 Talker Identity 163
9.1.7.7 Talker Priority Status 163
9.1.7.8 VGCS AMR Configuration 163
9.1.7.9 Individual priorities 163
9.1.8 Channel request 163
9.1.9 Ciphering mode command 165

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d6984cd7-fde-4d7a-9367-13a7905144/etsi-ts-144-018-v11.9.0-2015-07

9.1.10 Ciphering mode complete 166
9.1.10.1 Mobile Equipment Identity 166
9.1.11 Classmark change 167
9.1.11.1 Additional Mobile Station Classmark Information 167
9.1.11.2 Mobile Station Classmark 167
9.1.11a UTRAN Classmark Change 167
9.1.11b cdma2000 Classmark Change 168
9.1.11c (void) 169
9.1.11d GERAN IU Mode Classmark Change 169
9.1.12 Classmark enquiry 169
9.1.12a (void) 170
9.1.12b Configuration change command 170
9.1.12b.1 Description of the multislot allocation 170
9.1.12b.2 Mode of Channel Set "X" (1=<X<=8) 170
9.1.12c Configuration change acknowledge 171
9.1.12d Configuration change reject 171
9.1.12e DTM Assignment Command 172
9.1.12e.1 (void) 172
9.1.12e.2 RR Packet Uplink Assignment and RR Packet Downlink Assignment IEs 172
9.1.12e.3 MultiRate configuration 173
9.1.12e.4 Ciphering Mode Setting 173
9.1.12e.5 (void) 173
9.1.12e.6 Mobile Allocation and Frequency List 173
9.1.12e.7 Mobile Allocation C2, Frequency List C2, Channel Description C2 and Description of the Downlink Packet Channel Assignment Type 2 173
9.1.12f DTM Assignment Failure 174
9.1.12g DTM Information 174
9.1.12g.1 Routeing Area Identification 174
9.1.12h DTM Reject 175
9.1.12i DTM Request 175
9.1.13 Frequency redefinition 176
9.1.13.1 Cell Channel Description 176
9.1.13.2 Carrier Indication 176
9.1.13.3 Mobile Allocation C2 and Channel Description C2 176
9.1.13a (void) 177
9.1.13b GPRS suspension request 177
9.1.13b.1 General 177
9.1.13b.2 Routeing Area Identification 177
9.1.13b.3 Temporary Logical Link Identity 177
9.1.14 Handover access 177
9.1.15 Handover command 179
9.1.15.1 Synchronization Indication 180
9.1.15.2 Mode of the First Channel (Channel Set 1) and Mode of Channel Set "X" (2=<X<=8) 180
9.1.15.3 Description of the Second Channel 180
9.1.15.4 Mode of the Second Channel 181
9.1.15.5 Frequency Channel Sequence, Frequency List, Frequency short list and Mobile Allocation, after time. 181
9.1.15.6 Starting Time 181
9.1.15.7 Reference cell frequency list 182
9.1.15.8 Real Time Difference 182
9.1.15.9 Timing Advance 182
9.1.15.10 Cipher Mode Setting 182
9.1.15.11 VGCS target mode indication 182
9.1.15.12 Description of the multislot allocation 183
9.1.15.13 MultiRateconfiguration 183
9.1.15.14 Dynamic ARFCN Mapping 183
9.1.15.15 VGCS Target cell Ciphering information 183
9.1.15.16 Dedicated Service Information 183
9.1.15a Inter System To UTRAN Handover Command 184
9.1.15b Inter System To cdma2000 Handover Command 184
9.1.15c HANDOVER TO GERAN Iu MODE Command 185
9.1.15d Inter System To E-UTRAN Handover Command 185

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0c3ded7-130-4d7a-9367-1a0d79054443/etsi-ts-144-018-v11.9.0-2015-07

9.1.16 Handover complete 185
9.1.16.1 Mobile Observed Time Difference 186
9.1.16.2 Mobile Observed Time Difference on Hyperframe level 186
9.1.17 Handover failure 186
9.1.17.1 PS Cause 186
9.1.18 Immediate assignment 186
9.1.18.0a Dedicated mode or TBF 187
9.1.18.0b Channel Description 187
9.1.18.0c Packet Channel Description 187
9.1.18.0d Request Reference 188
9.1.18.0e Timing Advance 188
9.1.18.1 Mobile Allocation 188
9.1.18.2 Starting Time 188
9.1.18.3 IA Rest Octets (Frequency parameters, before time) 188
9.1.18.4 IA Rest Octets (assignment of uplink or downlink TBF) 188
9.1.18a (void) 189
9.1.18b Immediate packet assignment 189
9.1.19 Immediate assignment extended 189
9.1.19.1 Unnecessary IEs 190
9.1.19.2 Mobile Allocation 190
9.1.19.3 Starting Time 190
9.1.19.4 Maximum message length 190
9.1.19.5 IAX Rest Octets 191
9.1.20 Immediate assignment reject 191
9.1.20.1 Use of the indexes 191
9.1.20.2 Filling of the message 191
9.1.20.2a Request Reference 192
9.1.20.3 Wait Indication 192
9.1.20.4 IAR Rest Octets 192
9.1.21 Measurement report 192
9.1.21a Notification/FACCH 192
9.1.21a.1 (void) 195
9.1.21a.2 (void) 195
9.1.21a.3 (void) 195
9.1.21a.4 (void) 195
9.1.21b Notification/NCH 195
9.1.21b.1 (void) 196
9.1.21b.2 (void) 196
9.1.21c (void) 196
9.1.21d Notification response 196
9.1.21e (void) 197
9.1.21f Packet Assignment 197
9.1.21f.1 RR Packet Uplink Assignment and RR Packet Downlink Assignment IEs 197
9.1.21f.2 (void) 198
9.1.21f.3 Frequency List C2, Mobile Allocation C2 and Description of the Downlink Packet Channel Assignment Type 2 198
9.1.21g Packet Notification 198
9.1.21g.1 P-TMSI 198
9.1.21g.2 Mobile identity 198
9.1.21h VBS/VGCS reconfigure 199
9.1.21i VBS/VGCS reconfigure2 200
9.1.21j MBMS Announcement 200
9.1.22 Paging request type 1 201
9.1.22.1 Unnecessary IE 202
9.1.22.2 Channels needed for Mobiles 1 and 2 202
9.1.22.3 Mobile Identities 202
9.1.22.4 P1 Rest Octets 202
9.1.23 Paging request type 2 202
9.1.23.1 Channels needed for Mobiles 1 and 2 203
9.1.23.2 Mobile Identity 3 203
9.1.23.3 P2 Rest Octets 203
9.1.24 Paging request type 3 203

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0984ed7-5fe0-4d7a-9367-13ad79054435/etsi-ts-144-018-v11.9.0-2015-07

9.1.24.1 Channels needed for Mobiles 1 and 2 204
9.1.24.2 P3 Rest Octets 204
9.1.25 Paging response 204
9.1.25.1 Mobile Station Classmark 205
9.1.25.2 Additional Update Parameters 205
9.1.26 Partial release 205
9.1.26.1 Channel Description 205
9.1.27 Partial release complete 206
9.1.28 Physical information 206
9.1.28a (void) 206
9.1.29 RR Status 206
9.1.30a Synchronization channel information 207
9.1.30b COMPACT Synchronization channel information 207
9.1.31 System information type 1 208
9.1.32 System information type 2 208
9.1.33 System information type 2bis 209
9.1.34 System information type 2ter 209
9.1.34a System information type 2quater 210
9.1.34b System information type 2n 211
9.1.35 System information type 3 211
9.1.36 System information type 4 212
9.1.36.1 CBCH Channel description 213
9.1.36.2 CBCH Mobile Allocation 213
9.1.36.3 SI 4 Rest Octets 213
9.1.37 System information type 5 213
9.1.38 System information type 5bis 213
9.1.39 System information type 5ter 214
9.1.40 System information type 6 215
9.1.40.1 Cell Identity 215
9.1.40.2 Location Area Identification 215
9.1.40.3 Cell Options 215
9.1.40.4 NCC permitted 215
9.1.41 System information type 7 216
9.1.42 System information type 8 216
9.1.43 System information Type 9 217
9.1.43a System information Type 13 217
9.1.43b (void) 218
9.1.43c (void) 218
9.1.43d System information type 16 218
9.1.43e System information type 17 218
9.1.43f System information type 19 219
9.1.43g System information type 18 219
9.1.43h System information type 20 220
9.1.43i System information type 14 220
9.1.43j System information type 15 221
9.1.43k System information Type 13alt 221
9.1.43m System information type 21 222
9.1.43n System information type 22 222
9.1.43o System information type 23 222
9.1.44 Talker indication 223
9.1.44a Priority Uplink Request 223
9.1.44b Data Indication 224
9.1.44c Data Indication 2 225
9.1.45 Uplink access 225
9.1.46 Uplink busy 226
9.1.46.1 Talker Priority and Emergency Indication 226
9.1.46.2 Token 226
9.1.46.3 Talker Identity 226
9.1.46.4 Uplink Access Indication 227
9.1.47 Uplink free 227
9.1.48 Uplink release 227
9.1.49 VGCS uplink grant 228

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sist/d0984ed7-5fe0-4d7a-9367-13ad79054435/etsi-ts-144-018-v11.9.0-2015-07