

SLOVENSKI STANDARD SIST EN 301 841-3 V2.1.1:2016

01-november-2016

Digitalna povezava VHF zrak-tla, 2. način - Tehnične karakteristike in merilne metode za talno opremo - 3. del: Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU

VHF air-ground Digital Link (VDL) Mode 2 - Technical characteristics and methods of measurement for ground-based equipment - Part 3: Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 301 841-3 V2.1.1:2016</u> https://standards.iteh.ai/catalog/standards/sist/1dc3e291-9624-48bf-a113-8e69a32013bf/sist-en-301-841-3-v2-1-1-2016

Ta slovenski standard je istoveten z: ETSI EN 301 841-3 V2.1.1 (2016-09)

ICS:

33.060.99 Druga oprema za radijske

komunikacije

Other equipment for radiocommunications

SIST EN 301 841-3 V2.1.1:2016

en

SIST EN 301 841-3 V2.1.1:2016

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 841-3 V2.1.1:2016 https://standards.iteh.ai/catalog/standards/sist/1dc3e291-9624-48bf-a113-8e69a32013bf/sist-en-301-841-3-v2-1-1-2016 SIST EN 301 841-3 V2.1.1:2016

ETSI EN 301 841-3 V2.1.1 (2016-09)



VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment; Part 3: Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU

Reference

REN/ERM-TGAERO-34

Keywords

aeronautical, AM, DSB, harmonised standard, radio, testing, VHF

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la

Teh Sous-Préfecture de Grasse (06) N° 7803/88/ IEW

(standards.iteh.ai)

SIST EN 301 841-3 V2.1.1:2016 https://standards.iteh.ai/catalog/standards/sist/1dc3e291-9624-48bf-a113-8e69a32013/mportant/notice/v2-1-1-2016

> The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT[™], **PLUGTESTS**[™], **UMTS**[™] and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**[™] and **LTE**[™] are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intelle	ctual Property Rights	5		
Forew	ord	5		
Modal verbs terminology5				
1	Scope	6		
	•			
	References			
2.1 2.2	Normative references			
2.2	Informative references	0		
3	Definitions and abbreviations	7		
3.1	Definitions	7		
3.2	Abbreviations	8		
4	Technical requirements specifications	Q		
 4.1	Environmental profile	۰و و		
4.2	Conformance requirements			
4.2.1	Transmitter requirements			
4.2.1 4.2.1.1	Frequency error			
4.2.1.1				
4.2.1.1				
4.2.1.2				
4.2.1.2				
4.2.1.2		9		
4.2.1.3	Adjacent channel power	9		
4.2.1.3	.1 Requirement standards iteh ai	9		
4.2.1.3	Adjacent channel power 1 Requirement standards.itch.ai 2 Conformance	9		
4.2.1.4	Transmitter Conducted spurious emissions	9		
4.2.1.4	Transmitter Conducted spurious emissions Requirement Conformance Transmitter Cabinet radiation 13bf/sist-en-301-841-3-v2-1-1-2016	9		
4.2.1.4	.2 Conformance 2600 22013 by sixt on 2018 41.3 x2 11.2016	9		
4.2.1.5	Transmitter Cabinet radiation	9		
4.2.1.5				
4.2.1.5				
4.2.1.6				
4.2.1.7 4.2.1.7				
4.2.1. <i>1</i> 4.2.1.7	1			
4.2.1. <i>1</i> 4.2.1.8				
4.2.1.8 4.2.1.9				
4.2.1.9				
4.2.1.9	1			
4.2.1.1				
4.2.1.1				
4.2.1.1				
4.2.1.1				
4.2.1.1	1.1 Requirement	.10		
4.2.1.1	1.2 Conformance	.11		
4.2.1.1	2 Load VSWR capability	.11		
4.2.1.1	1			
4.2.1.1				
4.2.2	Receiver requirements			
4.2.2.1				
4.2.2.1	1			
4.2.2.1				
4.2.2.2				
4.2.2.2				
4.2.2.2				
4.2.2.3	First adjacent channel rejection	. 1 1		

ETSI EN 301 841-3 V2.1.1 (2016-09)

Annex B	(informative): Bibliography	1
Annex A	(normative): Relationship between the present document and the esser requirements of Directive 2014/53/EU	
5.3.2.9	Cabinet Radiation	1
5.3.2.8	Conducted spurious emission	
5.3.2.7	Blocking or desensitization	
5.3.2.6	In-band Intermodulation rejection	
5.3.2.5	Spurious response rejection of signals outside the VHF aeronautical band	
5.3.2.4	Spurious response rejection of signals within the VHF aeronautical band	
5.3.2.3	First Adjacent channel rejection	
5.3.2.2	Co-channel interference	
5.3.2.1	Sensitivity	
5.3.2	Receiver test specifications	
5.3.1.12	Load VSWR capability	
5.3.1.11	Modulation accuracy - Symbol constellation error	
5.3.1.10.2		
5.3.1.10.1	Receiver to transmitter turn-around time	
5.3.1.10	Transient behaviour of the transmitter	
5.3.1.9	RF power release time	
5.3.1.8	Void	
5.3.1.7	Inter-modulation attenuation	1
5.3.1.6	Cabinet Radiation8e69a32013bf/sist-en-301-841-3-v2-1-1-2016	
5.3.1.4	Conducted Spurious emissions analog/standards/sist/1dc3e291-9624-48bf-a113-	
5.3.1.3 5.3.1.4		
5.3.1.2	Manufacturer's declared output power	
5.3.1.1 5.3.1.2		
	Transmitter test specifications (Standards.iteh.ai)	l 1
5.3 5.3.1	Transmitter test specifications	l
5.2	Interpretation of the measurement results. Conformance tests I	
5.1.2	Normal and extreme test conditions	
5.1.1	Test power source	
5.1.0	General	
	Environmental conditions for testing	
	sting for compliance with technical requirements	
4.2.2.9.2	Conformance	
4.2.2.9.1	Requirement	
4.2.2.9	Receiver Cabinet radiation	
4.2.2.8.2	Conformance	
4.2.2.8.1	Requirement	
4.2.2.8	Receiver Conducted spurious emission	
4.2.2.7.2	Conformance	
4.2.2.7.1	Requirement	
4.2.2.0.2 4.2.2.7	Blocking or desensitization	
4.2.2.6.2	Conformance	
4.2.2.6.1	Requirement	
+.2.2.3.2 4.2.2.6	In-band Intermodulation response rejection	
4.2.2.5.1 4.2.2.5.2	Requirement	
+.2.2.3 4.2.2.5.1		
4.2.2.4.2 4.2.2.5	Conformance	
4.2.2.4.1	Requirement	
4.2.2.4	Spurious response rejection of signals within the VHF aeronautical band	
4.2.2.3.2	Conformance	
4.2.2.3.1	Requirement	

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.4] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 3 of a multi-part deliverable covering VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment, as identified below:

Part 1: "Physical layer and MAC sub-layer" layer layer

Part 2: "Upper layers"; 8e69a32013bf/sist-en-301-841-3-v2-1-1-2016

Part 3: "Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".

National transposition dates	
Date of adoption of this EN:	13 September 2016
Date of latest announcement of this EN (doa):	31 December 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2017
Date of withdrawal of any conflicting National Standard (dow):	30 June 2018

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document applies to VDL Mode 2 ground-air digital communications using Differential Eight Phase Shift Keying (D8PSK), intended for channel increments of 25 kHz. The VDL Mode 2 system provides data communication exchanges between aircraft and ground-based systems, operating in the VHF band (117,975 MHz to 137,000 MHz). The scope of the present document is limited to ground based stations.

NOTE: The VDL Mode 2 can be used as an Air/Ground sub-network of the Aeronautical Telecommunication Network (ATN) using a band with AM(R)S spectrum allocation.

The present document contains requirements to demonstrate that "... Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference" [i.1].

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Directive 2014/53/EU [i.1] as well as essential requirements under the SES Interoperability Regulation No 552/2004 [i.5] and related implementing rules and/or essential requirements under the EASA basic Regulation No 216/2008 [i.6] as amended by Regulation No 1108/2009 [i.7] may apply to equipment within the scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at http://docbox.etsi.org/Reference. SIST EN 301 841-3 V2.1.1 2016

https://standards.iteh.ai/catalog/standards/sist/1dc3e291-9624-48bf-a113-

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 841-1 (V1.4.1) (04-2015): "VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment; Part 1: Physical layer and MAC sub-layer".
- [2] ETSI EN 300 113-1 (V1.7.1) (11-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

7

[i.2]	ETSI TR 100 028-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
[i.3]	ETSI TR 100 028-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
[i.4]	Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
[i.5]	Regulation (EC) No 552/2004 of the European Parliament and of the Council of 10 March 2004 on the interoperability of the European Air Traffic Management network (interoperability Regulation), OJ L 96, 31.03.2004, p. 26 as amended by Regulation (EC) No 1070/2009, OJ L 300, 14.11.2009, p. 34.
[i.6]	Regulation (EC) No 216/2008 of the European Parliament and of the Council of 20 February 2008 on common rules in the field of civil aviation and establishing a European Aviation Safety Agency, and repealing Council Directive 91/670/EEC, Regulation (EC) No 1592/2002 and

Regulation (EC) No 1108/2009 of the European Parliament and of the Council of 21 October 2009 amending Regulation (EC) No 216/2008 in the field of aerodromes, air traffic management and air

3 Definitions and abbreviations

navigation services and repealing Directive 2006/23/EC.

3.1 Definitions (standards.iteh.ai)

Directive 2004/36/EC.

[i.7]

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [i.1] and the following apply: https://standards.iteh.ai/catalog/standards/sist/1dc3e291-9624-48bf-a113-8e69a32013bf/sist-en-301-841-3-v2-1-1-2016

adjacent channel power: amount of the modulated RF signal power transmitted outside of the assigned channel

NOTE: Adjacent channel power includes discrete spurious, signal sidebands, and noise density (including phase noise) at the transmitter output.

adjacent channel rejection: receiver's ability to demodulate the desired signal and meet the uncorrected BER requirement in the presence of an interfering signal in an adjacent channel

NOTE: The ratio (in dB) between the adjacent interfering signal level and the desired signal level necessary to achieve the specified minimum uncorrected BER, is the Adjacent Channel Rejection (ACR) ratio.

Aeronautical Mobile Service (AMS): mobile service between ground based stations and airborne stations, or between aircraft stations, in which survival craft stations may participate

average transmitter output power: average power supplied to the antenna transmission line by a transmitter during an interval of time sufficiently long, compared with the lowest frequency encountered in the modulation, taken under normal operating conditions

Bit Error Rate (BER): ratio between the number of erroneous bits received and the total number of bits received

NOTE: The uncorrected BER represents the BER without the benefit of Forward Error Correction (FEC).

Co-Channel Interference (CCI): capability of a receiver to demodulate the desired signal and achieve the minimum specified BER performance in the presence of an unwanted signal at the same assigned channel

NOTE: The ratio (in dB) between the wanted signal level and the unwanted signal level is the co-channel interference ratio.

conducted measurements: measurements which are made using a direct RF connection to the equipment under test

8

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

ground based station: aeronautical station equipment, in the Aeronautical Mobile Service (AMS), for use with an external antenna and intended for use at a fixed location

radiated measurements: measurements which involve the measurement of a radiated field

spurious emissions: conducted RF emissions on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information

Spurious emissions include parasitic emissions, intermodulation products and frequency conversion products.

X 25: ITU-T standard for the protocols and message formats that define the interface between a terminal and a packet switching network

3.2 **Abbreviations**

For the purposes of the present document, the following abbreviations apply:

ACR Adjacent Channel Rejection AM Amplitude Modulation AM(R)S Aeronautical Mobile (Route) Service **AMS** Aeronautical Mobile Service

ATN Aeronautical Telecommunication Network

BER Bit Error Rate

Co-Channel Interference ANDARD PREVIEW CCI

Differential Eight Phase Shift Keying Double Side Band (Standards.iteh.ai) D8PSK DSB

European Aviation Safety Agency **EASA**

Forward Error Corrections TEN 301 841-3 V2.1.1:2016 FEC

Medium Access Control a/catalog/standards/sist/1dc3e291-9624-48bf-a113-Radio and Telecommunications Terminal Equipment 1-2016 MAC

R&TTE

RF Radio Frequency TXTransmission VHF Data Link **VDL** Very High Frequency **VHF**

VSWR Voltage Standing Wave Ratio

Technical requirements specifications 4

Environmental profile 4.1

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Conformance requirements

4.2.1 Transmitter requirements

4.2.1.1 Frequency error

4.2.1.1.1 Requirement

Frequency tolerance shall be as specified in ETSI EN 301 841-1 [1], clause 6.1.1.

4.2.1.1.2 Conformance

Conformance tests as defined in clause 5.3.1.1 shall be carried out with the limits defined by clause 4.2.1.1.1.

4.2.1.2 Manufacturer's declared output power

4.2.1.2.1 Requirement

Manufacturer's declared output power shall be as specified in ETSI EN 301 841-1 [1], clause 6.1.2.

4.2.1.2.2 Conformance

Conformance tests as defined in clause 5.3.1.2 shall be carried out with the limits defined by clause 4.2.1.2.1.

iTeh STANDARD PREVIEW

4.2.1.3 Adjacent channel power

(ständards.iteh.ai)

4.2.1.3.1 Requirement

SIST EN 301 841-3 V2.1.1:2016

Adjacent channel power shall be as specified in ETSLEN 301841-1 [1] clause 6.1.3 bf-a113-

8e69a32013bf/sist-en-301-841-3-v2-1-1-2016

4.2.1.3.2 Conformance

Conformance tests as defined in clause 5.3.1.3 shall be carried out with the limits defined by clause 4.2.1.3.1.

4.2.1.4 Transmitter Conducted spurious emissions

4.2.1.4.1 Requirement

Conducted spurious emissions shall be as specified in ETSI EN 301 841-1 [1], clause 6.1.4.

4.2.1.4.2 Conformance

Conformance tests as defined in clause 5.3.1.4 shall be carried out with the limits defined by clause 4.2.1.4.1.

4.2.1.5 Transmitter Cabinet radiation

4.2.1.5.1 Requirement

Cabinet radiation shall be as specified in ETSI EN 301 841-1 [1], clause 6.1.5.

4.2.1.5.2 Conformance

Conformance tests as defined in clause 5.3.1.5 shall be carried out with the limits defined by clause 4.2.1.5.1.