

Draft **ETSI EN 300 392-2** V3.7.2 (2016-04)



**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 2: Air Interface (AI)**

Standard Preview
(standards.itd.eu)
Full standard/standards/etsi-en-300-392-v3-7-2-16-04-08
https://standards.itd.eu/catalog/standards/etsi-en-300-392-v3-7-2-16-04-08
44e-ac73-2b1ac687c299/etsi-en-300-392-v3-7-2-16-04-08

Reference

REN/TCCE-03240

Keywords

air interface, radio, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	45
Foreword.....	45
1 Scope	46
2 References	47
2.1 Normative references	47
2.2 Informative references.....	49
3 Definitions and abbreviations.....	50
3.1 Definitions.....	50
3.2 Abbreviations	58
4 Radio aspects.....	65
4.1 Introduction	65
4.2 Set of logical channels.....	65
4.3 Reference configuration	65
4.4 Error control schemes.....	66
4.5 Multiple access and timeslot structure.....	66
4.5.1 General.....	66
4.5.2 Hyperframes, multiframes and frames.....	67
4.5.3 Timeslots and bursts	67
4.5.4 Mapping of logical channels onto physical channels.....	68
4.6 Coding, interleaving and scrambling.....	68
4.7 Modulation	68
4.8 Transmission and reception.....	68
4.9 Other radio-related functions.....	68
4.10 Performance	69
4.11 TETRA modes of operation	69
4.11.0 General.....	69
4.11.1 Main control channel modes of operation.....	70
4.11.1.1 Conventional Access (CA) mode.....	70
4.11.1.2 Direct Access (DA) mode	70
4.11.2 Transmission modes	70
4.11.2.1 Downlink-Continuous Transmission (D-CT) mode.....	70
4.11.2.2 Downlink-Carrier Timesharing Transmission (D-CTT) mode.....	70
4.11.2.3 Downlink-Main Control Channel Timesharing Transmission (D-MCCTT) mode.....	70
4.11.2.4 Multiple Slot Transmission (MST) mode	70
4.11.3 Control modes.....	70
4.11.3.1 Normal Control Mode (NCM)	70
4.11.3.2 Minimum Control Mode (MCM).....	71
5 Modulation	72
5.1 Introduction	72
5.2 Modulation type	72
5.3 Modulation rate	72
5.4 Modulation symbol definition.....	72
5.5 Modulated signal definition.....	74
5.6 Modulation filter definition	74
5.7 Modulation block diagram	75
5.8 Introduction to QAM channels.....	75
5.9 Modulation type	75
5.10 Use of sub-carriers in QAM carriers	75
5.11 Modulation rate	75
5.12 Modulation symbol definition.....	76
5.13 Bit to symbol mapping	76
5.14 Data, synchronization and pilot symbol multiplexing	79
5.15 Sub-carrier frequency domain multiplexing.....	80
5.16 Modulated signal definition.....	80
5.17 Modulation filter definition	81

5.18	Modulation block diagram	82
6	Radio transmission and reception.....	83
6.1	Introduction	83
6.2	Frequency bands and channel arrangement.....	83
6.3	Reference test planes	83
6.4	Transmitter characteristics.....	84
6.4.1	Output power for phase modulation	84
6.4.1.0	General	84
6.4.1.1	Base Station (BS).....	84
6.4.1.2	Mobile Station (MS)	85
6.4.2	Unwanted conducted emissions for phase modulation	85
6.4.2.1	Definitions.....	85
6.4.2.2	Unwanted emissions close to the carrier	86
6.4.2.2.0	General	86
6.4.2.2.1	Emission during the useful part of the burst	86
6.4.2.2.2	Emission during the switching transients	86
6.4.2.3	Unwanted emissions far from the carrier	87
6.4.2.4	Unwanted emissions during the CLCH and BLCH	87
6.4.2.5	Unwanted emissions in the non-transmit state	88
6.4.3	Unwanted radiated emissions for phase modulation.....	88
6.4.4	RF tolerance for phase modulation.....	88
6.4.5	RF Output power time mask for phase modulation	88
6.4.5.0	General	88
6.4.5.1	BS.....	89
6.4.5.2	MS.....	89
6.4.6	Transmitter intermodulation attenuation for phase modulation	89
6.4.6.1	Definition	89
6.4.6.2	BS.....	90
6.4.6.3	MS.....	90
6.4.7	Intra-BS intermodulation requirements.....	90
6.4.8	Output power for QAM	90
6.4.8.0	General.....	90
6.4.8.1	BS.....	91
6.4.8.2	MS.....	91
6.4.9	Unwanted conducted emissions for QAM.....	92
6.4.9.1	Definitions.....	92
6.4.9.2	Unwanted emissions close to the carrier	92
6.4.9.2.0	General	92
6.4.9.2.1	Emission during the useful part of the burst	92
6.4.9.2.2	Emission during the switching transients	93
6.4.9.3	Unwanted emissions far from the carrier	93
6.4.9.4	Unwanted emissions during the CLCH-Q and BLCH-Q.....	94
6.4.9.5	Unwanted emissions in the non-transmit state	95
6.4.10	RF Output power time mask for QAM.....	95
6.4.10.0	General.....	95
6.4.10.1	BS.....	96
6.4.10.2	MS.....	96
6.4.11	Transmitter intermodulation attenuation.....	96
6.4.12	Intra-BS intermodulation requirements	96
6.5	Receiver characteristics	96
6.5.0	General.....	96
6.5.1	Blocking characteristics	96
6.5.1.1	Definition	96
6.5.1.2	Specification for Phase Modulation	97
6.5.1.3	Specification for QAM.....	97
6.5.2	Spurious response rejection	98
6.5.2.1	Definition	98
6.5.2.2	Specification for phase modulation.....	98
6.5.2.3	Specification for QAM.....	98
6.5.3	Intermodulation response rejection.....	99
6.5.3.1	Definition	99

6.5.3.2	Specification for Phase Modulation	99
6.5.3.3	Specification for QAM.....	99
6.5.4	Unwanted conducted emissions	100
6.5.4.1	Definition	100
6.5.4.2	Specification.....	100
6.5.5	Unwanted radiated emissions	100
6.6	Transmitter/receiver performance for phase modulation.....	100
6.6.0	General.....	100
6.6.1	Transmitter performance for phase modulation.....	100
6.6.1.1	Modulation accuracy for phase modulation	100
6.6.1.2	Vector error magnitude requirement at symbol time for phase modulation.....	101
6.6.2	Receiver performance for phase modulation	102
6.6.2.0	General	102
6.6.2.1	Nominal error rates for phase modulation.....	102
6.6.2.1.1	Nominal error rates for $\pi/4$ -DQPSK modulation	102
6.6.2.1.2	Nominal error rates for $\pi/8$ -D8PSK modulation	102
6.6.2.2	Dynamic reference sensitivity performance for phase modulation	103
6.6.2.2.0	General	103
6.6.2.2.1	BS receiver performance	103
6.6.2.2.2	MS receiver performance	105
6.6.2.3	Receiver performance at reference interference ratios for Phase Modulation.....	106
6.6.2.3.0	General	106
6.6.2.3.1	BS receiver performance	107
6.6.2.3.2	MS receiver performance	108
6.6.2.4	Static reference sensitivity performance for phase modulation	109
6.6.2.4.0	General	109
6.6.2.4.1	BS receiver performance	109
6.6.2.4.2	MS receiver performance	110
6.6.2.5	MS receiver performance for synchronization burst acquisition.....	111
6.7	Transmitter/receiver performance for QAM.....	111
6.7.0	General.....	111
6.7.1	Transmitter performance for QAM.....	111
6.7.1.1	Modulation accuracy for QAM.....	111
6.7.1.2	Vector error magnitude requirement at symbol time for QAM.....	112
6.7.2	Receiver performance for QAM	113
6.7.2.0	General	113
6.7.2.1	Nominal error rates for QAM.....	113
6.7.2.2	Dynamic reference sensitivity performance for QAM.....	113
6.7.2.3	Receiver performance at reference interference ratios for QAM	116
6.7.2.3.1	Adjacent channel interference	116
6.7.2.3.2	Co-channel interference.....	116
6.7.2.4	Static reference sensitivity performance for QAM	117
6.7.2.5	MS receiver performance for frequency correction burst acquisition on a DA cell.....	117
6.8	Propagation conditions	117
6.8.0	General.....	117
6.8.1	Propagation conditions - introduction.....	117
6.8.2	Tap-gain process types.....	118
6.8.3	Propagation models.....	119
7	Radio sub-system synchronization	120
7.1	Introduction	120
7.2	General description of synchronization system.....	120
7.3	Timebase counters for phase modulation	120
7.3.1	Timing counters for phase modulation	120
7.3.2	Values of the counters for phase modulation.....	120
7.4	Timing of phase modulation signals.....	121
7.5	Timebase counters for QAM	121
7.5.1	Timing counters for QAM.....	121
7.5.2	Values of the counters for QAM.....	121
7.6	Timing of QAM signals	122
7.7	BS requirements for synchronization	122
7.8	MS requirements for synchronization	123

8	Channel coding and scrambling	124
8.1	Introduction	124
8.2	General	124
8.2.1	Interfaces in the error control structure	124
8.2.1.1	Interfaces for phase modulation	124
8.2.1.2	Interfaces for QAM	126
8.2.2	Notation	127
8.2.3	Definition of error control codes	127
8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes	127
8.2.3.1.0	General	127
8.2.3.1.1	Encoding by the 16-state mother code of rate 1/4	127
8.2.3.1.2	Puncturing of the mother code	128
8.2.3.1.3	Puncturing scheme of the RCPC code of rate 2/3	128
8.2.3.1.4	Puncturing scheme of the RCPC code of rate 1/3	128
8.2.3.1.5	Puncturing scheme of the RCPC code of rate 292/432	128
8.2.3.1.6	Puncturing scheme of the RCPC code of rate 148/432	128
8.2.3.2	Shortened (30,14) Reed-Muller (RM) code	129
8.2.3.3	($K_I + 16, K_I$) block code	129
8.2.3.4	8-state Parallel Concatenated Convolutional Code (PCCC) for QAM	130
8.2.3.4.0	General	130
8.2.3.4.1	Encoding by the upper 8-state RSC encoder of rate 1/2	130
8.2.3.4.2	Interleaving by the quadratic-congruence interleaver	131
8.2.3.4.3	Encoding the interleaved bits by the lower 8-state RSC encoder of rate 1/2	132
8.2.3.4.4	Merging the systematic and parity bits for the PCCC encoder	132
8.2.3.4.5	Puncturing scheme for the PCCC encoder	133
8.2.3.4.6	Puncturing scheme for the PCCC encoder with coding rate 2/3	133
8.2.3.4.7	Puncturing scheme for the PCCC encoder with coding rate 1/2	133
8.2.3.5	(16,5) Reed-Muller (RM) code for QAM	133
8.2.4	Definition of interleaving schemes	133
8.2.4.1	Block interleaving for phase modulation	133
8.2.4.2	Interleaving over N blocks	134
8.2.4.3	Block interleaving for QAM	134
8.2.5	Definition of scrambling	135
8.2.5.1	Scrambling method	135
8.2.5.2	Scrambling sequence	135
8.3	Error control schemes	136
8.3.1	Error control schemes for phase modulation	136
8.3.1.0	General	136
8.3.1.1	Access Assignment Channel (AACH)	138
8.3.1.2	Broadcast Synchronization Channel (BSCH)	138
8.3.1.3	Traffic channels in circuit switched mode	139
8.3.1.3.1	Frame stealing and multi-slot transmission	139
8.3.1.3.2	Traffic CHannel, net rate = 4,8 kbit/s (TCH/4,8)	139
8.3.1.3.3	Traffic CHannel, net rate = 2,4 kbit/s (TCH/2,4)	140
8.3.1.3.4	Traffic CHannel, net rate = 7,2 kbit/s (TCH/7,2)	140
8.3.1.3.5	Traffic Channel-P8, net rate = 10,8 kbit/s (TCH-P8/10,8)	141
8.3.1.3.6	Speech Traffic Channel, full slot (TCH/S)	141
8.3.1.3.7	Speech Traffic Channel, half slot (TCH/S)	141
8.3.1.4	Signalling channels for signalling and packet mode data	142
8.3.1.4.1	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH/HD), Broadcast Network CHannel (BNCH), and STealing CHannel (STCH)	142
8.3.1.4.2	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH-P8/HD)	142
8.3.1.4.3	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH/HU)	143
8.3.1.4.4	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH-P8/HU)	143
8.3.1.4.5	Signalling CHannel for mapping onto Full bursts (SCH/F)	143
8.3.1.4.6	Signalling CHannel for mapping onto Full bursts (SCH-P8/F)	144
8.3.2	Error control schemes for QAM	145
8.3.2.0	General	145
8.3.2.1	Slot Information Channel - QAM/Uplink (SICH-Q/U)	145
8.3.2.2	Slot Information Channel - QAM/Downlink (SICH-Q/D)	146
8.3.2.3	Access Assignment Channel - QAM (AACH-Q)	146

8.3.2.4	Signalling Channel - QAM/Half slot Uplink (SCH-Q/HU)	147
8.3.2.5	Signalling Channel - QAM/Uplink (SCH-Q/U).....	147
8.3.2.6	Signalling Channel - QAM/Downlink (SCH-Q/D) and Broadcast Network Channel - QAM (BNCH-Q).....	148
8.3.2.7	Signalling Channel - QAM/Random Access (SCH-Q/RA)	149
8.3.2.8	Broadcast Synchronization Channel - QAM (BSCH-Q).....	149
8.3.2.9	Signalling Channel Data set B - QAM (SCH-Q/B).....	150
9	Channel multiplexing	151
9.1	Introduction	151
9.2	Logical channels.....	151
9.2.0	General.....	151
9.2.1	Logical channels hierarchy	151
9.2.2	Traffic channels for $\pi/4$ -DQPSK	151
9.2.2a	Traffic channels for $\pi/8$ -D8PSK.....	151
9.2.3	Control CHannels (CCH) for phase modulation.....	152
9.2.3.1	General	152
9.2.3.2	BCCH.....	152
9.2.3.3	LCH.....	152
9.2.3.4	SCH for $\pi/4$ -DQPSK.....	152
9.2.3.4a	SCH for $\pi/8$ -D8PSK	153
9.2.3.5	AACH	153
9.2.3.6	STCH	153
9.2.4	QAM Control CHannels (CCH-Q)	153
9.2.4.1	General	153
9.2.4.2	BCCH-Q	153
9.2.4.3	LCH-Q	154
9.2.4.4	SCH-Q.....	154
9.2.4.4a	SCH-Q/B.....	155
9.2.4.5	AACH-Q.....	155
9.2.4.6	SICH-Q	155
9.3	The physical resource	156
9.3.1	General.....	156
9.3.2	RF channels for phase modulation.....	156
9.3.2a	RF channels for QAM.....	157
9.3.2b	Random access RF channels for QAM.....	157
9.3.3	Timeslots	157
9.3.4	TDMA frame	158
9.3.5	Timeslot numbering	158
9.3.6	Subslot	158
9.3.6a	Random access uplink RF channel subslots for QAM.....	158
9.3.7	Multiframe	158
9.3.8	Hyperframe	158
9.3.9	Frame alignment	158
9.4	Physical channels	158
9.4.1	General.....	158
9.4.2	Types of physical channels for phase modulation	159
9.4.2.0	General	159
9.4.2.1	CP channel for phase modulation.....	159
9.4.2.2	TP channel.....	159
9.4.2.3	UP channel	159
9.4.3	Bursts for phase modulation	159
9.4.3.1	General	159
9.4.3.2	Phase modulation symbol numbering	160
9.4.3.3	Phase modulation bit numbering.....	160
9.4.3.4	Burst timing.....	160
9.4.4	Type of bursts for phase modulation	161
9.4.4.1	General	161
9.4.4.2	Modulation bits allocation.....	163
9.4.4.2.0	General	163
9.4.4.2.1	Control uplink Burst (CB).....	164
9.4.4.2.2	Linearization uplink Burst (LB).....	164

9.4.4.2.3	Linearization downlink burst.....	164
9.4.4.2.4	Normal Uplink Burst (NUB).....	164
9.4.4.2.5	Normal continuous downlink burst.....	165
9.4.4.2.6	Synchronization continuous downlink burst.....	166
9.4.4.2.7	Normal discontinuous downlink burst.....	166
9.4.4.2.8	Synchronization discontinuous downlink burst.....	167
9.4.4.3	Burst fields.....	167
9.4.4.3.1	Frequency correction field.....	167
9.4.4.3.2	Normal training sequence.....	167
9.4.4.3.3	Extended training sequence.....	168
9.4.4.3.4	Synchronization training sequence.....	168
9.4.4.3.5	Tail bits.....	169
9.4.4.3.6	Phase adjustment bits.....	169
9.4.5	Transmission modes for phase modulation.....	170
9.4.5.1	BS continuous transmission.....	170
9.4.5.2	BS timesharing transmission.....	170
9.4.5.3	MS multiple slot transmission.....	171
9.4.6	Types of physical channels for QAM.....	172
9.4.6.0	General.....	172
9.4.6.1	CP channel for QAM.....	172
9.4.6.2	UP channel.....	172
9.4.7	Bursts for QAM.....	172
9.4.7.1	General.....	172
9.4.7.2	Modulation symbol numbering.....	172
9.4.7.3	Modulation bit numbering.....	173
9.4.7.4	Burst timing.....	173
9.4.8	Type of bursts for QAM.....	174
9.4.8.1	General.....	174
9.4.8.2	Modulation symbols allocation.....	175
9.4.8.3	Burst sub-carrier symbol sets.....	175
9.4.8.3.1	General on burst sub-carrier symbol sets.....	175
9.4.8.3.2	Uplink sync sequence set.....	175
9.4.8.3.3	Downlink sync sequence set.....	176
9.4.8.3.3a	Secondary sync sequence set.....	176
9.4.8.3.4	Half-slot uplink pilots set.....	176
9.4.8.3.5	Full-slot uplink pilots set.....	176
9.4.8.3.6	Full-slot downlink pilots set.....	177
9.4.8.3.7	Filler sets.....	177
9.4.8.3.8	Linearization downlink zeroed set.....	177
9.4.8.3.9	Frequency correction set.....	177
9.4.8.3.10	Frequency correction data set A.....	177
9.4.8.3.11	Frequency correction data set B.....	178
9.4.9	Transmission modes for QAM.....	178
9.4.9.1	BS transmission.....	178
9.4.9.2	MS multiple slot transmission.....	178
9.5	Mapping of logical channels into physical channels.....	178
9.5.0	General.....	178
9.5.1	General mapping of logical channels into $\pi/4$ -DQPSK physical channels.....	179
9.5.1a	General mapping of logical channels into D8PSK physical channels.....	180
9.5.1b	General mapping of logical channels into unallocated physical channels for phase modulation.....	181
9.5.2	Mapping of BCCH and CLCH for phase modulation.....	181
9.5.3	Mapping of SCH for $\pi/4$ -DQPSK physical channels.....	182
9.5.3a	Mapping of SCH for $\pi/8$ -D8PSK physical channels.....	182
9.5.4	Mapping of TCH and STCH for phase modulation.....	183
9.5.5	Mapping of AACH for phase modulation.....	183
9.5.6	General mapping of logical channels for QAM.....	183
9.5.7	General mapping of logical channels into unallocated physical channels for QAM.....	184
9.5.8	Mapping of BCCH-Q and CLCH-Q for QAM.....	184
9.5.9	Mapping of SCH-Q for QAM.....	185
9.5.10	Mapping of SICH-Q and AACH-Q for QAM.....	185
9.6	Monitoring pattern for transmitting MSs.....	186

9.7	BS timesharing transmission	186
9.7.1	Carrier sharing for Phase Modulation	186
9.7.2	MCCCH sharing for Phase Modulation	186
9.7.3	BS timesharing transmission for QAM	187
9.8	Modes of control	187
9.8.0	General	187
9.8.1	Normal Control Mode	187
9.8.2	Minimum Control Mode	188
10	Radio subsystem link control	189
10.1	Introduction	189
10.2	RF power control	189
10.3	Radio link measurements	189
10.3.0	General	189
10.3.1	Received signal strength	189
10.3.1.1	Signal strength measurement	189
10.3.1.2	Sample duration for signal strength measurement	189
10.3.2	Signal quality	189
10.3.3	Round-trip MS-BS path delay	189
10.4	Link adaptation	190
11	Call Control (CC) service description	191
11.1	Introduction	191
11.2	Services offered	191
11.3	CC service	192
11.3.1	CC primitives exchanged through the TNCC-SAP	192
11.3.2	Service primitives at the TNCC-SAP	192
11.3.3	Primitive description	193
11.3.3.0	General	193
11.3.3.1	TNCC-ALERT primitive	193
11.3.3.2	TNCC-COMPLETE primitive	194
11.3.3.3	TNCC-DTMF primitive	194
11.3.3.4	TNCC-MODIFY primitive	195
11.3.3.5	TNCC-NOTIFY primitive	195
11.3.3.6	TNCC-PROCEED primitive	196
11.3.3.7	TNCC-RELEASE primitive	196
11.3.3.8	TNCC-SETUP primitive	196
11.3.3.9	TNCC-TX primitive	198
11.3.4	Parameter description	198
11.4	States for CC SAP	206
12	Supplementary Service (SS) service description	207
12.1	Introduction	207
12.2	Services offered	207
12.3	SS service	207
12.3.1	Primitives exchanged through TNSS-SAP	207
12.3.2	Parameter description	208
13	Short Data Service (SDS) service description	208
13.1	Introduction	208
13.2	Services offered	208
13.3	SDS	208
13.3.1	SDS primitives exchanged through the TNSDS-SAP	208
13.3.2	Service primitives at the TNSDS-SAP	209
13.3.2.0	General	209
13.3.2.1	TNSDS-STATUS primitive	209
13.3.2.2	TNSDS-REPORT primitive	210
13.3.2.3	TNSDS-UNITDATA primitive	210
13.3.2.4	TNSDS-CANCEL primitive	211
13.3.3	Parameter description	211
13.3.4	State description	214
13.3.4.1	NULL state	214
13.3.4.2	SHORT DATA INITIATED state	214

13.3.5	Service state diagram for the TNSDS-SAP	214
14	CMCE protocol	215
14.1	Introduction	215
14.2	Overview of CMCE.....	215
14.2.0	General.....	215
14.2.1	Communication routes of the CMCE model.....	216
14.2.2	Protocol structure and protocol stack.....	216
14.2.3	Addressing rules	218
14.2.4	CC, SS and SDS sub-entities	218
14.2.4.0	General	218
14.2.4.1	CC sub-entity	219
14.2.4.2	SS sub-entity	219
14.2.4.3	SDS sub-entity	219
14.2.5	PC sub-entity	219
14.2.6	Internal routes	220
14.2.7	Intra-CMCE primitive summary	222
14.2.7.0	General	222
14.2.7.1	Down link CC PDU parameters	222
14.2.7.2	Uplink CC PDU parameters.....	222
14.2.7.3	Downlink SS PDU parameters	223
14.2.7.4	Uplink SS PDU parameters.....	223
14.2.7.5	Down link SDS PDU parameters	223
14.2.7.6	Uplink SDS PDU parameters	223
14.2.7.7	CMCE management primitives.....	224
14.2.7.7.0	ACTIVITY request.....	224
14.2.7.7.1	BREAK indication.....	224
14.2.7.7.1a	BUSY indication	224
14.2.7.7.2	CANCEL request.....	224
14.2.7.7.3	CLOSE indication	224
14.2.7.7.4	CONFIGURE indication	224
14.2.7.7.5	CONFIGURE request	225
14.2.7.7.6	IDENTITIES request.....	225
14.2.7.7.6a	IDLE indication	225
14.2.7.7.6b	INFO indication.....	225
14.2.7.7.7	OPEN indication.....	225
14.2.7.7.8	REOPEN indication.....	225
14.2.7.7.9	REPORT indication.....	225
14.2.7.7.10	RESUME indication.....	226
14.3	Overview of services required by the CMCE.....	226
14.4	CMCE protocol states	226
14.4.0	General.....	226
14.4.1	States for PC	226
14.4.1.0	General	226
14.4.1.1	CLOSED	226
14.4.1.2	OPEN	226
14.4.2	States for CC.....	227
14.4.2.0	General	227
14.4.2.1	IDLE	229
14.4.2.2	MO-CALL-SETUP	229
14.4.2.3	MT-CALL-SETUP	229
14.4.2.4	CALL ACTIVE.....	230
14.4.2.5	CALL DISCONNECT	230
14.4.2.6	WAIT	230
14.4.3	States for SS.....	230
14.4.4	States for SDS.....	231
14.5	Procedures	231
14.5.0	General.....	231
14.5.1	Individual CC procedures	232
14.5.1.0	General	232
14.5.1.1	Call set-up procedures.....	232
14.5.1.1.0	General	232

14.5.1.1.1	Incoming call	233
14.5.1.1.2	Outgoing call	235
14.5.1.1.3	Colliding calls.....	236
14.5.1.1.4	Unsuccessful call set-up	236
14.5.1.1.5	Call rejection	237
14.5.1.2	Call maintenance procedures	237
14.5.1.2.0	General	237
14.5.1.2.1	Transmission control procedures.....	238
14.5.1.2.2	Call status information procedures	242
14.5.1.2.3	Call modification procedures.....	243
14.5.1.2.4	Call restoration procedures.....	244
14.5.1.2.5	DTMF procedures	246
14.5.1.2.6	Calls to and from external subscribers.....	248
14.5.1.3	Call disconnection procedures	248
14.5.1.3.0	General	248
14.5.1.3.1	User initiated disconnection	248
14.5.1.3.2	Network initiated disconnection.....	249
14.5.1.3.3	Reception of disconnection request	249
14.5.1.3.4	Expiry of timers	249
14.5.1.3.5	Colliding disconnection.....	250
14.5.1.4	U-Plane switching	250
14.5.1.4.0	General	250
14.5.1.4.1	End of call set-up phase.....	251
14.5.1.4.2	During call maintenance phase.....	251
14.5.1.4.3	Call disconnection phase	252
14.5.2	Group CC procedures	252
14.5.2.0	General	252
14.5.2.1	Call set-up procedures.....	252
14.5.2.1.0	General	252
14.5.2.1.1	Incoming call	254
14.5.2.1.2	Outgoing call	254
14.5.2.1.3	Colliding calls.....	255
14.5.2.1.4	Unsuccessful call set-up	256
14.5.2.1.5	Call rejection	256
14.5.2.2	Call maintenance procedures	256
14.5.2.2.0	General	256
14.5.2.2.1	Transmission control procedures.....	257
14.5.2.2.2	Call status information procedures	261
14.5.2.2.3	Call modification procedures.....	262
14.5.2.2.4	Call restoration procedures.....	263
14.5.2.2.5	DTMF procedures	266
14.5.2.2.6	Temporary address handling procedures.....	266
14.5.2.2.7	Calls to and from external subscribers.....	267
14.5.2.3	Call disconnection procedures	267
14.5.2.3.0	General	267
14.5.2.3.1	User initiated disconnection	268
14.5.2.3.2	Network initiated disconnection.....	269
14.5.2.3.3	Reception of disconnection request	269
14.5.2.3.4	Colliding disconnection.....	269
14.5.2.3.5	Expiry of timers.....	269
14.5.2.4	U-Plane switching	270
14.5.2.4.0	General	270
14.5.2.4.1	End of call set-up phase.....	270
14.5.2.4.2	During call maintenance phase.....	271
14.5.2.4.3	Call disconnection phase	272
14.5.2.5	Void.....	272
14.5.2.6	Acknowledged group call procedures	272
14.5.2.7	Call ownership	273
14.5.3	Traffic channel assignment procedures.....	273
14.5.3.1	SwMI related procedures	273
14.5.3.2	MS related procedures.....	274
14.5.3.2.1	General procedures.....	274

14.5.3.2.2	Procedures for acceptance of individually-addressed channel allocation.....	275
14.5.3.2.3	Procedures for acceptance of group-addressed channel allocation.....	276
14.5.4	SS procedures	277
14.5.5	SDS procedures	277
14.5.5.0	General	277
14.5.5.1	Incoming short data message	277
14.5.5.2	Outgoing short data messages	278
14.5.6	PC procedures.....	278
14.5.6.0	General	278
14.5.6.1	Access to the communication resources.....	278
14.5.6.2	Access priority handling	278
14.5.6.2.0	General	278
14.5.6.2.1	Cancel.....	279
14.5.6.3	CMCE PDU exchange	280
14.5.6.3.0	General	280
14.5.6.3.1	Choice of layer 2 service	280
14.5.6.4	Control information exchange.....	280
14.5.6.5	PC protocol error conditions	280
14.5.6.5.1	PDU type error	280
14.5.6.5.2	Invalid call identifier	281
14.5.6.5.3	MS busy.....	281
14.5.6.6	Temporary Disablement.....	281
14.5.7	Subscriber class	281
14.5.8	Activity handling	282
14.5.9	Not-permitted cells	282
14.6	Protocol timers	282
14.7	PDU descriptions.....	283
14.7.0	General.....	283
14.7.1	PDU description tables - downlink	284
14.7.1.1	D-ALERT.....	284
14.7.1.2	D-CALL PROCEEDING.....	285
14.7.1.3	D-CALL RESTORE.....	285
14.7.1.4	D-CONNECT.....	286
14.7.1.5	D-CONNECT ACKNOWLEDGE.....	286
14.7.1.6	D-DISCONNECT	287
14.7.1.7	D-FACILITY	287
14.7.1.8	D-INFO	288
14.7.1.9	D-RELEASE.....	288
14.7.1.10	D-SDS-DATA.....	289
14.7.1.11	D-STATUS	289
14.7.1.12	D-SETUP	290
14.7.1.13	D-TX CEASED.....	290
14.7.1.14	D-TX CONTINUE.....	291
14.7.1.15	D-TX GRANTED.....	291
14.7.1.16	D-TX INTERRUPT	292
14.7.1.17	D-TX WAIT.....	292
14.7.2	PDU description tables - uplink.....	293
14.7.2.1	U-ALERT.....	293
14.7.2.2	U-CALL RESTORE	293
14.7.2.3	U-CONNECT.....	294
14.7.2.4	U-DISCONNECT	294
14.7.2.5	U-FACILITY	294
14.7.2.6	U-INFO	295
14.7.2.7	U-STATUS	295
14.7.2.8	U-SDS-DATA.....	296
14.7.2.9	U-RELEASE.....	297
14.7.2.10	U-SETUP	297
14.7.2.11	U-TX CEASED.....	298
14.7.2.12	U-TX DEMAND.....	298
14.7.3	PDU description tables - downlink and uplink	298
14.7.3.1	General rules for function not supported.....	298
14.7.3.2	CMCE FUNCTION NOT SUPPORTED	298

14.8	Information elements coding.....	299
14.8.0	General.....	299
14.8.1	Area Selection.....	299
14.8.2	Basic service information	300
14.8.3	Call identifier.....	300
14.8.3a	Call identifier present.....	300
14.8.4	Call ownership.....	300
14.8.5	Called party type identifier	301
14.8.6	Called party SNA.....	301
14.8.7	Called party extension	301
14.8.8	Called party SSI.....	301
14.8.9	Calling party type identifier.....	302
14.8.10	Calling party extension	302
14.8.11	Calling party SSI.....	302
14.8.12	Call priority.....	302
14.8.13	Call status	303
14.8.14	Call queued	303
14.8.15	Continue.....	303
14.8.16	Call time-out	304
14.8.17	Call time-out, set-up phase	304
14.8.17a	Circuit mode type	305
14.8.17b	CLIR control.....	305
14.8.17c	Communication type.....	305
14.8.18	Disconnect cause	306
14.8.18a	DM-MS address	306
14.8.19	DTMF	306
14.8.19a	DTMF digit.....	307
14.8.19b	DTMF type	307
14.8.20	External subscriber number	308
14.8.21	Encryption control	308
14.8.21a	Encryption flag	308
14.8.22	Facility	309
14.8.23	Hook method selection	309
14.8.24	Length indicator.....	309
14.8.25	New call identifier	309
14.8.26	Modify	309
14.8.27	Notification indicator.....	310
14.8.27a	Other party type identifier.....	310
14.8.27b	Other party SNA	310
14.8.27c	Other party extension.....	310
14.8.27d	Other party SSI	310
14.8.28	PDU type	311
14.8.29	Poll request	311
14.8.30	Poll response.....	311
14.8.31	Poll response addresses.....	312
14.8.32	Poll response number.....	312
14.8.33	Poll response percentage.....	312
14.8.34	Pre-coded status	313
14.8.35	Proprietary	313
14.8.36	Request to transmit/send data	313
14.8.37	Reset call time-out timer (T310).....	313
14.8.38	Short data type identifier.....	314
14.8.39	Simplex/duplex selection.....	314
14.8.39a	Slots per frame.....	314
14.8.40	Speech service	314
14.8.41	Temporary address.....	314
14.8.42	Transmission grant.....	315
14.8.43	Transmission request permission.....	315
14.8.44	Transmitting party type identifier	315
14.8.45	Transmitting party extension	315
14.8.46	Transmitting party SSI.....	316
14.8.47	TX demand priority	316