



**Digital cellular telecommunications system (Phase 2+);
Mobile Station (MS) conformance specification;
Part 1: Conformance specification
(3GPP TS 51.010-1 version 12.6.0 Release 12)**

https://standards.iteh.ai/standard/3gpp/51.010-1/v12.6.0-
51b1-4031-a7c9-6e56703f77a1-00000000000000000000000000000000



Reference

RTS/TSGG-0351010-1vc60

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

iTEx STANDARD PREVIEW
<https://standards.iteh.ai/catalog/standards/sist/5p9a2e0-51b1-4031-a7c9-6e56703f725/etsi-ts-151-010-1-v12.6.0>

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 66 |
| 1 Scope | 67 |
| 2 References | 67 |
| 3 Definitions, conventions and applicability | 76 |
| 3.1 Mobile station definition and configurations..... | 76 |
| 3.2 Applicability..... | 77 |
| 3.2.1 Applicability of this specification..... | 77 |
| 3.2.1.1 MS equipped with a connector..... | 77 |
| 3.2.1.2 GPRS..... | 77 |
| 3.2.2 Applicability of the individual tests | 77 |
| 3.2.3 Applicability to terminal equipment | 77 |
| 3.3 Definitions | 77 |
| 3.4 Conventions for mathematical notations | 78 |
| 3.4.1 Mathematical signs | 78 |
| 3.4.2 Powers to the base 10..... | 78 |
| 3.5 Conventions on electrical terms | 78 |
| 3.5.1 Radio Frequency (RF) input signal level..... | 78 |
| 3.5.2 Reference sensitivity level | 79 |
| 3.5.3 Power level of fading signal | 79 |
| 3.6 Terms on test conditions..... | 79 |
| 3.6.1 Radio test conditions..... | 79 |
| 4 Test Equipment | 81 |
| 4.1 Terms used to describe test equipment in the present document..... | 81 |
| 4.2 Functional requirements of test equipment | 81 |
| 5 Testing methodology in general (layers 1, 2, and 3) | 81 |
| 5.1 Testing of optional functions and procedures..... | 81 |
| 5.2 Test interfaces and facilities | 81 |
| 5.3 Different protocol layers | 82 |
| 5.4 Information to be provided by the apparatus supplier | 82 |
| 5.5 Definitions of transmit and receive times..... | 82 |
| 6 Reference test methods..... | 82 |
| 6.1 General | 82 |
| 6.2 Choice of frequencies in the frequency hopping mode | 83 |
| 6.3 "Ideal" radio conditions..... | 84 |
| 6.4 Standard test signals | 84 |
| 6.5 Power (control) levels | 84 |
| 7 Implicit testing..... | 84 |
| 8 Measurement uncertainty | 84 |
| 9 Format of tests | 84 |
| 10 Generic call set up procedures..... | 87 |
| 10.1 Generic call set-up procedure for mobile terminating speech calls..... | 87 |
| 10.1.1 Initial conditions | 87 |
| 10.1.2 Definition of system information messages | 87 |
| 10.1.3 Procedure | 89 |
| 10.1.4 Specific message contents | 90 |
| 10.1a Generic call set-up procedure for mobile terminating signalling only connection..... | 91 |
| 10.1a.1 Initial conditions | 91 |

| | | |
|----------|---|-----|
| 10.1a.2 | Definition of system information messages | 92 |
| 10.1a.3 | Procedure | 92 |
| 10.1a.4 | Specific message contents | 92 |
| 10.2 | Generic call set-up procedure for mobile originating speech calls | 93 |
| 10.2.1 | Initial conditions | 93 |
| 10.2.2 | Definition of system information messages | 93 |
| 10.2.3 | Procedure | 93 |
| 10.2.4 | Specific message contents | 94 |
| 10.2a | Generic call set-up procedure for mobile originating signalling only connection | 95 |
| 10.2a.1 | Initial conditions | 95 |
| 10.2a.2 | Definition of system information messages | 95 |
| 10.2a.3 | Procedure | 95 |
| 10.2a.4 | Specific message contents | 96 |
| 10.3 | Generic call set-up procedure for mobile terminating data calls | 96 |
| 10.3.1 | Initial conditions | 96 |
| 10.3.2 | Definition of system information messages | 97 |
| 10.3.3 | Procedure | 97 |
| 10.3.4 | Specific message contents | 97 |
| 10.4 | Generic call set-up procedure for mobile originating data calls | 99 |
| 10.4.1 | Initial conditions | 99 |
| 10.4.2 | Definition of system information messages | 99 |
| 10.4.3 | Procedure | 99 |
| 10.4.4 | Specific message contents | 100 |
| 10.5 | Generic call set-up procedure for mobile terminating multislot configuration, minimum number of timeslots allocated | 102 |
| 10.5.1 | Initial conditions | 102 |
| 10.5.2 | Definition of system information messages | 102 |
| 10.5.3 | Procedure | 102 |
| 10.5.4 | Specific message contents | 103 |
| 10.6 | Generic call set-up procedure for mobile originating multislot configuration, minimum number of timeslots allocated | 105 |
| 10.6.1 | Initial conditions | 105 |
| 10.6.2 | Definition of system information messages | 105 |
| 10.6.3 | Procedure | 106 |
| 10.6.4 | Specific message contents | 106 |
| 10.7 | Generic procedure for GPRS downlink data transfer | 108 |
| 10.7.1 | Initial conditions | 108 |
| 10.7.2 | Definition of system information messages | 108 |
| 10.7.3 | Procedure | 108 |
| 10.7.4 | Specific message contents | 109 |
| 10.8 | Generic procedure for GPRS uplink data transfer | 109 |
| 10.8.1 | Initial conditions | 109 |
| 10.8.2 | Definition of system information messages | 109 |
| 10.8.3 | Procedure | 109 |
| 10.8.4 | Specific message contents | 110 |
| 10.9 | Void..... | 112 |
| 10.10 | Void..... | 112 |
| 11 | General tests | 112 |
| 11.1 | Verification of support and non-support of services (multiple numbering scheme or ISDN) | 112 |
| 11.1.1 | Mobile Terminated (MT) calls..... | 112 |
| 11.1.2 | Mobile Originated (MO) calls | 113 |
| 11.2 | Verification of support of the single numbering scheme | 114 |
| 11.3 | Verification of non-support of services (Advice of Charge Charging (AoCC))..... | 115 |
| 11.4 | Verification of non-support of services (call hold)..... | 116 |
| 11.5 | Verification of non-support of services (multiparty) | 117 |
| 11.6 | Verification of non-support of feature (Fixed Dialling Number (FDN)) | 118 |
| 11.7 | IMEI Security | 119 |
| 11.7.4 | Declaration..... | 119 |
| 11.8 | Coding of the Bearer Capability information element..... | 119 |
| 11.8.1 | Network to MS Direction | 120 |
| 11.8.1.1 | BS 21 to 26 - Asynchronous Service | 120 |

| | | |
|------------|--|-----|
| 11.8.1.1.1 | BS 21 | 120 |
| 11.8.1.1.2 | BS 22 | 123 |
| 11.8.1.1.3 | BS 24 | 124 |
| 11.8.1.1.4 | BS 25 | 124 |
| 11.8.1.1.5 | BS 26 | 124 |
| 11.8.1.1.6 | BS 23 | 124 |
| 11.8.1.2 | BS 31 to 34 - Synchronous Service..... | 125 |
| 11.8.1.2.1 | BS 32 | 125 |
| 11.8.1.2.2 | BS 31 | 129 |
| 11.8.1.2.3 | BS 33 | 129 |
| 11.8.1.2.4 | BS 34 | 130 |
| 11.8.1.3 | BS 61 - Alternate Speech / Data..... | 130 |
| 11.8.1.3.1 | Speech/Asynchronous Data, Transparent | 130 |
| 11.8.1.3.2 | Speech/Asynchronous Data, Non Transparent | 132 |
| 11.8.1.3.3 | Speech/Synchronous Data | 133 |
| 11.8.1.4 | BS 81 - Speech followed by Data | 134 |
| 11.8.1.4.1 | Speech followed by Asynchronous Data | 134 |
| 11.8.1.4.2 | Speech followed by Synchronous Data | 134 |
| 11.8.1.5 | TS 61 - Alternate Speech / Facsimile group 3..... | 134 |
| 11.8.1.5.1 | TS 61 - Alternate Speech / Facsimile group 3, Transparent | 135 |
| 11.8.1.5.2 | TS 61 - Alternate Speech / Facsimile group 3, Non-Transparent | 136 |
| 11.8.1.6 | TS 62 - Automatic Facsimile group 3 | 137 |
| 11.8.2 | MS to SS direction..... | 137 |
| 11.8.2.1 | BS 21 to 26 - Asynchronous Service | 137 |
| 11.8.2.1.1 | BS 21 | 138 |
| 11.8.2.1.2 | BS 22 | 141 |
| 11.8.2.1.3 | BS 24 | 142 |
| 11.8.2.1.4 | BS 25 | 142 |
| 11.8.2.1.5 | BS 26 | 142 |
| 11.8.2.1.6 | BS 23 | 142 |
| 11.8.2.2 | BS 31 to 34 - Synchronous Service..... | 143 |
| 11.8.2.2.1 | BS 32 | 143 |
| 11.8.2.2.2 | BS 31 | 147 |
| 11.8.2.2.3 | BS 33 | 147 |
| 11.8.2.2.4 | BS 34 | 148 |
| 11.8.2.3 | BS 41 to 46 - PAD Access Asynchronous | 148 |
| 11.8.2.3.1 | ²⁾ BS 41 | 148 |
| 11.8.2.3.2 | BS 42 | 149 |
| 11.8.2.3.3 | BS 44 | 150 |
| 11.8.2.3.4 | BS 45 | 150 |
| 11.8.2.3.5 | BS 46 | 150 |
| 11.8.2.3.6 | BS 43 | 150 |
| 11.8.2.4 | BS 51 to 53 - Packet Service Synchronous | 151 |
| 11.8.2.4.1 | 2) BS 51 | 151 |
| 11.8.2.4.2 | BS 52 | 151 |
| 11.8.2.4.3 | BS 53 | 151 |
| 11.8.2.5 | BS 61 - Alternate Speech / Data..... | 151 |
| 11.8.2.5.1 | Speech/Asynchronous Data, Transparent | 152 |
| 11.8.2.5.2 | Speech/Asynchronous Data, Non Transparent | 154 |
| 11.8.2.5.3 | Speech/Synchronous Data | 155 |
| 11.8.2.6 | BS 81 - Speech followed by Data | 157 |
| 11.8.2.6.1 | Speech followed by Asynchronous Data | 157 |
| 11.8.2.6.2 | Speech followed by Synchronous Data | 157 |
| 11.8.2.7 | TS 61 - Alternate Speech / Facsimile group 3..... | 157 |
| 11.8.2.7.1 | TS 61 - Alternate Speech / Facsimile group 3, Transparent | 158 |
| 11.8.2.7.2 | TS 61 - Alternate Speech / Facsimile group 3, Non Transparent | 159 |
| 11.8.2.8 | TS 62 - Automatic Facsimile group 3 | 159 |
| 11.8.2.9 | TS 11 and TS 12 - Speech..... | 160 |
| 11.8.2.9.1 | Support of only full/half rate speech version 1 | 160 |
| 11.8.2.9.2 | Support of speech full rate version 2 (Enhanced Full Rate) | 160 |
| 11.8.2.9.3 | Support of full rate speech version 2 (EFR) and full and/or half rate speech version 3 (AMR)...161 | |

| | | |
|--------|--|-----|
| 12 | Transceiver | 165 |
| 12.1 | Conducted spurious emissions | 165 |
| 12.1.1 | MS allocated a channel | 165 |
| 12.1.2 | MS in idle mode | 168 |
| 12.2 | Radiated spurious emissions | 170 |
| 12.2.1 | MS allocated a channel | 170 |
| 12.2.2 | MS in idle mode | 172 |
| 12.3 | Conducted spurious emissions for MS supporting the R-GSM or ER-GSM frequency band | 174 |
| 12.3.1 | MS allocated a channel | 174 |
| 12.3.2 | MS in idle mode | 176 |
| 12.4 | Radiated spurious emissions for MS supporting the R-GSM or ER-GSM frequency band | 177 |
| 12.4.1 | MS allocated a channel | 178 |
| 12.4.2 | MS in idle mode | 179 |
| 13 | Transmitter | 181 |
| 13.1 | Frequency error and phase error | 181 |
| 13.1.1 | Definition | 181 |
| 13.1.2 | Conformance requirement | 181 |
| 13.1.3 | Test purpose | 182 |
| 13.1.4 | Method of test | 182 |
| 13.1.5 | Test requirements | 184 |
| 13.1a | Frequency error in VAMOS configuration | 184 |
| 13.1b | Frequency error and phase error in TIGHTER configuration \ with legacy TSC in VAMOS mode | 186 |
| 13.2b | Frequency error under multipath and interference conditions in TIGHTER configuration \ with legacy TSC in VAMOS mode | 187 |
| 13.2 | Frequency error under multipath and interference conditions | 189 |
| 13.2.1 | Definition | 189 |
| 13.2.2 | Conformance requirement | 189 |
| 13.2.3 | Test purpose | 189 |
| 13.2.4 | Method of test | 190 |
| 13.2.5 | Test requirements | 191 |
| 13.2a | Frequency error under multipath and interference conditions in VAMOS configuration | 191 |
| 13.3 | Transmitter output power and burst timing | 193 |
| 13.3.1 | Definition | 193 |
| 13.3.2 | Conformance requirement | 194 |
| 13.3.3 | Test purpose | 195 |
| 13.3.4 | Methods of test | 196 |
| 13.3.5 | Test requirements | 199 |
| 13.4 | Output RF spectrum | 203 |
| 13.4.1 | Definition | 203 |
| 13.4.2 | Conformance requirement | 203 |
| 13.4.3 | Test purpose | 204 |
| 13.4.4 | Method of test | 204 |
| 13.4.5 | Test requirements | 206 |
| 13.5 | Void | 210 |
| 13.6 | Frequency error and phase error in HSCSD multislot configurations | 210 |
| 13.6.1 | Definition | 210 |
| 13.6.2 | Conformance requirement | 210 |
| 13.6.3 | Test purpose | 211 |
| 13.6.4 | Method of test | 211 |
| 13.6.5 | Test requirements | 213 |
| 13.7 | Transmitter output power and burst timing in HSCSD configurations | 213 |
| 13.7.1 | Definition | 213 |
| 13.7.2 | Conformance requirement | 213 |
| 13.7.3 | Test purpose | 215 |
| 13.7.4 | Methods of test | 216 |
| 13.7.5 | Test requirements | 219 |
| 13.8 | Output RF spectrum in HSCSD multislot configuration | 225 |
| 13.8.1 | Definition | 225 |
| 13.8.2 | Conformance requirement | 225 |
| 13.8.3 | Test purpose | 226 |
| 13.8.4 | Method of test | 226 |

| | | |
|--------------------|---|-----|
| 13.8.5 | Test requirements..... | 228 |
| 13.9 | Output RF spectrum for MS supporting the R-GSM or ER-GSM frequency band..... | 232 |
| 13.9.1 | Definition..... | 232 |
| 13.9.2 | Conformance requirement | 232 |
| 13.9.3 | Test purpose..... | 232 |
| 13.9.4 | Method of test | 233 |
| 13.9.5 | Test requirements..... | 235 |
| 13.10 | Void..... | 237 |
| 13.11 | Void..... | 237 |
| 13.12 | Void..... | 237 |
| 13.13 | Void..... | 237 |
| 13.14 | Void..... | 237 |
| 13.15 | Void..... | 237 |
| 13.16 | GPRS transmitter tests..... | 237 |
| 13.16.1 | Frequency error and phase error in GPRS multislot configuration..... | 237 |
| 13.16.2 | Transmitter output power in GPRS multislot configuration | 240 |
| 13.16.3 | Output RF spectrum in GPRS multislot configuration | 253 |
| 13.17 | EGPRS transmitter tests | 260 |
| 13.17.1 | Frequency error and Modulation accuracy in EGPRS Configuration..... | 260 |
| 13.17.1a | Frequency error and Modulation accuracy in EGPRS2A Configuration..... | 264 |
| 13.17.2 | Frequency error under multipath and interference conditions | 268 |
| 13.17.2a | Frequency error under multipath and interference conditions for EGPRS2A configuration | 270 |
| 13.17.3 | EGPRS Transmitter output power | 273 |
| 13.17.3a | Transmitter output power in EGPRS2A configuration | 282 |
| 13.17.4 | Output RF spectrum in EGPRS configuration | 292 |
| 13.17.4a | Output RF spectrum in EGPRS2A configuration | 298 |
| 13.17.5 | Void | 309 |
| 14 | Receiver..... | 310 |
| 14.1 | Bad frame indication | 316 |
| 14.1.1 | Bad frame indication - TCH/FS | 316 |
| 14.1.2 | Bad frame indication - TCH/HS | 318 |
| 14.1.3 | Void | 320 |
| 14.1.4 | Void | 320 |
| 14.1.5 | Bad frame indication - TCH/AFS (Speech frame)..... | 320 |
| 14.1.6 | Bad frame indication - TCH/AHS | 322 |
| 14.1.6.1 | Bad frame indication - TCH/AHS - Random RF input | 322 |
| 14.1.7 | Void | 323 |
| 14.2 | Reference sensitivity | 323 |
| 14.2.1 | Reference sensitivity - TCH/FS | 323 |
| 14.2.1a | Reference sensitivity - TCH/FS in TIGHTER configuration..... | 325 |
| 14.2.2 | Reference sensitivity - TCH/HS (Speech frames) | 327 |
| 14.2.2a | Reference sensitivity - TCH/HS in TIGHTER configuration..... | 329 |
| 14.2.3 | Reference sensitivity - FACCH/F..... | 331 |
| 14.2.3a | Reference sensitivity - FACCH/F in TIGHTER configuration | 332 |
| 14.2.4 | Reference sensitivity - FACCH/H | 333 |
| 14.2.4a | Reference sensitivity - FACCH/H in TIGHTER configuration..... | 334 |
| 14.2.5 | Reference sensitivity - full rate data channels..... | 335 |
| 14.2.6 | Reference sensitivity - half rate data channels | 336 |
| 14.2.7 | Reference sensitivity - TCH/EFS..... | 337 |
| 14.2.7a | Reference sensitivity - TCH/EFS in TIGHTER configuration | 339 |
| 14.2.8 | Reference sensitivity - full rate data channels in multislot configuration | 341 |
| 14.2.9 | Reference sensitivity - TCH/FS for MS supporting the R-GSM or ER-GSM band | 342 |
| 14.2.10 | Reference sensitivity - TCH/AFS | 344 |
| 14.2.10a | Reference sensitivity - TCH/AFS in TIGHTER configuration..... | 347 |
| 14.2.11 to 14.2.17 | Void..... | 350 |
| 14.2.18 | Reference sensitivity - TCH/AHS | 350 |
| 14.2.18a | Reference sensitivity - TCH/AHS in TIGHTER configuration | 357 |
| 14.2.19 | Reference sensitivity - TCH/AFS-INB | 362 |
| 14.2.20 | Reference sensitivity - TCH/AHS-INB | 364 |
| 14.2.21 | Reference sensitivity – O-TCH/AHS..... | 365 |
| 14.2.22 | Reference sensitivity – O-TCH/WFS | 368 |

| | | |
|--------------------|--|-----|
| 14.2.23 | Reference sensitivity – O-TCH/WHS | 370 |
| 14.2.24 | Reference sensitivity - TCH/WFS | 373 |
| 14.2.24a | Reference sensitivity - TCH/WFS in TIGHTER configuration..... | 377 |
| 14.2.25 | Reference sensitivity – Repeated FACCH/F | 382 |
| 14.2.26 | Reference sensitivity – Repeated SACCH..... | 385 |
| 14.2.27 | Reference sensitivity - TCH/FS – DARP Phase II..... | 387 |
| 14.2.28 | Reference sensitivity TCH/HS in VAMOS configuration..... | 390 |
| 14.2.29 | Reference sensitivity TCH/EFS in VAMOS configuration | 395 |
| 14.2.30 | Reference sensitivity TCH/AFS in VAMOS configuration..... | 401 |
| 14.2.31 | Reference sensitivity TCH/AHS in VAMOS configuration | 407 |
| 14.2.32 | Reference sensitivity TCH/WFS in VAMOS configuration..... | 416 |
| 14.2.33 | Reference sensitivity FACCH/F performance in VAMOS configuration | 425 |
| 14.2.34 | Reference sensitivity – FACCH/H Performance in VAMOS configuration..... | 428 |
| 14.2.35 | Reference sensitivity SACCH performance in VAMOS configuration..... | 431 |
| 14.2.36 | Reference sensitivity – Repeated SACCH in VAMOS configuration | 435 |
| 14.2.37 | Reference sensitivity – Repeated FACCH/F in VAMOS configuration..... | 438 |
| 14.3 | Usable receiver input level range | 441 |
| 14.4 | Co-channel rejection..... | 442 |
| 14.4.1 | Co-channel rejection - TCH/FS | 442 |
| 14.4.1a | Co-channel rejection - TCH/FS in TIGHTER configuration..... | 444 |
| 14.4.2 | Co-channel rejection - TCH/HS..... | 445 |
| 14.4.2a | Co-channel rejection - TCH/HS in TIGHTER configuration | 447 |
| 14.4.3 | Void | 449 |
| 14.4.4 | Co-channel rejection - FACCH/F | 449 |
| 14.4.4a | Co-channel rejection - FACCH/F in TIGHTER configuration..... | 450 |
| 14.4.5 | Co-channel rejection - FACCH/H | 451 |
| 14.4.5a | Co-channel rejection - FACCH/H in TIGHTER configuration..... | 452 |
| 14.4.6 | Co-channel rejection - TCH/EFS | 453 |
| 14.4.6a | Co-channel rejection - TCH/EFS in TIGHTER configuration | 454 |
| 14.4.7 | Receiver performance in the case of frequency hopping and co-channel interference on one carrier | 456 |
| 14.4.8 | Co-channel rejection - TCH/AFS | 457 |
| 14.4.8a | Co-channel rejection - TCH/AFS in TIGHTER configuration | 462 |
| 14.4.9 to 14.4.15 | Void..... | 464 |
| 14.4.16 | Co-channel rejection - TCH/AHS | 464 |
| 14.4.16a | Co-channel rejection - TCH/AHS in TIGHTER configuration | 470 |
| 14.4.17 | Co-channel rejection - TCH/AFS-INB | 474 |
| 14.4.18 | Co-channel rejection - TCH/AHS-INB | 476 |
| 14.4.19 | Co-channel rejection - O-TCH/AHS | 478 |
| 14.4.20 | Co-channel rejection – O-TCH/AHS-INB..... | 481 |
| 14.4.21 | Co-channel rejection – O-FACCH/H..... | 483 |
| 14.4.22 to 14.4.23 | Void..... | 485 |
| 14.4.24 | Co-channel interference - O-TCH/WFS | 485 |
| 14.4.25 | Co-channel interference – O-TCH/WHS | 488 |
| 14.4.26 | Co-channel rejection - O-TCH/WFS-INB | 491 |
| 14.4.27 | Void | 493 |
| 14.4.28 | Co-channel rejection - TCH/WFS | 493 |
| 14.4.28a | Co-channel rejection - TCH/WFS in TIGHTER configuration | 498 |
| 14.4.29 | Co-channel interference - TCH/WFS-INB | 501 |
| 14.4.30 | Co-channel interference - O-FACCH/F..... | 503 |
| 14.4.31 | Co-channel rejection – Repeated FACCH/F..... | 505 |
| 14.4.32 | Co-channel rejection – Repeated SACCH | 508 |
| 14.5 | Adjacent channel rejection | 511 |
| 14.5.1 | Adjacent channel rejection - speech channels..... | 511 |
| 14.5.1.1 | TCH/FS | 511 |
| 14.5.1.1a | Adjacent Channel Interference - TCH/FS in TIGHTER configuration..... | 514 |
| 14.5.1.2 | TCH/AFS | 516 |
| 14.5.1.2a | Adjacent channel rejection - TCH/AFS in TIGHTER configuration | 521 |
| 14.5.1.3 | TCH/AHS | 525 |
| 14.5.1.3a | Adjacent channel rejection - TCH/AHS in TIGHTER configuration | 529 |
| 14.5.1.4 | O-TCH/AHS | 533 |
| 14.5.1.5 | O-TCH/WFS | 536 |
| 14.5.1.6 | Adjacent channel interference O-TCH/WHS | 540 |

| | | |
|------------|--|-----|
| 14.5.1.7 | TCH/WFS Adjacent Channel Interference..... | 543 |
| 14.5.1.7a | Adjacent Channel Interference - TCH/WFS in TIGHTER configuration..... | 547 |
| 14.5.2 | Adjacent channel rejection - control channels | 550 |
| 14.6 | Intermodulation rejection | 553 |
| 14.6.1 | Intermodulation rejection - speech channels..... | 553 |
| 14.6.2 | Intermodulation rejection - control channels | 554 |
| 14.7 | Blocking and spurious response | 556 |
| 14.7.1 | Blocking and spurious response - speech channels..... | 556 |
| 14.7.2 | Blocking and spurious response - control channels | 562 |
| 14.7.3 | Blocking and spurious response - speech channels for MS supporting the R-GSM or ER-GSM 900 band | 567 |
| 14.7.4 | Blocking and spurious response - control channels for MS supporting the R-GSM or ER-GSM 900 band | 570 |
| 14.8 | AM suppression..... | 573 |
| 14.8.1 | AM suppression - speech channels..... | 573 |
| 14.8.2 | AM suppression - control channels..... | 574 |
| 14.8.3 | AM suppression - packet channels | 576 |
| 14.9 | Paging performance at high input levels | 578 |
| 14.10 | Performance of the Codec Mode Request Generation for Adaptive Multi-Rate Codecs | 579 |
| 14.10.1 | Performance of the Codec Mode Request Generation – TCH/AFS..... | 579 |
| 14.10.2 | Performance of the Codec Mode Request Generation – TCH/AHS | 585 |
| 14.10.3 | Performance of the Codec Mode Request Generation – TCH/AFS - improved RX..... | 591 |
| 14.10.4 | Performance of the Codec Mode Request Generation – TCH/AHS – improved RX | 599 |
| 14.10.5 | Performance of the Codec Mode Request Generation – O-TCH/AHS | 607 |
| 14.10.6 | Performance of the Codec Mode Request Generation – O-TCH/WFS..... | 613 |
| 14.10.7 | Performance of the Codec Mode Request Generation – O-TCH/WHS | 619 |
| 14.10.8 | Performance of the Codec Mode Request Generation – TCH/WFS | 624 |
| 14.10.9 | Performance of the Codec Mode Request Generation – TCH/WFS - improved RX..... | 630 |
| 14.11 | DARP Phase 1 Speech bearer tests..... | 638 |
| 14.11.1 | TCH/FS..... | 638 |
| 14.11.1.1 | DTS-1..... | 638 |
| 14.11.1.1a | DARP Phase 1 Speech bearer test TCH/FS DTS-1 in TIGHTER configuration | 641 |
| 14.11.2 | TCH/AFS..... | 643 |
| 14.11.2.1 | DTS-1..... | 643 |
| 14.11.2.1a | DARP Phase 1 Speech bearer test TCH/AFS DTS-1 in TIGHTER configuration | 647 |
| 14.11.2.2 | DTS-4..... | 650 |
| 14.11.2.2a | DARP Phase 1 Speech bearer test TCH-AFS DTS-4 in TIGHTER configuration | 653 |
| 14.11.2.3 | DTS-2/3/5 | 655 |
| 14.11.2.3a | DARP Phase 1 Speech bearer test TCH/AFS DTS-2/3/5 in TIGHTER configuration | 659 |
| 14.11.3 | TCH/AHS | 662 |
| 14.11.3.1 | DTS-1..... | 662 |
| 14.11.3.1a | DARP Phase 1 Speech bearer test TCH/AHS DTS-1 in TIGHTER configuration..... | 666 |
| 14.11.3.2 | Void..... | 669 |
| 14.11.3.3 | DTS-2/3..... | 669 |
| 14.11.3.3a | DARP Phase 1 Speech bearer test - TCH-AHS / DTS-2/3 in TIGHTER configuration | 673 |
| 14.12 | DARP Phase 1 Signalling bearer tests..... | 676 |
| 14.12.1 | FACCH/F..... | 676 |
| 14.12.1.1 | FACCH – DTS-1 | 676 |
| 14.12.1.2 | FACCH – DTS-2-3 | 680 |
| 14.12.1.2a | DARP Phase 1 Signalling bearer test - FACCH – DTS-2-3 in TIGHTER configuration | 683 |
| 14.13 | Void..... | 686 |
| 14.14 | Void..... | 686 |
| 14.15 | Void..... | 686 |
| 14.16 | GPRS receiver tests | 686 |
| 14.16.1 | Minimum Input level for Reference Performance | 688 |
| 14.16.1a | Minimum Input level for Reference Performance in TIGHTER configuration | 691 |
| 14.16.2 | Co-channel rejection | 696 |
| 14.16.2.1 | Co-channel rejection for packet channels | 696 |
| 14.16.2.1a | Co-channel rejection for packet channels – TIGHTER configuration | 698 |
| 14.16.3 | Acknowledged mode / Downlink TBF / I_LEVEL measurement report..... | 701 |
| 14.16.3.1 | Conformance requirements | 701 |
| 14.16.3.2 | References | 701 |

| | | |
|------------|---|-----|
| 14.16.3.3 | Test purpose | 701 |
| 14.16.3.4 | Method of test | 702 |
| 14.16.3.5 | Initial Conditions..... | 702 |
| 14.16.3.6 | Void..... | 702 |
| 14.16.3.7 | Test Procedure..... | 702 |
| 14.16.4 | DARP Phase 1 GPRS tests | 703 |
| 14.16.4.1 | Synchronous single co-channel interferer (DTS-1)..... | 703 |
| 14.16.4.1a | Synchronous single co-channel interferer (DTS-1) in TIGHTER configuration | 705 |
| 14.16.4.2 | Synchronous multiple interferers (DTS-2 / DTS-3)..... | 707 |
| 14.16.4.2a | Synchronous multiple interferers (DTS-2 / DTS-3) in TIGHTER configuration | 710 |
| 14.16.5 | DARP Phase II GPRS tests..... | 712 |
| 14.16.5.1 | Synchronous single co-channel interferer (DTS-1)..... | 712 |
| 14.16.5.2 | Multiple interferers (DTS-2 / DTS-5) | 714 |
| 14.17 | | 717 |
| 14.18 | EGPRS receiver tests..... | 717 |
| 14.18.1 | Minimum Input level for Reference Performance | 720 |
| 14.18.1a | Minimum Input level for Reference Performance in EGPRS2A Configuration..... | 725 |
| 14.18.1b | Minimum Input level for Reference Performance in TIGHTER configuration | 731 |
| 14.18.1c | Minimum Input level for Reference Performance – in TIGHTER configuration..... | 737 |
| 14.18.2 | Co-channel rejection | 743 |
| 14.18.2a | Co-channel rejection in EGPRS2A | 747 |
| 14.18.2b | Co-channel rejection – in TIGHTER configuration..... | 752 |
| 14.18.2c | Co-channel rejection in EGPRS2A with TIGHTER configuration | 755 |
| 14.18.3 | Adjacent channel rejection..... | 761 |
| 14.18.3a | Adjacent channel rejection in EGPRS2A configuration | 766 |
| 14.18.3b | Adjacent channel rejection for packet channels in TIGHTER configuration | 773 |
| 14.18.3c | Adjacent channel rejection in EGPRS2A configuration with TIGHTER configuration..... | 779 |
| 14.18.3d | Adjacent channel rejection in DLMC configuration..... | 787 |
| 14.18.4 | Intermodulation rejection..... | 791 |
| 14.18.4a | Intermodulation rejection in EGPRS2A configuration | 794 |
| 14.18.5 | Blocking and spurious response..... | 798 |
| 14.18.5a | Blocking and spurious response in EGPRS2A configuration | 807 |
| 14.18.5b | Blocking and spurious response in DLMC configuration..... | 818 |
| 14.18.6 | EGPRS Usable receiver input level range | 824 |
| 14.18.6a | EGPRS Usable receiver input level range in EGPRS2A Configuration..... | 826 |
| 14.18.7 | Incremental Redundancy Performance | 828 |
| 14.18.7a | Incremental Redundancy Performance in EGPRS2A configuration | 829 |
| 14.18.8 | DARP Phase 1 EGPRS tests | 831 |
| 14.18.8.1 | Synchronous single co-channel interferer (DTS-1)..... | 831 |
| 14.18.8.1a | Synchronous single co-channel interferer (DTS-1) in TIGHTER configuration | 833 |
| 14.18.8.2 | Synchronous single co-channel interferer (DTS-2 / DTS-3)..... | 835 |
| 14.18.8.2a | Synchronous single co-channel interferer (DTS-2 / DTS-3) in TIGHTER configuration | 837 |
| 14.18.9 | DARP Phase II EGPRS tests | 840 |
| 14.18.9.1 | Synchronous single co-channel interferer (DTS-1)..... | 840 |
| 14.18.9.2 | Synchronous single co-channel interferer (DTS-1b)..... | 842 |
| 14.18.9.3 | Multiple interferers (DTS-2 / DTS-5) | 844 |
| 14.18.10 | Latency Reductions..... | 847 |
| 14.18.10.1 | Minimum Input level for Reference Performance for PAN | 847 |
| 14.19 | DARP Phase II Speech bearer tests..... | 850 |
| 14.19.1 | TCH/FS..... | 850 |
| 14.19.2 | TCH/AFS..... | 853 |
| 14.19.3 | TCH/AHS | 860 |
| 14.20 | VAMOS speech bearer tests..... | 866 |
| 14.20.1 | TCH HS – VDTS-1,VDTS-2/3 and VDTS-4 | 866 |
| 14.20.2 | TCH EFS – VDTS-1, VDTS-2/3 and VDTS-4..... | 879 |
| 14.20.3 | TCH AFS – VDTS-1, VDTS-2/3 and VDTS-4 | 892 |
| 14.20.4 | TCH AHS – VDTS-1,VDTS-2/3 and VDTS-4 | 910 |
| 14.20.5 | TCH WFS – VDTS-1, VDTS-2/3 and VDTS-4 | 926 |
| 14.20.6 | FACCH/F – VDTS-1 | 941 |
| 14.20.7 | FACCH/H – VDTS-1 | 944 |
| 14.20.8 | SACCH – VDTS-1 | 947 |
| 14.20.9 | Repeated FACCH/F – VDTS-1 | 951 |

| | | |
|----------|--|------|
| 14.20.10 | Repeated SACCH – VDTS-1..... | 954 |
| 14.20.11 | Downlink DTX TCH / AHS in VAMOS configuration | 957 |
| 15 | Timing advance and absolute delay | 960 |
| 15.1 | GSM Timing advance and absolute delay..... | 960 |
| 15.2 | Void..... | 961 |
| 15.3 | Void..... | 961 |
| 15.4 | Void..... | 961 |
| 15.5 | Void..... | 961 |
| 15.6 | GPRS Timing advance and absolute delay..... | 961 |
| 15.7 | ECSD Timing advance and absolute delay | 965 |
| 15.8 | EGPRS timing advance and absolute delay | 966 |
| 15.9 | Timing Advance whilst in DTM | 970 |
| 16 | Reception time tracking speed | 972 |
| 17 | Access times during handover..... | 974 |
| 17.1 | Intra cell channel change | 974 |
| 17.2 | Inter cell handover..... | 977 |
| 18 | Temporary reception gaps | 980 |
| 18.1 | Temporary reception gaps, single slot..... | 980 |
| 18.2 | Temporary reception gaps in HSCSD multislot configurations | 981 |
| 19 | Channel release after unrecoverable errors | 982 |
| 19.1 | Channel release after unrecoverable errors - 1 | 983 |
| 19.2 | Channel release after unrecoverable errors - 2 | 984 |
| 19.3 | Channel release after unrecoverable errors - 3 | 985 |
| 20 | Cell selection and reselection | 986 |
| 20.1 | Cell selection | 988 |
| 20.2 | Cell selection with varying signal strength values | 989 |
| 20.3 | Basic cell reselection | 991 |
| 20.4 | Cell reselection using TEMPORARY_OFFSET, CELL_RESELECT_OFFSET, POWER_OFFSET and PENALTY_TIME parameters..... | 994 |
| 20.5 | Cell reselection using parameters transmitted in the System Information type 2bis, type 2ter, type 7 and type 8 messages..... | 995 |
| 20.6 | Cell reselection timings | 997 |
| 20.7 | Priority of cells | 998 |
| 20.8 | Cell reselection when C1 (serving cell) < 0 for 5 s | 1000 |
| 20.9 | Running average of the surrounding cell BCCH carrier signal levels..... | 1001 |
| 20.10 | Running average of the serving cell BCCH carrier signal level | 1002 |
| 20.11 | Updating the list of six strongest neighbour carriers and decoding the BCCH information of a new carrier on the list..... | 1003 |
| 20.12 | Decoding the BCCH information of the neighbour carriers on the list of six strongest neighbour carriers | 1004 |
| 20.13 | Decoding the BSIC of the neighbour carriers on the list of six strongest neighbour carriers | 1005 |
| 20.14 | Emergency calls | 1006 |
| 20.15 | Cell reselection due to MS rejection "LA not allowed" | 1007 |
| 20.16 | Downlink signalling failure | 1008 |
| 20.17 | Cell selection if no suitable cell found in 10 s..... | 1010 |
| 20.18 | Cell reselection due to MS rejection "Roaming not allowed in this LA" | 1010 |
| 20.19 | Cell selection on release of SDCCH and TCH | 1012 |
| 20.20 | Multiband cell selection and reselection | 1013 |
| 20.20.1 | Multiband cell selection and reselection / Cell Selection | 1013 |
| 20.20.2 | Multiband cell selection and reselection / Cell reselection | 1015 |
| 20.21 | R-GSM or ER-GSM cell selection and reselection | 1017 |
| 20.21.1 | R-GSM or ER-GSM cell selection | 1018 |
| 20.21.2 | R-GSM or ER-GSM cell selection with varying signal strength values | 1020 |
| 20.21.3 | R-GSM or ER-GSM basic cell reselection | 1022 |
| 20.21.4 | R-GSM or ER-GSM cell reselection using TEMPORARY_OFFSET, CELL_RESELECT_OFFSET, POWER_OFFSET and PENALTY_TIME parameters | 1024 |
| 20.21.5 | R-GSM or ER-GSM cell reselection using parameters transmitted in the System Information type 2bis, type 2ter, type 7 and type 8 messages | 1025 |
| 20.21.6 | R-GSM or ER-GSM cell reselection timings | 1027 |

| | | |
|------------|--|------|
| 20.21.7 | R-GSM or ER-GSM priority of cells | 1028 |
| 20.21.8 | R-GSM or ER-GSM cell reselection when C1 (serving cell) < 0 for 5 s..... | 1030 |
| 20.21.9 | R-GSM or ER-GSM running average of the surrounding cell BCCH carrier signal levels..... | 1031 |
| 20.21.10 | R-GSM or ER-GSM running average of the serving cell BCCH carrier signal level..... | 1032 |
| 20.21.11 | R-GSM or ER-GSM Updating the list of six strongest neighbour carriers and decoding the BCCH information of a new carrier on the list..... | 1033 |
| 20.21.12 | R-GSM or ER-GSM decoding the BCCH information of the neighbour carriers on the list of six strongest neighbour carriers..... | 1034 |
| 20.21.13 | R-GSM or ER-GSM decoding the BSIC of the neighbour carriers on the list of six strongest neighbour carriers | 1035 |
| 20.21.14 | R-GSM or ER-GSM emergency calls..... | 1036 |
| 20.21.15 | R-GSM or ER-GSM cell reselection due to MS rejection "LA not allowed"..... | 1037 |
| 20.21.16 | R-GSM or ER-GSM downlink signalling failure | 1039 |
| 20.21.17 | R-GSM or ER-GSM cell selection if no suitable cell found in 10 s | 1040 |
| 20.21.18 | R-GSM or ER-GSM cell reselection due to MS rejection "Roaming not allowed in this LA" | 1041 |
| 20.21.19 | R-GSM or ER-GSM cell selection on release of SDCCH and TCH | 1042 |
| 20.22 | GRPS Cell Selection and Reselection | 1043 |
| 20.22.1 | Void | 1045 |
| 20.22.2 | Void | 1045 |
| 20.22.3 | Void | 1045 |
| 20.22.4 | Void | 1045 |
| 20.22.5 | Void | 1045 |
| 20.22.6 | Void | 1045 |
| 20.22.7 | Void | 1045 |
| 20.22.8 | Cell selection when the best cell does not support GPRS | 1045 |
| 20.22.9 | Cell reselection when the best cell does not support GPRS | 1046 |
| 20.22.10 | Void | 1049 |
| 20.22.11 | Void | 1049 |
| 20.22.12 | Cell Selection on "LA Not Allowed" | 1049 |
| 20.22.13 | Void | 1050 |
| 20.22.14 | Void | 1050 |
| 20.22.15 | Cell Reselection/ ready state / no reselection | 1050 |
| 20.22.16 | Cell Reselection/ ready state/ Reselection and Cell update procedure | 1051 |
| 20.22.17 | C2 reselection in another RA - no cell reselection | 1053 |
| 20.22.18 | C2 reselection in another Routing Area. Routing Area Update | 1054 |
| 20.22.19 | Borders between routing areas - reselection of a GPRS cell in a homogenous network | 1056 |
| 20.22.20 | Void | 1057 |
| 20.22.21 | Void | 1057 |
| 20.22.22 | Cell Reselection with cells in different Routing area..... | 1057 |
| 20.22.23 | Void | 1059 |
| 20.22.24 | Void | 1059 |
| 20.22.25 | Void | 1059 |
| 20.22.26 | Void | 1059 |
| 20.22.27 | Void | 1059 |
| 20.22.28 | Void | 1059 |
| 20.22.29 | Packet Measurement order procedure / Downlink transfer / Normal case/ 3G cell reselection dedicated parameters..... | 1059 |
| 20.22.29a | Packet Measurement order procedure / Downlink transfer / Normal case/ 3G cell reselection dedicated parameters with GEA2 and UEA2 ciphering..... | 1065 |
| 20.22.29b | Packet Measurement order procedure / Downlink transfer / Normal case/ 3G cell reselection dedicated parameters with GEA3 and UEA2 ciphering..... | 1065 |
| 20.22.29c | Packet Measurement order procedure / Downlink transfer / Normal case/ 3G cell reselection dedicated parameters with GEA4 and UEA2 ciphering..... | 1066 |
| 20.22.30 | Cell Reselection/usage of BA(GPRS)..... | 1066 |
| 20.22.30.1 | Cell Reselection/usage of BA(GPRS)/ Most suitable cell not in BA(GPRS) | 1066 |
| 20.22.30.2 | Cell Reselection / usage of BA(GPRS) / Change of BA(GPRS) | 1067 |
| 20.22.30.3 | Cell Reselection/usage of BA(GPRS)/ Measurement on first 32 entries | 1068 |
| 20.22.31 | Network controlled cell reselection / Transfer mode | 1069 |
| 20.22.31.1 | Network controlled cell reselection / Downlink transfer / Normal case/ Location and Routing Area Update/ NMO I..... | 1069 |
| 20.22.31.2 | Network controlled cell reselection / Downlink transfer / Normal case/ Location and Routing Area Update/ NMO II | 1071 |