

ETSI TS 103 383 V13.0.0 (2015-10)



**Smart Cards;
Embedded UICC;
Requirements Specification
(Release 13)**

iTeh Standards Preview
(Standard: itg-ai)
https://standards.itih.ai/standards/sist/ae8ff6c9-2f46-41e9-9c78-f9214d9e534e/etsi-ts-103-383-v13.0.0-2015-10

ReferenceRTS/SCP-ReUICCvd00

Keywordsembedded, Smart Card

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|---|-----------|
| Intellectual Property Rights | 5 |
| Foreword..... | 5 |
| Modal verbs terminology..... | 5 |
| Introduction | 5 |
| 1 Scope | 7 |
| 2 References | 7 |
| 2.1 Normative references | 7 |
| 2.2 Informative references..... | 7 |
| 3 Definitions and abbreviations..... | 8 |
| 3.1 Definitions | 8 |
| 3.1a Definitions for further study..... | 9 |
| 3.2 Abbreviations | 10 |
| 4 Abstract (informative)..... | 10 |
| 5 Background (informative)..... | 11 |
| 5.1 Overview of the use cases | 11 |
| 5.2 Use Case 1 - Provisioning of multiple eUICCs for M2M..... | 11 |
| 5.2.1 Overview | 11 |
| 5.2.2 Use case 1 - example a) - Utility Meters..... | 11 |
| 5.2.3 Use case 1 - example b) - Security Camera..... | 12 |
| 5.2.4 Use case 1 - example c) - Telematics..... | 12 |
| 5.3 Use case 2 - Provisioning of an eUICC for a first subscription with a new connected device..... | 12 |
| 5.3.1 Overview | 12 |
| 5.3.2 Use case 2 - example a) - Provisioning of a new device..... | 12 |
| 5.3.3 Use case 2 - example b) - Provisioning of multiple new devices for an enterprise..... | 13 |
| 5.4 Use case 3 - Change of subscription for a device..... | 13 |
| 5.4.1 Overview | 13 |
| 5.4.2 Use case 3 - example a) - Change of subscription by consumer..... | 13 |
| 5.4.3 Use case 3 - example b) - Change of subscriptions for devices for enterprise workforce | 13 |
| 5.5 Use Case 4 - Change of SM-SR | 13 |
| 5.6 Use Case 5 - Terminal state and capabilities reporting | 14 |
| 5.7 Use Case 6 - Profile Update | 14 |
| 5.8 Use Case 7 - Provisioning of devices with only IP connectivity..... | 14 |
| 5.9 Use Case 8 - Provisioning a device in markets with multiple roots of trust (CAs)..... | 14 |
| 6 Requirements..... | 14 |
| 6.1 General | 14 |
| 6.2 Profile, Application and File Structure..... | 15 |
| 6.3 Procedural..... | 15 |
| 6.4 Security | 17 |
| 6.5 Profile Interoperability and Interactions..... | 18 |
| 6.6 Policy Enforcement | 18 |
| 6.7 Policy Control | 19 |
| 6.8 Policy Rules..... | 19 |
| Annex A (informative): Void | 20 |
| Annex B (informative): States (see also annex D)..... | 21 |
| B.0 Foreword | 21 |
| B.1 States of eUICC..... | 21 |
| B.2 States of Profiles..... | 21 |
| B.3 States of Applications in Profiles | 21 |

Annex C (informative): Logical aspects of eUICC Architecture and associated Security Credentials.....22

Annex D (informative): Profiles and NAA (Network Access Application) States23

Annex E (informative): Profile Aspects.....24

E.0 Foreword24

E.1 Profile Content24

E.2 Profile Related Principles24

Annex F (informative): Change history26

Annex G (informative): Bibliography.....28

History29

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/ae8ff6e9-2f46-41e9-9c78-f9214d9e884c/etsi-ts-103-383-v13.0.0-2015-10>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 0 early working draft;
 - 1 presented to TC SCP for information;
 - 2 presented to TC SCP for approval;
 - 3 or greater indicates TC SCP approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

Work on Machine-to-Machine (M2M) applications has given rise to the possibility of having a UICC that is embedded in a communication device in such a way that the UICC is not easily accessible or replaceable. The ability to change network subscriptions on such devices becomes problematic, thus necessitating new methods for securely and remotely provisioning access credentials on these Embedded UICCs (eUICC) and managing subscription changes from one MNO to another.

In its current state, the present document is to be considered as a "work in progress". It contains a restricted set of requirements related to the provisioning of profiles in an eUICC as well as general requirements on the architecture of the eUICC. As a consequence, some of the elements required to specify a complete technical solution are missing, among which are requirements for:

- management of profiles;

- management of credentials;
- the policy control function;

which will be defined in further versions of the present document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/ae8ff6e9-2f46-41e9-9c78-f9214d9e884c/etsi-ts-103-383-v13.0.0-2015-10>

1 Scope

The present document defines the use cases and requirements for an embedded UICC.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 221: "Smart Cards; UICC-Terminal interface; Physical and logical characteristics".
- [2] ETSI TS 102 671: "Smart Cards; Machine to Machine UICC; Physical and logical characteristics".
- [3] Void.
- [4] ETSI TS 102 241: "Smart Cards; UICC Application Programming Interface (UICC API) for Java Card (TM)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Recommendation ITU-T E.212: "The international identification plan for public networks and subscriptions".
- [i.2] ETSI TR 102 216: "Smart cards; Vocabulary for Smart Card Platform specifications".
- [i.3] ETSI TS 123 682: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Architecture enhancements to facilitate communications with packet data networks and applications (3GPP TS 23.682)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI TR 102 216 [i.2] and the following apply:

Attribute (of a Profile): indication that a Profile delivers some specific functions; the knowledge of attributes offered by Profiles could be used by any authorized entity accessing the eUICC (terminal, server, etc.) to determine a particular behaviour

Embedded UICC: UICC which is not easily accessible or replaceable, is not intended to be removed or replaced in the terminal, and enables the secure changing of subscriptions

Enabled Profile: Profile, the files and/or applications (e.g. NAA) of which are selectable over the UICC-Terminal interface

eUICC Management Credentials: credentials used to verify the authorization for the establishment of Profile Management Credentials and Profile Provisioning Credentials

eUICC Supplier: supplier of the eUICC modules and resident software (such as firmware and operating system)

Mobile Network Operator (MNO): entity providing communication services to its customers through mobile networks

Network Access Application (NAA): application residing on an eUICC that provides authorization to access a network

EXAMPLE: A USIM application.

NOTE: Copied from ETSI TR 102 216 [i.2], to be deleted when the current document is finalized.

Network Access Credentials (NAC): data required to authenticate to an ITU E.212 [i.1] Network

NOTE: Network Access Credentials may include data such as Ki/K, and IMSI stored within a NAA.

Operational Attribute: indication that a Profile, containing network access applications and associated network access credentials, is associated to an Operational Subscription

Operational Subscription: subscription that enables a device to access an ITU E.212 [i.1] network for the purpose of accessing telecommunication and related services

Policy: principles reflected in a set of rules that govern the behaviour of an eUICC and/or entities involved in the remote management of the eUICC

Policy Control Function: function that defines, updates or removes Policy Rules to implement a Policy

Policy Enforcement Function: function that executes Policy Rules to implement a Policy

Policy Rule: defines the actions required to implement a Policy and the conditions under which they are executed

eUICC Policy Control Credentials: credentials used for authorization and authentication for the establishment and update of the Policy Rules defined on the eUICC outside Profiles

NOTE: This definition might be refined according to the decision about the need to have Policy Rules defined inside and/or outside Profiles.

Profile: combination of a file structure, data and applications to be provisioned onto, or present on, an eUICC

Profile Access Credentials: data required to exist within a Profile so that secured communication can be set up between an external entity and the eUICC in order to manage that Profile's structure and its data (e.g. operator OTA keys)

Profile Container: logical container for a Profile on an eUICC providing security services, enabling separation of Profiles and providing secure communication

Profile Container Initialization: process of preparing a Profile Container so that it is ready for Profile Loading and Installation

Profile Loading: transfer of a Profile from a Profile Provisioning Credentials holder into the eUICC so that it is ready for installation

Profile Transport: transfer of a cryptographically protected Profile from a Profile Management Credential holder to the eUICC

Profile Installation: process of allocating resources and registering parameters for a Profile to bring it to a state where it can be enabled

Profile Provisioning Credentials: data required to exist within an eUICC so that a Profile downloaded from an external entity can be decrypted and installed on the eUICC

Profile Management Credentials: data required to exist within an eUICC so that a secured communication can be set up between an external entity and the eUICC in order to manage the Profiles on the eUICC

Profile Management Operations: consists of Profile Transport, Profile deletion, Profile enabling, and Profile disabling

Provisioning: container creation and initialization, loading, and installation of a Profile into an eUICC

Provisioning Attribute: indication that a Profile, containing network access applications and associated network access credentials, is associated with the Provisioning Subscription

Provisioning Subscription: subscription, with its associated Profile, that enables a device to access a mobile network for the purpose of management of operational Profiles on the eUICC

Subscriber: entity that has a subscription with a telecommunications service provider

Subscription: commercial relationship for the supply of services between the Subscriber and Telecommunications Service Provider

Subscription Manager: combination of the functions of the SM-SR and the SM-DP

Subscription Manager - Data Preparation (SM-DP): role that prepares Profiles to be securely provisioned on the eUICC e.g. encryption of Profile

NOTE 1: Also known as Profile Provisioning Credentials holder.

NOTE 2: "securely" is felt to relate to requirements captured in an appropriate section of the present document. The term "securely" may be removed from this definition once those requirements are specified.

Subscription Manager - Secure Routing (SM-SR): role that securely performs functions which directly manage the Profiles on the eUICC

NOTE: "securely" is felt to relate to requirements captured in an appropriate section of the present document. The term "securely" may be removed from this definition once those requirements are specified.

Telecommunications Service Provider: MNO, or party trusted by the MNO acting on behalf of the MNO, which provides services to the subscriber

3.1a Definitions for further study

Definitions are required for the following terms:

- **Initialized State:**

NOTE: This definition is required. Best proposal so far: "refers to the state the eUICC is in when a Profile with the Operational Attribute is either not active or not present, and the eUICC is only accessible for the purpose of management of operational Profiles".

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|--------|--|
| ATR | Answer To Reset |
| CA | Certificate Authority |
| CAT | Card Application Toolkit |
| CS | Circuit Switched |
| CSIM | CDMA Subscriber Identity Module |
| eUICC | embedded UICC |
| FFS | For Further Study |
| IMS | IP Multimedia Subsystem |
| IMSI | International Mobile Subscriber Identity |
| IP | Internet Protocol |
| ISIM | IM Services Identity Module |
| M2M | Machine to Machine (communication) |
| MF | Master File |
| MNO | Mobile Network Operator |
| MSISDN | Mobile Subscriber Integrated Services Digital Network Number |
| MTC | Machine-Type Communication |
| NAA | Network Access Application |
| NAC | Network Access Credentials |
| NAS | Non Access Stratum |
| OEM | Original Equipment Manufacturer |
| OTA | Over-The-Air |
| PCF | Policy Control Function |
| PIN | Personal Identification Number |
| PKI | Public Key Infrastructure |
| PMC | Profile Management Credentials |
| PS | Packet Switched |
| PUK | PIN Unblocking Key |
| RAM | Remote Application Management |
| RFM | Remote File Management |
| SD | Security Domain |
| SIM | Subscriber Identity Module |
| SM | Subscription Manager |
| SM-DP | Subscription Manager - Data Preparation |
| SM-SR | Subscription Manager - Secure Routing |
| SMS | Short Message Service |
| SP | Service Provider |
| TBD | To Be Defined |
| USIM | Universal Subscriber Identity Module |

4 Abstract (informative)

The present document enables remote management of an embedded UICC (eUICC) for purposes of changing an MNO subscription without requiring a physical removal and replacement of the UICC in the end Device.

The present document develops use cases and requirements for the "enhanced, remote management" of a UICC, which is embedded in a communication device, i.e. where the UICC is not intended to be removed. This type of embedded UICC (eUICC) is compatible with Machine-to-Machine (M2M) applications. The eUICC may be embedded at the manufacturing site in advance, depending on the country and network operator, and is compatible for use in a variety of end-user equipment. In these scenarios there may be a requirement to remotely change a subscription easily, similar to what is currently achieved by physically changing the UICC.

The purpose for defining these requirements is to provide ease of use and deployment benefits for end users/consumers and thereby stimulate the M2M sector. A further intent is to enable the creation of common standards and processes for remote management of profiles on an eUICC, such that interoperability is ensured.