



Designation: E479 – 91(Reapproved 2006)

Standard Guide for Preparation of a Leak Testing Specification¹

This standard is issued under the fixed designation E479; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This standard² is intended as a guide. It enumerates factors to be considered in preparing a definitive specification for maximum permissible gas leakage of a component, device, or system. The guide relates and provides examples of data for the preparation of leak testing specifications. It is primarily applicable for use in specifying halogen leak testing methods.

1.2 Two types of specifications are described:

1.2.1 Operational specifications (OS), and

1.2.2 Testing specifications (TS):

1.2.2.1 Total, and

1.2.2.2 Each leak.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*³

E427 Practice for Testing for Leaks Using the Halogen Leak Detector Alkali-Ion Diode (Withdrawn 2013)⁴

E432 Guide for Selection of a Leak Testing Method

3. Terminology

3.1 *Definitions:*

3.1.1 *operational specification (OS)*—a specification from which the others are derived. The specification specifies and states the limits of the leakage rate of the fluid to be used for the product using criteria such as failure to operate, safety, or appearance.

¹ This guide is under the jurisdiction of ASTM Committee E07 on Nondestructive Testing and is the direct responsibility of Subcommittee E07.08 on Leak Testing Method.

Current edition approved May 1, 2006. Published June 2006. Originally approved in 1973. Last previous edition approved in 2000 as E479 - 91(2000). DOI: 10.1520/E0479-91R06.

² For ASME Boiler and Pressure Vessel Code applications see related Guide SE-479 in Section II of that Code.

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

⁴ The last approved version of this historical standard is referenced on www.astm.org.

3.1.2 *testing specification (TS)*—a specification for the detection, location, or measurement, or a combination thereof, of leakage. The operational fluid usually is not detectable with commercially available leak detectors. The leak test must be performed with a suitable test gas containing a tracer to which the detector is sensitive. The pressure magnitude and pressure direction may vary greatly from operational conditions. These and other factors are to be considered and evaluated when the leak testing performed to the requirements of the TS is to result in a product that meets most of the OS requirements. In addition, should a product be tested with a detector or tracer probe from point to point, allowance should be made for the possibility of two or more leaks, each causing less leakage than the total leakage maximum, but adding up to an amount greater than allowed.

4. Specification Content and Units

4.1 The content and units of the specification should relate the following data:

4.1.1 Mass flow per unit of time, preferably in moles per second (mol/s).

4.1.2 The pressure differential across the two sides of possible leaks, and the direction, in pounds per square inch (psi) or moles (mol).

4.1.3 Any special restrictions or statement of facts that might prohibit the use of a particular type of leak testing method.

4.1.4 The methods of the leakage specification shall not be limited to any one particular method unless it is the only one suitable. Specific leak testing methods can be selected when careful consideration of the facts is outlined (refer to Guide E432 or the other applicable documents of Section 2).

5. Significance and Use

5.1 For any product to be tested the geometrical complexity will vary widely. However, the basic concept of determining an operative leakage specification regardless of geometries is much the same for all, whether it be simple, ordinary, or complex.

5.2 The data required for writing the OS, which is total leakage (moles), time(s), and pressure difference across the leak, are either available or can be determined by tests or measurements.

5.3 A user who selects values to be used in a leakage specification as a result of someone else having used the value or simply because of prestige reasons, may find the value or values unsatisfactory for the product.

5.4 A specification that is too restrictive may result in excessive leak testing costs. A specification that is not restrictive enough may result in premature product failure, or increased warranty costs, or both.

5.5 A typical illustration for determining a leakage specification, using the complex geometry of a refrigerant system for an example, will be used throughout this recommended guide. It is well to point out that the user should realize that the values and test methods selected do not necessarily represent the best or typical ones for this application.

6. Procedure

6.1 The example that follows is to be construed as applicable to the equipment and testing method cited, and is not to be construed as setting up mandatory leakage rates for any other equipment or method of testing. The example used to illustrate the use of this guide is as follows: An automotive air-conditioning system using Refrigerant-12 (R-12, dichlorodifluoromethane) and consisting of a compressor, condensing coil, thermostatic expansion valve, evaporating coil, vacuum-operated hot gas bypass capacity control valve, and a sealed temperature control thermostat.

6.2 *OS, Refrigerant Circuit*—It is desirable that the rechargeable portions of the system operate three years before requiring additional refrigerant; for the sealed parts, 5 years. Tests show that 6 oz of the normal charge can be lost before serious operational inefficiency begins, and the neoprene connecting hoses have a basic permeation rate of 1 oz/year. Inspection of the system shows that the vacuum operator of the capacity valve and the thermostat are not directly connected to the refrigerant circuit, and can thus be considered separately.

6.2.1 Calculations:

Leakage to be detected = 6 oz (total loss) – 1 oz × 3 years = 3 oz
 Period = 3 years
 Rate = 3 oz/3 years = 1 oz/year. Rate (standard units) = 1 oz/year × 1.8×10^{-4} (or 0.00018 = R-12 conversion factor) = 7.308×10^{-9} moles/s. See 6.6.3

Pressure—The maximum operating temperature of the system will be 77°C at which temperature the pressure of the refrigerant will be about 2.07 MPa. Pressure difference = 2.07 MPa (internal) – 0.10 MPa (atmosphere) = 1.97 MPa.

6.2.2 Therefore, the following would appear on the appropriate documents: Leakage Specification (Operational): 3.6×10^{-5} MPa max at 1.97 MPa pressure difference (7.308×10^{-9} moles/s excluding hose permeation).

6.3 TS, Refrigerant Circuit:

6.3.1 For a unit to be tested at the OS level, any inaccuracies in the test could cause possible unit acceptance when in fact the unit may leak in excess of the amount allowed. Most testing conditions cannot duplicate operating conditions. Should a point-by-point probing technique be used, a number of smaller leaks may allow a total leakage in excess of the value specified.

6.3.2 In addition, some portions of the system may be purchased as a completed operative component. Their potential contribution to the total system leakage must be limited. It is

because of the requirements of the testing specification that these and other factors are considered, and that required leak testing at levels to ensure acceptable quality levels in the final product is made with the consideration for a lesser testing cost. Often it is necessary to divide the leakage allowance equitably among various components, taking into account the statistical probability of the largest allowable leakage occurring in a number of a given set of components.

6.3.2.1 *Division of Leakage Allowance Among System Components*—Assume in the previous example that the compressor, condensing and evaporating coils, the expansion valve, capacity control valve, and sealed thermostat all have to be considered. Also assume that the compressor and evaporating coil will both be tested separately before assembly into the system, as each has a number of fabricated joints more prone to leakage than the condensing coil. The condensing coil, considered a continuous length of tubing, can be tested at the final system test. All components except the thermostat make up some portion of the refrigerant circuit. How then should the leakage allowance be divided among them? The usually equitable way is to make the division on the basis of the number of joints in each, considering 25 mm of seam as one “joint.” A tabulation example on this basis follows:

	No. of Joints	% of Total
Compressor	36	28
Condensing coil	78	60
Expansion	7	5
Capacity control valve	9	7
Total	130	100

6.4 *Factor of Safety for Leak Testing Accuracy*—When establishing the data for the factor of safety for leak testing accuracy and when performed by various people using different equipment, facilities, or operating standards, the resulting data usually will vary tremendously. Results of a round-robin test conducted by ASTM resulted in a spread of the test data of about one decade. This value is considered valid for leak tests using procedures and equipment described in Section 2. Therefore any operational specification may apply a factor of $\frac{1}{3}$ or 0.3.

6.5 *Factor of Safety for Number of Leaks per System*—When a unit or device has a number of points that may leak, the leak test is to be performed by point-to-point probing. There is a possibility that the sum of all leaks smaller than the specification total may add up to an amount in excess of it. However, this is dependent upon the number of leak possibilities or on whether there is any distortion of the normal leak distribution curve, which covers many decades of sizes. The factor assigned here may depend upon a judgment of the probability of such an event occurring, the degree of confidence needed in the leak test, and the safety factor that can be afforded. In this example, assume that the condensing coil is of welded aluminum which has a strong tendency to have porosities that leak in the range of 4.06×10^{-10} moles/s. For this reason, the TS total will be divided by five for this item, and by three for the others, that is, a factor of 0.2 and 0.3 respectively.

6.6 *Factor of Safety for Test versus Operating Conditions:*