

ETSI TS 102 361-2 v2.4.1 (2017-10)



Electromagnetic compatibility and Radio spectrum Matters (ERM); Digital Mobile Radio (DMR) Systems; Part 2: DMR voice and generic services and facilities

iTeh Standards PREVIEW
(Standard is available)
Full Standard
<https://standards.iteh.ai/catalogue/2201e9d/etsi-ts-102-361-2-v2.4.1-2017-10>
49c1-9c9d-907e2201e9d

Reference

RTS/ERM-TGDMR-357

Keywords

air interface, digital, PMR, protocol, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.
GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	10
3 Definitions and abbreviations.....	10
3.1 Definitions	10
3.2 Abbreviations	12
4 Overview	14
4.0 Overview introduction.....	14
4.1 Protocol architecture.....	14
4.1.0 Protocol architecture - Introduction	14
4.1.1 Air Interface Physical Layer (layer 1).....	15
4.1.2 Air Interface Data Link Layer (layer 2)	15
4.1.3 Air Interface layer 3 (CCL).....	16
4.2 Overview of voice and generic services and facilities.....	16
4.3 Feature interoperability	17
5 DMR services	17
5.1 Generic services	17
5.1.1 Generic BS services	17
5.1.1.0 Generic BS services - Introduction.....	17
5.1.1.1 BS outbound activation	19
5.1.1.1.0 BS outbound activation - Introduction.....	19
5.1.1.1.1 BS Outbound Activation SDL.....	20
5.1.1.1.2 BS MSCs	20
5.1.1.1.3 BS_Outbound_Activation	21
5.1.1.2 Voice call repeating	22
5.1.1.3 Voice call hangtime	23
5.1.1.4 CSBK repeating	24
5.1.1.5 BS outbound deactivation.....	25
5.1.1.6 Channel authorization	25
5.1.1.6.0 General	25
5.1.1.6.1 BS Channel Authorization Procedures	26
5.1.1.6.2 MS Channel Authorization Procedures	27
5.1.2 Feature Not Supported (FNS) signalling	27
5.1.2.0 Feature Not Supported (FNS) signalling - Introduction.....	27
5.1.2.1 FNS Data Bursts/Fields.....	27
5.1.2.2 MS FNS MSC	27
5.2 Primary voice services.....	28
5.2.1 Group call service	28
5.2.1.0 Group call service - Introduction	28
5.2.1.1 Service description.....	29
5.2.1.2 Group call data bursts/fields.....	29
5.2.1.2.1 Direct mode	29
5.2.1.2.2 Repeater mode	29
5.2.1.3 MS group call control.....	30
5.2.1.3.1 MS group call SDL.....	30
5.2.1.3.2 MS group call HMSC	31
5.2.1.3.3 MS group call MSCs	32
5.2.2 Individual call service.....	42
5.2.2.0 Individual call service - Introduction	42
5.2.2.1 Service description.....	42

5.2.2.2	Individual call data bursts/fields	42
5.2.2.2.1	Direct mode	42
5.2.2.2.2	Repeater mode	43
5.2.2.3	MS Individual call channel access	43
5.2.2.3.0	MS individual call channel access - Introduction	43
5.2.2.3.1	UU_V_Req channel access SDL	43
5.2.2.3.2	UU_Ans_Rsp channel access SDL	44
5.2.2.4	MS Individual call control	45
5.2.2.4.0	MS individual call control - Introduction	45
5.2.2.4.1	MS OACSU Individual call source CCL SDL	46
5.2.2.4.2	MS OACSU Individual call setup MSCs	47
5.3	Supplementary voice services	49
5.3.1	Unaddressed voice call service	49
5.3.1.0	Unaddressed voice call service - Introduction	49
5.3.1.1	Unaddressed voice call data burst/fields	49
5.3.1.2	MS Unaddressed voice call control	49
5.3.2	All call voice service	49
5.3.2.0	All call voice service - Introduction	49
5.3.2.1	All call data bursts/fields	49
5.3.2.2	MS All call control	49
5.3.2.3	BS All call control	50
5.3.2.3.1	All call voice repeating	50
5.3.2.3.2	All call end of transmission	50
5.3.3	Broadcast call voice service	51
5.3.3.0	Broadcast call voice service - Introduction	51
5.3.3.1	Broadcast call data bursts/fields	51
5.3.3.2	MS Broadcast call control	51
5.3.3.3	BS Broadcast call control	51
5.3.3.3.1	Broadcast call voice repeating	51
5.3.3.3.2	Broadcast call end of transmission	51
5.3.4	Open voice channel mode service	51
5.3.4.0	Open voice channel mode service - Introduction	51
5.3.4.1	OVCM service description	52
5.4	Voice associated inband data services	52
5.4.1	Voice associated inband data services - Introduction	52
5.4.2	Inband positioning data service	53
5.4.3	Inband talker alias data service	53
6	DMR facilities	54
6.1	Transmit timeout	54
6.2	TDMA direct mode wide area timing	54
6.2.1	Facility description	54
6.2.1.0	Facility description - Introduction	54
6.2.1.1	Leader_and_Timing_Unknown	54
6.2.1.2	Leader_Unknown	54
6.2.1.3	Leader_and_Timing_Known	55
6.2.1.4	Leader	55
6.2.2	TDMA direct mode data bursts/fields	55
6.2.2.1	Synchronization	55
6.2.2.2	Colour Code	55
6.2.2.3	Channel Timing CSBK	55
6.2.2.3.0	Channel Timimg CSBK - Introduction	55
6.2.2.3.1	CT_CSBK_Beacon	56
6.2.2.3.2	CT_CSBK_Prop	56
6.2.2.3.3	CT_CSBK_Term	56
6.2.2.3.4	CT_CSBK_Req	57
6.2.2.3.5	CT_CSBK_Resp	57
6.2.3	TDMA direct mode SDL	57
6.2.3.0	TDMA direct mode SDL - Introduction	57
6.2.3.1	Power up and channel change SDL	58
6.2.3.2	Leader and timing unknown SDL	58
6.2.3.3	Leader unknown SDL	60

6.2.3.4	Leader and timing known SDL	61
6.2.3.5	Leader SDL	62
6.2.3.6	Leader identifier conflict SDL	63
6.2.3.7	CT_CSBK evaluation SDL	64
6.2.3.8	Send correction SDL	66
6.2.3.9	Accept leader SDL	68
6.2.3.10	Appoint new leader SDL	68
6.2.3.11	Timing push SDL	69
6.2.3.12	Transmit procedure SDL	70
7	PDU description	71
7.0	PDU description - Introduction	71
7.1	Layer 3 PDUs	72
7.1.0	Layer 3 PDUs - Introduction	72
7.1.1	Full Link Control PDUs	72
7.1.1.1	Group Voice Channel User LC PDU	72
7.1.1.2	Unit to Unit Voice Channel User LC PDU	73
7.1.1.3	GPS Info LC PDU	73
7.1.1.4	Talker Alias header LC PDU	73
7.1.1.5	Talker Alias block LC PDU	74
7.1.2	Control Signalling Block (CSBK) PDUs	74
7.1.2.1	BS Outbound Activation CSBK PDU	74
7.1.2.2	Unit to Unit Voice Service Request CSBK PDU	75
7.1.2.3	Unit to Unit Voice Service Answer Response CSBK PDU	75
7.1.2.4	Negative Acknowledge Response CSBK PDU	76
7.1.2.5	Preamble CSBK PDU	76
7.1.2.6	Channel Timing CSBK PDU	76
7.1.3	Short Link Control PDUs	77
7.1.3.1	Null Message	77
7.1.3.2	Activity Update	78
7.2	Layer 3 information element coding	79
7.2.0	Layer 3 information element coding - Introduction	79
7.2.1	Service Options	79
7.2.2	Answer Response	79
7.2.3	Reason Code	80
7.2.4	Service Type	80
7.2.5	Source Type	80
7.2.6	Additional Information Field	80
7.2.7	CSBK Blocks to Follow (CBF)	80
7.2.8	Identifier (ID)	81
7.2.9	Dynamic Identifier (DI)	81
7.2.10	Wide Area Timing Identifier (WATID)	81
7.2.11	Channel Timing Opcode (CTO)	81
7.2.12	New Leader (NL)	82
7.2.13	Generation (Gen)	82
7.2.14	Sync Age (SA)	82
7.2.15	Position Error	83
7.2.16	Longitude	83
7.2.17	Latitude	83
7.2.18	Talker Alias Data Format	83
7.2.19	Talker Alias Data Length	83
Annex A (normative):	Timers and constants in DMR	85
A.0	Timers and constants in DMR - Introduction	85
A.1	Layer 3 timers	85
A.2	Layer 3 constants	86
Annex B (normative):	Opcode Reference Lists	87
B.1	Full Link Control Opcode List	87

B.2	CSBK Opcode List	87
B.3	Short Link Control Opcode List	87
Annex C (informative):	Numbering and dialling plan	88
C.1	Introduction to the numbering and dialling plan	88
C.2	Subscriber mapping	89
C.2.1	User Interface - Air Interface	89
C.2.1.0	User Interface - Air Interface - Introduction	89
C.2.1.1	Mapping for MS individual address space	90
C.2.1.1.0	Mapping for MS individual address space - Introduction	90
C.2.1.1.1	Mapping for diallable addresses (prefix 0 to 9)	91
C.2.1.1.2	Mapping for non-diallable individual addresses (prefix 10 to 14)	91
C.2.1.1.3	Examples of individual address mapping	92
C.2.1.2	Mapping for MS talkgroup address space	92
C.2.1.2.0	Mapping for MS talkgroup address space - Introduction	92
C.2.1.2.1	The concept of the wildcard character	92
C.2.1.2.2	The concept of stored parameters	93
C.2.1.2.3	The concept of ad-hoc arrangement	93
C.2.1.2.4	The rules for the sender	93
C.2.1.2.5	The rules for the recipient	93
C.2.1.2.6	Mapping of dialled strings to the AI talkgroup address space	94
C.2.1.2.6.0	Mapping of dialled strings to the AI talkgroup address space - Introduction	94
C.2.1.2.6.1	Mapping of numeric dialled strings to the AI talkgroup address space	94
C.2.1.2.6.2	Mapping for non-diallable talkgroup addresses (prefix 10 to 14)	96
C.2.1.2.6.3	Examples of talkgroup non-diallable address mapping	96
C.2.1.2.7	The concept of the prefix	96
C.2.2	Addresses	98
C.2.3	Conversion rules	98
C.2.3.1	MS addresses	98
C.2.3.2	Limiting the length of the destination address	98
C.2.3.3	All talkgroup address	98
C.2.3.4	Gateways	99
C.3	User dialling plan	99
C.3.1	User numbering	99
C.3.1.0	User numbering - Introduction	99
C.3.1.1	Dialling method	99
C.3.1.2	Call Type determination	99
C.3.1.3	Call modifier strings	99
C.3.2	Dialled digits to address mapping	100
C.3.3	Storage requirements	100
C.3.3.1	MS individual address	100
C.3.3.2	Talkgroups	100
C.3.3.3	All MSs	100
C.3.3.4	Non-diallable numbers	100
C.3.3.5	Talkgroup recognition	101
C.3.3.5.1	All numeric talkgroups	101
C.3.3.5.2	Talkgroups defined by wildcards	101
C.3.3.5.3	MS receives a talkgroup call	101
C.3.4	Dialling procedures	102
C.3.4.1	MS calls	102
C.3.4.1.1	Seven digit dialling	102
C.3.4.1.2	Abbreviated dialling	102
C.3.4.1.3	Individual call	103
C.3.4.1.4	Talkgroup Call	103
C.3.4.1.5	All Call	103
C.3.4.2	Gateway calls	103
C.3.4.2.1	Telephone call	103
C.3.4.2.1.0	Telephone call - introduction	103
C.3.4.2.1.1	Telephone numeric padding format	103

C.3.4.2.1.2	Telephone star modifier format	104
C.3.4.2.2	PABX call	104
C.3.4.2.2.0	PABX call - Introduction.....	104
C.3.4.2.2.1	PABX numeric padding format.....	104
C.3.4.2.2.2	PABX star modifier format	104
C.3.4.2.3	IP call	104
C.3.4.3	Call modifiers	105
C.3.4.3.0	Call modifiers - Introduction.....	105
C.3.4.3.1	Broadcast call.....	105
C.3.4.3.2	Priority call.....	105
C.3.4.3.3	Emergency call.....	105
C.3.4.3.4	Status call	105
C.3.4.3.5	Divert own call.....	106
C.3.4.3.6	Open channel voice mode call	106
C.3.4.3.7	Force talkgroup service	106
C.3.4.3.8	Multiple call modifiers	106
C.3.4.4	MS behaviour commands	106
C.3.4.4.0	MS behaviour commands - Introduction.....	106
C.3.4.4.1	Edit the talkgroup table	106
C.3.4.4.2	Queue Incoming call	107
C.3.4.4.3	Display own identity	107
C.3.4.4.4	Display Own talkgroup table.....	107
C.3.4.5	Call set-up abandon or call complete	107
Annex D (informative):	Change requests	108
Annex E (informative):	Bibliography	109
History	110

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/37985/5-158x49c1-9c9d-907e2201e9d/etsi-ts-102-361-2-v2.4.1-2017-10>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 2 of a multi-part deliverable covering the Technical Requirements for Digital Mobile Radio (DMR), as identified below:

- Part 1: "DMR Air Interface (AI) protocol";
- Part 2: "DMR voice and generic services and facilities";**
- Part 3: "DMR data protocol";
- Part 4: "DMR trunking protocol".

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document contains technical requirements for Digital Mobile Radio (DMR) operating in the existing licensed land mobile service frequency bands, as identified in CEPT/ERC/T/R 25-08 [i.1].

The present document describes the voice and generic services and facilities of a scalable Digital Mobile Radio system which covers three tiers of possible products:

- Tier I: DMR equipment having an integral antenna and working in direct mode (communication without infrastructure) under a general authorization with no individual rights operation.
- Tier II: DMR systems operating under individual licences working in direct mode (unit-to-unit) or using a Base Station (BS) for repeating.
- Tier III: DMR trunking systems under individual licences operating with a controller function that automatically regulates the communications.

NOTE 1: Tier II and Tier III products encompass both simulcast and non-simulcast systems.

NOTE 2: The three tiers of possible products will work only independently and not interoperable.

The present document specifies the voice and generic services and facilities of DMR that has been specifically developed with the intention of being suitable for all identified product tiers. The DMR protocol is intended to be applicable to the land mobile frequency bands, physical channel offset, duplex spacing, range assumptions and all other spectrum parameters without need for any change.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 361-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Digital Mobile Radio (DMR) Systems; Part 1: DMR Air Interface (AI) protocol".
- [2] ETSI TS 102 361-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Digital Mobile Radio (DMR) Systems; Part 3: DMR data protocol".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT/ERC/T/R 25-08: "Planning criteria and co-ordination of frequencies in the Land Mobile Service in the range 29,7-921 MHz".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

1:1-mode: 1 traffic channel mode

NOTE: 1:1-mode supports one "MS to fixed end" duplex call or one simplex call with an optional inbound Reverse Channel using a two frequency BS.

2:1-mode: 2 traffic channel mode

NOTE: 2:1-mode supports two independent calls which may be either "MS to fixed end" duplex calls, simplex calls using a two frequency BS or simplex calls between MS units on a single frequency.

Base Station (BS): fixed end equipment that is used to obtain DMR services

bearer service: telecommunication service providing the capability for information transfer between access points

burst: elementary amount of bits within the physical channel

NOTE 1: Three different bursts exist with different number of bits. The Traffic burst contains 264 bits, the CACH burst contains 24 bits and the RC burst contains 96 bits.

NOTE 2: The burst may include a guard time at the beginning and end of the burst used for power ramp-up and ramp-down.

NOTE 3: For detailed burst definition see clause 4.2.1.

call: complete sequence of related transactions between MSs

NOTE: Transactions may be one or more bursts containing specific call related information.

channel slot timing: time slot 1 and time slot 2 timing boundaries established by a TDMA direct mode leader

Control plane (C-plane): part of the DMR protocol stack dedicated to control and data services

Digital Mobile Radio (DMR): physical grouping that contains all of the mobile and/or fixed end equipment that is used to obtain DMR services

direct mode: mode of operation where MSs may communicate outside the control of a network

NOTE 1: This is communication technique where any radio unit (MS) may communicate with one or more other radio units (MSs) without the need for any additional equipment (e.g. BS).

NOTE 2: Supports one transmission per 12,5 kHz frequency; 12,5 kHz equivalent (12,5e) spectral efficiency.

duplex: mode of operation by which information can be transferred in both directions and where the two directions are independent

NOTE: Duplex is also known as full duplex.

frame: two contiguous time slots labelled 1 and 2

NOTE: A frame has a length of 60 ms.

inbound: MS to BS transmission

logical channel: distinct data path between logical endpoints

NOTE: The logical channels are labelled 1 and 2. The logical channel may consist of sub-channels, e.g. SYNC, embedded signalling, etc.

Mobile Station (MS): physical grouping that contains all of the mobile equipment that is used to obtain DMR mobile services

octet: 8 bits grouped together, also called a byte

outbound: BS to MS transmission

payload: bits in the information field

personalization: address and configuration information that characterizes a particular DMR MS

NOTE: This information may be programmed by the installer before putting an MS into service.

physical channel: RF carrier that is modulated with information bits of the bursts

NOTE: The RF carrier may be a single frequency or a duplex pair of frequencies. The physical channel of a DMR subsystem is required to support the logical channels.

polite protocol: "Listen Before Transmit" (LBT) protocol

NOTE: This is a medium access protocol that implements a LBT function in order to ensure that the channel is free before transmitting.

prefix: most significant digit of a MS address in the user domain

privacy: secret transformation

NOTE: Any transformation of transmitted information that is derived from a shared secret between the sender and receiver.

Protocol Data Unit (PDU): unit of information consisting of protocol control information (signalling) and possibly user data exchanged between peer protocol layer entities

Radio Frequency channel: Radio Frequency carrier (RF carrier)

NOTE: This is a specified portion of the RF spectrum. In DMR, the RF carrier separation is 12,5 kHz. The physical channel may be a single frequency or a duplex spaced pair of frequencies.

repeater mode: mode of operation where MSs may communicate through a BS

NOTE: This is a communication technique where any radio unit (MS) may communicate with one or more other radio units (MSs) with the need for an intermediate BS.

signalling: exchange of information specifically concerned with the establishment and control of connections, and with management, in a telecommunication network

simplex: mode of working by which information can be transferred in both directions but not at the same time

superframe: 6 continues traffic bursts on a logical channel labelled "A" to "F"

NOTE: A superframe has a length of 360 ms and is used for voice traffic only.

TDMA direct mode: direct mode operation that supports two transmissions per 12,5 kHz frequency

NOTE: Supports 6,25 kHz equivalent (6,25e) spectral efficiency.

time slot (or slot): elementary timing of the physical channel

NOTE: A timeslot has a length of 30 ms and will be numbered "1" or "2".

transmission: transfer period of bursts containing information or signalling

NOTE: The transmission may be continuous, i.e. multiple bursts transmission without ramp-up, ramp-down, or discontinuous, i.e. single burst transmission with ramp-up and ramp-down period.

trunking: network controlled communication

NOTE: This is a communication technique where any radio unit (MS) may communicate with one or more other radio units (MSs) using a trunking protocol and all MSs will be under control of a network.

user numbering: decimal representation of DMR air interface addresses

NOTE: The user numbering is that visible to a user or seen by the user.

User plane (U-plane): part of the DMR protocol stack dedicated to user voice services

wildcard: character in the user domain that represents all digits 0 to 9

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACK	(positive) ACKnowledgement
AI	Air Interface
AL	Accept Leader
ANL	Announce New Leader
AT	Access Type
BOC	Beginning Of Call
BOR	Beginning Of Repeat
BOT	Beginning Of Transmission
BS	Base Station
CACH	Common Announcement Channel
CBF	CSBK Blocks to Follow
CC	Colour Code
CCE	CT_CSBK Evaluation
CCITT	Consultative Committee on International Telegraphy and Telephony
CCL	Call Control Layer
CCL_1	Call Control Layer: Slot 1 process
CCL_2	Call Control Layer: Slot 2 process
CCL_BS	Call Control Layer: Both Slot process
C-plane	Control-plane
CRC	Cyclic Redundancy Checksum for data error detection
CSBK	Control Signalling BlocK
CSBKO	CSBK Opcode
CT	Channel Timing
CT_CSBK	Channel Timing CSBK
CTO	Channel Timing Opcode
DI	Dynamic Identifier
DLL	Data Link Layer
DMR	Digital Mobile Radio
EOC	End Of Call
EOR	End Of Repeat
EOT	End Of Transmission
FEC	Forward Error Correction
FID	Feature set ID

FLCO	Full Link Control Opcode
FNS	Feature Not Supported
Gen	Generation
GPS	Global Positioning System
Grp_V_Ch_Usr	Group Voice Channel User
HMSC	High level Message Sequence Chart
ID	Identifier
IO	Input Output
IP	Internet Protocol
LB	Last Block
LBT	Listen Before Transmit
LC	Link Control
LDI	Leader Dynamic Identifier
LDR	LeaDeR CT_CSBK evaluation
LID	Leader Identifier
LIP	Location Information Protocol
LLC	Logical Link Control
LSB	Least Significant Bit
LWATID	Leader Wide Area Timing IDentifier
MAC	Medium Access Control
MFID	Manufacturer's FID
MMI	Man Machine Interface
MS	Mobile Station (either portable or mobile unit)
MSB	Most Significant Bit
MSC	Message Sequence Chart
MS_DI	Mobile Station Dynamic Identifier
N xxxx	Layer 3 constant

NOTE: As defined in clause A.2.

NA	Not Applicable
NL	New Leader
OACSU	Off Air Call SetUp
OVCM	Open Voice Channel Mode service
PABX	Private Automatic Branch eXchange
PATCS	Press And Talk Call Setup
PDU	Protocol Data Unit
PF	Protect Flag
PL	Physical Layer
PSTN	Public Switched Telephone Network
PTT	Push-To-Talk
RC	Reason Code
RC	Reverse Channel
RF	Radio Frequency
RX	Receive
SA	Sync Age
SC	Send Correction
SDI	SourceDynamic Identifier
SDL	Specification and Description Language
SFID	Standards FID
SID	Source Identifier
SLCO	Short Link Control Opcode
SMS	Short Message Service
SO	Service Options
SWATID	Source Wide Area Timing IDentifier
SYNC	Synchronization
T xxxx	Layer 3 Timer

NOTE: As defined in clause A.1.

TD_LC	Terminator Data Link Control
TDMA	Time Division Multiple Access
TO	Time Out

*Itch STANDARD PREVIEW
[\(https://standards.iteh.ai/ccl-9e9d-907e2201e9d/catalog/standards/sist/3e798515-158f/Full%20standard%20-%20\(standards.iteh.ai\)\)](https://standards.iteh.ai/ccl-9e9d-907e2201e9d/catalog/standards/sist/3e798515-158f/Full%20standard%20-%20(standards.iteh.ai))*