



**Short Range Devices (SRD) operating in
the frequency range 25 MHz to 1 000 MHz;
Part 2: Harmonised Standard covering the essential
requirements of article 3.2 of the Directive 2014/53/EU
for non specific radio equipment**

PREVIEW
https://standards.iteh.ai/catalog/standards/sls/4512-b241-7d93b8a8df7c/et-300-220-2-v3-1-0-2016-05-30db-4512-b241-7d93b8a8df7c

Reference

REN/ERM-TG28-534

Keywords

Harmonised standard, radio, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols.....	9
3.3 Abbreviations	9
4 Technical requirements specifications	10
4.1 Environmental profile.....	10
4.2 All equipment conformance requirements	10
4.2.0 Compliance	10
4.2.1 Operating frequency	10
4.2.1.1 Description.....	10
4.2.1.2 Limits	10
4.2.1.3 Conformance.....	10
4.2.2 Unwanted emissions in the spurious domain	10
4.2.2.1 Description	10
4.2.2.2 Limits	10
4.2.2.3 Conformance.....	10
4.3 Transmitters conformance requirements	10
4.3.1 Effective Radiated Power	10
4.3.1.0 Applicability.....	10
4.3.1.1 Description	10
4.3.1.2 Limits	11
4.3.1.3 Conformance.....	11
4.3.2 Maximum e.r.p spectral density	11
4.3.2.0 Applicability.....	11
4.3.2.1 Description	11
4.3.2.2 Limits	11
4.3.2.3 Conformance.....	11
4.3.3 Duty Cycle	11
4.3.3.0 Applicability.....	11
4.3.3.1 Description	11
4.3.3.2 Limits	11
4.3.3.3 Conformance.....	11
4.3.4 Occupied Bandwidth.....	11
4.3.4.0 Applicability.....	11
4.3.4.1 Description	11
4.3.4.2 Limits	12
4.3.4.3 Conformance.....	12
4.3.5 Tx Out Of Band Emissions	12
4.3.5.0 Applicability.....	12
4.3.5.1 Description	12
4.3.5.2 Limits	12
4.3.5.3 Conformance.....	12
4.3.6 Transient power	12
4.3.6.0 Applicability.....	12
4.3.6.1 Description	12
4.3.6.2 Limits	12

4.3.6.3	Conformance	12
4.3.7	Adjacent Channel Power	12
4.3.7.0	Applicability.....	12
4.3.7.1	Description	12
4.3.7.2	Limits for equipment with operating channel width less than 25 kHz	12
4.3.7.3	Conformance	13
4.3.8	TX behaviour under Low Voltage Conditions.....	13
4.3.8.0	Applicability.....	13
4.3.8.1	Description	13
4.3.8.2	Limits	13
4.3.8.3	Conformance.....	13
4.3.9	Adaptive Power Control	13
4.3.9.0	Applicability.....	13
4.3.9.1	Description	13
4.3.9.2	Limits	13
4.3.9.3	Conformance.....	13
4.3.10	FHSS equipment.....	13
4.3.10.0	Applicability.....	13
4.3.10.1	Description	13
4.3.10.2	Limits	14
4.3.10.3	Conformance.....	14
4.3.11	Short term behaviour	14
4.3.11.0	Applicability.....	14
4.3.11.1	Description	15
4.3.11.2	Limits	15
4.3.11.3	Conformance.....	15
4.4	Receivers conformance requirements.....	15
4.4.1	RX sensitivity	15
4.4.1.0	Applicability.....	15
4.4.1.1	Description	15
4.4.1.2	Limits	15
4.4.1.3	Conformance.....	15
4.4.2	Blocking.....	15
4.4.2.0	Applicability.....	15
4.4.2.1	Description	15
4.4.2.2	Limits	15
4.4.2.3	Conformance.....	15
4.4.3	Clear Channel Assessment threshold.....	15
4.4.3.0	Applicability.....	15
4.4.3.1	Description	16
4.4.3.2	Limits	16
4.4.3.3	Conformance.....	16
4.4.4	Polite spectrum access	16
4.4.4.0	Applicability.....	16
4.4.4.1	Description	16
4.4.4.2	Limits	16
4.4.4.3	Conformance.....	16
4.5	Other conformance requirements	16
4.5.1	Adaptive Frequency Agility.....	16
4.5.1.0	Applicability.....	16
4.5.1.1	Description	16
4.5.1.2	Conformance.....	16
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	17
Annex B (normative):	EU wide harmonised national radio interfaces from 25 MHz to 1 000 MHz.....	19
Annex C (normative):	National Radio Interfaces not EU wide harmonised	22
Annex D (informative):	Application form for testing.....	27

D.1	Introduction	27
D.2	Information to declare according to ETSI EN 300 220-2	27
Annex E (informative):	Selection of technical parameters	29
E.1	Introduction	29
E.2	Receiver parameters	29
Annex F (informative):	Bibliography	30
Annex G (informative):	Change History	31
History		32

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/a8c5ac54-3ddb-4512-b241-7d93b8a8d7c/etsi-en-300-220-2-v3.1.1-2017-02>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.5] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 2 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part 2 of a multi-part deliverable, covering non specific Short Range Devices (SRD) operating in the frequency range 25 MHz to 1 000 MHz. Full details of the entire series can be found in part 1 [1].

The present document is structured as follows:

Clause 2 provides references.

Clause 3 provides definitions of terms and abbreviations used.

Clause 4 provides technical requirements.

Annex A (normative) provides a relationship between the present document and essential requirements of Directive 2014/53/EU [i.2].

Annex B (normative): EU wide harmonised national radio interfaces from 25 MHz to 1 000 MHz.

Annex C (informative): National Radio Interfaces not EU wide harmonised.

Annex D (informative): Application form for testing.

Annex E (informative): Selection of parameters.

Annex F (informative): Bibliography.

Annex G (informative): Change History.

ITEH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/a8c5ac54-3ddb-4512-b241-7d93b8a8d17c/etsi-en-300-220-2-v3.1.1-2017-02>

1 Scope

The present document applies to Non-specific Short Range Devices category equipment types.

Non specific SRDs category is defined by the EU Commission Decision 2013/752/EU [i.3] as:

"The non-specific short-range device category covers all kinds of radio devices, regardless of the application or the purpose, which fulfil the technical conditions as specified for a given frequency band. Typical uses include telemetry, telecommand, alarms, data transmissions in general and other applications".

The present document covers equipment intended for fixed, mobile or nomadic use, e.g.:

- stand-alone radio equipment;
- plug-in radio devices intended for use with or within a variety of host systems;
- plug-in radio devices intended for use within combined equipment.

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1.

Table 1: SRDs frequency ranges

Short Range Devices frequency ranges	
Transmit and receive	26,957 MHz to 27,283 MHz
Transmit and receive	40,660 MHz to 40,700 MHz
Transmit and receive	138,2 MHz to 138,45 MHz
Transmit and receive	169,4 MHz to 169,8125 MHz
Transmit and receive	433,040 MHz to 434,790 MHz
Transmit and receive	863 MHz to 876 MHz
Transmit and receive	915 MHz to 921 MHz
NOTE:	It should be noted that not all frequency bands in table 1 are implemented in all European countries. Annex B provides an overview of radio interfaces which are harmonised in the European Union. Annex C provides an overview of national radio interfaces not harmonised in the European Union.

It is noted that in the European Commission Decision on Short Range Devices [i.3], some harmonised frequency bands may be subject to usage restrictions such as the exclusion of video or audio use.

Equipment transmitting voice with analog modulation are excluded from the present document.

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 220-1 (V3.1.0) (05-2016): "Short Range Devices (SRD) operating in the frequency range 25 MHz to 1 000 MHz; Part 1: Technical characteristics and methods of measurement".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1] CEPT/ERC/REC 70-03: "Relating to the use of Short Range Devices (SRD)".

NOTE: Available at <http://www.erodocdb.dk/docs/doc98/official/pdf/rec7003e.pdf>.

[i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

[i.3] Commission Decision 2013/752/EC on harmonization of the radio spectrum for use by short-range devices as amended by subsequent Commission Decisions.

[i.4] ETSI EG 203 336: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

[i.5] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

[i.6] ECC Report 200: "Co-existence studies for proposed SRD and RFID applications in the frequency band 870-876 MHz and 915-921 MHz". September 2013.

[i.7] Commission Decision 2000/299/EU: "Commission Decision of 6 April 2000 establishing the initial classification of radio equipment and telecommunications terminal equipment and associated identifiers (notified under document number C(2000) 938) (Text with EEA relevance)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in RE-Directive [i.2] and ETSI EN 300 220-1 [1] apply.

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI EN 300 220-1 [1] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 300 220-1 [1] apply.

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile. Normal and extreme tests conditions are defined in ETSI EN 300 220-1 [1], clauses 4.3.3 and 4.3.4.

4.2 All equipment conformance requirements

4.2.0 Compliance

When an operational frequency band is selected from annex B or C for the equipment under test, the equipment shall comply with all parameters, exclusions and notes from the row in annex B or C unless a different National Radio Interface applies.

4.2.1 Operating frequency

4.2.1.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.1.1 applies.

4.2.1.2 Limits

The provider may declare either one or more operating frequencies and operating channels.

Operating channel(s) shall be included in operational frequency bands allowed by annex B or C.

4.2.1.3 Conformance

The conformance for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.1.2.

4.2.2 Unwanted emissions in the spurious domain

4.2.2.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.9.1 applies.

4.2.2.2 Limits

The EUT shall comply with reference limits defined in ETSI EN 300 220-1 [1], clause 5.9.2 under normal test condition.

4.2.2.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.9.3.

Conformance shall be established under normal test conditions.

4.3 Transmitters conformance requirements

4.3.1 Effective Radiated Power

4.2.1.0 Applicability

Effective radiated power applies only to transmitters.

4.3.1.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.2.1 applies.

4.3.1.2 Limits

The effective radiated power shall not be greater than the value allowed in annex B or C for the chosen operational frequency band(s). The signal shall be located within the operational frequency band.

4.3.1.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.2.2.

Conformance shall be established under normal and extreme test conditions.

4.3.2 Maximum e.r.p spectral density

4.3.2.0 Applicability

Maximum e.r.p. spectral density applies to transmitters using annex B bands I, L.

Maximum e.r.p. spectral density applies to transmitters using DSSS or other wideband techniques other than FHSS modulation in annex C band X.

4.3.2.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.3.1 applies.

4.3.2.2 Limits

The Maximum e.r.p. spectral density shall not be greater than the value allowed in annex B or C for the chosen operational frequency band(s).

4.3.2.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.3.2.

Conformance shall be established under normal test conditions.

4.3.3 Duty Cycle

4.3.3.0 Applicability

Duty cycle applies to all transmitters except EUT with polite spectrum access using bands L, M, N, O, P, R and X.

4.3.3.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.4.1 applies.

4.3.3.2 Limits

The Duty Cycle at the operating frequency shall not be greater than values in annex B or C for the chosen operational frequency band(s).

4.3.3.3 Conformance

The conformance tests for this requirement shall be as defined in ETSI EN 300 220-1 [1], clause 5.4.2.

4.3.4 Occupied Bandwidth

4.3.4.0 Applicability

Maximum occupied bandwidth applies to all transmitters.

4.3.4.1 Description

For the purpose of the present document, the description in ETSI EN 300 220-1 [1], clause 5.6.1 applies.