



SLOVENSKI STANDARD
SIST EN 301 908-21 V6.1.1:2016
01-julij-2016

Celična omrežja IMT - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU - 21. del: Uporabniška oprema FDD OFDMA TDD WMAN (mobilni WiMAX™)

IMT cellular networks - Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU - Part 21: OFDMA TDD WMAN (Mobile WiMAX™) FDD User Equipment (UE)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 908-21 V6.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/029eab3e-ceac-409f-baa1-d28603908c62/sist-en-301-908-21-v6-1-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/029eab3e-ceac-409f-baa1-d28603908c62/sist-en-301-908-21-v6-1-1-2016>

Ta slovenski standard je istoveten z: ETSI EN 301 908-21 V6.1.1 (2016-05)

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.99	Druge mobilne storitve	Other mobile services

SIST EN 301 908-21 V6.1.1:2016 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 908-21 V6.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/029eab3e-ceac-409f-baa1-d28603908c62/sist-en-301-908-21-v6-1-1-2016>

ETSI EN 301 908-21 V6.1.1 (2016-05)



IMT cellular networks;
Harmonised Standard covering the essential requirements
of article 3.2 of the Directive 2014/53/EU;
Part 21: OFDMA TDD WMAN (Mobile WiMAX™)
FDD User Equipment (UE)

SIST EN 301 908-21 V6.1.1:2016
<https://standards.globalspec.com/std/60122/baa1-d28603908c62/sist-en-301-908-21-v6-1-1-2016>

Reference

REN/MSG-TFES-11-21-RED

Keywords

FDD, IMT, IMT-2000, mobile, OFDMA, radio, regulation, WiMAX, WMAN

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 908-21 V6.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/029eab3e-ceac-409f-baa1-d28603908c02-2016-11-2016-1-v6-1-1-2016>
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	8
3.1 Definitions	8
3.2 Symbols.....	9
3.3 Abbreviations	10
4 Technical requirements specification.....	10
4.1 Environmental profile.....	10
4.2 Conformance requirements	10
4.2.0 General.....	10
4.2.1 Introduction.....	10
4.2.2 Transmitter spectrum emission mask.....	11
4.2.2.1 Definition	11
4.2.2.2 Limits	11
4.2.2.2.1 Requirements for 5 MHz channel bandwidth	11
4.2.2.2.2 Requirements for 10 MHz channel bandwidth	12
4.2.2.3 Conformance.....	12
4.2.3 Transmitter Adjacent Channel Leakage power Ratio (ACLR).....	12
4.2.3.1 Definition	12
4.2.3.2 Limits	12
4.2.3.2.1 ACLR requirements for 5 MHz bandwidth	12
4.2.3.2.2 ACLR requirements for 10 MHz bandwidth	12
4.2.3.3 Conformance.....	12
4.2.4 Transmitter spurious emissions.....	13
4.2.4.1 Definition	13
4.2.4.2 Limits	13
4.2.4.2.1 Requirements for 5 MHz channel bandwidth	13
4.2.4.2.2 Requirements for 10 MHz channel bandwidth	13
4.2.4.2.3 Requirements for UE coexistence	14
4.2.4.3 Conformance.....	14
4.2.5 Transmitter Maximum Output Power	14
4.2.5.1 Definition	14
4.2.5.2 Limits	14
4.2.5.3 Conformance.....	14
4.2.6 Transmitter Minimum Output Power.....	14
4.2.6.1 Definition	14
4.2.6.2 Limits	14
4.2.6.3 Conformance.....	14
4.2.7 Receiver spurious emissions	14
4.2.7.1 Definition	14
4.2.7.2 Limits	15
4.2.7.3 Conformance.....	15
4.2.8 Receiver Adjacent Channel Selectivity (ACS)	15
4.2.8.1 Definition	15
4.2.8.2 Limits	15
4.2.8.3 Conformance.....	16
4.2.9 Receiver blocking characteristics	16
4.2.9.1 Definition	16

4.2.9.2	Limits	16
4.2.9.3	Conformance	17
4.2.10	Receiver intermodulation characteristics	17
4.2.10.1	Definition and applicability	17
4.2.10.2	Limits	17
4.2.10.3	Conformance	17
4.2.11	Receiver spurious response	17
4.2.11.1	Definition	17
4.2.11.2	Limits	18
4.2.11.3	Conformance	18
4.2.12	Receiver reference sensitivity level	18
4.2.12.1	Definition	18
4.2.12.2	Limits	18
5	Testing for compliance with technical requirements	19
5.1	Environmental conditions for testing	19
5.2	Product information	19
5.3	Interpretation of the measurement results	19
5.4	Essential radio test suites	20
5.4.1	Transmitter Spectrum Emission Mask	20
5.4.1.1	Method of measurement	20
5.4.1.1.1	Initial conditions	21
5.4.1.1.2	Procedure	21
5.4.1.2	Test requirements	21
5.4.2	Transmitter Adjacent Channel Leakage Power Ratio	21
5.4.2.1	Method of measurement	22
5.4.2.1.1	Initial conditions	22
5.4.2.1.2	Procedure	22
5.4.2.2	Test requirements	23
5.4.3	Transmitter spurious emissions	23
5.4.3.1	Method of measurement	23
5.4.3.1.1	Initial conditions	24
5.4.3.1.2	Procedure	24
5.4.3.2	Test requirements	24
5.4.4	Transmitter Maximum and Minimum Output Power	24
5.4.4.1	Method of measurement	24
5.4.4.1.1	Initial conditions	25
5.4.4.1.2	Procedure	25
5.4.4.2	Test requirements	25
5.4.5	Receiver spurious emissions	25
5.4.5.1	Method of measurement	26
5.4.5.1.1	Initial conditions	26
5.4.5.1.2	Procedure	26
5.4.5.2	Test requirements	26
5.4.6	Receiver Adjacent Channel Selectivity (ACS)	26
5.4.6.1	Method of measurement	27
5.4.6.1.1	Initial conditions	27
5.4.6.1.2	Procedure	27
5.4.6.2	Test requirements	28
5.4.7	Receiver blocking characteristics	28
5.4.7.1	Method of measurement	28
5.4.7.1.1	Initial conditions	29
5.4.7.1.2	Procedure	29
5.4.7.2	Test requirements	29
5.4.8	Receiver intermodulation characteristics	29
5.4.8.1	Method of measurement	29
5.4.8.1.1	Initial conditions	30
5.4.8.1.2	Procedure	30
5.4.8.2	Test requirements	31
5.4.9	Receiver spurious response	31
5.4.9.1	Method of measurement	31
5.4.9.1.1	Initial conditions	31

5.4.9.1.2	Procedure.....	31
5.4.9.2	Test requirements.....	32
5.4.10	Receiver reference sensitivity level	32
5.4.10.1	Method of test	32
5.4.10.2	Test requirement	32
Annex A (normative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	33
Annex B (normative):	Environmental profile specification	35
Annex C (informative):	Void	36
Annex D (informative):	Bibliography.....	37
History		38

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 908-21 V6.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/029eab3e-ceac-409f-baa1-d28603908c62/sist-en-301-908-21-v6-1-1-2016>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.7] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 21 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.8].

iTech STANDARD PREVIEW
(standards.ittech.ai)

National transposition dates	
Date of adoption of this EN:	20 April 2016
Date of latest announcement of this EN (doa):	31 July 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2017
Date of withdrawal of any conflicting National Standard (dow):	31 January 2018

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI that is designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 366 [i.3] as applicable.

1 Scope

The present document applies to the following radio equipment type:

- Mobile WiMAX™ FDD User Equipment for IMT-OFDMA TDD WMAN.

This radio equipment type is capable of operating in all or any part of the frequency bands given in table 1-1.

Table 1-1: Mobile WiMAX™ FDD Operating frequency bands

Mobile WiMAX™ Band Class Index	Direction of transmission	Mobile WiMAX FDD frequency bands
7G	Transmit	880 MHz to 915 MHz
	Receive	925 MHz to 960 MHz
6C	Transmit	1 710 MHz to 1 785 MHz
	Receive	1 805 MHz to 1 880 MHz

The present document contains requirements to demonstrate that Radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Radio Equipment Directive 2014/53/EU [i.2] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] WMF-T25-002-R010v06 (2012): "WiMAX Forum® Test Procedures - Mobile Radio Conformance Tests" - Release 1 v06.
- [2] CEPT/ERC/Recommendation 74-01E (Siófok 98, Nice 99, Sesimbra 02, Hradec Kralove 05, Cardiff 11) (01-2011): "Unwanted emissions in the spurious domain".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Recommendation ITU-R SM.329-10 (2012): "Unwanted emissions in the spurious domain".

- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (Text with EEA relevance).
- [i.3] ETSI EG 203 336 (V1.1.1) (2015): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonized Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] ETSI EN 300 019-1-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [i.5] ETSI TR 102 215 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.6] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.8] ETSI EN 301 908-1 (V11.1.1): "IMT cellular networks; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU; Part 1: Introduction and common requirements".

iTech STANDARD PREVIEW
(standards.iteh.ai)

3 Definitions, symbols and abbreviations

3.1 Definitions

SIST EN 301 908-21 V6.1.1:2016

For the purposes of the present document, the terms and definitions given in the Directive 2014/53/EU [i.2] and the following apply:

burst: period during which radio waves are intentionally transmitted, preceded and succeeded by periods during which no intentional transmission is made

environmental profile: declared range of environmental conditions under which equipment within the scope of the present document is required to be compliant

Eval_BW 1: test condition where the pass band of a rectangular filter with a bandwidth of 4,75 MHz for 5 MHz equipment and 9,5 MHz for 10 MHz equipment is used for measurement centred on an operating channel or a victim channel

Eval_BW 2: measurement for EVAL_BW2 on the operating channel is performed using a rectangular filter with a 4,75 MHz or 9,5 MHz bandwidth and the measurement on the victim channel is performed using an RRC filter with a 3,84 MHz or 7,68 MHz bandwidth (respectively) both with roll-off factor of 0,22 centred on the 1st adjacent victim channel

integral antenna: antenna which is declared to be part of the radio equipment by the manufacturer

NOTE: Even when equipment with an integral antenna is concerned, it might still be possible to separate the antenna from the equipment using a special tool. In such cases the assessment of the radio equipment and of the antenna against requirements of this multi-part deliverable may be done separately.

maximum output power: mean power level per carrier of the base station measured at the antenna connector in a specified reference condition

mean power: power (transmitted or received) in a bandwidth when applied to a modulated signal

NOTE: The term "mean" here is used to exclude the amplitude fluctuation related to those theoretical variations present in signal for example due to amplitude modulation, pulse shaping, pre-equalization, etc. Time averaging should be applied to estimate mean power with the effect of the theoretical variations. The duty cycle corresponding to burst activity within a frame should be also incorporated for "mean" power estimation.

nominal maximum output power: maximum nominal mean power level measured over total allocated channel bandwidth of the user equipment available at the antenna connector declared by the manufacturer; for equipment implementing dynamic change of modulation format, it is intended as the maximum nominal mean power associated to the modulation format delivering the highest power

operating nominal RF channel width: nominal amount of spectrum used by a single device operating on an identified centre frequency

receiver thermal noise power: equal to $k \times T \times BW \times F$

WiMAX™: trademarked name for the OFDMA TDD WMAN IMT technology

NOTE: WiMAX™ is an example of a suitable technology available commercially. This information is given for the convenience of users of the present document and does not constitute an endorsement by ETSI of this technology.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

A_{BS}	Base Station Interface A
A_{MS}	Mobile Station Interface A
A_{UUT}	Unit Under Test Interface A
dB	decibel
dBc	decibel relative to P_{nom} carrier power measured in Eval_BW1
dBm	decibel relative to 1 milliwatt
BW	Assigned channel bandwidth
f	Frequency of measurement
F_c	centre frequency of the assigned channel
F	Receiver noise figure
k	Boltzmann's constant
GHz	GigaHertz
M_{BS}	Base Station Interface M
MHz	MegaHertz
M_{MS}	Mobile Station Interface M
N	Maximum number of antennas in a multiple antenna configuration
N_{th}	Receiver thermal noise power expressed in dBm
P_{SENS}	Receiver sensitivity level at $BER \leq 10^{-6}$ (or equivalent PER) performance corresponding to the most robust modulation and coding rate supported by the technology
P_{nom}	declared nominal maximum output Power
P_{SENS5}	sensitivity levels at $BER \leq 10^{-6}$, for a 5 MHz channel, corresponding to the most robust modulation and coding rate supported by the technology
P_{SENS10}	sensitivity levels at $BER \leq 10^{-6}$, for a 10 MHz channel, corresponding to the most robust modulation and coding rate supported by the technology
T	Ambient temperature in Kelvin

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
BER	Bit Error Ratio
BS	Base Station
BW	BandWidth
CW	Continuous Wave
EC	European Commission
EFTA	European Free Trade Association
ERM	Electromagnetic compatibility and Radio spectrum Matters
EUT	Equipment Under Test
FDD	Frequency Division Duplexing
IMT	International Mobile Telecommunications
MS	Mobile Station
MSG	Mobile Standards Group
OFDMA	Orthogonal Frequency-Division Multi Access
PER	Packet Error Ratio
RED	Radio Equipment Directive
RF	Radio Frequency
RMS	Root Mean Square
SM	Spectrum Management
TDD	Time Division Duplex
TFES	Task Force for European Standards for IMT
TPC	Transmit Power Control
UE	User Equipment
UUT	Unit Under Test
WMAN	Wireless Metropolitan Area Network

STANDARD PREVIEW
(standards.iteh.ai)

4 Technical requirements specification

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Conformance requirements

4.2.0 General

This clause describes the conformance requirements for OFDMA FDD WMAN User Equipment (UE).

4.2.1 Introduction

To meet the essential requirement under article 3.2 of the Directive 2014/53/EU [i.2] (Radio Equipment Directive) for IMT User Equipment (UE), a set of essential parameters in addition to those in ETSI EN 301 908-1 [i.8] have been identified. Table 4.2.1-1 provides a cross reference between these essential parameters and the corresponding technical requirements for equipment within the scope of the present document.

To fulfil an essential parameter the compliance with all the corresponding technical requirements in table 4.2.1-1 shall be verified.

Table 4.2.1-1: Cross references

Essential parameter	Corresponding technical requirements	Corresponding test suite
Transmitter spectrum mask		5.4.1
Transmitter unwanted emissions in the out of band domain	4.2.2 Transmitter Spectrum emissions mask	5.4.2
	4.2.3 Transmitter adjacent channel leakage power ratio	
Transmitter unwanted emissions in the spurious domain	4.2.4 Transmitter spurious emissions	5.4.4
Transmitter power limits	4.2.5 Transmitter maximum output power	5.4.4
Transmitter power accuracy	4.2.6 Transmitter minimum output power	5.4.4
Receiver unwanted emissions in the spurious domain	4.2.7 Receiver spurious emissions	5.4.5
Receiver blocking	4.2.9 Receiver Blocking characteristics	5.4.7
Receiver spurious response rejection	4.2.11 Receiver spurious response	5.4.9
Receiver radio-frequency intermodulation	4.2.10 Receiver Intermodulation characteristics	5.4.8
Receiver adjacent signal selectivity	4.2.8 Receiver Adjacent Channel Selectivity (ACS)	5.4.6
Receiver sensitivity	4.2.12 Receiver Reference Sensitivity level	5.4.10
Antenna		

Unless otherwise stated, the transmitter and receiver characteristics are specified at the antenna connector(s) of the UE. For UE(s) with an integral antenna only, a reference antenna(s) with a gain of 0 dBi should be assumed for each antenna port(s). A UE with integral antenna(s) may be taken into account by converting these power levels into field strength requirements, assuming a 0 dBi gain antenna.

4.2.2 Transmitter spectrum emission mask

4.2.2.1 Definition (standards.iteh.ai)

Spectrum emission mask defines an out of band emission requirement for the transmitter. These out of band emissions are unwanted emissions outside the channel bandwidth resulting from the modulation process and non-linearity in the transmitter but excluding spurious emissions.

4.2.2.2 Limits

A user equipment device transmitting on a single RF carrier configured in accordance with the manufacturer's specification shall meet the requirement. Emissions shall not exceed the maximum level specified in tables 4.2.2.2.1-1 and 4.2.2.2.2-1 for the appropriate UE maximum output power and nominal channel bandwidths of 5 MHz and 10 MHz.

Integration bandwidth refers to the frequency range over which the emission power is integrated.

Δf is defined as the frequency offset in MHz from the channel centre frequency.

4.2.2.2.1 Requirements for 5 MHz channel bandwidth

Table 4.2.2.2.1-1: Spectrum emission mask requirement

Segment number	Offset from channel centre frequency (Δf) (MHz)	Integration bandwidth (kHz)	Allowed emission level within the integration bandwidth (dBm)
1	2,5 to < 3,5	50	-13
2	3,5 to < 7,5	1 000	-10
3	7,5 to < 8,5	1 000	-13
4	8,5 to \leq 12,5	1 000	-25