



SLOVENSKI STANDARD

SIST EN 303 406 V1.1.1:2017

01-maj-2017

Naprave kratkega dosega (SRD) - Oprema za socialne alarme, ki deluje v frekvenčnem območju od 25 MHz do 1000 MHz - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU

Short Range Devices (SRD) - Social Alarms Equipment operating in the frequency range 25 MHz to 1 000 MHz - Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 303 406 V1.1.1:2017
https://standards.iteh.ai/catalog/standards/sist/8866d0e1-3a24-4d9a-ad75-e816de462cf3/sist-en-303-406-v1-1-1-2017](https://standards.iteh.ai/catalog/standards/sist/8866d0e1-3a24-4d9a-ad75-e816de462cf3/sist-en-303-406-v1-1-1-2017)

Ta slovenski standard je istoveten z: ETSI EN 303 406 V1.1.1 (2017-02)

ICS:

13.320	Alarmni in opozorilni sistemi	Alarm and warning systems
33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications

SIST EN 303 406 V1.1.1:2017

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 303 406 V1.1.1:2017](https://standards.iteh.ai/catalog/standards/sist/8866d0e1-3a24-4d9a-ad75-e816de462cf3/sist-en-303-406-v1-1-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/8866d0e1-3a24-4d9a-ad75-e816de462cf3/sist-en-303-406-v1-1-1-2017>

ETSI EN 303 406 V1.1.1 (2017-02)



**Short Range Devices (SRD);
Social Alarms Equipment operating
in the frequency range 25 MHz to 1 000 MHz;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU**

SIST EN 303 406 V1.1.1:2017
http://www.etsi.org/standards-store/catalogue.htm?cid=303406
e816de462cf3/sist-en-303-406-v1-1-1-2017

Reference

DEN/ERM-TG28-529

Keywords

alarm, harmonised standard, SRD

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 303 406 V1.1.1:2017

<https://standards.iteh.ai/catalog/standards/sist/8866d0e1-3a24-4d9a-ad75-e816de462188-41-30-41/v1-1-1-2017>
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols.....	9
3.3 Abbreviations	10
4 Technical requirements specifications	10
4.1 Environmental profile.....	10
4.2 Technical requirements for transmit mode.....	10
4.2.1 Applicability	10
4.2.2 Operating Frequency and Channel.....	10
4.2.2.1 Description.....	10
4.2.2.2 Limits	10
4.2.2.3 Conformance.....	10
4.2.3 Effective Radiated Power	10
4.2.3.1 Description	10
4.2.3.2 Limits	11
4.2.3.3 Conformance.....	11
4.2.4 Duty Cycle	11
4.2.4.1 Description and Applicability.....	11
4.2.4.2 Limits	11
4.2.4.3 Conformance.....	11
4.2.5 Short term behaviour	11
4.2.5.1 Description and applicability	11
4.2.5.2 Limits	11
4.2.5.3 Conformance.....	12
4.2.6 Adjacent Channel Power for OCW ≤ 25 kHz.....	12
4.2.6.1 Description and Applicability	12
4.2.6.2 Limits	12
4.2.6.3 Conformance.....	12
4.2.7 Occupied Bandwidth.....	12
4.2.7.1 Description and Applicability	12
4.2.7.2 Limits	12
4.2.7.3 Conformance.....	12
4.2.8 Tx Out Of Band Emissions	13
4.2.8.1 Description and Applicability	13
4.2.8.2 Limits	13
4.2.8.3 Conformance.....	13
4.2.9 Transmitter Frequency Error.....	13
4.2.9.1 Description and Applicability	13
4.2.9.2 Limits	13
4.2.9.3 Conformance.....	13
4.2.10 Transmitter Transient Power.....	13
4.2.10.1 Description	13
4.2.10.2 Limits	13
4.2.10.3 Conformance.....	14
4.2.11 Tx Behaviour under Low Voltage Conditions.....	14
4.2.11.1 Description and Applicability	14

4.2.11.2	Limits	14
4.2.11.3	Conformance	14
4.3	Technical requirements for all EUT	14
4.3.1	Applicability	14
4.3.2	Spurious Emissions	14
4.3.2.1	Description	14
4.3.2.2	Limits	14
4.3.2.3	Conformance	14
4.4	Receiver Parameters	14
4.4.1	Applicability	14
4.4.2	Blocking	15
4.4.2.1	Description	15
4.4.2.2	Limits	15
4.4.2.3	Conformance	15
5	Technical Requirements for Uni-Directional Communication	15
5.1	Mode A Applicability and Conformance Requirements	15
5.2	Communication method	15
5.3	Transmitter Parameters	15
5.4	Receiver Parameters	15
5.4.1	Applicability	15
5.4.2	Adjacent Channel Selectivity	15
5.4.2.1	Description	15
5.4.2.2	Limits	16
5.4.3	Blocking	16
5.4.3.1	Description	16
5.4.3.2	Limits	16
5.4.3.3	Conformance	16
5.4.4	Adjacent Channel Saturation	16
5.4.4.1	Description	16
5.4.4.2	Limits	16
5.4.4.3	Conformance	16
5.4.5	Spurious Response Rejection	16
5.4.5.1	Description	16
5.4.5.2	Limits	16
5.4.5.3	Conformance	16
5.4.6	Behaviour at high wanted signal level	17
5.4.6.1	Description	17
5.4.6.2	Limits	17
5.4.6.3	Conformance	17
6	Bi-Directional Communication with Frequency Agility	17
6.1	Mode BN Applicability and Conformance Requirements	17
6.2	Bi-directional Communication and Frequency Agility	17
6.2.1	Applicability	17
6.2.2	Acknowledgement	17
6.2.2.1	Description	17
6.2.2.2	Limits	17
6.2.2.3	Conformance	17
6.2.3	Ability to change communication frequency	18
6.2.3.1	Description	18
6.2.3.2	Limits	18
6.2.3.3	Conformance	18
6.3	Transmitter Parameters	18
6.4	Receiver Parameters	18
6.4.1	Applicability	18
6.4.2	Adjacent Channel Selectivity	18
6.4.2.1	Description	18
6.4.2.2	Limits	18
6.4.2.3	Conformance	18
6.4.3	Blocking	18
6.4.3.1	Description	18

6.4.3.2	Limits	19
6.4.3.3	Conformance	19
6.4.4	Adjacent Channel Saturation	19
6.4.4.1	Description	19
6.4.4.2	Limits	19
6.4.4.3	Conformance	19
6.4.5	Spurious Response Rejection.....	19
6.4.5.1	Description	19
6.4.5.2	Limits	19
6.4.5.3	Conformance	19
6.4.6	Behaviour at high wanted signal level	20
6.4.6.1	Description	20
6.4.6.2	Limits	20
6.4.6.3	Conformance	20
7	Testing for compliance with technical requirements.....	20
7.1	General	20
7.2	Presentation of equipment for testing purposes	20
7.3	Wanted performance criteria	21
7.3.1	Receiver response	21
7.4	Radio test suites - Transceivers	21
7.4.1	Frequency Agility	21
7.4.1.1	Description	21
7.4.1.2	Test Conditions	21
7.4.1.3	Method of measurement.....	21
7.4.1.4	Measurement procedure	21
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	23
Annex B (normative):	Operating bands and technical parameters	25
Annex C (informative):	Selection of technical parameters	27
C.1	Introduction	27
C.2	Receiver sensitivity	27
C.3	Other receiver parameters	27
C.4	Transmitter short term behaviour	27
C.5	Listen before talk.....	28
Annex D (informative):	Bibliography.....	29
History		30

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.10] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

(standards.iteh.ai)

National transposition dates	
Date of adoption of this EN:	10 February 2017
Date of latest announcement of this EN (doa):	31 May 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2017
Date of withdrawal of any conflicting National Standard (dow):	30 November 2018

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio equipment within the scope of the Radio Equipment Directive (RED) [i.2].

It is recognized that the radio communications link alone does not determine the overall operation of a system, but that a functioning radio communications link is an essential foundation upon which a system may be built.

The present document sets out various means and features by which the performance of a radio communications link may be improved. These include:

- 1) Spectrum Access Rules - with the aim of reducing the probability of collisions between transmissions from different equipment.
- 2) Receiver Parameters - with the aim of reducing the probability of interference from equipment on other frequencies.
- 3) Bi-Directional Communications - with the aim of reducing the time and number of transmissions required to achieve a given level of confidence in successful communication.
- 4) Frequency Agility - with the aim of enabling the equipment to change its operating frequency to avoid certain types of interference.

Application of these features, separately or in combination, does not necessarily ensure successful radio communication. In addition, there are other features that may be considered, such as listen before talk or error correction, that may improve overall performance.

Clauses 1 and 3 provide a general description on the types of equipment covered by the present document and the definitions and abbreviations used.

Clause 4 specifies technical requirements to be met by all equipment.

Clause 5 specifies technical requirements for receivers in equipment with uni-directional communications.

Clause 6 specifies technical requirements for equipment with bi-directional communications and frequency agility.

Clause 7 specifies the methods for testing for compliance with the technical requirements.

Annex A summarizes the requirements relevant to the RE-Directive [i.2].

1 Scope

The present document specifies technical characteristics and methods of measurements for social alarm systems operating on a range of frequencies that may be shared with other equipment types.

Social alarms are defined in Commission Decision 2013/752/EU [i.3] as:

"Social alarm devices" are radio communications systems that allow reliable communication for a person in distress in a confined area to initiate a call for assistance. Typical uses of social alarm are to assist elderly or disabled people.

These radio equipment types are capable of operating, for transmission or reception, in all or part of the frequency bands given in table 1.

Table 1: Frequency bands and usage information

Frequency band	Usage information
169,400 MHz to 169,8125 MHz	This band is shared with other SRD equipment
868,600 MHz to 868,700 MHz	This band is shared with other SRD alarm equipment
869,250 MHz to 869,400 MHz	This band is shared with other SRD alarm equipment
869,650 MHz to 869,700 MHz	This band is shared with other SRD alarm equipment
863,000 MHz to 870,000 MHz	This band is shared with other SRD equipment, except as noted above
870,000 MHz to 876,000 MHz	This band is shared with other SRD equipment
915,000 MHz to 921,000 MHz	This band is shared with other SRD equipment

NOTE 1: The probability of interference may be different when operating in bands shared with other short range devices compared to bands from which other short range devices are excluded.

NOTE 2: Social alarms operating in a designated band are covered in ETSI EN 300 220-3-1 [i.5].

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.2] under the conditions identified in annex A.

[SIST EN 303 406 V1.1.1:2017
https://standards.iteh.ai/catalog/standards/sist/8866d0e1-3a24-4d9a-ad75-e816de462cf3/sist-en-303-406-v1-1-1-2017](https://standards.iteh.ai/catalog/standards/sist/8866d0e1-3a24-4d9a-ad75-e816de462cf3/sist-en-303-406-v1-1-1-2017)

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 220-1 (V3.1.1) (02-2017): "Short Range Devices (SRD) operating in the frequency range 25 MHz to 1 000 MHz; Part 1: Technical characteristics and methods of measurement".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EG 203 336: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
 - [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (the "RED").
 - [i.3] Commission Decision 2013/752/EU amending Decision 2006/771/EC on harmonisation of the radio spectrum for use by short-range devices and repealing Decision 2005/928/EC.
 - [i.4] ETSI TS 103 060: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Method for a harmonized definition of Duty Cycle Template (DCT) transmission as a passive mitigation technique used by short range devices and related conformance test methods".
 - [i.5] ETSI EN 300 220-3-1: "Short Range Devices (SRD) operating in the frequency range 25 MHz to 1 000 MHz; Part 3-1: Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU; Low duty cycle high reliability equipment, social alarms equipment operating on designated frequencies (869,200 MHz to 869,250 MHz)".
 - [i.6] CEPT/ERC/REC 70-03: "Relating to the use of Short Range Devices (SRD)".
 - [i.7] ECC Report 37: "Compatibility of planned SRD applications with currently existing radiocommunications applications in the frequency band 863 - 870 MHz".
 - [i.8] ECC Report 181: "Improving spectrum efficiency in the SRD bands".
 - [i.9] "Channel Access Rules for SRDs", study by IMST GmbH (November 2012).
- NOTE: Available at http://www.bundesnetzagentur.de/SharedDocs/Downloads/DE/Sachgebiete/Telekommunikation/Unternehmen_Institutionen/Koexistenzstudie_3_EN.pdf?__blob=publicationFile&v=2
- [i.10] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the Directive 2014/53/EU [i.2], ETSI EN 300 220-1 [1] and the following apply:

mode A: mode of operation with uni-directional communication (specified in clause 5)

mode BN: mode of operation with bi-directional communication and frequency agility (specified in clause 6)

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI EN 300 220-1 [1] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 300 220-1 [1] and the following apply:

ACK	ACKnowledgement
ER-GSM	Extended Railway Global System for Mobile communications
MI	Message Initiator
MR	Message Responder

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile.

Normal and extreme test conditions are described in ETSI EN 300 220-1 [1], clauses 4.3.3 and 4.3.4.

4.2 Technical requirements for transmit mode

4.2.1 Applicability

The requirements in clause 4.2 apply to all EUT when operating in transmit mode, except where stated.

4.2.2 Operating Frequency and Channel

4.2.2.1 Description

The nominal operating frequency is the centre of a channel of width OCW.

4.2.2.2 Limits

The channel widths, OCW, shall comply with the limits given in annex B for the relevant band. The channels shall lie on a raster formed by the OCW and the edges of the bands.

4.2.2.3 Conformance

There is no conformance test specified for this requirement.

The manufacturer shall details of the operating frequency.

NOTE: More than one operating frequency on one or more channels may be declared.

4.2.3 Effective Radiated Power

4.2.3.1 Description

The effective radiated power (e.r.p) is the power radiated in the direction of the maximum field strength under specified conditions of measurements for any condition of modulation. For equipment with a permanent or temporary antenna connection it may be taken as the power delivered from that connector.

If the equipment is designed to operate with different carrier powers, the rated power for each level or range of levels shall be declared by the manufacturer.