

# ETSI TS 123 060 V12.11.0 (2016-03)



**Digital cellular telecommunications system (Phase 2+);  
Universal Mobile Telecommunications System (UMTS);  
General Packet Radio Service (GPRS);  
Service description;  
Stage 2  
(3GPP TS 23.060 version 12.11.0 Release 12)**



## Reference

---

RTS/TSGS-0223060vcb0

## Keywords

---

GSM,UMTS**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**Important notice**

---

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope .....	13
2 References .....	13
3 Definitions, abbreviations and symbols .....	18
3.1 Definitions .....	18
3.2 Abbreviations .....	19
3.3 Symbols.....	21
4 Main Concept.....	22
5 General GPRS Architecture and Transmission Mechanism.....	23
5.1 GPRS Access Interfaces and Reference Points .....	23
5.2 Network Interworking .....	24
5.2.1 Internet (IP) Interworking.....	24
5.3 High-Level Functions.....	24
5.3.0 General.....	24
5.3.1 Network Access Control Functions.....	24
5.3.1.1 Registration Function .....	24
5.3.1.2 Authentication and Authorisation Function.....	25
5.3.1.3 Admission Control Function .....	25
5.3.1.4 Message Screening Function.....	25
5.3.1.5 Packet Terminal Adaptation Function.....	25
5.3.1.6 Charging Data Collection Function.....	25
5.3.1.7 Operator Determined Barring Function.....	25
5.3.2 Packet Routing and Transfer Functions .....	25
5.3.2.1 Relay Function .....	25
5.3.2.2 Routing Function.....	25
5.3.2.3 Address Translation and Mapping Function .....	26
5.3.2.4 Encapsulation Function.....	26
5.3.2.5 Tunneling Function .....	26
5.3.2.6 Compression Function .....	26
5.3.2.7 Ciphering Function.....	26
5.3.2.8 Domain Name Server Function.....	26
5.3.2.9 DHCP function.....	26
5.3.3 Mobility Management Functions .....	26
5.3.3.1 General .....	26
5.3.3.2 Idle Mode Signalling Reduction Function .....	26
5.3.4 Logical Link Management Functions (A/Gb mode).....	27
5.3.4.1 Logical Link Establishment Function .....	27
5.3.4.2 Logical Link Maintenance Functions.....	27
5.3.4.3 Logical Link Release Function .....	27
5.3.5 Radio Resource Management Functions.....	27
5.3.5.1 General .....	27
5.3.5.2 RAT/Frequency Selection Priority.....	27
5.3.5.3 Service identification for improved radio utilisation for GERAN .....	28
5.3.6 Network Management Functions .....	29
5.3.6.1 General .....	29
5.3.6.1a GTP-C signalling based Load and Overload Control.....	29
5.3.6.2 NAS level congestion control .....	29
5.3.6.2.1 General .....	29
5.3.6.2.2 APN based Session Management congestion control.....	30

5.3.6.2.3	APN based Mobility Management congestion control .....	31
5.3.6.2.4	General NAS level Mobility Management congestion control .....	31
5.3.6.3	GGSN control of overload .....	32
5.3.6.4	SGSN control of overload .....	32
5.3.6.5	S4-SGSN control of overload .....	33
5.3.7	Selection functions .....	33
5.3.7.1	SGW/PGW/GGSN selection function (3GPP accesses) .....	33
5.3.7.2	Serving GW selection function .....	34
5.3.7.3	SGSN selection function .....	34
5.3.8	IMS voice over PS Session Supported Indication .....	34
5.3.8A	Homogenous Support of IMS Voice over PS Sessions Indication .....	35
5.3.9	Closed Subscriber Group functions .....	35
5.3.10	UE Reachability function .....	35
5.3.11	Location Service functions .....	35
5.3.12	Selected IP Traffic Offload (SIPTO) function .....	36
5.3.12.1	SIPTO with GW Selection .....	36
5.3.12.1A	SIPTO at the Local Network .....	36
5.3.12.1A.1	General .....	36
5.3.12.1A.2	SIPTO at the Local Network with stand-alone GW (S-GW/L-GW collocated) function .....	37
5.3.12.1A.3	SIPTO at the Local Network with L-GW function collocated with HNB .....	37
5.3.12.2	Support for SIPTO at Iu-ps .....	37
5.3.13	Machine Type Communication (MTC) .....	37
5.3.13.1	General .....	37
5.3.13.2	Overview of Protection from Potential MTC Related Overload .....	38
5.3.13.3	MS configuration and usage of indicators .....	39
5.3.13.4	Void .....	41
5.3.13.5	Optimizing periodic RAU Signalling .....	41
5.3.13.6	Support of MSs configured for low access priority, Extended Access Barring and permission for override .....	42
5.3.14	Local IP Access (LIPA) function .....	42
5.3.15	Voice domain preference and UE's usage setting .....	42
5.3.16	Support for Application / Service Layer Rate Adaptation .....	43
5.3.17	Support for subscriptions without MSISDN .....	43
5.3.18	PS-only Service Provision and PS domain SMS support .....	43
5.3.19	Access and Mobility Restrictions .....	45
5.3.20	MS Power Saving Mode .....	45
5.3.21	Access network selection and traffic steering based on RAN-assisted WLAN interworking .....	46
5.4	Logical Architecture .....	46
5.4.0	General .....	46
5.4.1	GPRS Core Network Nodes .....	48
5.4.1.1	General .....	48
5.4.1.2	Gateway GPRS Support Node .....	48
5.4.1.3	Serving GPRS Support Node .....	48
5.4.1.4	Serving Gateway .....	48
5.4.1.5	PDN Gateway .....	49
5.4.2	Packet Domain PLMN Backbone Networks .....	49
5.4.3	HLR/HSS .....	50
5.4.4	SMS-GMSC and SMS-IW MSC .....	50
5.4.5	Mobile Stations (A/Gb mode) .....	50
5.4.6	Mobile Stations (Iu mode) .....	51
5.4.7	Charging Gateway Functionality .....	51
5.4.8	PCRF .....	51
5.4.9	HNB subsystem .....	51
5.4.10	CSG Subscriber Server .....	52
5.5	Assignment of Functions to General Logical Architecture .....	53
5.6	User and Control Planes .....	54
5.6.1	User Plane (A/Gb mode) .....	54
5.6.1.1	MS – P-GW/GGSN .....	54
5.6.1.2	Core Network Node - Core Network Node .....	55
5.6.2	User Plane (Iu mode) .....	55
5.6.2.1	MS – GGSN user plane with GERAN in Iu mode .....	55
5.6.2.2	MS – P-GW/GGSN user plane with UTRAN .....	56

5.6.2.3	Core Network Node - Core Network Node	57
5.6.3	Control Plane	57
5.6.3.1	MS - SGSN (A/Gb mode)	58
5.6.3.2	MS - SGSN (Iu mode)	58
5.6.3.3	Gn/Gp-SGSN - HLR	59
5.6.3.4	SGSN - MSC/VLR	59
5.6.3.5	SGSN - EIR	59
5.6.3.5a	S4-SGSN - EIR	60
5.6.3.6	SGSN - SMS-GMSC or SMS-IW MSC	60
5.6.3.7	Core Network Node - Core Network Node	61
5.6.3.8	GGSN - HLR	61
5.6.3.8.1	MAP-based GGSN - HLR Signalling	61
5.6.3.8.2	GTP and MAP-based GGSN - HLR Signalling	62
5.6.3.9	S4-SGSN - HSS	62
5.6.3.10	Gn/Gp-SGSN - CSS	63
5.6.3.11	S4-SGSN - CSS	63
5.7	Functionality Needed for Mobile IPv4	63
5.8	Functionality for Intra Domain Connection of RAN Nodes to Multiple CN Nodes	64
5.9	Functionality for network sharing	64
5.10	IMS Emergency Session Support	64
5.10.1	Introduction	64
5.10.2	PS Domain Functions for IMS Emergency Session Support	65
5.10.2.1	General	65
5.10.2.2	Reachability Management for Emergency Attached MS in PMM-IDLE state	65
5.10.2.3	Mobility and Access Restrictions for Emergency Services	65
5.10.3	Attach handling	65
5.10.4	PDP Context Activation for emergency bearer services	66
5.10.5	Handling of PDN Connections for Emergency Bearer Services	67
6	Mobility Management Functionality	67
6.1	Definition of Mobility Management States	67
6.1.0	General	67
6.1.1	Mobility Management States (A/Gb mode)	67
6.1.1.1	IDLE (GPRS) State	67
6.1.1.2	STANDBY State	68
6.1.1.3	READY State	68
6.1.1.4	State Transitions and Functions	69
6.1.2	Mobility Management States (Iu mode)	70
6.1.2.1	PMM-DETACHED State	70
6.1.2.2	PMM-IDLE State	70
6.1.2.3	PMM-CONNECTED State	70
6.1.2.4	State Transitions and Functions	71
6.1.2.4.1	Handling of Un-synchronous States in the UE and the Network	72
6.2	Mobility Management Timer Functions	73
6.2.1	READY Timer Function (A/Gb mode)	73
6.2.2	Periodic RA Update Timer Function	73
6.2.3	Mobile Reachable Timer Function	74
6.3	Interactions Between SGSN and MSC/VLR	74
6.3.0	General	74
6.3.1	Administration of the SGSN - MSC/VLR Association	75
6.3.2	Combined RA / LA Updating	76
6.3.3	CS Paging (A/Gb mode)	77
6.3.3.1	Paging Co-ordination in A/Gb mode	78
6.3.4	CS Paging (Iu mode)	79
6.3.4.1	Network Operation Modes for Iu mode	79
6.3.4a	CS Paging (in case Selective RA Update)	80
6.3.5	Non-GPRS Alert	80
6.3.6	MS Information Procedure	80
6.3.7	MM Information Procedure	81
6.4	MM Procedures	81
6.5	GPRS Attach Function	82
6.5.0	General	82

6.5.1	A/Gb mode GPRS Attach Procedure .....	82
6.5.2	Iu mode GPRS Attach Procedure .....	83
6.5.3	Combined GPRS / IMSI Attach procedure.....	84
6.5.3A	Combined GPRS / IMSI Attach procedure, Delete Bearer by the new SGSN, using S4.....	90
6.5.3B	Combined GPRS / IMSI Attach procedure, Delete Bearer by the old SGSN, using S4 .....	90
6.6	Detach Function .....	91
6.6.1	MS-Initiated Detach Procedure.....	92
6.6.2	Network-Initiated Detach Procedure .....	93
6.6.2.1	SGSN-Initiated Detach Procedure .....	93
6.6.2.2	HLR-Initiated Detach Procedure.....	94
6.6.3	SGSN interaction during Detach Procedure when using S4 .....	95
6.7	Purge Function .....	96
6.8	Security Function .....	96
6.8.0	General.....	96
6.8.1	Authentication.....	96
6.8.1.1	GSM Authentication procedure .....	97
6.8.1.2	UMTS Authentication procedure .....	97
6.8.2	User Identity Confidentiality .....	98
6.8.2.1	User Identity Confidentiality (A/Gb mode) .....	98
6.8.2.2	User Identity Confidentiality (Iu mode).....	98
6.8.2.3	P-TMSI Signature .....	99
6.8.2.4	P-TMSI Reallocation Procedure .....	99
6.8.3	User Data and GMM/SM Signalling Confidentiality .....	99
6.8.3.1	Scope of Ciphering.....	99
6.8.3.2	Ciphering Algorithm .....	100
6.8.3.3	Start of Ciphering.....	100
6.8.4	Identity Check Procedures .....	100
6.8.5	Data Integrity Procedure (Iu mode).....	100
6.9	Location Management Function .....	101
6.9.0	General.....	101
6.9.1	Location Management Procedures (A/Gb mode).....	101
6.9.1.1	Cell Update Procedure .....	102
6.9.1.2	Routeing Area Update Procedure.....	102
6.9.1.2.0	General .....	102
6.9.1.2.1	Intra SGSN Routeing Area Update.....	103
6.9.1.2.2	Inter SGSN Routeing Area Update.....	105
6.9.1.2.2a	Inter SGSN Routeing Area Update and Combined Inter SGSN RA / LA Update using S4.....	109
6.9.1.3	Combined RA / LA Update Procedure.....	111
6.9.1.3.0	General .....	111
6.9.1.3.1	Combined Intra SGSN RA / LA Update .....	112
6.9.1.3.2	Combined Inter SGSN RA / LA Update .....	115
6.9.2	Location Management Procedures (Iu-mode).....	120
6.9.2.1	Routeing Area Update Procedure.....	121
6.9.2.1a	Routeing Area Update Procedure using S4.....	130
6.9.2.2	Serving RNS Relocation Procedures.....	132
6.9.2.2.1	Serving RNS Relocation Procedure.....	133
6.9.2.2.1a	Serving RNS Relocation Procedure, Combined Hard Handover and SRNS Relocation Procedure, and Combined Cell / URA Update and SRNS Relocation Procedure Using S4 .....	140
6.9.2.2.2	Combined Hard Handover and SRNS Relocation Procedure.....	141
6.9.2.2.3	Combined Cell / URA Update and SRNS Relocation Procedure.....	148
6.9.2.2.4	SRNS Relocation Cancel Procedure.....	154
6.9.2.2.4a	SRNS Relocation Cancel Procedure Using S4 .....	155
6.9.2.2.5	Enhanced Serving RNS Relocation Procedure.....	155
6.9.2.2.5A	Enhanced Serving RNS Relocation Procedure using S4 .....	157
6.9.3	Periodic RA and LA Updates .....	159
6.9.4	PS Handover Procedure .....	159
6.9.5	UE Radio Capability Match Request.....	160
6.10	Tunnelling of non-GSM Signalling Messages Function (A/Gb mode).....	161
6.10.1	Uplink Tunnelling of non-GSM Signalling Messages Procedure.....	161
6.10.2	Downlink Tunnelling of non-GSM Signalling Messages Procedure .....	162
6.11	Subscriber Management Function.....	162
6.11.1	Subscriber Management Procedures.....	162

6.11.1.1	Insert Subscriber Data Procedure .....	162
6.11.1.2	Delete Subscriber Data Procedure.....	163
6.11.1.3	Insert CSG Subscriber Data Procedure .....	164
6.12	Service Request Procedure (Iu mode) .....	164
6.12.0	General.....	164
6.12.1	MS Initiated Service Request Procedure Using Gn/Gp .....	165
6.12.1A	UE Initiated Service Request Procedure Using S4 .....	167
6.12.2	Network Initiated Service Request Procedure using Gn/Gp.....	168
6.12.2A	Void .....	170
6.13	Intersystem Change .....	171
6.13.1	Intra SGSN Intersystem Change.....	171
6.13.1.1	Iu mode to A/Gb mode Intra SGSN Change.....	171
6.13.1.1.1	Iu mode to A/Gb mode Intra SGSN Change using Gn/Gp.....	171
6.13.1.1.2	Iu mode to A/Gb mode Intra SGSN Change using S4.....	174
6.13.1.2	A/Gb mode to Iu mode Intra-SGSN Change.....	175
6.13.1.2.1	A/Gb mode to Iu mode Intra-SGSN Change using Gn/Gp.....	175
6.13.1.2.2	A/Gb mode to Iu mode Intra-SGSN Change using S4 .....	178
6.13.1.3	Selective RA Update .....	179
6.13.1.3.1	Uplink Signalling or Data Transmission .....	179
6.13.1.3.2	Downlink Signalling or Data Transmission.....	179
6.13.2	Inter-SGSN Inter-system Change .....	180
6.13.2.1	Iu mode to A/Gb mode Inter-SGSN Change.....	180
6.13.2.1.1	Iu mode to A/Gb mode Inter-SGSN Change using Gn/Gp.....	180
6.13.2.1.2	Iu mode to A/Gb mode Inter-SGSN Change using S4 .....	185
6.13.2.2	A/Gb mode to Iu mode Inter-SGSN Change.....	187
6.13.2.2.1	A/Gb mode to Iu mode Inter-SGSN Change using Gn/Gp.....	187
6.13.2.2.2	A/Gb mode to Iu mode Inter-SGSN Change using S4 .....	192
6.14	Classmark Handling .....	194
6.14.1	Radio Access Classmark.....	194
6.14.1.1	MS Radio Access Capability (A/Gb mode).....	194
6.14.1.2	UE Capability (Iu mode).....	195
6.14.2	Core Network Capability.....	196
6.15	UE Reachability procedures .....	196
6.16	Update CSG Location Procedure .....	197
7	Network Management Functionality .....	197
8	Radio Resource Functionality .....	198
8.1	Radio Resource Functionality (A/Gb mode) .....	198
8.1.1	Cell Selection and Reselection.....	198
8.1.2	Discontinuous Reception .....	198
8.1.3	Radio Resource Management .....	198
8.1.3.1	Layer Functions.....	198
8.1.3.2	Model of Operation.....	199
8.1.3.2.1	Dynamic Allocation of Radio Resources .....	199
8.1.3a	Ready to Standby state transition in S4 architecture.....	199
8.1.4	Paging for GPRS Downlink Transfer (A/Gb mode).....	199
8.1.4A	Paging response for GPRS Downlink Transfer with no established user plane on S4 .....	200
8.1.5	RAN Information Management (RIM) procedures.....	201
8.1.5.1	General .....	201
8.1.5.2	Addressing, routing and relaying .....	202
8.1.5.2.1	Addressing.....	202
8.1.5.2.2	Routing .....	202
8.1.5.2.3	Relaying.....	202
8.1.5.3	Void.....	202
8.1.5.4	Void.....	202
8.1.5.5	Applications using the RIM Procedures.....	202
8.1.6	BSS Paging Co-ordination.....	202
8.2	Radio Resource Functionality (Iu mode).....	203
8.2.1	Radio Resource Management .....	203
8.2.2	RRC State Machine .....	203
8.2.3	Discontinuous Reception .....	204

8.2.4	Paging Initiated by CN .....	204
8.2.4.1	PS Paging Initiated by SGSN (Iu mode) without RRC Connection for CS .....	205
8.2.4.1A	Serving GW Triggered Paging (Iu mode) with S4 .....	206
8.2.4.2	PS Paging Initiated by 3G-SGSN With RRC Connection for CS .....	206
8.2.5	Paging Initiated by RAN .....	207
9	Packet Routing and Transfer Functionality .....	207
9.1	Definition of Packet Data Protocol States .....	207
9.1.0	General .....	207
9.1.1	INACTIVE State .....	208
9.1.2	ACTIVE State .....	208
9.2	PDP Context Activation, Modification, Deactivation, and Preservation Functions .....	209
9.2.0	General .....	209
9.2.1A	Principles for mapping between PDP Contexts and EPS Bearers .....	212
9.2.1	Static and Dynamic PDP Addresses .....	212
9.2.1.1	Stateless IPv6 Address Autoconfiguration .....	214
9.2.1.2	IPv6 Prefix Delegation via DHCPv6 .....	216
9.2.2	Activation Procedures .....	217
9.2.2.1	PDP Context Activation Procedure .....	217
9.2.2.1A	PDP Context Activation Procedure using S4 .....	222
9.2.2.1.1	Secondary PDP Context Activation Procedure .....	226
9.2.2.1.1A	Secondary PDP Context Activation Procedure, PDP Creation part, using S4 .....	229
9.2.2.1.1B	Void .....	231
9.2.2.2	Network-Requested PDP Context Activation Procedure .....	231
9.2.2.2.1	Successful Network-Requested PDP Context Activation Procedure .....	232
9.2.2.2.2	Unsuccessful Network-Requested PDP Context Activation Procedure .....	232
9.2.2.3	Network Requested Secondary PDP Context Activation Procedure using Gn .....	234
9.2.2.3A	Network Requested Secondary PDP Context Activation Procedure using S4 .....	235
9.2.2.4	S4-SGSN triggered Serving GW relocation .....	237
9.2.3	Modification Procedures .....	238
9.2.3.0	General .....	238
9.2.3.1	SGSN-Initiated PDP Context Modification Procedure .....	240
9.2.3.1A	Request part of SGSN-Initiated EPS Bearer Modification Procedure using S4 .....	242
9.2.3.1B	Update part of SGSN-Initiated EPS Bearer Modification Procedure using S4 .....	243
9.2.3.2	SGSN-Initiated PDP Context Modification Procedure .....	243
9.2.3.2A	PDN GW Initiated EPS Bearer Modification Procedure, using S4 .....	246
9.2.3.3	MS-Initiated PDP Context Modification Procedure .....	247
9.2.3.3A	Request part of MS-Initiated EPS Bearer Modification Procedure using S4 .....	249
9.2.3.3B	Execution part of MS-Initiated Modification Procedure using S4 .....	252
9.2.3.3C	Response part of MS-Initiated Modification Procedure using S4 .....	253
9.2.3.4	RNC/BSS-Initiated PDP Context Modification Procedure .....	254
9.2.3.5	RAB Release-Initiated Local PDP Context Modification Procedure .....	255
9.2.3.6	RAN-initiated RAB Modification Procedure (Iu mode) .....	256
9.2.3.7	SGSN-initiated procedure on UE's CSG membership change .....	256
9.2.4	Deactivation Procedures .....	257
9.2.4.1	MS Initiated PDP Context Deactivation Procedure .....	257
9.2.4.1A	MS- and SGSN Initiated Bearer Deactivation Procedure using S4 .....	258
9.2.4.1A.1	MS-and SGSN Initiated PDN connection Deactivation Procedure using S4 .....	258
9.2.4.1A.2	MS-and SGSN Initiated Bearer Deactivation Procedure .....	259
9.2.4.2	SGSN-initiated PDP Context Deactivation Procedure .....	261
9.2.4.3	SGSN-initiated PDP Context Deactivation Procedure .....	262
9.2.4.3A	PDN GW initiated Bearer Deactivation Procedure using S4, part 1 .....	263
9.2.4.3B	PDN GW initiated Bearer Deactivation Procedure using S4, part 2 .....	264
9.2.5	Preservation Procedures .....	264
9.2.5.1	Release of RABs Triggered by an Iu mode RAN .....	264
9.2.5.1.1	RAB Release Procedure .....	264
9.2.5.1.2	Iu Release Procedure .....	264
9.2.5.2	Re-establishment of RABs .....	265
9.3	Packet Routing and Transfer Function .....	265
9.4	Relay Function .....	267
9.5	Packet Terminal Adaptation Function .....	267
9.6	Encapsulation Function .....	267

9.6.1	Encapsulation Between Core Network Nodes .....	268
9.6.2	Encapsulation Between SGSN and RAN in Iu mode .....	268
9.6.3	Encapsulation Between SGSN and MS in A/Gb mode.....	268
9.6.4	Encapsulation Between RAN and MS in Iu mode.....	268
9.7	Home NodeB Multicast Packet Forwarding Function.....	268
10	Message Screening Functionality.....	268
11	Compatibility Issues.....	268
11.1	Interaction between Releases 97/98 and 99.....	269
11.1.1	Interactions Between GTP v0 (R97) and GTP v1 (R99) .....	269
11.1.2	Interactions Between MS R97 and CN R99 .....	269
11.1.3	Interactions Between SM R97 and SM R99 .....	269
11.1.4	Interactions Between MAP R97 and MAP R99 .....	269
11.1a	Interactions between Release 7 and earlier Releases.....	269
11.1a.1	Interactions Between CN (R7) and Iu-mode RAN (pre-R7).....	269
11.1a.2	Interactions between CN and RAN to handle Rel-7 QoS extensions .....	269
11.2	Network Configuration for Interaction with E-UTRAN and S4-SGSNs .....	270
11.3	Interactions between CN and RAN to support higher bit rates .....	270
12	Transmission .....	270
12.1	Transmission Modes.....	270
12.1.1	GTP-U Transmission Modes .....	271
12.1.2	LLC Transmission Modes (A/Gb mode) .....	271
12.1.3	RLC Transmission Modes .....	271
12.2	Logical Link Control Functionality (A/Gb mode).....	271
12.2.1	Addressing .....	271
12.2.2	Services.....	271
12.2.3	Functions .....	272
12.3	Subnetwork Dependent Convergence Functionality (A/Gb mode).....	272
12.3.1	Services.....	273
12.3.2	Subfunctions .....	273
12.4	PDCP (Iu mode).....	274
12.5	Point-to-Point Protocol Functionality.....	274
12.5.1	User Plane for PDP Type PPP .....	274
12.5.2	Functions .....	275
12.6	Gb Interface (A/Gb mode).....	275
12.6.1	Physical Layer Protocol .....	275
12.6.2	Link Layer Protocols .....	275
12.6.3	BSS GPRS Protocol.....	275
12.6.3.1	Inter-dependency of the BSSGP and LLC Functions.....	276
12.6.3.2	BSSGP Addressing .....	276
12.6.3.3	BVCI Contexts in BSS and in SGSN.....	277
12.6.3.4	Flow Control Between SGSN and BSS over the Gb Interface.....	277
12.6.3.5	BSS Context .....	277
12.6.3.5.1	BSS Packet Flow Context Creation Procedure.....	278
12.6.3.5.2	SGSN-Initiated BSS Packet Flow Context Modification Procedure .....	279
12.6.3.5.3	BSS-Initiated BSS Packet Flow Context Modification Procedure .....	279
12.6.3.5.4	BSS Packet Flow Context Deletion Procedures .....	279
12.7	Iu Interface (Iu mode).....	280
12.7.1	Consistent Sequence Numbering of PDUs on Iu and Gn Interfaces.....	281
12.7.2	RAB Release Procedure.....	281
12.7.2.1	RAB Release Procedure using Gn/Gp.....	281
12.7.2.2	RAB Release Procedure using S4 .....	281
12.7.3	Iu Release Procedure .....	282
12.7.3.1	Iu Release Procedure Using Gn/Gp .....	282
12.7.3.2	Iu Release Procedure Using S4 .....	283
12.7.4	RAB Assignment Procedure .....	284
12.7.4.1	RAB Assignment Procedure Using Gn/Gp.....	284
12.7.4.2	RAB Assignment Procedure Using S4.....	285
12.7.5	Location Reporting Procedure .....	285
12.8	Abis Interface (A/Gb mode).....	286
12.8.1	Remote Packet Control Unit .....	287

12.9	Gn Interface (A/Gb mode).....	288
13	Information Storage.....	288
13.1	HLR/HSS .....	288
13.2	SGSN.....	291
13.2.1	General.....	291
13.2.2	Parameter exchange between S4-SGSNs.....	291
13.2.3	Context fields for one MS.....	292
13.2.4	SGSN Emergency Configuration Data for Iu Mode .....	296
13.3	GGSN .....	298
13.3a	Serving GW.....	299
13.3b	PDN GW .....	299
13.4	MS .....	300
13.5	MSC/VLR .....	301
13.6	BSS in A/Gb mode .....	301
13.7	RNC/BSC for Iu mode .....	302
13.8	Direct Tunnel specific error handling .....	302
13.9	Void.....	303
13.10	CSS.....	303
14	Identities .....	303
14.1	IMSI .....	303
14.2	Packet TMSI.....	303
14.2A	GUTI .....	303
14.3	NSAPI and TLLI for A/Gb mode.....	303
14.4	NSAPI, RB Identity, and RAB ID for Iu mode.....	304
14.4A	EPS Bearer Identity .....	305
14.5	PDP Address .....	305
14.6	TEID.....	305
14.7	Routeing Area Identity .....	306
14.8	RAN Registration Area Identity (Iu mode) .....	306
14.9	Cell Identity.....	306
14.10	Service Area Identity (Iu mode) .....	306
14.11	CN Node Addresses .....	307
14.11.1	CN Node Address .....	307
14.11.2	GSN Number .....	307
14.12	RNC/BSC Addresses (Iu mode).....	307
14.12.1	RNC/BSC Address .....	307
14.12.2	RNC/BSC Number .....	307
14.13	Access Point Name.....	307
14.14	Closed Subscriber Group ID .....	307
15	Operational Aspects .....	308
15.1	Charging.....	308
15.1.0	General.....	308
15.1.1	Charging Information .....	308
15.1.1a	General impacts of applying Flow Based Charging .....	309
15.1.2	Reverse Charging.....	310
15.1.3	Location and CSG dependent charging .....	310
15.1.3.1	Basic principles .....	310
15.1.3.2	Interaction with CGI / SAI / user CSG information reporting .....	312
15.1.3.2a	Interaction with CGI / SAI / user CSG information reporting using S4 .....	313
15.1.3.3	Reporting of Presence Reporting Area entering and leaving .....	313
15.2	Quality of Service Profile.....	314
15.2.0	General.....	314
15.2.1	Radio Priority Levels (A/Gb mode).....	315
15.2.1a	APN-AMBR .....	315
15.2.2	UE-AMBR.....	315
15.3	Traffic Flow Template.....	315
15.3.0	General.....	315
15.3.1	Rules for Operations on TFTs.....	317
15.3.2	Packet Filter Attributes .....	317
15.3.2.0	General .....	317

15.3.2.1	Remote Address and Subnet Mask.....	318
15.3.2.2	Protocol Number / Next Header.....	318
15.3.2.2A	Local Address and Mask.....	318
15.3.2.3	Port Numbers.....	318
15.3.2.4	IPSec Security Parameter Index.....	318
15.3.2.5	Type of Service / Traffic Class and Mask.....	318
15.3.2.6	Flow Label.....	318
15.3.3	Example Usage of Packet Filters.....	319
15.3.3.0	General.....	319
15.3.3.1	IPv4 Multi-field Classification.....	319
15.3.3.2	IPv4 TOS-based Classification.....	319
15.3.3.3	IPv4 Multi-field Classification for IPSec Traffic.....	319
15.3.3.4	Services with IP flows in only one direction.....	319
15.4	APN Restriction.....	319
15.5	Automatic Device Detection.....	320
15.6	Direct Tunnel Functionality.....	321
15.7	HPLMN Notification with specific indication due to SGSN initiated Bearer removal.....	322
16	Interactions with Other Services.....	322
16.0	General.....	322
16.1	Point-to-point Short Message Service.....	322
16.1.1	Mobile-terminated SMS Transfer.....	323
16.1.1.1	Unsuccessful Mobile-terminated SMS Transfer.....	324
16.1.2	Mobile-originated SMS Transfer.....	326
16.2	Circuit-switched Services (A/Gb mode).....	326
16.2.1	Suspension of GPRS Services.....	326
16.2.1.1	Suspend and Resume procedure (A/Gb mode).....	327
16.2.1.1.1	Intra-SGSN Suspend and Resume procedure.....	327
16.2.1.1.2	Inter-SGSN Suspend and Resume procedure.....	328
16.2.1.2	Inter-System Suspend and Resume procedure.....	329
16.2.1.2.1	Intra-SGSN Suspend and Resume procedure.....	329
16.2.1.2.2	Inter-SGSN Suspend and Resume procedure.....	330
16.2.1.3	Inter System Resume procedure.....	331
16.2.1.3.1	Intra-SGSN Resume procedure.....	331
16.2.1.3.2	Inter-SGSN Resume procedure.....	331
16.2.2	GPRS and Dedicated Mode Priority Handling.....	331
16.3	Supplementary Services.....	332
16.4	CAMEL Services.....	332
<b>Annex A (normative):</b>	<b>APN and P-GW/GGSN Selection.....</b>	<b>333</b>
A.0	General.....	333
A.1	Definitions.....	333
A.2	Selection Rules.....	334
<b>Annex B (informative):</b>	<b>Selected IP Traffic Offload at Iu-PS.....</b>	<b>344</b>
B.1	SIPTO with Traffic Offload Function.....	344
B.2	Support for SIPTO at Iu-ps.....	345
<b>Annex C (informative):</b>	<b>Link MTU considerations.....</b>	<b>346</b>
<b>Annex D (informative):</b>	<b>Change History.....</b>	<b>348</b>
History.....		352

---

## Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/c0c30185-a02f-4e03-9a28-d8e1534c1dc0/etsi-ts-123-060-v12.11.0-2016-03>