

SLOVENSKI STANDARD
SIST EN 303 413 V1.1.1:2017**01-september-2017**

Satelitske zemeljske postaje in sistemi (SES) - Sprejemniki globalnih navigacijskih satelitskih sistemov (GNSS) - Radijska oprema, ki deluje v frekvenčnem območju od 1164 MHz do 1300 MHz in od 1559 MHz do 1610 MHz - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU

Satellite Earth Stations and Systems (SES) - Global Navigation Satellite System (GNSS) receivers - Radio equipment operating in the 1 164 MHz to 1 300 MHz and 1 559 MHz to 1 610 MHz frequency bands - Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU

(standards.iteh.ai)

[SIST EN 303 413 V1.1.1:2017](https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017>

Ta slovenski standard je istoveten z: ETSI EN 303 413 V1.1.1 (2017-06)

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.070.40	Satelit	Satellite

SIST EN 303 413 V1.1.1:2017 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 303 413 V1.1.1:2017](https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017>

ETSI EN 303 413 V1.1.1 (2017-06)



**Satellite Earth Stations and Systems (SES);
Global Navigation Satellite System (GNSS) receivers;
Radio equipment operating in the 1 164 MHz to 1 300 MHz
and 1 559 MHz to 1 610 MHz frequency bands;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU**

Reference

DEN/SES-00404

Keywords

GNSS, harmonised standard, navigation,
receiver, satellite**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 303 413 V1.1.1:2017

<https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017>
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Executive summary	5
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations	9
4 Technical requirements specifications	10
4.1 Environmental profile.....	10
4.2 Conformance specifications	10
4.2.1 GUE adjacent frequency band selectivity performance.....	10
4.2.1.1 Definition	10
4.2.1.2 Specifications.....	10
4.2.1.3 Conformance.....	11
4.2.2 Spurious emissions	12
4.2.2.1 Definition	12
4.2.2.2 Limit.....	12
4.2.2.3 Conformance.....	12
5 Testing for conformance with technical requirements	12
5.1 Environmental conditions for testing.....	12
5.2 Interpretation of the measurement results	13
5.3 Test methodology for adjacent frequency band selectivity test.....	13
5.3.1 General.....	13
5.3.2 Test setup for conducted measurements	13
5.3.2.1 Test equipment.....	13
5.3.2.2 EUT configuration	13
5.3.3 Test setup for radiated measurements	14
5.3.3.1 General	14
5.3.3.2 Test equipment.....	14
5.3.3.3 EUT configuration	14
5.4 GUE adjacent frequency band selectivity test.....	15
5.4.1 General.....	15
5.4.2 Test conditions.....	15
5.4.3 Test method for GUE utilizing the 1 559 MHz to 1 610 MHz RNSS band.....	15
5.4.4 Test method for GUE utilizing the 1 164 MHz to 1 300 MHz RNSS bands	16
5.5 Receiver spurious emissions test	16
5.5.1 Test conditions.....	16
5.5.2 Test method	16
5.5.2.1 Conducted measurement	16
5.5.2.1.1 Introduction	16
5.5.2.1.2 Pre-scan	17
5.5.2.1.3 Measurement of the emissions identified during the pre-scan.....	18
5.5.2.2 Radiated measurement	18
Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU	19

Annex B (normative):	Details of parameters used in technical requirements specifications (clause 4)	20
B.1	Adjacent frequency signal	20
B.1.1	Definition	20
B.1.2	Recommended measurement technique for the adjacent frequency signal settings	21
B.2	GNSS signals	21
B.2.1	Definition	21
B.2.2	GNSS signal details	21
B.2.3	GNSS satellite details	22
Annex C (informative):	C/N₀ degradation metric	23
C.1	General	23
C.2	Definition	23
C.3	Example calculation of nominal 1 dB degradation of C/N ₀	23
Annex D (informative):	Test Report Application Form for ETSI EN 303 413	25
D.1	The right to copy	25
D.2	General	25
D.3	Information as required by clause 5.4.3 and clause 5.4.4	25
D.4	Information as required by clause 5.5	27
Annex E (informative):	Bibliography	28
Annex F (informative):	Change history	29
History		30

[SIST EN 303 413 V1.1.1:2017](https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.8] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

(standards.iteh.ai)

National transposition dates	
Date of adoption of this EN:	12 June 2017
Date of latest announcement of this EN (doa):	30 September 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2018
Date of withdrawal of any conflicting National Standard (dow):	31 March 2019

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Executive summary

The present document gives the technical requirements (clause 4) and test methodology (clause 5) for presumption of conformity of GNSS User Equipment with article 3.2 of the Radio Equipment Directive (2014/53/EU) [i.1].

Introduction

ETSI has designed a modular structure for the standards. Each standard is a module in the structure. The modular structure is shown in ETSI EG 203 336 [i.2].

The present document defines technical requirements to support the essential requirements of article 3.2 of the Radio Equipment Directive [i.1] which states "*Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*".

The present document does not contain any requirement, recommendation, or information about the installation of the GNSS user equipment.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 303 413 V1.1.1:2017](https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017>

1 Scope

The present document specifies technical characteristics and methods of measurements for Global Navigation Satellite System (GNSS) User Equipment (GUE).

Global Navigation Satellite System (GNSS) User Equipment (GUE) is capable of operating as part of one or more radionavigation-satellite service (RNSS) systems in the RNSS frequency bands given in table 1-1.

Table 1-1: Radionavigation-satellite service (RNSS) frequency bands

RNSS frequency bands	Comments
1 164 MHz to 1 300 MHz	space-to-Earth
1 559 MHz to 1 610 MHz	space-to-Earth

A GUE receives radio signals from one or more GNSS for the purpose of radiodetermination of the position, velocity, and/or other characteristics of an object, or the obtaining of information relating to those parameters, by means of the propagation properties of radio waves. RNSS is defined as "A radiodetermination-satellite service used for the purpose of radionavigation" (article 1.43 of ITU Radio Regulations [i.13]).

The present document applies to all GUE operating in the bands given in table 1-1 with the ability to receive any GNSS (e.g. Galileo, Global Positioning System (GPS), BeiDou (BDS), Global Navigation Satellite System (GLONASS), Space Based Augmentation Systems (SBAS)).

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.1] under the conditions identified in annex A.

iTeh STANDARD PREVIEW

2 References (standards.iteh.ai)

2.1 Normative references

SIST EN 303 413 V1.1.1:2017

<https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017>

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 328 (V2.1.1) (11-2016): "Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU".

2.2 Informative references

Informative references are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI EG 203 336 (V1.1.1) (08-2015): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.3] Recommendation ITU-R M.1787: "Description of systems and networks in the radionavigation-satellite service (space-to-Earth and space-to-space) and technical characteristics of transmitting space stations operating in the bands 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz".
- [i.4] Recommendation ITU-R M.1901: "Guidance on ITU-R Recommendations related to systems and networks in the radionavigation-satellite service operating in the frequency bands 1 164-1 215 MHz, 1 215-1 300 MHz, 1 559-1 610 MHz, 5 000-5 010 MHz and 5 010-5 030 MHz".
- [i.5] Recommendation ITU-R M.1902: "Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) operating in the band 1 215-1 300 MHz".
- [i.6] Recommendation ITU-R M.1903: "Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) and receivers in the aeronautical radionavigation service operating in the band 1 559-1 610 MHz".
- [i.7] Recommendation ITU-R M.1905: "Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) operating in the band 1 164-1 215 MHz".
- [i.8] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.9] CISPR 16-1-4 Ed.3.0 (2010): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".
- [i.10] ETSI TR 102 273 all parts: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.11] ETSI TR 100 028-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [i.12] ETSI TR 100 028-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.13] ITU Radio Regulations (edition of 2016).

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [i.1] and the following apply:

C/N_0 : carrier to noise-density ratio, expressed in dB-Hz

NOTE: The ratio of the received (GNSS) signal carrier power C , in dBW or dBm, to the noise power spectral density, in dBW/Hz or dBm/Hz, in the absence of interference.

$C/(N_0+I)$: carrier to noise-and-interference-density ratio, $C/(N_0+I)$, in dB-Hz

conducted measurements: measurements of the performance of the EUT made by direct wired connection to the antenna port

Equipment Under Test (EUT): equipment under test and subject to the performance requirements of the present document

GNSS User Equipment (GUE): radiodetermination equipment capable of receiving signals from one or more GNSS

NOTE: Such a receiver can acquire and then track GNSS signals to determine its location and/or velocity and/or time and/or other related parameters.

radiated measurements: measurements of the performance of the EUT made by placing the EUT in a suitable shielded container and radiating the required signals to the EUT

NOTE: I.e. without using a direct wired connection to the antenna port.

RadioNavigation-Satellite Service (RNSS): service(s) used for the purpose of radionavigation, that is for the determination of the position, velocity, and/or other characteristics of an object

NOTE: Includes the use of GNSS and other systems.

RNSS frequency band: continuous ranges of frequencies detailed in table 1-1, allocated by the ITU Radio Regulations to the RNSS [i.13]

spurious emissions: any unintentional GUE emissions, whether inside or outside the receiver bandwidth

NOTE: Since a GNSS receiver is receive-only, any emission is unintentional.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AM(R)S	Aeronautical Mobile (Route) Service
ARNS	Aeronautical RadioNavigation Service
AWGN	Additive White Gaussian Noise
BDS	BeiDou Navigation Satellite System

NOTE: See Recommendation ITU-R M.1787 [i.3], annex 7.

e.i.r.p.	effective isotropically radiated power
e.r.p.	effective radiated power
GPS	Global Positioning System

NOTE: See Recommendation ITU-R M.1787 [i.3], annex 2.

GLONASS GLObalnaya NAVigatsionnaya Sputnikovaya Sistema

NOTE: Latin transliteration of the Cyrillic abbreviation ГЛОНАСС which stands for Глобальная навигационная спутниковая система translating to Global Navigation Satellite System (see Recommendation ITU-R M.1787 [i.3], annex 1).

GNSS Global Navigation Satellite System
 GUE GNSS User Equipment
 ITU International Telecommunication Union
 MEO Medium Earth Orbit
 MSS Mobile Satellite Service
 OOBE Out-Of-Band Emissions
 RF Radio Frequency
 RNSS RadioNavigation Satellite Service

NOTE: See Recommendations ITU-R 1901 [i.4], 1902 [i.5], 1903 [i.6], 1905 [i.7].

RMS Root Mean Square
 SBAS Space Based Augmentation System

NOTE: See Recommendation ITU-R M.1787 [i.3], annex 8.

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the GUE, which shall be declared by the manufacturer. The GUE shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile. [SIST EN 303 413 V1.1.1:2017](https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/4907e74f-6332-4408-81dd-8077ab1eb385/sist-en-303-413-v1-1-1-2017>

4.2 Conformance specifications

4.2.1 GUE adjacent frequency band selectivity performance

4.2.1.1 Definition

GUE adjacent frequency band selectivity is the ability of the GUE to achieve the specified performance in the presence of noise produced by signals operating in accordance with the allocation table of the ITU Radio Regulations [i.13] in frequency bands adjacent or near-adjacent to the relevant RNSS band.

4.2.1.2 Specifications

The C/N_0 metric reported by the GUE for all GNSS and GNSS signals given in table 4-1 and supported by the GUE shall not degrade by more than the value given in equation 4-1 when an adjacent frequency signal is applied. The adjacent frequency signal is defined in table 4-4, with the frequencies and power levels defined in table 4-2 and/or in table 4-3 depending on the RNSS bands supported by the GUE.

Equation 4-1: Maximum degradation in C/N_0

$$\Delta C/N_0 \leq 1 \text{ dB} \quad (4-1)$$