

# ETSI TS 145 008 V13.0.0 (2016-01)



TECHNICAL SPECIFICATION

**Digital cellular telecommunications system (Phase 2+) (GSM);  
Radio subsystem link control  
(3GPP TS 45.008 version 13.0.0 Release 13)**

*PREVIEW*  
iTech Standards (standards.it-eah.net)  
Full standards catalog: <https://standards.it-eah.net/catalogue/standards/380faa61-b9a2-43d7-a7a4-38a614b03a51/3gpp-ts-45-008-v13-0-0-2016-01>



## Reference

---

RTS/TSGG-0145008vd00

## Keywords

---

LTE

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	8
1 Scope .....	9
1.1 References .....	9
1.2 Abbreviations .....	11
1.3 Definitions.....	11
1.4 Restrictions.....	11
2 General .....	11
3 Handover .....	13
3.1 Overall process.....	13
3.2 MS measurement procedure.....	13
3.3 BSS measurement procedure.....	13
3.4 Strategy .....	13
4 RF power control.....	14
4.1 Overall process.....	14
4.2 MS implementation .....	14
4.3 MS power control range .....	16
4.4 BSS implementation.....	16
4.4.1 VAMOS subchannel power control for BSS in downlink.....	16
4.5 BSS power control range.....	16
4.6 Strategy .....	16
4.7 Timing.....	17
4.7.1 Normal Power Control.....	17
4.7.2 Fast Power Control .....	17
4.7.3 Enhanced Power Control .....	18
4.8 Dedicated channels used for a voice group call or voice broadcast.....	18
5 Radio link failure.....	18
5.1 Criterion .....	18
5.2 MS procedure .....	19
5.3 BSS procedure.....	19
6 Idle mode tasks.....	19
6.1 Introduction .....	19
6.2 Measurements for normal cell selection.....	20
6.3 Measurements for stored list cell selection.....	21
6.4 Criteria for cell selection and reselection .....	21
6.5 Downlink signalling failure.....	23
6.6 Measurements for Cell Reselection.....	23
6.6.0 General.....	23
6.6.1 Monitoring of received signal level and BCCH data.....	24
6.6.1a Reduced Monitoring of received signal level and BCCH data .....	25
6.6.2 Path loss criteria and timings for cell re-selection .....	26
6.6.3 Cell reselection algorithm for SoLSA.....	26
6.6.4 Measurements on cells of other radio access technologies .....	27
6.6.5 Algorithm for cell re-selection from GSM to UTRAN based on cell ranking.....	31
6.6.6 Algorithm for inter-RAT cell re-selection based on priority information.....	32
6.6.7 Cell selection and re-selection to CSG cells and hybrid cells.....	35
6.6.7.1 Cell re-selection to CSG cells .....	35
6.6.7.1a Cell re-selection to hybrid cells.....	36
6.6.7.2 Manual CSG ID selection .....	36

6.7	Release of TCH, SDCCH and DBPSCH.....	36
6.7.1	Normal case .....	36
6.7.2	Call re-establishment .....	37
6.8	Abnormal cases and emergency calls.....	37
7	Network pre-requisites .....	38
7.1	BCCH carriers .....	38
7.2	Identification of surrounding BSS for handover measurements.....	40
7.3	Handover measurements on other radio access technologies.....	41
7.4	Handover measurements on UTRAN CSG cells and hybrid cells .....	44
8	Radio link measurements .....	45
8.1	Signal level.....	45
8.1.1	General.....	45
8.1.2	Physical parameter.....	45
8.1.3	Statistical parameters .....	46
8.1.4	Range of parameter.....	46
8.1.5	Measurement quantity for other radio access technologies .....	47
8.1.5.1	UTRAN FDD.....	47
8.1.5.2	UTRAN TDD.....	47
8.1.5.3	cdma2000.....	47
8.1.5.4	E-UTRAN FDD .....	48
8.1.5.5	E-UTRAN TDD.....	49
8.2	Signal quality.....	49
8.2.1	General.....	49
8.2.2	Physical parameter.....	49
8.2.3	Statistical parameters .....	50
8.2.3.1	RXQUAL .....	50
8.2.3.2	MEAN_BEP and CV_BEP .....	50
8.2.4	Range of parameter RXQUAL .....	51
8.2.5	Range of parameters MEAN_BEP and CV_BEP .....	52
8.3	Aspects of discontinuous transmission (DTX).....	56
8.4	Measurement reporting.....	57
8.4.1	Measurement reporting for the MS.....	57
8.4.1a	Measurement reporting for the MS in FPC mode .....	59
8.4.1b	Measurement reporting for the MS in EPC mode .....	59
8.4.2	Measurement reporting for the MS on a SDCCH.....	60
8.4.3	Additional cell reporting requirements for multi band MS .....	60
8.4.4	Common aspects for the MS on a TCH, a SDCCH or a DBPSCH.....	61
8.4.5	Measurement reporting for the BSS .....	61
8.4.6	Extended measurement reporting .....	62
8.4.7	Additional cell reporting requirements for multi-RAT MS .....	62
8.4.8	Enhanced Measurement Reporting.....	64
8.4.8.1	Reporting Priority .....	64
8.4.8.2	Measurement Reporting .....	65
8.4.8.3	NBR_RCVD_BLOCKS for FLO.....	66
8.4.9	Requirements for measurement and reporting of CSG cells and hybrid cells .....	66
8.5	Absolute MS-BTS distance .....	67
8.5.1	General.....	67
8.5.2	Physical parameter.....	67
9	Control parameters .....	68
10	GPRS mode tasks .....	76
10.1	Cell Re-selection .....	76
10.1.0	General.....	76
10.1.1	Monitoring the received signal level and PBCCH data .....	77
10.1.1.0	General .....	77
10.1.1.1	Packet idle mode or MAC-Idle state .....	78
10.1.1.2	Packet transfer mode or MAC-Shared state .....	78
10.1.1.2a	Broadcast/multicast receive mode.....	79
10.1.1.3	Monitoring cells of other radio access technologies .....	80
10.1.2	Cell Re-selection Criteria.....	84

10.1.3	Cell Re-selection Algorithm .....	85
10.1.3.1	Abnormal cell reselection .....	86
10.1.3.2	Algorithm for cell re-selection from GSM to UTRAN based on cell ranking .....	87
10.1.3.3	Algorithm for inter-RAT cell re-selection based on priority information .....	88
10.1.3.4	Cell selection and re-selection to CSG cells and hybrid cells .....	88
10.1.4	Network controlled Cell re-selection .....	88
10.1.4.1	Measurement reporting .....	89
10.1.4.2	Cell re-selection command .....	94
10.1.4.3	Exceptional cases .....	94
10.1a	Measurement and Reporting of CSG Cells and hybrid cells .....	94
10.2	RF Power Control .....	95
10.2.1	MS output power .....	95
10.2.2	BTS output power .....	96
10.2.3	Measurements at MS side .....	97
10.2.3.1	Deriving the C value .....	98
10.2.3.1.1	Packet idle mode or MAC-Idle state .....	98
10.2.3.1.2	Packet transfer mode or MAC-Shared state .....	98
10.2.3.2	Derivation of Channel Quality Report .....	100
10.2.3.2.1	Packet transfer mode or MAC-Shared state .....	100
10.2.3.2.2	Void .....	103
10.2.3.2.3	Measurement reporting .....	103
10.2.3.2.4	Measurement reporting - additional requirements for downlink dual carrier .....	104
10.2.3.2.5	Measurement reporting - additional requirements for downlink multi carrier .....	105
10.2.3.3	Range of parameters MEAN_BEP and CV_BEP for EGPRS2 .....	105
10.2.4	Measurements at BSS side .....	109
10.2a	Packet-switched Handover .....	109
10.3	Measurement requirements .....	109
10.4	Control parameters .....	109
11	CTS mode tasks .....	117
11.1	CTS idle mode tasks .....	117
11.1.1	CTS cell selection .....	118
11.1.1.1	Synchronization and measurements for CTS cell selection .....	118
11.1.1.2	Initial sychronization of CTS-MS .....	118
11.1.2	Criterion for CTS cell selection .....	118
11.1.3	Monitoring of CTSBCH and CTSPCH .....	119
11.1.3.1	Monitoring of received signal level .....	119
11.1.3.2	Downlink beacon failure .....	119
11.1.3.3	Downlink paging failure .....	119
11.1.4	Procedures with reporting to the CTS-FP .....	119
11.1.4.1	AFA monitoring .....	119
11.1.4.2	BCCH detection .....	120
11.1.4.3	Observed Frequency Offset (OFO) measurement .....	120
11.2	Intra-cell handover .....	120
11.2.1	Overall process .....	120
11.2.2	CTS-MS measurement procedure .....	120
11.2.3	CTS-FP measurement procedure .....	121
11.2.4	Strategy .....	121
11.3	RF power control .....	121
11.3.1	Overall process .....	121
11.3.2	CTS-MS implementation .....	121
11.3.3	CTS-MS power control range .....	121
11.3.4	CTS-FP implementation .....	122
11.3.5	CTS-FP power control range .....	122
11.3.6	Strategy .....	122
11.3.7	Timing .....	122
11.4	Radio link failure .....	122
11.4.1	Criterion .....	122
11.4.2	CTS-MS procedure .....	122
11.4.3	CTS-FP procedure .....	123
11.5	Radio link measurements .....	123
11.5.1	Signal strength .....	123

11.5.1.1	General .....	123
11.5.1.2	Physical parameter .....	123
11.5.1.3	Statistical parameters .....	123
11.5.1.4	Range of parameter .....	123
11.5.2	Signal quality .....	124
11.5.2.1	General .....	124
11.5.2.2	Physical parameter .....	124
11.5.2.3	Statistical parameters .....	124
11.5.2.4	Range of parameter .....	124
11.5.3	Aspects of discontinuous transmission (DTX) .....	124
11.5.4	Measurement reporting for the CTS-MS on a TCH .....	124
11.6	Control of CTS-FP service range .....	125
11.7	Control parameters .....	125
12	COMPACT Mode Tasks .....	127
12.1	Introduction .....	127
12.2	Network Pre-requisites .....	127
12.2.1	CPBCCCH carriers .....	127
12.3	COMPACT Idle Mode Tasks .....	127
12.3.1	Introduction .....	127
12.3.2	Measurements for COMPACT Cell Selection .....	127
12.3.3	Measurements for COMPACT Stored List Cell Selection .....	128
12.3.4	Criteria for COMPACT Cell Selection .....	128
12.3.5	Downlink Signalling Failure .....	128
12.4	COMPACT Cell Reselection .....	128
12.4.1	Monitoring the received signal level and CPBCCCH data .....	129
12.4.1.1	Packet idle mode or MAC-Idle state .....	129
12.4.1.2	Packet transfer mode or MAC-Shared state .....	129
12.4.2	COMPACT cell reselection criteria .....	130
12.4.3	COMPACT cell reselection algorithm .....	130
12.4.4	Network controlled Cell reselection .....	130
12.4.5	COMPACT cell reselection measurement opportunities .....	130
<b>Annex A (informative): Definition of a basic GSM or DCS 1 800 handover and RF power control algorithm .....</b>		<b>131</b>
A.1	Scope .....	131
A.2	Functional requirement .....	131
A.3	BSS pre-processing and threshold comparisons .....	132
A.3.1	Measurement averaging process .....	132
A.3.2	Threshold comparison process .....	133
A.3.2.1	RF power control process .....	133
A.3.2.2	Handover Process .....	134
A.4	BSS decision algorithm .....	135
A.4.1	Internal intracell handover according to radio criteria: (Interference problems) .....	135
A.4.2	Internal handover according to other criteria .....	136
A.4.3	General considerations .....	136
A.5	Channel allocation .....	136
A.6	Handover decision algorithm in the MSC .....	137
<b>Annex B (informative): Power Control Procedures .....</b>		<b>139</b>
B.1	Open loop control .....	139
B.2	Closed loop control .....	140
B.3	Quality based control .....	140
B.4	BTS power control .....	141
B.5	Example .....	141



B.6 Interworking between normal and fast power control for ECSD .....142

B.7 Interworking between normal and enhanced power control (EPC) .....143

**Annex C (informative): Example Interference Measurement Algorithm .....145**

**Annex D (informative): Example Selection of Modulation and Coding Schemes based on Link Quality Reports.....146**

**Annex E (informative): Change history .....147**

History .....157

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/380faa61-b9a2-43d7-a7a4-38a614b03a51/etsi-ts-145-008-v13.0.0-2016-01>



---

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/38a614b03a514b9a2-43d7-a7a4-38a614b03a51-etsi-ts-145-008-v13.0.0-2016-01>

# 1 Scope

The present document specifies the Radio sub-system link control implemented in the Mobile Station (MS), Base Station System (BSS) and Mobile Switching Centre (MSC) of the digital cellular telecommunications systems GSM.

Unless otherwise specified, references to GSM also include operation in any band.

## 1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: 'Vocabulary for 3GPP Specifications'.
- [2] 3GPP TS 23.003: 'Numbering, addressing and identification'.
- [3] 3GPP TS 23.009: 'Handover procedures'.
- [4] 3GPP TS 23.122: 'NAS Functions related to Mobile Station (MS) in idle mode'.
- [5] 3GPP TS 25.101: 'UE Radio transmission and reception (FDD)'.
- [6] 3GPP TS 25.123: 'Requirements for support of Radio Resource Management (TDD)'.
- [7] 3GPP TS 25.133: 'Requirements for support of Radio Resource Management (FDD)'.
- [8] 3GPP TS 25.304: 'UE Procedures in Idle Mode and Procedures for Cell Reselection in Connected Mode'.
- [9] 3GPP TS 25.331: 'Radio Resource Control (RRC); Protocol Specification'.
- [10] 3GPP TS 26.093: 'AMR Speech Codec; Source Controlled Rate operation'.
- [11] 3GPP TS 43.022: 'Functions related to Mobile Station (MS) in idle mode and group receive mode'.
- [12] 3GPP TS 43.064: 'Overall description of the GPRS Radio Interface; Stage 2'.
- [13] 3GPP TS 43.246: 'Multimedia Broadcast Multicast Service (MBMS) in the GERAN; Stage 2'.
- [14] 3GPP TS 43.068: 'Voice Group Call Service (VGCS); Stage 2'.
- [15] 3GPP TS 44.004: 'Layer 1; General requirements'.
- [16] 3GPP TS 44.006: 'Mobile Station - Base Station System (MS - BSS) interface; Data Link (DL) layer specification'.
- [17] 3GPP TS 44.018: 'Mobile radio interface layer 3 specification; Radio Resource Control Protocol'.
- [18] 3GPP TS 44.056: 'GSM Cordless Telephony System (CTS), Phase 1; CTS radio interface layer 3 specification'.
- [19] 3GPP TS 44.060: 'General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control (RLC) / Medium Access Control (MAC) protocol'.

- [20] 3GPP TS 44.118: 'Mobile radio interface layer 3 specification, Radio Resource Control (RRC) Protocol, Iu Mode'.
- [21] 3GPP TS 44.160: 'Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control/Medium Access Control (RLC/MAC) protocol; Iu mode'.
- [22] 3GPP TS 45.002: 'Multiplexing and multiple access on the radio path'.
- [23] 3GPP TS 45.003: 'Channel coding'
- [24] 3GPP TS 45.005: 'Radio transmission and reception'.
- [25] 3GPP TS 45.010: 'Radio subsystem synchronization'.
- [26] 3GPP TS 45.056: 'CTS-FP radio subsystem'.
- [27] 3GPP TR 45.902: 'Flexible Layer One'.
- [28] 3GPP TS 46.011: 'Full rate speech; Substitution and muting of lost frames for full rate speech channels'.
- [29] 3GPP TS 46.012: 'Full rate speech; Comfort noise aspect for full rate speech traffic channels'.
- [30] 3GPP TS 46.031: 'Full rate speech; Discontinuous Transmission (DTX) for full rate speech traffic channels'.
- [31] 3GPP TS 48.008: 'Mobile-services Switching Centre - Base Station System (MSC - BSS) interface, Layer 3 specification'.
- [32] 3GPP TS 48.058: 'Base Station Controller - Base Transceiver Station (BSC - BTS) interface; Layer 3 specification'.
- [33] 3GPP TS 51.010: 'Mobile Station (MS) conformity specification'.
- [34] 3GPP TS 51.011: 'Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface'.
- [35] TIA/EIA/IS-2000-5-A: 'Upper Layer (Layer 3) Signaling Standard for cdma2000 Spread Spectrum Systems'.
- [36] TIA/EIA/IS-833: 'Multi-Carrier Specification for Spread Spectrum Systems on GSM MAP (MC-MAP) (Lower Layers Air Interface)'.
- [37] 3GPP TS 36.101: 'Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception'.
- [38] 3GPP TS 36.104: 'Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception'.
- [39] 3GPP TS 36.133: 'Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for support of radio resource management'.
- [40] 3GPP TS 36.304: 'Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) procedures in idle mode'.
- [41] 3GPP TS 36.331: 'Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol Specification'.
- [42] 3GPP TS 31.102: 'Characteristics of the Universal Subscriber Identity Module (USIM) application'.
- [43] 3GPP TS 24.301: 'Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3'.
- [44] 3GPP TS 22.268: 'Public Warning System (PWS) requirements; Stage 1'.
- [45] 3GPP TS 23.251: "Network sharing; Architecture and functional description".

- [46] 3GPP TS 24.008: "Mobile Radio Interface Layer 3 specification; Core Network Protocols - Stage 3".
- [47] 3GPP TS 25.306: "UE Radio Access capabilities".
- [48] 3GPP TR 45.926: 'Solutions for GSM/EDGE BTS Energy Saving'.

## 1.2 Abbreviations

Abbreviations used in the present document are listed in 3GPP TR 21.905.

UFPS Unique Frequency Parameter Set

## 1.3 Definitions

**CSG Whitelist:** A list provided by NAS containing all the CSG identities and their PLMN IDs of the CSGs to which the subscriber belongs, see 3GPP TS 23.122 [4].

NOTE: This list is known as 'Allowed CSG List' in Rel-8 specifications.

**CSG cell:** The definition of CSG cell for UTRAN is given in 3GPP TS 25.304 [8]; the definition of CSG cell for E-UTRAN is given in 3GPP TS 36.304 [40].

**Hybrid cell:** The definition of hybrid cell for UTRAN is given in 3GPP TS 25.304 [8]; the definition of hybrid cell for E-UTRAN is given in 3GPP TS 36.304 [40].

**Network sharing:** network sharing is an optional feature that allows different core network operators to connect to the same shared radio access network (see 3GPP TS 23.251 [45]). When network sharing is in use within a given cell, the network broadcasts within system information the PLMN identities of the PLMNs sharing the cell. A mobile station supporting network sharing uses this information for its PLMN (re)selection processes and indicates the selected PLMN to the BSS.

**Power Efficient Operation (PEO):** see definition in 3GPP TS 43.064 [12].

**Power Saving Mode (PSM):** see definition in 3GPP TS 43.064 [12].

**Unique Frequency Parameter Set:** defined by a single ARFCN or a MA. In case of a radio frequency channel assigned a frequency parameter set consisting of a single ARFCN, the UFPS is defined by that ARFCN. In case of a radio frequency channel assigned a frequency parameter set consisting of a MA, MAIO and HSN, that radio frequency channel belong to the same UFPS as other radio frequency channels assigned the same MA.

## 1.4 Restrictions

Independently of what is stated elsewhere in this and other 3GPP specifications, mobile station support for PBCCH and PCCCH is optional for A/Gb-mode of operation. The network shall never enable PBCCH and PCCCH.

---

# 2 General

The radio sub-system link control aspects that are addressed are as follows:

- Handover;
- RF Power control in *A/Gb mode*, including fast power control for E-TCH and enhanced power control for TCH and O-TCH;
- RF Power control in *Iu mode*, including fast power control for E-TCH and enhanced power control for DBPSCH (in MAC-Dedicated and MAC-DTM states);
- Radio link Failure;

- Cell selection and re-selection in Idle mode, in Group Receive mode, in GPRS mode and in broadcast/multicast receive mode (see 3GPP TS 43.022);
- CTS mode tasks.

NOTE: A distinction is made between *A/Gb mode* and *Iu mode* only when necessary. Procedures and mechanisms described in this TS apply to both modes of operation unless otherwise stated. In *Iu mode*, unless otherwise stated, DBPSCH covers TCH, PDTCH and FLO.

Handover is required to maintain a call in progress as a MS engaged in a point-to-point call or with access to the uplink of a channel used for a voice group call passes from one cell coverage area to another and may also be employed to meet network management requirements, e.g. relief of congestion.

Handover may occur during a call from one TCH or multiple TCHs (in the case of multislot configuration) to another TCH or multiple TCHs. It may also occur from DCCH to DCCH or from DCCH to one or multiple TCH(s), e.g. during the initial signalling period at call set-up. Additionally in *Iu mode*, handover may occur in MAC-Dedicated and MAC-DTM states:

- on PDTCH or multiple PDTCHs (in the case of multislot configuration) on DBPSCH(s) to another PDTCH or multiple PDTCHs on DBPSCH(s);
- for FLO, from one DBPSCH or multiple DBPSCHs (in the case of multislot configuration) to another DBPSCH or multiple DBPSCHs.

The handover may be either from channel(s) on one cell to other channel(s) on a surrounding cell, or between channels on the same cell which are carried on the same frequency band. Examples are given of handover strategies, however, these will be determined in detail by the network operator.

For a multiband MS, the handover described is also allowed between any channels on different cells which are carried on different frequency bands, e.g. between a GSM 900/TCH and a DCS 1-800/TCH. Handover between two co-located cells, carried on different frequency bands, is considered as inter-cell handover irrespective of the handover procedures used.

For a multi-RAT MS, i.e. an MS supporting multiple radio access technologies, handover is allowed between GSM and other radio access technologies.

NOTE: At handover, the MS will normally not be able to verify the PLMN of the target cell and will thus assume that the same system information apply after the handover unless the network provides new system information.

Adaptive control of the RF transmit power from an MS and optionally from the BSS is implemented in order to optimize the uplink and downlink performance and minimize the effects of co-channel interference in the system.

The criteria for determining radio link failure are specified in order to ensure that calls which fail either from loss of radio coverage or unacceptable interference are satisfactorily handled by the network. Radio link failure may result in either re-establishment or release of the call in progress. For channels used for a voice group call, a radio uplink failure results in the freeing up of the uplink.

Procedures for cell selection and re-selection whilst in Idle mode (i.e. not actively processing a call), are specified in order to ensure that a mobile is camped on a cell with which it can reliably communicate on both the radio uplink and downlink. The operations of an MS in Idle Mode are specified in 3GPP TS 43.022.

Cell re-selection is also performed by the MS when attached to GPRS, except when the MS simultaneously has a circuit switched connection. Optional procedures are also specified for network controlled cell re-selection for GPRS. Cell re-selection for GPRS is defined in subclause 10.1.

For a multi-RAT MS, cell selection and re-selection is allowed between GSM and other radio access technologies.

An MS listening to a voice group call or a voice broadcast use cell re-selection procedures to change cell. This may be supported by a list of cells carrying the voice group or voice broadcast call downlink, provided to the MS by the network. The operations of an MS in Group Receive Mode are specified in 3GPP TS 43.022.

Information signalled between the MS and BSS is summarized in tables 1, 2 and 3. A full specification of the Layer 1 header is given in 3GPP TS 44.004, of the Layer 3 fields in 3GPP TS 44.018 and 3GPP TS 44.118, and of the Layer 2 fields in 3GPP TS 44.060 and 3GPP TS 44.160.