

# ETSI TS 148 018 V13.0.0 (2016-01)



**Digital cellular telecommunication system (Phase 2+) (GSM);  
General Packet Radio Service (GPRS);  
Base Station System (BSS)  
- Serving GPRS Support Node (SGSN);  
BSS GPRS protocol (BSSGP)  
(3GPP TS 48.018 version 13.0.0 Release 13)**



## Reference

---

RTS/TSGG-0248018vd00

## Keywords

---

LTE**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**Important notice**

---

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	13
1 Scope .....	14
2 References .....	14
3 Abbreviations .....	16
3.1 Vocabulary .....	16
4 Logical configuration of the Gb-interface.....	17
4.1 High-level characteristics of the Gb-interface .....	17
4.2 Position of BSSGP within the protocol stack on the Gb-interface .....	17
5 Elements for layer-to-layer communication.....	18
5.1 Definition of service model .....	18
5.2 Service primitives provided by the BSSGP at a BSS .....	20
5.2.1 RL-DL-UNITDATA.ind.....	22
5.2.2 RL-UL-UNITDATA.req.....	22
5.2.3 (void) .....	23
5.2.3a RL-DL-MBMS-UNITDATA.ind.....	23
5.2.3b RL-UL-MBMS-UNITDATA.req.....	23
5.2.4 GMM-PAGING.ind.....	23
5.2.5 GMM-RA-CAPABILITY.ind.....	23
5.2.6 GMM-RA-CAPABILITY-UPDATE.req.....	23
5.2.7 GMM-RA-CAPABILITY-UPDATE.cnf.....	23
5.2.8 GMM-RADIO-STATUS.req.....	23
5.2.9 GMM-SUSPEND.req.....	23
5.2.10 GMM-SUSPEND.cnf.....	23
5.2.11 GMM-RESUME.req.....	23
5.2.12 GMM-RESUME.cnf.....	23
5.2.12a GMM-MS-REGISTRATION-ENQUIRY.req.....	24
5.2.12b GMM-MS-REGISTRATION-ENQUIRY.res.....	24
5.2.13 NM-FLUSH-LL.ind.....	24
5.2.14 NM-FLUSH-LL.res.....	24
5.2.15 NM-LLC-DISCARDED.req.....	24
5.2.16 NM-FLOW-CONTROL-BVC.req.....	24
5.2.17 NM-FLOW-CONTROL-BVC.cnf.....	24
5.2.18 NM-FLOW-CONTROL-MS.req.....	24
5.2.19 NM-FLOW-CONTROL-MS.cnf.....	24
5.2.19a NM-FLOW-CONTROL-PFC.req.....	24
5.2.19b NM-FLOW-CONTROL-PFC.cnf.....	24
5.2.20 NM-STATUS.req.....	25
5.2.21 NM-STATUS.ind.....	25
5.2.22 NM-BVC-BLOCK.req.....	25
5.2.23 NM-BVC-BLOCK.cnf.....	25
5.2.24 NM-BVC-UNBLOCK.req.....	25
5.2.25 NM-BVC-UNBLOCK.cnf.....	25
5.2.26 NM-BVC-RESET.req.....	25
5.2.27 NM-BVC-RESET.res.....	25
5.2.28 NM-BVC-RESET.ind.....	25
5.2.29 NM-BVC-RESET.cnf.....	25
5.2.30 NM-TRACE.ind.....	25
5.2.30a NW-OVERLOAD.ind.....	25
5.2.31 PFM-DOWNLOAD-BSS-PFC.req.....	26

5.2.32	PFM-CREATE-BSS-PFC.ind	26
5.2.33	PFM-CREATE-BSS-PFC.res	26
5.2.34	PFM-MODIFY-BSS-PFC.req	26
5.2.35	(void)	26
5.2.36	(void)	26
5.2.37	PFM-MODIFY-BSS-PFC.cnf	26
5.2.38	PFM-DELETE-BSS-PFC.ind	26
5.2.39	PFM-DELETE-BSS-PFC.res	26
5.2.39a	PFM-DELETE-BSS-PFC.req	26
5.2.39b	PFM-PS-HANDOVER-REQUIRED.req	26
5.2.39c	PFM-PS-HANDOVER-REQUIRED.cnf	26
5.2.39d	PFM-PS-HANDOVER-REQUEST.ind	27
5.2.39e	PFM-PS-HANDOVER-REQUEST.res	27
5.2.39f	PFM-PS-HANDOVER-COMPLETE.req	27
5.2.39g	PFM-PS-HANDOVER-CANCEL.req	27
5.2.40	LCS-LOCATE.ind	27
5.2.41	LCS-LOCATE.res	27
5.2.42	LCS-ABORT.ind	27
5.2.43	LCS-INFORMATION-TRANSFER.req	27
5.2.44	LCS-INFORMATION-TRANSFER.cnf	27
5.2.45	RIM-PDU-TRANSFER.req	27
5.2.46	RIM-PDU-TRANSFER.ind	27
5.2.47	(void)	28
5.2.48	(void)	28
5.2.49	(void)	28
5.2.50	(void)	28
5.2.51	(void)	28
5.2.52	(void)	28
5.2.53	MBMS-SESSION-START-REQUEST.ind	28
5.2.54	MBMS-SESSION-START-RESPONSE.res	28
5.2.55	MBMS-SESSION-STOP-REQUEST.ind	28
5.2.56	MBMS-SESSION-STOP-RESPONSE.res	28
5.2.57	MBMS-SESSION-UPDATE-REQUEST.ind	28
5.2.58	MBMS-SESSION-UPDATE-RESPONSE.res	28
5.3	Service primitives provided by the BSSGP at an SGSN	28
5.3.1	BSSGP-DL-UNITDATA.req	31
5.3.2	BSSGP-UL-UNITDATA.ind	32
5.3.3	(void)	32
5.3.3a	BSSGP-DL-MBMS-UNITDATA.req	32
5.3.3b	BSSGP-UL-MBMS-UNITDATA.ind	32
5.3.4	GMM-PAGING.req	32
5.3.5	GMM-RA-CAPABILITY.req	32
5.3.6	GMM-RA-CAPABILITY-UPDATE.ind	32
5.3.7	GMM-RA-CAPABILITY-UPDATE.res	32
5.3.8	GMM-RADIO-STATUS.ind	32
5.3.9	GMM-SUSPEND.ind	32
5.3.10	GMM-RESUME.ind	32
5.3.10a	GMM-MS-REGISTRATION-ENQUIRY.ind	32
5.3.10b	GMM-MS-REGISTRATION-ENQUIRY.res	33
5.3.11	NM-FLUSH-LL.req	33
5.3.12	NM-FLUSH-LL.cnf	33
5.3.13	NM-LLC-DISCARDED.ind	33
5.3.14	NM-FLOW-CONTROL-BVC.ind	33
5.3.15	NM-FLOW-CONTROL-MS.ind	33
5.3.15a	NM-FLOW-CONTROL-PFC.ind	33
5.3.16	NM-STATUS.req	33
5.3.17	NM-STATUS.ind	33
5.3.18	NM-BVC-BLOCK.ind	33
5.3.19	NM-BVC-UNBLOCK.ind	33
5.3.20	NM-BVC-RESET.req	33
5.3.21	NM-BVC-RESET.res	34
5.3.22	NM-BVC-RESET.ind	34

5.3.23	NM-BVC-RESET.cnf.....	34
5.3.24	NM-TRACE.req.....	34
5.3.24a	NM-OVERLOAD-START.req.....	34
5.3.25	PFM-DOWNLOAD-BSS-PFC.ind.....	34
5.3.26	PFM-CREATE-BSS-PFC.req.....	34
5.3.27	PFM-CREATE-BSS-PFC.cnf.....	34
5.3.28	PFM-MODIFY-BSS-PFC.ind.....	34
5.3.29	PFM-MODIFY-BSS-PFC.res.....	34
5.3.30	PFM-DELETE-BSS-PFC.req.....	34
5.3.31	PFM-DELETE-BSS-PFC.cnf.....	34
5.3.31a	PFM-DELETE-BSS-PFC.ind.....	35
5.3.31b	PFM-PS-HANDOVER-REQUIRED.ind.....	35
5.3.31c	PFM-PS-HANDOVER-REQUIRED.res.....	35
5.3.31d	PFM-PS-HANDOVER-REQUEST.req.....	35
5.3.31e	PFM-PS-HANDOVER-REQUEST.cnf.....	35
5.3.31f	PFM-PS-HANDOVER-COMPLETE.ind.....	35
5.3.31g	PFM-PS-HANDOVER-CANCEL.ind.....	35
5.3.32	LCS-LOCATE.req.....	35
5.3.33	LCS-LOCATE.cnf.....	35
5.3.34	LCS-ABORT.req.....	35
5.3.35	LCS-INFORMATION-TRANSFER.ind.....	35
5.3.36	LCS-INFORMATION-TRANSFER.res.....	36
5.3.37	RIM-PDU-TRANSFER.req.....	36
5.3.38	RIM-PDU-TRANSFER.ind.....	36
5.3.39	(void).....	36
5.3.40	(void).....	36
5.3.41	(void).....	36
5.3.42	(void).....	36
5.3.43	(void).....	36
5.3.44	(void).....	36
5.3.45	MBMS-SESSION-START-REQUEST.req.....	36
5.3.46	MBMS-SESSION-START-RESPONSE.cnf.....	36
5.3.47	MBMS-SESSION-STOP-REQUEST.req.....	36
5.3.48	MBMS-SESSION-STOP-RESPONSE.cnf.....	36
5.3.49	MBMS-SESSION-UPDATE-REQUEST.req.....	36
5.3.50	MBMS-SESSION-UPDATE-RESPONSE.cnf.....	37
5.4	Primitive parameters.....	37
5.4.1	BSSGP Virtual Connection Identifier (BVCI).....	37
5.4.2	Link Selector Parameter (LSP).....	38
5.4.3	[functional-name] PDU.....	38
5.4.4	Network Service Entity Identifier (NSEI).....	39
5.4.5	BSS Context.....	39
5.4.6	MBMS Service Context.....	39
5.4.7	TLLI.....	39
6	User data and signalling procedures between RL and BSSGP SAPs.....	39
6.1	Downlink UNITDATA procedure.....	39
6.1.1	Abnormal conditions.....	41
6.2	Uplink UNITDATA procedure.....	41
6.2.1	Abnormal conditions.....	42
6.3	RA-CAPABILITY procedure.....	42
6.3.1	Abnormal conditions.....	42
6.4	Downlink MBMS-UNITDATA procedure.....	42
6.5	Uplink MBMS-UNITDATA procedure.....	43
6.6	Rerouting procedure in case of MOCN configuration for network sharing.....	43
6.6.1	General.....	43
6.6.2	Reroute Indication.....	44
6.6.3	Reroute complete.....	45
6.6.4	Abnormal Conditions.....	45
6.7	Rerouting procedure in case of GWCN configuration for network sharing.....	45
6.7.1	General.....	45
6.7.2	Reroute indication.....	46

6.7.3	Reroute complete .....	47
6.7.4	Abnormal Conditions.....	47
7	Signalling procedures between GMM SAPs .....	47
7.1	Paging procedure.....	47
7.2	Radio Access Capability Update procedure .....	48
7.2.1	Abnormal conditions.....	49
7.3	Radio Status procedure.....	49
7.4	SUSPEND procedure .....	50
7.4.1	Abnormal conditions.....	50
7.5	RESUME procedure.....	50
7.5.1	Abnormal conditions.....	51
7.6	MS Registration Enquiry.....	51
7.6.1	General.....	51
7.6.2	Registration enquiry.....	51
7.6.3	Registration response.....	52
8	Signalling procedures between NM SAPs .....	52
8.1	FLUSH-LL (logical link) procedure.....	52
8.1.1	Abnormal Conditions.....	53
8.2	Flow Control procedure.....	53
8.2.1	General model of operation .....	53
8.2.2	Mode of operation.....	54
8.2.3	Flow Control of Traffic from an SGSN to BSS.....	55
8.2.3.1	Control of the downlink throughput by the SGSN.....	55
8.2.3.2	Flow Control Conformance Definition .....	56
8.2.3.3	Response time within the SGSN to flow control messages.....	58
8.2.3.4	Frequency of sending BVC or MS or PFC Flow Control PDUs.....	58
8.2.3.5	FLOW-CONTROL PDUs.....	58
8.2.3.6	Condition of Bmax for MS after Initial Flow-Control-BVC.....	59
8.2.4	Flow Control of Uplink Traffic from a BSS to an SGSN.....	59
8.3	BVC blocking and unblocking procedure .....	59
8.3.1	PTP BVC.....	59
8.3.2	Signalling BVC.....	60
8.3.3	Abnormal Conditions.....	60
8.4	BVC-RESET procedure .....	61
8.4.1	Signalling BVC.....	62
8.4.2	PTP BVC.....	62
8.4.3	Abnormal Conditions.....	62
8.5	Trace procedure.....	63
8.6	Overload Control procedure.....	63
8.6.1	General.....	63
8.6.2	Overload Operation.....	63
8a	Signalling procedures between PFM SAPs .....	64
8a.1	Create BSS PFC procedure .....	64
8a.1.0	General.....	64
8a.1.0a	Allocation/Retention Priority handling.....	65
8a.1.1	Abnormal conditions.....	66
8a.2	Modify BSS PFC procedure.....	66
8a.2.1	Abnormal conditions.....	67
8a.3	Delete BSS PFC procedure .....	67
8a.4	PS Handover Required procedure .....	67
8a.4.1	Abnormal conditions.....	69
8a.5	PS Handover Request procedure.....	69
8a.5.1	Abnormal conditions.....	70
8a.6	PS Handover Complete procedure .....	71
8a.6.1	Abnormal conditions.....	72
8a.7	PS Handover Cancel procedure.....	72
8a.7.1	Abnormal conditions.....	73
8b	Signalling Procedures between LCS SAPs .....	73
8b.1	Location Procedure.....	73

8b.1.1	Unsuccessful Operation .....	73
8b.1.2	Abnormal Conditions.....	73
8b.1.3	Overload .....	74
8b.2	Position Command Procedure .....	74
8b.2.1	Position Command.....	74
8b.2.2	Position Response.....	74
8b.2.3	Unsuccessful Operation .....	74
8c	Signalling procedures between RIM SAPs .....	75
8c.1	General .....	75
8c.1.1	Introduction.....	75
8c.1.2	Definitions .....	75
8c.1.2.1	Controlling and serving nodes.....	75
8c.1.2.2	RIM association .....	75
8c.1.2.3	RIM variables.....	76
8c.1.3	RIM PDUs description.....	76
8c.1.3.1	RAN-INFORMATION-REQUEST PDU .....	76
8c.1.3.2	RAN-INFORMATION PDU .....	76
8c.1.3.3	RAN-INFORMATION-ACK PDU .....	76
8c.1.3.4	RAN-INFORMATION-ERROR PDU.....	77
8c.1.3.5	RAN-INFORMATION-APPLICATION-ERROR PDU .....	77
8c.1.4	RIM addressing and routing principles .....	77
8c.1.4.1	RIM routing address.....	77
8c.1.4.1.1	GERAN BSS identification .....	77
8c.1.4.1.2	UTRAN RNS identification .....	77
8c.1.4.1.3	E-UTRAN eNodeB identification.....	77
8c.1.4.1.4	eHRPD eAN identification.....	77
8c.1.4.2	Routing via the core network .....	77
8c.1.4.3	Address mirroring .....	77
8c.1.5	In-order delivery and reliable transfer - RSN .....	78
8c.1.5.1	General .....	78
8c.1.5.2	Allocating RSN values at the sending BSS .....	79
8c.1.5.3	Comparing RSN values at the receiving BSS .....	79
8c.1.6	RIM Protocol Version Number.....	79
8c.2	RIM procedures.....	79
8c.2.1	General.....	79
8c.2.2	RAN Information Request procedure .....	80
8c.2.2.1	RAN Information Request/Single Report procedure .....	80
8c.2.2.1.1	Initiation by the controlling BSS .....	80
8c.2.2.1.2	Reception of a valid RAN-INFORMATION-REQUEST/Single Report PDU by the serving BSS.....	80
8c.2.2.1.3	Reception of a valid RAN-INFORMATION/Single Report PDU by the controlling BSS .....	81
8c.2.2.1.4	Expiration of T(RIR) in the controlling BSS.....	81
8c.2.2.2	RAN Information Request/Multiple Report procedure.....	81
8c.2.2.2.1	Initiation by the controlling BSS .....	81
8c.2.2.2.2	Reception of a valid RAN-INFORMATION-REQUEST/Multiple Report PDU by the serving BSS .....	82
8c.2.2.2.3	Reception of a valid RAN-INFORMATION PDU/Initial Multiple Report PDU by the controlling BSS .....	82
8c.2.2.2.4	Expiration of T(RIR) in the controlling BSS.....	82
8c.2.2.3	RAN Information Request/Stop procedure .....	83
8c.2.2.3.1	Initiation by the controlling BSS .....	83
8c.2.2.3.2	Reception of a valid RAN-INFORMATION-REQUEST/Stop PDU by the serving BSS .....	83
8c.2.2.3.3	Reception of a valid RAN-INFORMATION/Stop PDU by the controlling BSS.....	84
8c.2.2.3.4	Expiration of T(RIR) in the controlling BSS.....	84
8c.2.3	RAN Information Send procedure .....	84
8c.2.3.1	Initiation by the serving BSS .....	84
8c.2.3.2	Reception of a valid RAN-INFORMATION PDU by the controlling BSS.....	85
8c.2.3.3	Reception of a valid RAN-INFORMATION-ACK PDU in the serving BSS.....	85
8c.2.3.4	Expiration of T(RI) in the serving BSS.....	86
8c.2.4	RAN Information Application Error procedure.....	86
8c.2.4.1	Initiation by the controlling BSS.....	86

8c.2.4.2	Reception of a valid RAN-INFORMATION-APPLICATION-ERROR PDU by the serving BSS.....	86
8c.2.4.3	Reception of a valid RAN-INFORMATION-ACK PDU by the controlling BSS .....	87
8c.2.4.4	Expiration of T(RIAE) in the controlling BSS .....	87
8c.2.5	RAN Information Error procedure.....	87
8c.3	Abnormal conditions .....	88
8c.3.0	General.....	88
8c.3.1	Abnormal conditions at the BSSGP level.....	88
8c.3.1.1	General .....	88
8c.3.1.2	RIM addressing error in BSS .....	88
8c.3.1.3	RIM addressing error in the CN.....	88
8c.3.1.4	RIM PDU addressed to a BSS not supporting RIM .....	88
8c.3.2	Abnormal conditions encountered in the RIM container .....	88
8c.3.2.1	Unknown RIM Application Identity .....	88
8c.3.2.2	Erroneous PDU Type Extension field .....	89
8c.3.2.3	Missing conditional IE .....	89
8c.3.2.4	Missing mandatory IE.....	89
8c.3.2.5	Syntactical error in an expected conditional IE.....	89
8c.3.2.6	Syntactical error in a mandatory IE.....	89
8c.3.2.7	Unexpected conditional IE.....	90
8c.3.2.8	Containers with out-of-sequence information elements .....	90
8c.3.2.9	Container with semantically incorrect content .....	90
8c.3.3	Unexpected RIM PDU.....	90
8c.3.4	RIM error reporting .....	90
8c.3.4.1	General .....	90
8c.3.4.2	Sending of a RAN-INFORMATION-ERROR PDU .....	90
8c.3.4.3	Reception of a RAN-INFORMATION-ERROR PDU in the BSS .....	91
8c.4	RIM timers .....	91
8c.5	Action upon deletion of a cell in a BSS.....	91
8c.5.0	General.....	91
8c.5.1	Actions due to the deletion of the cell.....	92
8c.5.2	Additional actions in the case the deleted cell is used as a source cell by RIM.....	92
8c.6	Specific requirements related to RIM applications.....	92
8c.6.0	General requirements .....	92
8c.6.1	Requirements related to the NACC RIM application .....	92
8c.6.2	SI3 application .....	93
8c.6.3	MBMS data channel application.....	93
8c.6.4	Requirements related to the SON Transfer RIM application .....	94
8c.6.5	Requirements related to the UTRA SI RIM application.....	94
8d	Signalling procedures between MBMS SAPs .....	95
8d.1	General .....	95
8d.2	MBMS Session Start .....	95
8d.2.1	Abnormal Conditions.....	97
8d.3	MBMS Session Stop .....	97
8d.3.1	Abnormal Conditions.....	97
8d.4	MBMS Session Update .....	97
8d.4.1	Abnormal Conditions.....	99
9	General Protocol Error Handling .....	99
10	PDU functional definitions and contents.....	99
10.1	General Structure Of A PDU.....	99
10.2	PDU functional definitions and contents at RL and BSSGP SAPs .....	100
10.2.1	DL-UNITDATA .....	100
10.2.2	UL-UNITDATA .....	101
10.2.3	RA-CAPABILITY .....	102
10.2.4	(void) .....	103
10.2.5	DL-MBMS-UNITDATA .....	103
10.2.6	UL-MBMS-UNITDATA.....	103
10.3	PDU functional definitions and contents at GMM SAP.....	103
10.3.1	PAGING PS.....	103
10.3.2	PAGING CS .....	104
10.3.3	RA-CAPABILITY-UPDATE.....	104

10.3.4	RA-CAPABILITY-UPDATE-ACK .....	105
10.3.5	RADIO-STATUS .....	105
10.3.6	SUSPEND .....	105
10.3.7	SUSPEND-ACK.....	106
10.3.8	SUSPEND-NACK.....	106
10.3.9	RESUME.....	106
10.3.10	RESUME-ACK .....	107
10.3.11	RESUME-NACK .....	107
10.3.12	PAGING PS REJECT.....	107
10.3.13	DUMMY PAGING PS .....	108
10.3.14	DUMMY PAGING PS RESPONSE .....	108
10.4	PDU functional definitions and contents at NM SAP .....	109
10.4.1	FLUSH-LL .....	109
10.4.2	FLUSH-LL-ACK.....	109
10.4.3	LLC-DISCARDED.....	109
10.4.4	FLOW-CONTROL-BVC .....	110
10.4.5	FLOW-CONTROL-BVC-ACK.....	110
10.4.6	FLOW-CONTROL-MS.....	111
10.4.7	FLOW-CONTROL-MS-ACK .....	111
10.4.8	BVC-BLOCK .....	111
10.4.9	BVC-BLOCK-ACK.....	112
10.4.10	BVC-UNBLOCK .....	112
10.4.11	BVC-UNBLOCK-ACK .....	112
10.4.12	BVC-RESET.....	113
10.4.13	BVC-RESET-ACK.....	113
10.4.14	STATUS .....	114
10.4.14.1	Static conditions for BVCI.....	114
10.4.15	SGSN-INVOKE-TRACE .....	114
10.4.16	DOWNLOAD-BSS-PFC .....	115
10.4.17	CREATE-BSS-PFC .....	115
10.4.18	CREATE-BSS-PFC-ACK .....	115
10.4.19	CREATE-BSS-PFC-NACK .....	116
10.4.20	MODIFY-BSS-PFC .....	116
10.4.21	MODIFY-BSS-PFC-ACK .....	116
10.4.22	DELETE-BSS-PFC .....	117
10.4.23	DELETE-BSS-PFC-ACK.....	117
10.4.24	FLOW-CONTROL-PFC .....	117
10.4.25	FLOW-CONTROL-PFC-ACK.....	118
10.4.26	DELETE-BSS-PFC-REQ.....	118
10.4.27	PS-HANDOVER-REQUIRED.....	118
10.4.28	PS-HANDOVER-REQUIRED-ACK .....	119
10.4.29	PS-HANDOVER-REQUIRED-NACK .....	119
10.4.30	PS-HANDOVER-REQUEST .....	120
10.4.31	PS-HANDOVER-REQUEST-ACK .....	120
10.4.32	PS-HANDOVER-REQUEST-NACK .....	121
10.4.33	PS-HANDOVER-COMplete.....	121
10.4.34	PS-HANDOVER-CANCEL.....	121
10.4.35	PS-HANDOVER-COMplete-ACK .....	122
10.5	PDU functional definitions and contents at LCS SAP .....	122
10.5.1	PERFORM-LOCATION-REQUEST .....	122
10.5.2	PERFORM-LOCATION-RESPONSE.....	123
10.5.3	PERFORM-LOCATION-ABORT .....	124
10.5.4	POSITION-COMMAND.....	124
10.5.5	POSITION-RESPONSE .....	125
10.6	PDU functional definitions and contents at RIM SAP .....	125
10.6.1	RAN-INFORMATION-REQUEST .....	125
10.6.2	RAN-INFORMATION.....	126
10.6.3	RAN-INFORMATION-ACK.....	126
10.6.4	RAN-INFORMATION-ERROR .....	126
10.6.5	RAN-INFORMATION-APPLICATION-ERROR.....	127
10.7	PDU functional definitions and contents at MBMS SAP .....	127
10.7.1	MBMS-SESSION-START-REQUEST.....	127

10.7.2	MBMS-SESSION-START-RESPONSE.....	128
10.7.3	MBMS-SESSION-STOP-REQUEST.....	128
10.7.4	MBMS-SESSION-STOP-RESPONSE.....	128
10.7.5	MBMS-SESSION-UPDATE-REQUEST.....	128
10.7.6	MBMS-SESSION-UPDATE-RESPONSE.....	129
11	General information elements coding .....	129
11.1	General structure of the information elements .....	129
11.2	Information element description.....	129
11.3	Information Element Identifier (IEI) .....	130
11.3.1	Alignment octets.....	132
11.3.2	Bmax default MS.....	132
11.3.3	BSS Area Indication .....	132
11.3.4	Bucket Leak Rate (R) .....	133
11.3.5	BVC Bucket Size.....	133
11.3.6	BVCI (BSSGP Virtual Connection Identifier).....	133
11.3.7	BVC Measurement .....	133
11.3.8	Cause .....	134
11.3.9	Cell Identifier.....	136
11.3.10	Channel needed.....	136
11.3.11	DRX Parameters .....	136
11.3.12	eMLPP-Priority.....	136
11.3.13	Flush Action.....	137
11.3.14	IMSI.....	137
11.3.15	LLC-PDU .....	137
11.3.16	LLC Frames Discarded.....	138
11.3.17	Location Area .....	138
11.3.18	LSA Identifier List.....	138
11.3.19	LSA Information.....	138
11.3.20	Mobile Id .....	138
11.3.21	MS Bucket Size .....	139
11.3.22	MS Radio Access Capability .....	139
11.3.23	OMC Id.....	139
11.3.24	PDU In Error.....	139
11.3.25	PDU Lifetime.....	140
11.3.26	PDU Type .....	141
11.3.27	Priority .....	142
11.3.28	QoS Profile .....	142
11.3.29	Radio Cause .....	144
11.3.30	RA-Cap-UPD-Cause.....	144
11.3.31	Routeing Area.....	145
11.3.32	R_default_MS.....	145
11.3.33	Suspend Reference Number.....	145
11.3.34	Tag .....	145
11.3.35	Temporary logical link Identity (TLLI).....	146
11.3.36	Temporary Mobile Subscriber Identity (TMSI).....	146
11.3.37	Trace Reference .....	146
11.3.38	Trace Type .....	146
11.3.39	Transaction Id .....	147
11.3.40	Trigger Id.....	147
11.3.41	Number of octets affected.....	147
11.3.42	Packet Flow Identifier (PFI) .....	147
11.3.42a	(void) .....	148
11.3.43	Aggregate BSS QoS Profile.....	148
11.3.44	GPRS Timer.....	148
11.3.45	Feature Bitmap.....	148
11.3.46	Bucket Full Ratio.....	150
11.3.47	Service UTRAN CCO .....	150
11.3.48	NSEI (Network Service Entity Identifier) .....	151
11.3.49	RRLP APDU .....	151
11.3.50	LCS QoS.....	151
11.3.51	LCS Client Type.....	151

11.3.52	Requested GPS Assistance Data .....	152
11.3.53	Location Type .....	152
11.3.54	Location Estimate .....	152
11.3.55	Positioning Data.....	152
11.3.56	Deciphering Keys .....	153
11.3.57	LCS Priority.....	153
11.3.58	LCS Cause .....	153
11.3.59	LCS Capability .....	153
11.3.60	RRLP Flags.....	153
11.3.61	RIM Application Identity.....	154
11.3.62	RIM Sequence Number .....	155
11.3.62a	RIM Container .....	155
11.3.62a.0	General .....	155
11.3.62a.1	RAN-INFORMATION-REQUEST RIM Container.....	155
11.3.62a.2	RAN-INFORMATION RIM Container.....	156
11.3.62a.3	RAN-INFORMATION-ACK RIM Container .....	156
11.3.62a.4	RAN-INFORMATION-ERROR RIM Container .....	157
11.3.62a.5	RAN-INFORMATION-APPLICATION-ERROR RIM Container .....	157
11.3.63	Application Container.....	158
11.3.63.1	RAN-INFORMATION-REQUEST Application Container .....	158
11.3.63.1.0	General .....	158
11.3.63.1.1	RAN-INFORMATION-REQUEST Application Container for the NACC Application.....	158
11.3.63.1.2	RAN-INFORMATION-REQUEST Application Container for the SI3 Application .....	158
11.3.63.1.3	RAN-INFORMATION-REQUEST Application Container for the MBMS data channel Application .....	158
11.3.63.1.4	RAN-INFORMATION-REQUEST Application Container for the SON Transfer Application ..	159
11.3.63.1.5	RAN-INFORMATION-REQUEST Application Container for the UTRA SI Application .....	159
11.3.63.2	RAN-INFORMATION Application Container Unit.....	160
11.3.63.2.0	General .....	160
11.3.63.2.1	RAN-INFORMATION Application Container for the NACC Application.....	160
11.3.63.2.2	RAN-INFORMATION Application Container for the SI3 Application .....	161
11.3.63.2.3	RAN-INFORMATION Application Container for the MBMS data channel Application .....	161
11.3.63.2.4	RAN-INFORMATION Application Container for the SON Transfer Application .....	163
11.3.63.2.5	RAN-INFORMATION Application Container for the UTRA SI Application.....	163
11.3.64	Application Error Container .....	164
11.3.64.1	Application Error Container layout for the NACC application.....	164
11.3.64.2	Application Error Container for the SI3 application .....	164
11.3.64.3	Application Error Container for the MBMS data channel application.....	165
11.3.64.4	Application Error Container for the SON Transfer Application .....	166
11.3.64.5	Application Error Container for the UTRA SI Application .....	166
11.3.65	RIM PDU Indications .....	167
11.3.65.0	General .....	167
11.3.65.1	RAN-INFORMATION-REQUEST RIM PDU Indications.....	167
11.3.65.2	RAN-INFORMATION RIM PDU Indications .....	167
11.3.65.3	RAN-INFORMATION-APPLICATION-ERROR RIM PDU Indications .....	168
11.3.66	(void) .....	168
11.3.67	RIM Protocol Version Number.....	168
11.3.68	PFC Flow Control parameters .....	169
11.3.69	Global CN-Id .....	169
11.3.70	RIM Routing Information.....	170
11.3.71	MBMS Session Identity.....	171
11.3.72	MBMS Session Duration .....	171
11.3.73	MBMS Service Area Identity List .....	172
11.3.74	MBMS Response .....	172
11.3.75	MBMS Routing Area List.....	173
11.3.76	MBMS Session Information .....	173
11.3.77	TMGI (Temporary Mobile Group Identity).....	174
11.3.78	MBMS Stop Cause .....	174
11.3.79	Source BSS to Target BSS Transparent Container .....	175
11.3.80	Target BSS to Source BSS Transparent Container .....	175
11.3.81	NAS container for PS Handover.....	176
11.3.82	PFCs to be set-up list .....	176

11.3.83	List of set-up PFCs .....	177
11.3.84	Extended Feature Bitmap.....	178
11.3.85	Source to Target Transparent Container .....	178
11.3.86	Target to Source Transparent Container .....	179
11.3.87	RNC Identifier .....	179
11.3.88	Page Mode .....	180
11.3.89	Container ID .....	180
11.3.90	Global TFI .....	180
11.3.91	IMEI.....	181
11.3.92	Time to MBMS Data Transfer.....	181
11.3.93	MBMS Session Repetition Number.....	182
11.3.94	Inter RAT Handover Info .....	182
11.3.95	PS Handover Command.....	182
11.3.95a	PS Handover Indications .....	182
11.3.95b	SI/PSI Container .....	183
11.3.95c	Active PFCs List.....	184
11.3.96	Velocity Data .....	184
11.3.97	DTM Handover Command .....	184
11.3.98	CS Indication .....	185
11.3.99	Requested GANSS Assistance Data .....	185
11.3.100	GANSS Location Type.....	185
11.3.101	GANSS Positioning Data.....	185
11.3.102	Flow Control Granularity.....	186
11.3.103	eNB Identifier .....	186
11.3.104	E-UTRAN Inter RAT Handover Info .....	187
11.3.105	Subscriber Profile ID for RAT/Frequency priority .....	187
11.3.106	Request for Inter-RAT Handover Info.....	187
11.3.107	Reliable Inter-RAT Handover Info.....	188
11.3.108	SON Transfer Application Identity.....	188
11.3.109	CSG Identifier.....	188
11.3.110	Tracking Area Code.....	189
11.3.111	Redirect Attempt Flag.....	189
11.3.112	Redirection Indication.....	189
11.3.113	Redirection Completed .....	190
11.3.114	Unconfirmed send state variable.....	191
11.3.115	IRAT Measurement Configuration .....	191
11.3.116	SCI.....	192
11.3.117	GGSN/P-GW location .....	192
11.3.118	Selected PLMN ID.....	193
11.3.119	Priority Class Indicator .....	193
11.3.120	Source Cell ID IE.....	193
11.3.121	IRAT Measurement Configuration (extended E-ARFCNs).....	194
11.3.122	eDRX Parameters .....	195
11.3.123	Time Until Next Paging Occasion .....	195
11.3.124	Old Routing Area Identification .....	195
12	List of system variables.....	197
12.1	General Variables .....	197
12.2	Flow control variables .....	198
<b>Annex A (informative):</b>	<b>Change history .....</b>	<b>199</b>
History .....		200