



Designation: D 226 – 06

# Standard Specification for Asphalt-Saturated Organic Felt Used in Roofing and Waterproofing<sup>1</sup>

This standard is issued under the fixed designation D 226; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the Department of Defense.*

## 1. Scope

1.1 This specification covers asphalt-saturated organic felts, with or without perforations, intended to be used with asphalts conforming to the requirements of Specification **D 312** in the construction of built-up roofs, and with asphalts conforming to the requirements of Specification **D 449** in the construction of water proofing systems.

1.2 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 The following safety hazards caveat pertains only to the test method portion, Section 8, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

**D 70** Test Method for Density of Semi-Solid Bituminous Materials (Pycnometer Method)

**D 146** Test Methods for Sampling and Testing Bitumen-Saturated Felts and Woven Fabrics for Roofing and Waterproofing

**D 312** Specification for Asphalt Used in Roofing

**D 449** Specification for Asphalt Used in Dampproofing and Waterproofing

**D 727** Test Method for Kerosine Number of Roofing and Flooring Felt by the Vacuum Method

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee D08 on Roofing and Waterproofing and is the direct responsibility of Subcommittee D08.04 on Felts and Fabrics.

Current edition approved July 15, 2006. Published July 2006. Originally approved in 1925. Last previous edition approved in 2005 as D 226 – 05.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

**D 1079** Terminology Relating to Roofing and Waterproofing

## 3. Terminology

3.1 *Definitions*—For definitions of terms used in this specification, refer to Terminology **D 1079**.

## 4. Classification

4.1 Asphalt-saturated felts covered by this specification are of two types:

4.1.1 *Type I*—Commonly called No. 15 asphalt felt.

4.1.2 *Type II*—Commonly called No. 30 asphalt felt.

## 5. Materials and Manufacture

5.1 In the process of manufacture a single thickness of dry felt shall be saturated with an asphaltic saturant.

5.2 The felt shall be produced principally from organic fibers. The surface of the felt shall be uniform and relatively smooth. Upon splitting or tearing on the bias, the felt shall appear reasonably free of lumps or particles of foreign substances.

## 6. Physical Requirements

6.1 The material shall conform to the physical requirements prescribed in **Table 1** and the dimensions and masses prescribed in **Table 2**.

6.2 The finished product shall not crack nor be so sticky as to cause tearing or other damage upon being unrolled at temperatures between 10 and 60°C (50 and 140°F).

6.3 Perforated felts shall conform to the same requirements as the plain type but shall also have uniformly spaced perforations.

## 7. Workmanship, Finish, and Appearance

7.1 The felt shall be thoroughly and uniformly saturated, and shall show no unsaturated spots at any point upon cutting 50-mm (2-in.) wide strips at random across the entire sheet and splitting them open for their full length.